

# SAFETY DATA SHEET

Version 6.10 Revision Date 09/07/2024 Print Date 09/08/2024

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifiers

Product name : Ethyl acetate

Product Number : 34858 Brand : SIGALD

Index-No. : 607-022-00-5 CAS-No. : 141-78-6

# 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

Uses advised against : The product is being supplied under the TSCA R&D Exemption

(40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by

MilliporeSigma.

# 1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.

3050 SPRUCE ST ST. LOUIS MO 63103 UNITED STATES

Telephone : +1 314 771-5765 Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-

527-3887 CHEMTREC (International) 24

Hours/day; 7 Days/week

# **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture

# GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Eye irritation (Category 2A), H319

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

SIGALD - 34858

Page 1 of 13



For the full text of the H-Statements mentioned in this Section, see Section 16.

# 2.2 GHS Label elements, including precautionary statements

Pictogram

Signal Word Danger

Hazard Statements

H225 Highly flammable liquid and vapor.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

**Precautionary Statements** 

P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No

smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing mist or vapors.
P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water/ shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable

for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue

rinsing.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant

foam to extinguish.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/ container to an approved waste disposal

plant.

### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

Repeated exposure may cause skin dryness or cracking.

# **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

SIGALD - 34858

Page 2 of 13



Component	Classification	Concentration
ethyl acetate		
	Flam. Liq. 2; Eye Irrit. 2A; STOT SE 3; H225, H319, H336	<= 100 %
	Concentration limits: 20 %: STOT SE 3, H336;	

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### **SECTION 4: First aid measures**

# 4.1 Description of first-aid measures

#### **General advice**

Show this material safety data sheet to the doctor in attendance.

# If inhaled

After inhalation: fresh air. Call in physician.

#### In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

## In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

#### If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

## 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

# 4.3 Indication of any immediate medical attention and special treatment needed No data available

## **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

# Suitable extinguishing media

Carbon dioxide (CO2) Foam Dry powder

# Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

# 5.2 Special hazards arising from the substance or mixture

Carbon oxides Combustible.

SIGALD - 34858



Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

# 5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

#### 5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

## **SECTION 6: Accidental release measures**

# 6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

# 6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

## 6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemizorb® ). Dispose of properly. Clean up affected area.

## 6.4 Reference to other sections

For disposal see section 13.

## **SECTION 7: Handling and storage**

## 7.1 Precautions for safe handling

#### Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

## Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

# **Hygiene measures**

Change contaminated clothing. Preventive skin protection recommended. Wash hands after working with substance.

For precautions see section 2.2.

# 7.2 Conditions for safe storage, including any incompatibilities

# Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

#### Storage class

SIGALD - 34858

Page 4 of 13



# 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

# SECTION 8: Exposure controls/personal protection

# 8.1 Control parameters

Ingredients with workplace control parameters

Trigredients with workplace control parameters					
Component	CAS-No.	Value	Control parameters	Basis	
ethyl acetate	141-78-6	TWA	400 ppm	USA. ACGIH Threshold Limit Values (TLV)	
		TWA	400 ppm 1,400 mg/m3	USA. NIOSH Recommended Exposure Limits	
		TWA	400 ppm 1,400 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants	
		PEL	400 ppm 1,400 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)	

**Derived No Effect Level (DNEL)** 

Delived No Ellect Level (DNEL)				
Application Area	Routes of	Health effect	Value	
	exposure			
Workers	Inhalation	Acute systemic effects	1468 mg/m3	
Workers	Inhalation	Acute local effects	1468 mg/m3	
Workers	Skin contact	Long-term systemic effects	63mg/kg BW/d	
Workers	Inhalation	Long-term systemic effects	734 mg/m3	
Workers	Inhalation	Long-term local effects	734 mg/m3	
Consumers	Inhalation	Acute local effects, Acute systemic effects	734 mg/m3	
Consumers	Skin contact	Long-term systemic effects	37mg/kg BW/d	
Consumers	Inhalation	Long-term systemic effects	367 mg/m3	
Consumers	Ingestion	Long-term systemic effects	4.5mg/kg BW/d	
Consumers	Inhalation	Long-term local effects	367 mg/m3	

**Predicted No Effect Concentration (PNEC)** 

	- 1	
Compartment	Value	
Soil	0.24 mg/kg	
Sea water	0.026 mg/l	
Fresh water	0.26 mg/l	
Sea sediment	0.125 mg/kg	
Fresh water sediment	1.25 mg/kg	

SIGALD - 34858



### 8.2 Exposure controls

# **Appropriate engineering controls**

Change contaminated clothing. Preventive skin protection recommended. Wash hands after working with substance.

# Personal protective equipment

# Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

# Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact

Material: butyl-rubber

Minimum layer thickness: 0.7 mm Break through time: 120 min

Material tested: Butoject® (KCL 898)

# **Body Protection**

Flame retardant antistatic protective clothing.

# **Respiratory protection**

Recommended Filter type: Filter A (acc. to DIN 3181) for vapours of organic compounds

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

# Control of environmental exposure

Do not let product enter drains. Risk of explosion.

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

a) Appearance Form: clear, liquid

Color: colorless

b) Odor fruityc) Odor Threshold 0.1 ppm

d) pH No data available

e) Melting point/ range: -84 °C (-119 °F)

point/freezing point

SIGALD - 34858

Millipore Sigma f) Initial boiling point and boiling range

76.5 - 77.5 °C 169.7 - 171.5 °F

g) Flash point

-4 °C (25 °F) - closed cup - closed cup

h) Evaporation ratei) Flammability (solid,

No data available No data available

gas)

j) Upper/lower flammability or explosive limits Upper explosion limit: 11.5 %(V) Lower explosion limit: 2.1 %(V)

k) Vapor pressure No data available

I) Vapor density 3.04

m) Density 0.902 g/cm3 at 25 °C (77 °F)

Relative density No data available n) Water solubility No data available

o) Partition coefficient: log Po

log Pow: 0.73 - Bioaccumulation is not expected., (Lit.)

n-octanol/water
p) Autoignition

No data available

q) Decomposition temperature

temperature

Distillable in an undecomposed state at normal pressure.

r) Viscosity No data available

s) Explosive properties Not classified as explosive.

t) Oxidizing properties none

# 9.2 Other safety information

Relative vapor

3.04

density

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

Vapors may form explosive mixture with air.

# 10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature).

# 10.3 Possibility of hazardous reactions

Risk of ignition or formation of inflammable gases or vapours with:

Exothermic reaction with:

Fluorine

chlorosulfonic acid

Strong oxidizing agents

fuming sulfuric acid

SIGALD - 34858

Millipore

Risk of explosion with: lithium aluminium hydride Alkali metals hydrides Alkaline earth metals Violent reactions possible with: Strong acids and strong bases

# 10.4 Conditions to avoid

Warming.

# 10.5 Incompatible materials

No data available

## 10.6 Hazardous decomposition products

In the event of fire: see section 5

# **SECTION 11: Toxicological information**

# 11.1 Information on toxicological effects

# **Acute toxicity**

LD50 Oral - Rat - 5,620 mg/kg

Remarks: (RTECS)

Inhalation: No data available

LD50 Dermal - Rabbit - male - > 20,000 mg/kg

Remarks: (ECHA) No data available

#### Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation Remarks: (IUCLID)

# Serious eye damage/eye irritation

Remarks: Causes serious eye irritation.

Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

# Respiratory or skin sensitization

Maximization Test - Guinea pig

Result: negative

(OECD Test Guideline 406)

## Germ cell mutagenicity

Test Type: UDS (Unscheduled DNA synthesis assay)

Test system: Escherichia coli

Metabolic activation: with and without metabolic activation

Method: US-EPA Result: negative Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

SIGALD - 34858



Result: negative

Test Type: Chromosome aberration test in vitro Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: negative

Test Type: Micronucleus test Species: Chinese hamster

Cell type: Red blood cells (erythrocytes)

Application Route: Oral

Method: OECD Test Guideline 474

Result: negative

# Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

# Reproductive toxicity

No data available

# Specific target organ toxicity - single exposure

May cause drowsiness or dizziness. - Central nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

## Specific target organ toxicity - repeated exposure

No data available

# **Aspiration hazard**

No data available

#### 11.2 Additional Information

Repeated dose toxicity - Rat - male and female - Oral - 92 Days - NOAEL (No observed adverse effect level) - 900 mg/kg - LOAEL (Lowest observed adverse effect level) - 3,600 mg/kg

RTECS: AH5425000

Inhalation of high concentrations may cause:, Headache, Drowsiness, Dizziness, Vomiting, narcosis, anemia, Central nervous system depression

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Kidney - Irregularities - Based on Human Evidence

Kidney - Irregularities - Based on Human Evidence

SIGALD - 34858

Page 9 of 13



# **SECTION 12: Ecological information**

# 12.1 Toxicity

Toxicity to fish flow-through test LC50 - Pimephales promelas (fathead minnow) -

230 mg/l - 96 h

(US-EPA)

Toxicity to algae static test NOEC - Desmodesmus subspicatus (green algae) - > 100

mg/l - 72 h

(OECD Test Guideline 201)

Toxicity to bacteria Remarks: (IUCLID)

(ethyl acetate)

Toxicity to daphnia semi-static test NOEC - Daphnia magna (Water flea) - 2.4 mg/l - 21

and other aquatic of

invertebrates(Chronic (OECD Test Guideline 211)

toxicity)

# 12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 20 d

Result: ca.69 % - Readily biodegradable.

Remarks: (ECHA)

Theoretical oxygen 1,820 mg/g demand Remarks: (Lit.)

## 12.3 Bioaccumulative potential

Bioaccumulation Leuciscus idus melanotus - 3 Days

at 22.5 °C(ethyl acetate)

Bioconcentration factor (BCF): 30

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

# 12.6 Endocrine disrupting properties

No data available

# 12.7 Other adverse effects

No data available



## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### **Product**

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

# **SECTION 14: Transport information**

DOT (US)

UN number: 1173 Class: 3 Packing group: II

Proper shipping name: Ethyl acetate Reportable Quantity (RQ): 5000 lbs

Poison Inhalation Hazard: No

**IMDG** 

UN number: 1173 Class: 3 Packing group: II EMS-No: F-E, S-D

Proper shipping name: ETHYL ACETATE

**IATA** 

UN number: 1173 Class: 3 Packing group: II

Proper shipping name: Ethyl acetate

# **SECTION 15: Regulatory information**

# **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ethyl acetate	141-78-6	5000	5000

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

# **SARA 302 Extremely Hazardous Substances Threshold Planning Quantity**

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 : Fire Hazard

**Hazards** Acute Health Hazard Chronic Health Hazard

: This material does not contain any chemical

components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by

SARA Title III, Section 313.

SIGALD - 34858

**SARA 313** 

#### **Clean Air Act**

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489):

ethyl acetate 141-78-6 >= 90 - <= 100 %

#### **Clean Water Act**

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

# **US State Regulations**

# **Massachusetts Right To Know**

ethyl acetate 141-78-6

# Pennsylvania Right To Know

ethyl acetate 141-78-6

# **Maine Chemicals of High Concern**

Product does not contain any listed chemicals

# **Vermont Chemicals of High Concern**

Product does not contain any listed chemicals

## **Washington Chemicals of High Concern**

Product does not contain any listed chemicals

# The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

#### **TSCA list**

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

# **SECTION 16: Other information**

#### **Further information**

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its

SIGALD - 34858

Page 12 of 13



Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.10 Revision Date: 09/07/2024 Print Date: 09/08/2024

SIGALD - 34858 Page 13 of 13

