



# The Unix Shell


## Pipes and Filters




Copyright © Software Carpentry 2010


This work is licensed under the Creative Commons Attribution License

See <http://software-carpentry.org/license.html> for more information.




shell







shell



pwd	mkdir
cd	nano
ls	rm
.	rmdir
..	mv
	cp



shell



pwd	mkdir
cd	nano
ls	rm
.	rmdir
..	mv
	cp

*More powerful  
when combined*

```
$ ls molecules
```

```
cubane.pdb      ethane.pdb      methane.pdb
```

```
octane.pdb      pentane.pdb     propane.pdb
```

```
$
```

```
$ ls molecules
```

```
cubane.pdb      ethane.pdb      methane.pdb
```

```
octane.pdb      pentane.pdb     propane.pdb
```

```
$ cd molecules
```

```
$
```

```
$ ls molecules
```

```
cubane.pdb      ethane.pdb      methane.pdb
```

```
octane.pdb      pentane.pdb     propane.pdb
```

```
$ cd molecules
```

```
$ wc *.pdb
```

```
$ ls molecules
```

```
cubane.pdb      ethane.pdb      methane.pdb
```

```
octane.pdb      pentane.pdb     propane.pdb
```

```
$ cd molecules
```

```
$ wc *.pdb ← * is a wild card
```



```
$ ls molecules
```

```
cubane.pdb      ethane.pdb      methane.pdb
```

```
octane.pdb      pentane.pdb     propane.pdb
```

```
$ cd molecules
```

```
$ wc *.pdb
```



*\* is a wild card*

*matches zero or more characters*

```
$ ls molecules
```

```
cubane.pdb      ethane.pdb      methane.pdb
```

```
octane.pdb      pentane.pdb     propane.pdb
```

```
$ cd molecules
```

```
$ wc *.pdb
```



*\* is a wild card*

*matches zero or more characters*

*so \*.pdb matches all filenames*

*ending in .pdb*


```
$ ls molecules
```

```
cubane.pdb      ethane.pdb      methane.pdb
```

```
octane.pdb      pentane.pdb      propane.pdb
```

```
$ cd molecules
```

```
$ wc *.pdb
```



```
wc cubane.pdb ethane.pdb methane.pdb octane.pdb pentane.pdb propane.pdb
```

```
$ ls molecules
```

```
cubane.pdb      ethane.pdb      methane.pdb
```

```
octane.pdb      pentane.pdb      propane.pdb
```

```
$ cd molecules
```

```
$ wc *.pdb
```

← word count

```
$ ls molecules
```

```
cubane.pdb      ethane.pdb      methane.pdb
```

```
octane.pdb      pentane.pdb      propane.pdb
```

```
$ cd molecules
```

```
$ wc *.pdb
```



word count

counts lines, words, and  
characters in files

```
$ ls molecules
```

```
cubane.pdb      ethane.pdb      methane.pdb
octane.pdb      pentane.pdb     propane.pdb
```

```
$ cd molecules
```

```
$ wc *.pdb
```

```
 20   156  1158 cubane.pdb
 12    84   622 ethane.pdb
  9    57   422 methane.pdb
 30   246  1828 octane.pdb
 21   165  1226 pentane.pdb
 15   111   825 propane.pdb
107   819  6081 total
```

```
$
```

\$ `wc -l *.pdb` report only lines

```

20  cubane.pdb
12  ethane.pdb
 9  methane.pdb
30  octane.pdb
21  pentane.pdb
15  propane.pdb
107 total

```

\$

```
$ wc -l *.pdb
```

```
20  cubane.pdb
```

```
12  ethane.pdb
```

```
9   methane.pdb
```

```
30  octane.pdb
```

```
21  pentane.pdb
```

```
15  propane.pdb
```

```
107 total
```

```
$
```

report only lines  
use -w for words or  
-c for characters



```
20  cubane.pdb
12  ethane.pdb
 9  methane.pdb
30  octane.pdb
21  pentane.pdb
15  propane.pdb
107 total
```

Which file is shortest?

```
20  cubane.pdb
12  ethane.pdb
 9  methane.pdb
30  octane.pdb
21  pentane.pdb
15  propane.pdb
107 total
```

Which file is shortest?

Easy to see when there are six...

```
20  cubane.pdb
12  ethane.pdb
 9  methane.pdb
30  octane.pdb
21  pentane.pdb
15  propane.pdb
107 total
```

Which file is shortest?

Easy to see when there are six...

...but what if there were 6000?

```
$ wc -l *.pdb > lengths
```

```
$
```

```
$ wc -l *.pdb > lengths
```


```
$
```



*redirect* output to a file

```
$ wc -l *.pdb > lengths
```


```
$
```



*redirect* output to a file  
create file if it doesn't exist

```
$ wc -l *.pdb > lengths
```

```
$
```



*redirect* output to a file  
create file if it doesn't exist  
overwrite it if it does

```
$ wc -l *.pdb > lengths
```

```
$
```



no screen output



```
$ wc -l *.pdb > lengths
```

```
$ ls lengths
```

```
lengths
```

```
$
```

```
$ wc -l *.pdb > lengths
```

```
$ ls lengths
```

```
lengths
```

```
$ cat lengths
```

```
20  cubane.pdb
```

```
12  ethane.pdb
```

```
9   methane.pdb
```

```
30  octane.pdb
```

```
21  pentane.pdb
```

```
15  propane.pdb
```

```
107 total
```

```
$
```

```
$ wc -l *.pdb > lengths
```

```
$ ls lengths
```

```
lengths
```

```
$ cat lengths
```

← concatenate files

```
20 cubane.pdb
```

```
12 ethane.pdb
```

```
9 methane.pdb
```

```
30 octane.pdb
```

```
21 pentane.pdb
```

```
15 propane.pdb
```

```
107 total
```

```
$
```

```
$ wc -l *.pdb > lengths
```

```
$ ls lengths
```

```
lengths
```

```
$ cat lengths
```

*concatenate* files

in this case, only one

so file contents printed to screen

```
20 cubane.pdb
```

```
12 ethane.pdb
```

```
9 methane.pdb
```

```
30 octane.pdb
```

```
21 pentane.pdb
```

```
15 propane.pdb
```

```
107 total
```

```
$
```

```
$ sort -n lengths
```

```
9  methane.pdb
```

```
12 ethane.pdb
```

```
15 propane.pdb
```

```
20 cubane.pdb
```

```
21 pentane.pdb
```

```
30 octane.pdb
```

```
107 total
```

```
$
```

```
$ sort -n lengths > sorted-lengths
```

```
$
```

```
$ sort -n lengths > sorted-lengths
$ head -1 sorted-lengths
  9  methane.pdb
$
```

```
$ sort -n lengths > sorted-lengths
```

```
$ head -1 sorted-lengths
```

```
9 methane.pdb
```

get the first line of the file

```
$
```



```
$ sort -n lengths > sorted-lengths
```

```
$ head -1 sorted-lengths
```

```
9 methane.pdb
```

```
$
```

get the first line of the file  
this must be the PDB file  
with the fewest lines,  
since sorted-lengths holds  
files and line counts in  
order from least to greatest

```
$ sort -n lengths > sorted-lengths
```

```
$ head -1 sorted-lengths
```

```
9 methane.pdb
```

```
$
```

not particularly obvious

get the first line of the file  
this must be the PDB file  
with the fewest lines,  
since sorted-lengths holds  
files and line counts in  
order from least to greatest

```
$ sort -n lengths | head -1  
9 methane.pdb  
$
```

```
$ sort -n lengths | head -1  
9 methane.pdb
```

```
$
```

*a pipe*

```
$ sort -n lengths | head -1
```

```
9 methane.pdb
```

```
$
```

*a pipe*

use output of left side

```
$ sort -n lengths | head -1  
9 methane.pdb
```

```
$
```

*a pipe*

use output of left side  
as input to right side

```
$ sort -n lengths | head -1
```

```
9 methane.pdb
```

```
$
```

*a pipe*

use output of left side

as input to right side

*without creating temporary file*

```
$ wc -l *.pdb | sort -n | head -1
```

```
9  methane.pdb
```

```
$
```

don't need to create lengths file



```
$ wc -l *.pdb | sort -n | head -1  
9  methane.pdb  
$
```

This simple idea is why Unix has been so successful

```
$ wc -l *.pdb | sort -n | head -1  
9  methane.pdb  
$
```

This simple idea is why Unix has been so successful  
Create simple tools that:

```
$ wc -l *.pdb | sort -n | head -1  
9  methane.pdb  
$
```

This simple idea is why Unix has been so successful  
Create simple tools that:  
– do one job well

```
$ wc -l *.pdb | sort -n | head -1  
9  methane.pdb  
$
```

This simple idea is why Unix has been so successful

Create simple tools that:

- do one job well
- work well with each other


```
$ wc -l *.pdb | sort -n | head -1  
9  methane.pdb  
$
```

This simple idea is why Unix has been so successful


Create simple tools that:

- do one job well
- work well with each other


10 tools can be combined in 100 ways




running program





running program  
*process*

















```
$ wc -l *.pdb > lengths
```




```
$ wc -l *.pdb > lengths
```




WC



```
$ wc -l *.pdb > lengths
```




```
$ wc -l *.pdb > lengths
```



```
$ wc -l *.pdb | sort
```





```
$ wc -l *.pdb | sort | head -1
```

This programming model called *pipes and filters*

This programming model called *pipes and filters*

A *filter* transforms a stream of input into a stream of output

This programming model called *pipes and filters*

A *filter* transforms a stream of input into a stream of output

A *pipe* connects two filters

This programming model called *pipes and filters*

A *filter* transforms a stream of input into a stream of output

A *pipe* connects two filters

Any program that reads lines of text from standard input, and writes lines of text to standard output, can work with every other

This programming model called *pipes and filters*

A *filter* transforms a stream of input into a stream of output

A *pipe* connects two filters

Any program that reads lines of text from standard input, and writes lines of text to standard output, can work with every other

You can (and should) write such programs

pwd	mkdir
cd	nano
ls	rm
.	rmdir
..	mv
	cp

pwd	mkdir	wc
cd	nano	sort
ls	rm	head
.	rmdir	
..	mv	
	cp	



pwd	mkdir	wc
cd	nano	sort
ls	rm	head
.	rmdir	<i>tail</i>
..	mv	<i>split</i>
	cp	<i>cut</i>
		<i>uniq</i>

pwd	mkdir	wc	*
cd	nano	sort	>
ls	rm	head	
.	rmdir	<i>tail</i>	
..	mv	<i>split</i>	
	cp	<i>cut</i>	
		<i>uniq</i>	

pwd	mkdir	wc	*
cd	nano	sort	>
ls	rm	head	
.	rmdir	<i>tail</i>	<
..	mv	<i>split</i>	?
	cp	<i>cut</i>	
		<i>uniq</i>	



created by

Greg Wilson

August 2010



Copyright © Software Carpentry 2010

This work is licensed under the Creative Commons Attribution License

See <http://software-carpentry.org/license.html> for more information.