smartIAQ GridSet Pro

PRODUCT DATA SHEET

smartIAQ® GridSet Pro™ Low Profile Hard Ceiling Mounted Unit

PRODUCT DESCRIPTION

smartIAQ® GridSet Pro™ is an on-demand air cleaner for commercial spaces. It supports the easy application of the Indoor Air Quality Procedure (IAQP) by extracting design compounds listed in ASHRAE Standard 62.1-2019, -2022 and -2025. With low voltage power, occupant-based response, and designed to install onto hard ceilings, smartIAQ GridSet delivers immediate return on investment and supports ongoing savings with low service, installation, and design costs. Standard-sized filters and the smartIAQ operating system provide 2 years of maintenance-free operation. Status indicator, air quality sensor, and filter access are in the space, ensuring confident ownership and maintenance. Integrates with end-user BMS systems.


Suitable for classrooms, meeting rooms, retail stores, houses of worship, and some medical facilities, one smartIAQ GridSet cleans air in spaces up to 1,500ft2. Multiple units may be used to help larger spaces achieve compliance.


STANDARD FEATURES

- Single piece cleaner construction for use with Included hard ceiling mounting frame
- Installs onto the surface of a hard ceiling, with fascia plates on all sides for a clean finish
- Integral EC Blower - varies up to a Peak Clean flow of 150CFM to allow outdoor air reduction
- Virtually silent operation - NC25 at max flow
- 48VDC low voltage power: uses CAT-5 or CAT-5e wiring to a smartIAQ Hub-4 Pro (separate device)
- Full BMS integration with native option for:
    - BACnet MS/TP - (via Hub-4 Pro)
- Filter and operating profile provides closed loop for IAQP compliance
- Solid state motion and air quality sensors: no calibration or maintenance required:
    - Motion Sensor
    - CO2 Sensor
    - Formaldehyde Sensor
    - PM Sensor (1.0, 2.5, 4.0 & 10.0)
    - TVOC Sensor
    - NOX Sensor
- NPBI® Soft Ionization delivered to space at supply side



Single Zone





FILTRATION DETAILS

The SIAQ3-DIST utilizes a combined Particulate and Molecular filter to address defined design compounds:

CompleteAQ filter - SIAQ-CF1-20202

ASHRAE 52.2 rated to MERV 8

ASHRAE 145.2 rated for gas-phase contaminants

Unit achieves 2 years of filter life*

* Based on ASHRAE published generation rates for design compounds

OPTIONAL FEATURES


- Also available in Black (with additional lead-time)


smartIAQ GridSet Pro

PRODUCT DATA SHEET


smartIAQ® GridSet Pro™ Low Profile Hard Ceiling Mount

Side Elevation






End Elevation



Plan View



SIAQ3-DIST (Low-Profile): SPECIFICATIONS

Standard Input Voltage	48 VDC	**Weight**	Approx. 65 lbs
Airflow Capacity	Up to 150 CFM	**Power Consumption**	26 W
Sound Level (Nominal Cleaning)**	NC-25	**Temperature Range**	0 - 140 F
Filter Life	2 Years*	**Humidity Range**	5 - 85% RH (non-condensing)
Dimensions (L x W x H)	48 " x 24" x 9.5"	**Compliance and Certifications#**	UL 867, CSA 22.2 #187, UL 2998, CARB#

** 1m from unit

Certifications Pending

© 2026 GPS Air
GPS Air is the owner of certain trademarks that appear in our materials. Please visit www.gpsair.com/trademarks for a list of our marks.