

KOL Network Public API Spec

Generated: June 30, 2026

Content Hub producer API for CHT /kol-network

Dev: devhub.communityhealth.media

Source: docs/kol-network-api-spec.md

Implement against KOL_BASE_URL (catalog stays on MediaHub until cutover).

KOL Network - Content Hub Public API Spec

Version: Content Hub API v0.0.3+

Scope: KOL directory only (not catalog / playlists)

Audience: CHT platform implementation (cht-platform-tool)

Base URLs

Env	Base URL
Dev	https://devhub.communityhealth.media/api/public
Prod (future)	https://contenthub.communityhealth.media/api/public

Authentication

All routes require a server-side API key (never expose to the browser).

```
X-API-Key: <PUBLIC_API_KEY>
Content-Type: application/json
```

Status	Meaning
401	Missing or invalid X-API-Key
404	KOL slug not found (detail route)
422	Validation error (upsert body, query params)
429	Rate limit (100 requests/minute per route)

Error response shape (all /api/public/* errors)

```
{
  "errors": {
    "status_code": 401,
    "details": "Missing API key"
  }
}
```

HTTP status on the response matches errors.status_code. CHT should read errors.details for the message.

CHT integration pattern

```
Browser -> CHT backend /api/kol-network/*
|
+-- server-to-server --> Content Hub /api/public/kols/*
X-API-Key (KOL_BASE_URL - separate from catalog URL)
```

CHT should add KOL_BASE_URL pointing at Content Hub while MEDIAHUB_BASE_URL stays on EC2 for catalog until playlisting moves to Content Hub.

Endpoints

1. List KOL directory

GET /kols

Query parameters

Param	Type	Default	Description
region	string	-	Filter by region slug
institution	string	-	Exact institution match
q	string	-	Search name, institution, specialty, bio (max 200 chars)
new_only	boolean	false	Only KOLs with is_new=true
limit	int	200	Page size (1-500)
offset	int	0	Pagination offset

Response: PublicKolList

Notes

- total is count after filters (new_only, etc.), before pagination slice.
- regions and institutions are facets from the filtered set.
- intel is present when the KOL has a linked hcp_npi.

Example response (abbreviated)

```
{
  "items": [{
    "id": "969c7db9-85e2-4680-ba9a-27d237552fce",
    "slug": "bardia",
    "name": "Dr. Aditya Bardia",
    "title": null,
    "specialty": "Hematology & Oncology",
    "institution": "University Of California Los Angeles David Geffen School Of Medicine",
    "bio": "...",
    "photo_url": "https://contenthub-dev-assets-...amazonaws.com/kol-headshots/aditya-bardia.png",
    "region": "california",
    "region_label": "California",
    "shoot_count": 2,
    "first_appeared_at": "2026-01-24T05:24:26.544074Z",
    "is_new": false,
    "intel": {
      "npi": "1639210107",
      "specialty": "Hematology & Oncology",
      "location": "Los Angeles, CA",
      "email": "abardial@partners.org",
      "affiliation": "University Of California Los Angeles David Geffen School Of Medicine",
      "publications_approx": 17,
      "open_payments": null,
      "ai_brief": null
    }
  }],
  "total": 39,
  "regions": [{ "slug": "california", "label": "California", "kol_count": 5 }],
  "institutions": ["Dana-Farber Cancer Institute"]
}
```

2. KOL profile detail

GET /kols/{slug}

Response: PublicKol (same shape as list item)

Errors: 404 { "detail": "KOL not found" }

3. KOL publications

GET /kols/{slug}/publications

Query parameters

Param	Type	Default	Description
-------	------	---------	-------------

limit	int	20	1-100
offset	int	0	Pagination

Response: PublicKolPublicationList

Notes

- Returns { "items": [], "total": 0 } if KOL has no linked NPI or no publication signals (not an error).
- Data from hcp_signals where signal_type = "publication".

Example

```
{
  "items": [{
    "title": "Abstract C040: Sustained lymphopenia during neoadjuvant chemo-immunotherapy...",
    "url": "https://doi.org/10.1158/2326-6074.io2026-c040",
    "journal": "Cancer Immunology Research",
    "published_at": "2026-02-18T00:00:00Z",
    "is_first_author": false,
    "is_last_author": true
  }],
  "total": 17
}
```

4. HCP upsert (registration sync)

Same base URL; not used by KOL UI but part of the KOL/HCP ecosystem.

POST /hcp/upsert

Request body (snake_case)

```
{
  "npi": "1234567890",
  "first_name": "Jane",
  "last_name": "Doe",
  "email": "jane@example.com",
  "specialty": "Medical Oncology",
  "city": "Boston",
  "state": "MA",
  "zip": "02115",
  "institution": "Dana-Farber Cancer Institute",
  "source": "cht"
}
```

Field	Required	Notes
npi	yes	10 digits

first_name, last_name	yes	
email, specialty, city, state, zip, institution	no	specialty -> hcps.taxonomy; institution -> hcps.hospital_affiliations
source	no	default "cht"

Response: { "created": true, "npi": "1234567890" }

CHT caller: mediahub-sync.service.ts - only reads created.

TypeScript types (CHT)

Update existing types to include intel (new vs legacy MediaHub).

```
export interface PublicKolIntel {
  npi?: string | null;
  specialty?: string | null;
  location?: string | null;
  email?: string | null;
  affiliation?: string | null;
  publications_approx?: number | null;
  open_payments?: { total: number; records: number; years: string } | null;
  ai_brief?: { whoTheyAre?: string } | null;
}

export interface PublicKol {
  id: string;
  slug: string;
  name: string;
  title: string | null;
  specialty: string | null;
  institution: string | null;
  bio: string | null;
  photo_url: string | null;
  region: string | null;
  region_label: string | null;
  shoot_count: number;
  first_appeared_at: string | null;
  is_new: boolean;
  intel?: PublicKolIntel | null;
}

export interface PublicKolRegionFacet {
  slug: string;
  label: string;
  kol_count: number;
}

export interface PublicKolList {
  items: PublicKol[];
  total: number;
  regions: PublicKolRegionFacet[];
  institutions: string[];
}

export interface PublicKolPublication {
  title: string;
  url: string | null;
  journal: string | null;
  published_at: string;
  is_first_author: boolean;
  is_last_author: boolean;
}
```

```
export interface PublicKolPublicationList {
  items: PublicKolPublication[];
  total: number;
}
```

Field semantics

Field	Source	CHT usage
slug	Derived from last name (+ suffix if collision)	URL /kol-network/{slug}
photo_url	S3 CDN URL or null	Card avatar
shoot_count	Distinct shoots via KOL group membership	Videos count
first_appeared_at	min(shoot.shoot_date, shoot.created_at)	New badge timing
is_new	first_appeared_at within 60 days	Filter new_only=true
region / region_label	CMS taxonomy	Region filter chips
intel	HCP Intel via kols.hcp_npi	Replace dol-network.ts mock

Not on API yet (keep static or omit)

dol-network.ts field	Status
education	Not in API
role	Use title or static
linkedInUrl, twitterUrl, webUrl	Not in API
intel.aiBrief.focus, chmContext	Only whoTheyAre when present

Region taxonomy

Filter with ?region=<slug>.

slug	label
ny-northeast	New York & Northeast
new-england	New England
east-coast	East Coast Academic Centers
florida	Florida
midwest-chicago	Midwest - Chicago
midwest-indiana	Midwest - Indiana
missouri	Missouri

kansas	Kansas
tennessee	Tennessee
texas	Texas
colorado	Colorado
pacific-northwest	Pacific Northwest
california	California

Slug rules

1. Strip leading Dr. / Dr 2. Take portion before first comma 3. Use last word of name, lowercase alphanumeric + hyphens 4. Collisions: append -2, -3, ... (sorted by name)

Examples: Dr. Aditya Bardia -> bardia; duplicate last names -> smith-2.

CHT backend proxy

CHT route	Proxies to
GET /api/kol-network	GET {KOL_BASE_URL}/kols
GET /api/kol-network/:slug	GET {KOL_BASE_URL}/kols/:slug
GET /api/kol-network/:slug/publications	GET {KOL_BASE_URL}/kols/:slug/publications

Degradation (keep current behavior)

- List failure -> empty list payload
- Detail failure -> 404
- Publications failure -> empty items

Environment variables (CHT)

```
KOL_BASE_URL=https://devhub.communityhealth.media/api/public
```

```
KOL_API_KEY=<contenthub public_api_key>
```

```
MEDIAHUB_BASE_URL=https://mediahub.communityhealth.media/api/public
```

```
MEDIAHUB_API_KEY=...
```

Catalog stays on MEDIAHUB_BASE_URL until playlist migration.

Smoke test

```
KEY=<public_api_key>
BASE=https://devhub.communityhealth.media/api/public

curl -s -H "X-API-Key: $KEY" "$BASE/kols?limit=1"
curl -s -H "X-API-Key: $KEY" "$BASE/kols/bardia"
curl -s -H "X-API-Key: $KEY" "$BASE/kols/bardia/publications?limit=1"
```

Implementation checklist

- Add KOL_BASE_URL + dedicated HTTP client in KolNetworkModule
- Extend PublicKol / MediaHubKol with optional intel
- Prefer apiKol.intel over dol-network.ts for NPI, open payments, publications count, AI brief
- Keep dol-network.ts only for education, social URLs until API adds them
- Point registration upsert at /hcp/upsert when ready

Canonical source: backend/src/schemas/public.py, backend/src/public/router.py