BRUSA NLG5 Individual Specifications

Customer: Date: Created: Checked:

Charger Hardware

Charger Type:	NLG 511
Serial Number:	29041
Production Date:	31.12.2099
Firmware Version:	1.10.00
Mains Input Voltage Range:	100...264 VAC
Max. Mains Current:	16 A
Max. Mains Power:	3.7 kW
Charging Voltage Range:	130...260 VDC
Max. Charging Current:	25 A
Max. Charging Power:	3.3 kW

Charger Program

File Name:	Li_Ion_Valence_Ucharge_154V_2x100Ah.pfl
Operation Mode:	Automatic
Nominal Battery Voltage:	153.6 V
Maximum Mains Current:	16 A

Battery Temperature Handling

Batt. Temp. Sensor #1:	not active
Batt. Temp. Sensor #2:	not active
Batt. Temp. Sensor #3:	not active
Temp. Coeff. Gassing Voltage:	N/A
Reference Temp. for Voltages:	N/A
Current Reduction:	N/A

Emergency Shutdown Limits

Max. Battery Temperature:	N/A
Max. Battery Voltage:	176 V
Max. Battery Charge:	240 Ah
Max. Charging Time:	999 h

Charging Profile

Section 1:	max. Current [A]: 25	max. Voltage [V]: 165.6	until	
	-Charging current below [A]		10	OR
	-Charging time of this section above [Min]		690	
Section 2:	max. Current [A]: 0	max. Voltage [V]: 0		

Notes

Battery:	U24-12FN100, 2 strings, 12 units each
Chemistry:	Valence "Ucharge Saphion" (Li-Ion)
Nom. Volt:	153.6V (12 x 12.8V)
Capacity:	200Ah (2 x 100Ah)

This is only a CC/CV profile according to manufacturer's data sheet.
Temperature monitoring, Ah balance etc. must be controlled by BMS.