

ClaudeOS — Manual QA Test Plan

Version: 1.0 | **System:** Flask :5000 + Streamlit :8501

How to use: Work top-to-bottom. Mark each item PASS / FAIL / SKIP. Fix all FAILs before client handover.

PRE-FLIGHT (Do this first, every session)

```
# Terminal 1 – start both servers
.\scripts\start.ps1
```

Wait ~10 seconds, then verify:

Check	How	Expected
Flask alive	Browser → `http://localhost:5000/api/v1/health`	`{"status":"ok"}`
Streamlit alive	Browser → `http://localhost:8501`	Login page loads
DB exists	File exists: `data/claudeos.db`	File present, non-zero size
ChromaDB exists	Folder exists: `data/chromadb`	Folder present

If Flask returns nothing: check terminal for import errors. Common cause: missing package → `pip install -r requirements.txt`

SECTION 0 — AUTH (prerequisite for everything)

0.1 Login

1. Open `http://localhost:8501`
2. Enter username admin + correct password
3. Click Login (or press Enter)

Expected: Dashboard loads, sidebar shows all nav items, username visible bottom-left.

Fail signals: "Invalid credentials", blank page, spinner that never resolves.

0.2 Token auto-refresh (background check)

- Stay logged in for 60+ minutes → dashboard should NOT log you out
- If it does log out: token refresh is broken (check `dashboard/app.py` auto-refresh logic)

0.3 Logout

1. Click **Logout** button in sidebar
2. **Expected:** Returns to login page, session cleared

0.4 Wrong password logout

1. Logout, then attempt login with wrong password 5 times
2. **Expected:** Account locked message appears
3. Login as admin → Admin → Users → Unlock the account

SECTION 1 — OVERVIEW PAGE

Navigate to: Overview (first item in sidebar)

1.1 KPI Cards

Expected: Six metric cards visible:

- Memories | Agent Runs | Active Workflows | Projects | Outputs | Open Tickets
- All show numbers (0 is acceptable, "—" or error is NOT)

1.2 System Status (admin-visible)

Expected: Three status badges visible:

- API Status → green "online"
- Database → green "online"
- ChromaDB → green "online" (or yellow "degraded" if chromadb not indexed yet)

If Database shows red: Flask can't reach SQLite → restart server

1.3 Memory Breakdown

Expected: Per-namespace memory entry counts listed (may be 0 if no memories added yet)

1.4 Quick Dispatch (agent run from Overview)

1. Select any agent from dropdown
2. Select namespace `global`
3. Type a short prompt: `say hello`
4. Click Run

Expected: Response appears in the chat area within 30 seconds, no error banner.

Fail signals: "Stream error", "API unreachable", spinner forever.

1.5 Live Activity Feed

Expected: After completing 1.4, the feed shows the new run with status badge.

1.6 Auto-refresh toggle

1. Toggle on **Auto-refresh**
2. Wait 8–10 seconds
3. **Expected:** Page data refreshes without manual reload, no crash

SECTION 2 — AGENTS PAGE

Navigate to: Agents

2.1 Catalog Tab

1. Click **Catalog** tab
2. **Expected:** Grid of agent cards, each showing name, category badge, model, description
3. Try the search box — type `analysis`
4. **Expected:** Filters to matching agents only

If "No agents registered" appears: run ``python scripts/seed_agents.py`` then restart

2.2 Basic Chat (text only)

1. Click **Chat** tab
2. Select `analysis-agent` (or any enabled agent)
3. Namespace: `global`

4. Type prompt: What is 2 + 2?
5. Press Enter

Expected: Streaming response appears token-by-token, ends within 30s. Token count shown below response.

2.3 Image Upload (multimodal)

1. In Chat tab, use **Attach** panel to upload any .jpg or .png
2. Image thumbnail appears below uploader
3. Type prompt: Describe what you see in this image
4. Press Enter

Expected: Agent responds describing the image content. Response must NOT say "no image received."

Fail signal: "only text was received" → image pipeline broken (fixed in commit 291eece — verify server was restarted after that commit)

2.4 Multi-turn Conversation

1. Send message: My name is Test User
2. Send follow-up: What is my name?
3. **Expected:** Agent recalls "Test User" from earlier in conversation

2.5 Clear Conversation

1. Click **Clear conversation** button
2. Send: What is my name?
3. **Expected:** Agent does NOT recall "Test User" — fresh context
4. **Expected:** Voice input widget also resets (microphone button returns to default state, no previous audio retained)

2.6 A2A Agent Card

1. Expand **Agent Card (A2A)** section in left panel
2. **Expected:** JSON block showing agent name, capabilities, endpoint URLs

2.7 Run History Tab

1. Click **Run History** tab
2. **Expected:** Table showing recent runs with columns: Agent, Namespace, Status, Quality, Tokens, Duration
3. Runs from steps 2.2–2.4 should appear here

2.8 Voice Input (OPTIONAL — requires whisper)

1. Click microphone button, speak a sentence, stop recording
2. **Expected:** Text transcribed and placed in prompt field
3. **If error:** "openai-whisper not installed" → acceptable, mark SKIP

SECTION 3 — MEMORY PAGE

Navigate to: Memory

3.1 Add a Memory Entry

1. Click **Add Entry** tab
2. Fill in:
 - Namespace: global
 - Category: fact
 - Key: test_entry_001
 - Value: ClaudeOS QA test entry — created during manual test

- Source: manual_test

- Confidence: 1.0

3. Click **Save**

4. **Expected:** Success message, no error

3.2 Browse Entries

1. Click **Browse** tab

2. **Expected:** Table of memory entries, test_entry_001 visible

3. Try the namespace filter — select global

4. **Expected:** Filters to global entries only

3.3 Text Search

1. Click **Search** tab

2. Mode: text

3. Namespace: global

4. Query: QA test entry

5. **Expected:** test_entry_001 appears in results

3.4 Semantic Search

1. Same Search tab

2. Mode: semantic

3. Query: manual testing

4. **Expected:** Results returned (may include test_entry_001 or related entries)

5. **Fail signal:** Error about ChromaDB → vector DB issue. Check data/chromadb folder exists.

3.5 Hybrid Search

1. Mode: both (hybrid BM25+vector)

2. Same query

3. **Expected:** Combined results, no error

3.6 Delete Entry

1. In Browse tab, find test_entry_001

2. Delete it

3. **Expected:** Entry removed from list after refresh

SECTION 4 — WORKFLOWS PAGE

Navigate to: Workflows

4.1 Workflows List

1. **Workflows** tab

2. **Expected:** List of workflows with trigger type (schedule/manual), enabled toggle, step count

3. If empty: run `python scripts/seed_workflows.py` → restart

4.2 Manual Trigger a Workflow

1. Find any workflow with trigger type manual or schedule

2. Click **Run / Trigger** button

3. Context input (optional): leave blank or enter `{"test": true}`

4. Confirm trigger

Expected: Success toast or run record appears. No 500 error.

4.3 Workflow Run History

1. Click **Run History** tab
2. **Expected:** Table shows the run triggered in 4.2, with status done or running

4.4 Scheduler Tab

1. Click **Scheduler** tab
2. **Expected:** List of scheduled jobs with cron expression and next run time
3. Click **Reload Scheduler**
4. **Expected:** Success message, no crash

4.5 Webhooks Tab

1. Click **Webhooks** tab
2. Pick any workflow → click **Enable Webhook**
3. **Expected:** Webhook URL and secret displayed
4. Test via curl (in a new terminal):

```
# Replace <secret> and <workflow-name> with actual values
$secret = "<your-webhook-secret>"
$body = '{"test": true}'
Invoke-WebRequest -Uri "http://localhost:5000/api/v1/workflows/<workflow-name>/trigger" `
-Method POST `
-Headers @{ "X-Webhook-Secret" = $secret; "Content-Type" = "application/json" } `
-Body $body
```

Expected: HTTP 200 response, run record created

SECTION 5 — PROJECTS PAGE

Navigate to: Projects

5.1 Namespace List

1. **Namespaces** tab
2. **Expected:** Grid/list of namespaces with name, slug, type, project count
3. Toggle **Show disabled** — disabled namespaces appear if any exist

If empty: run `python scripts/seed\_namespaces.py`

5.2 Workspace Stats

1. Click any namespace to expand / select it
2. **Expected:** File counts per subdirectory (documents, outputs, context, etc.)

5.3 Projects Tab

1. Click **Projects** tab
2. Select a namespace from dropdown
3. **Expected:** Project cards with name, status badge, priority, tech stack

5.4 Create a Project

1. Click **New Project** (or equivalent button)
2. Fill: Name=QA Test Project, Namespace=global, Status=active
3. Save
4. **Expected:** Project appears in list

5.5 Context Files

1. Click **Context Files** tab
 2. Select namespace `global`
 3. Upload a small `.txt` file
 4. **Expected:** File appears in context file list for that namespace
-

SECTION 6 — OUTPUTS PAGE

Navigate to: Outputs

Note: Outputs are auto-created when agents run with "Save output" checked. Ensure you ran at least one agent run with save enabled (Section 2.2).

6.1 Browse Outputs

1. **Browse** tab
2. **Expected:** Table of outputs with type icon, title, namespace, tags, size, date
3. Bulk select checkbox works
4. Delete a test output with 2-click confirmation

6.2 Search Outputs

1. **Search** tab
2. Query: agent name used in Section 2
3. **Expected:** Matching outputs appear

6.3 Export an Output

1. Browse tab → click any output
2. Export as **Markdown**
3. **Expected:** File download or rendered content, no 404/500

6.4 Stats Tab

1. **Stats** tab
 2. **Expected:** Total count, per-namespace breakdown, per-type breakdown, no error
-

SECTION 7 — TICKETS PAGE

Navigate to: Tickets

7.1 Create a Ticket

1. Click **Create** tab
2. Fill:
 - Title: QA Test Ticket
 - Description: Testing ticket creation during QA
 - Category: bug
 - Priority: medium
 - Namespace: `global`
3. Submit
4. **Expected:** Success, ticket appears in Browse tab

7.2 Browse Tickets

1. **Browse** tab

2. **Expected:** QA Test Ticket visible, with SLA due date, status=open
3. Status filter works (filter by open)
4. Priority filter works

7.3 Advance Ticket Status

1. Click on QA Test Ticket
2. Change status: open → assigned → work_in_progress → completed
3. **Expected:** Each transition saves successfully

7.4 My Tickets Tab

1. Click **My Tickets**
2. **Expected:** QA Test Ticket appears (you are creator)

7.5 Bulk Delete

1. Browse tab → select QA Test Ticket via checkbox
 2. Click **Delete Selected**
 3. Confirm
 4. **Expected:** Ticket removed
-

SECTION 8 — OBSERVABILITY PAGE

Navigate to: Observability

(Only visible to admin and operator roles)

8.1 Quality Scores Tab

1. **Expected:** Bar chart of per-agent quality averages (0–5 scale)
2. Scores from agent runs in Section 2 should appear here
3. Agents with 0 runs show 0 or are absent

8.2 Latency Tab

1. **Expected:** Table showing p50/p95/p99 latency per agent
2. Agents run in Section 2 should have values

8.3 Token Cost Tab

1. **Expected:** Token usage breakdown per agent, cost estimate in USD

8.4 Memory Health Tab

1. **Expected:**
 - Total memory entries count
 - Stale entries count
 - Consolidation status (last run time)
 - Suggestion to run consolidation if stale entries > threshold

8.5 Namespace Usage Tab

1. **Expected:** Tab visible (admin/operator only)
 2. Table showing per-namespace: runs count, input tokens, output tokens, estimated USD cost, avg quality score, memory entries
 3. Stacked bar chart (plotly) comparing token usage across namespaces
 4. Data based on up to 500 most recent runs — no error on low-run systems (zeros acceptable)
-

SECTION 9 — SETTINGS PAGE

Navigate to: Settings

9.1 Email / Notification Config

1. **Expected:** SMTP fields visible (host, port, from, to)
2. Values should match .env (smtp.gmail.com, port 587)
3. Edit a field → Save → Reload page → value persists

9.2 Supabase Sync Status

1. **Expected:** Status badge visible
 2. If Supabase is configured: click **Test Connection** → should return success or clear error
 3. Click **Manual Push** → status updates
 4. If Supabase not configured: badge shows "not configured" or "disabled" → mark SKIP
-

SECTION 10 — ADMIN PAGE

Navigate to: Admin

(Admin role required)

10.1 Users Tab

1. **Expected:** Table of all users with role, namespace, active status
2. Admin user (yourself) visible
3. Click **Create User**:
 - Username: qa_test_user
 - Password: TestUser123!
 - Role: viewer
 - Namespace: global
4. **Expected:** User appears in table

10.2 API Keys Tab

1. Click **Create API Key**
2. Name: QA Test Key, Permissions: read, Namespace: global
3. **Expected:** Key created, token displayed (copy it — shown only once)
4. Test the key:

```
Invoke-WebRequest -Uri "http://localhost:5000/api/v1/health" `
-Headers @{ "X-API-Key" = "<your-key>" }
```

5. **Expected:** 200 OK

10.3 Audit Log Tab

1. **Expected:** Table of recent events (login_success, user_created, etc.)
2. Actions from this test session should appear
3. Filter by event type login_success → only login events shown

10.4 Sessions Tab

1. **Expected:** List of active sessions with IP, user-agent, expiry
2. Your current session visible
3. Revoke the qa_test_user session if one exists → no error

10.5 Security Settings Tab

1. **Expected:** Fields for:
 - Max failed attempts (default: 5)
 - Lockout minutes (default: 15)
 - Access token TTL minutes (default: 60)
 - Allow self-registration (toggle)
2. Change a value → Save → **Expected:** Success message, value persists on refresh

10.6 Cleanup test data

1. Delete qa_test_user from Users tab
2. Revoke QA Test Key from API Keys tab

10.7 Client Onboarding Tab

1. Click **Client Onboarding** tab (6th tab in Admin Panel)
2. **Expected:** Dropdown of client namespaces (not global/personal — client-type only)
3. Select a namespace → 14 fields appear (business name, industry, primary goals, brand tone, SLA tier, contact name, contact email, timezone, preferred language, custom instructions, etc.)
4. Fill in 2–3 fields → click **Save**
5. **Expected:** Success message; navigate away and return — values persist

10.8 Admin Unlock (Context-Aware)

1. In Users tab, find a user that is NOT locked
2. **Expected:** No "Unlock" button visible for unlocked users (button only appears when locked)
3. Lock a test account by logging in with wrong password 5 times (from Section 0.4)
4. Return to Admin → Users → find the locked user
5. **Expected:** Lock warning with expiry time AND a prominent Unlock button visible
6. Click Unlock → **Expected:** Lock cleared immediately, user can log in

SECTION 11 — CROSS-CUTTING CHECKS

These apply to ALL pages.

11.1 Role Scoping

1. Login as qa_test_user (viewer role, created in 10.1 — recreate if deleted)
2. **Expected nav visible:** Overview, Agents, Memory, Projects, Outputs, Tickets
3. **Expected nav HIDDEN:** Workflows, Observability, Settings, Admin
4. Try navigating directly to Admin → should redirect to login or show "Access denied"
5. Logout, re-login as admin

11.2 Dark/Light Mode

1. Click the circular toggle button (bottom area, fixed at left : 220px — clears sidebar text)
2. **Expected:** Entire dashboard switches theme — background, text, cards, sidebar all update
3. Switch back — state persists during session

11.5 Onboarding Tour (first-time user)

1. Create a brand-new user with a fresh namespace
2. Log in as that user for the first time
3. **Expected:** Onboarding tour/modal appears
4. Click through or dismiss it
5. Log out, log back in

6. **Expected:** Onboarding does NOT appear again (persisted via onboarding_done DB column)

11.3 Error Handling

For each page, check:

- No red Python tracebacks visible to user (internal errors should show friendly message)
- No NoneType or KeyError stack traces in the UI

11.4 API Key Auth (alternative to JWT)

```
# Replace with actual API key from Section 10.2
$key = "<your-api-key>"
Invoke-WebRequest "http://localhost:5000/api/v1/agents" -Headers @{ "X-API-Key" = $key }
```

Expected: 200 with agents list

KNOWN ISSUES TO VERIFY FIXED

Issue	Fix Commit	How to Verify
Images not sent to agent chat	`291eece`	Section 2.3 — image analysis works
Overview stats failed on non-main thread	`bed94f7`	Section 1.1 — KPI cards load without error
Browser refresh loses active page	`64c4140`	Navigate to Agents, press F5 — stays on Agents
XSS escaping / security hardening	`63a83d6`	Inputs accept text; no script injection renders
Voice input widget not clearing on conversation reset	`208d58b`	Section 2.5 — after Clear, microphone widget resets
Analysis agent namespace scope warning in logs	`8a36d10`	Run analysis-agent — no scope warning in Flask terminal
Workflow run delete broken	`8a36d10`	Section 4.3 — delete a run history entry, no 500 error
Theme toggle overlapping sidebar text	`86bbade`	Section 11.2 — toggle at bottom-left (left:220px), clears sidebar
Onboarding shows again after logout/re-login	`03366f6`	Complete onboarding, logout, log back in — tour does NOT appear again
Memory namespace list hardcoded to local path	`5423ba2`	Memory page namespace filter populates from API, not error
Context tiers duplicated when namespace==global	`70860f2`	Run agent in global namespace — no duplicate context in prompt
Admin unlock button always visible (not context-aware)	`eba9751`	Section 10.8 — Unlock only shown for actually-locked users

PASS/FAIL SUMMARY SHEET

Copy this to track results:

```
SECTION 0 — AUTH
0.1 Login [ ]
0.2 Token refresh [ ]
0.3 Logout [ ]
```

0.4 Lockout []

SECTION 1 – OVERVIEW

1.1 KPI Cards []

1.2 System Status []

1.3 Memory Breakdown []

1.4 Quick Dispatch []

1.5 Activity Feed []

1.6 Auto-refresh []

SECTION 2 – AGENTS

2.1 Catalog []

2.2 Basic Chat []

2.3 Image Upload []

2.4 Multi-turn []

2.5 Clear Conversation []

2.6 A2A Agent Card []

2.7 Run History []

2.8 Voice Input [SKIP if no whisper]

SECTION 3 – MEMORY

3.1 Add Entry []

3.2 Browse []

3.3 Text Search []

3.4 Semantic Search []

3.5 Hybrid Search []

3.6 Delete Entry []

SECTION 4 – WORKFLOWS

4.1 List []

4.2 Manual Trigger []

4.3 Run History []

4.4 Scheduler []

4.5 Webhooks []

SECTION 5 – PROJECTS

5.1 Namespace List []

5.2 Workspace Stats []

5.3 Projects Tab []

5.4 Create Project []

5.5 Context Files []

SECTION 6 – OUTPUTS

6.1 Browse []

6.2 Search []

6.3 Export []

6.4 Stats []

SECTION 7 – TICKETS

7.1 Create []

7.2 Browse + Filter []

7.3 Status Transitions []

7.4 My Tickets []

7.5 Bulk Delete []

SECTION 8 – OBSERVABILITY

8.1 Quality Scores []

8.2 Latency []

8.3 Token Cost []

```
8.4 Memory Health [ ]
8.5 Namespace Usage [ ]

SECTION 9 – SETTINGS
9.1 Email Config [ ]
9.2 Supabase Sync [SKIP if not configured]

SECTION 10 – ADMIN
10.1 Users [ ]
10.2 API Keys [ ]
10.3 Audit Log [ ]
10.4 Sessions [ ]
10.5 Security Settings [ ]
10.6 Cleanup [ ]
10.7 Client Onboarding Tab [ ]
10.8 Admin Unlock (ctx-aware)[ ]

SECTION 11 – CROSS-CUTTING
11.1 Role Scoping [ ]
11.2 Dark/Light Mode [ ]
11.3 Error Handling [ ]
11.4 API Key Auth [ ]
11.5 Onboarding Tour [ ]
```

REPORTING A FAILURE

When a test fails, note:

1. **Section + step number** (e.g. "3.4 Semantic Search")
2. **Exact error message** shown in UI
3. **Flask terminal output** — any Python traceback at the time of the failure
4. **Browser console errors** (F12 → Console tab)

This gives enough info to diagnose and fix quickly.