

ClaudeOS — Manual QA Test Plan

Version: 1.1 | **System:** Flask :5000 + Streamlit :8501 **How to use:** Work top-to-bottom. Mark each item PASS / FAIL / SKIP. Fix all FAILs before client handover.

PRE-FLIGHT (Do this first, every session)

```
`powershell`
```

Terminal 1 – start both servers

```
.\scripts\start.ps1
```

```
` Wait ~10 seconds, then verify:
```

```
|-----|-----|-----|
```

```
> If Flask returns nothing: check terminal for import errors. Common cause: missing package →  
pip install -r requirements.txt
```

SECTION 0 – AUTH (prerequisite for everything)

0.1 Login

- 1. Open `http://localhost:8501`
- 2. Enter username admin + correct password
- 3. Click Login (or press Enter)

Expected: Dashboard loads, sidebar shows all nav items, username visible bottom-left. **Fail signals:** "Invalid credentials", blank page, spinner that never resolves.

0.2 Token auto-refresh (background check)

- Stay logged in for 60+ minutes → dashboard should NOT log you out
- If it does log out: token refresh is broken (check `dashboard/app.py` auto-refresh logic)

0.3 Logout

- 1. Click **Logout** button in sidebar
- 2. **Expected:** Returns to login page, session cleared

0.4 Wrong password logout

- 1. Logout, then attempt login with wrong password 5 times
 - 2. **Expected:** Account locked message appears
 - 3. Login as admin → Admin → Users → Unlock the account
-

SECTION 1 – OVERVIEW PAGE

Navigate to: Overview (first item in sidebar)

1.1 KPI Cards

Expected: Six metric cards visible:

- Memories | Agent Runs | Active Workflows | Projects | Outputs | Open Tickets
- All show numbers (0 is acceptable, "-" or error is NOT)

1.2 System Status (admin-visible)

Expected: Three status badges visible:

- API Status → green "online"
- Database → green "online"
- ChromaDB → green "online" (or yellow "degraded" if chromadb not indexed yet)

> If Database shows red: Flask can't reach SQLite → restart server

1.3 Memory Breakdown

Expected: Per-namespace memory entry counts listed (may be 0 if no memories added yet)

1.4 Quick Dispatch (agent run from Overview)

1. Select any agent from dropdown
2. Select namespace global
3. Type a short prompt: say hello
4. Click Run

Expected: Response appears in the chat area within 30 seconds, no error banner. **Fail signals:** "Stream error", "API unreachable", spinner forever.

1.5 Live Activity Feed

Expected: After completing 1.4, the feed shows the new run with status badge.

1.6 Auto-refresh toggle

1. Toggle on **Auto-refresh**
2. Wait 8-10 seconds
3. **Expected:** Page data refreshes without manual reload, no crash

SECTION 2 – AGENTS PAGE

Navigate to: Agents

2.1 Catalog Tab

1. Click **Catalog** tab
2. **Expected:** Grid of agent cards, each showing name, category badge, model, description

- 3. Try the search box – type analysis
- 4. **Expected:** Filters to matching agents only

> If "No agents registered" appears: run `python scripts/seed_agents.py` then restart

2.2 Basic Chat (text only)

- 1. Click **Chat** tab
- 2. Select analysis-agent (or any enabled agent)
- 3. Namespace: global
- 4. Type prompt: What is 2 + 2?
- 5. Press Enter

Expected: Streaming response appears token-by-token, ends within 30s. Token count shown below response.

2.3 Image Upload (multimodal)

- 1. In Chat tab, use **Attach** panel to upload any .jpg or .png
- 2. Image thumbnail appears below uploader
- 3. Type prompt: Describe what you see in this image
- 4. Press Enter

Expected: Agent responds describing the image content. Response must NOT say "no image received." **Fail signal:** "only text was received" → image pipeline broken (fixed in commit 291eece – verify server was restarted after that commit)

2.4 Multi-turn Conversation

- 1. Send message: My name is Test User
- 2. Send follow-up: What is my name?
- 3. **Expected:** Agent recalls "Test User" from earlier in conversation

2.5 Clear Conversation

- 1. Click **Clear conversation** button
- 2. Send: What is my name?
- 3. **Expected:** Agent does NOT recall "Test User" – fresh context
- 4. **Expected:** Voice input widget also resets (microphone button returns to default state, no previous audio retained)

2.6 A2A Agent Card

- 1. Expand **Agent Card (A2A)** section in left panel
- 2. **Expected:** JSON block showing agent name, capabilities, endpoint URLs

2.7 Run History Tab

- 1. Click **Run History** tab
- 2. **Expected:** Table showing recent runs with columns: Agent, Namespace, Status, Quality, Tokens, Duration
- 3. Runs from steps 2.2–2.4 should appear here

2.8 Voice Input (OPTIONAL – requires whisper)

- 1. Click microphone button, speak a sentence, stop recording
- 2. **Expected:** Text transcribed and placed in prompt field
- 3. **If error:** "openai-whisper not installed" → acceptable, mark SKIP

SECTION 3 – MEMORY PAGE

Navigate to: Memory

3.1 Add a Memory Entry

- 1. Click **Add Entry** tab
- 2. Fill in:
 - Namespace: global
 - Category: fact
 - Key: test_entry_001
 - Value: ClaudeOS QA test entry – created during manual test
 - Source: manual_test
 - Confidence: 1.0
- 3. Click **Save**
- 4. **Expected:** Success message, no error

3.2 Browse Entries

- 1. Click **Browse** tab
- 2. **Expected:** Table of memory entries, test_entry_001 visible
- 3. Try the namespace filter – select global
- 4. **Expected:** Filters to global entries only

3.3 Text Search

- 1. Click **Search** tab
- 2. Mode: text
- 3. Namespace: global
- 4. Query: QA test entry
- 5. **Expected:** test_entry_001 appears in results

3.4 Semantic Search

- 1. Same Search tab
- 2. Mode: semantic
- 3. Query: manual testing
- 4. **Expected:** Results returned (may include test_entry_001 or related entries)
- 5. **Fail signal:** Error about ChromaDB → vector DB issue. Check data/chromadb folder exists.

3.5 Hybrid Search

- 1. Mode: both (hybrid BM25+vector)
- 2. Same query
- 3. **Expected:** Combined results, no error

3.6 Delete Entry

- 1. In Browse tab, find test_entry_001
- 2. Delete it
- 3. **Expected:** Entry removed from list after refresh

SECTION 4 – WORKFLOWS PAGE

Navigate to: Workflows

4.1 Workflows List

- 1. **Workflows** tab
- 2. **Expected:** List of workflows with trigger type (schedule/manual), enabled toggle, step count
- 3. If empty: run python scripts/seed_workflows.py → restart

4.2 Manual Trigger a Workflow

- 1. Find any workflow with trigger type manual or schedule
- 2. Click **Run / Trigger** button
- 3. Context input (optional): leave blank or enter {"test": true}
- 4. Confirm trigger

Expected: Success toast or run record appears. No 500 error.

4.3 Workflow Run History

- 1. Click **Run History** tab
- 2. **Expected:** Table shows the run triggered in 4.2, with status done or running

4.4 Scheduler Tab

- 1. Click **Scheduler** tab
- 2. **Expected:** List of scheduled jobs with cron expression and next run time
- 3. Click **Reload Scheduler**
- 4. **Expected:** Success message, no crash

4.5 Webhooks Tab

- 1. Click **Webhooks** tab
- 2. Pick any workflow → click **Enable Webhook**
- 3. **Expected:** Webhook URL and secret displayed
- 4. Test via curl (in a new terminal):

```
`powershell
```

Replace and with actual values

```
$secret = ""
```

```
$body = '{"test": true}'
```

```
Invoke-WebRequest -Uri "http://localhost:5000/api/v1/workflows//trigger"
```

```
-Method POST
```

```
-Headers @{"X-Webhook-Secret" = $secret; "Content-Type" = "application/json"}
```

```
-Body $body
```

```
..
```

Expected: HTTP 200 response, run record created

SECTION 5 – PROJECTS PAGE

Navigate to: Projects

5.1 Namespace List

- 1. **Namespaces** tab
- 2. **Expected:** Grid/list of namespaces with name, slug, type, project count
- 3. Toggle **Show disabled** – disabled namespaces appear if any exist

> If empty: run python scripts/seed_namespaces.py

5.2 Workspace Stats

- 1. Click any namespace to expand / select it
- 2. **Expected:** File counts per subdirectory (documents, outputs, context, etc.)

5.3 Projects Tab

- 1. Click **Projects** tab
- 2. Select a namespace from dropdown
- 3. **Expected:** Project cards with name, status badge, priority, tech stack

5.4 Create a Project

- 1. Click **New Project** (or equivalent button)
- 2. Fill: Name=QA Test Project, Namespace=global, Status=active
- 3. Save
- 4. **Expected:** Project appears in list

5.5 Context Files

- 1. Click **Context Files** tab
- 2. Select namespace global
- 3. Upload a small .txt file
- 4. **Expected:** File appears in context file list for that namespace

SECTION 6 – OUTPUTS PAGE

Navigate to: Outputs

> Note: Outputs are auto-created when agents run with "Save output" checked. Ensure you ran at least one agent run with save enabled (Section 2.2).

6.1 Browse Outputs

- 1. **Browse** tab
- 2. **Expected:** Table of outputs with type icon, title, namespace, tags, size, date
- 3. Bulk select checkbox works
- 4. Delete a test output with 2-click confirmation

6.2 Search Outputs

- 1. **Search** tab
- 2. Query: agent name used in Section 2
- 3. **Expected:** Matching outputs appear

6.3 Export an Output

- 1. Browse tab → click any output
- 2. Export as **Markdown**
- 3. **Expected:** File download or rendered content, no 404/500

6.4 Stats Tab

- 1. **Stats** tab
- 2. **Expected:** Total count, per-namespace breakdown, per-type breakdown, no error

6.5 Agent Attribution on Saved Outputs

- 1. Run research-agent with a prompt and **Save output** checked
- 2. Run analysis-agent with a different prompt and **Save output** checked
- 3. Navigate to Outputs → Browse

Expected: Two output entries – one titled research-agent – , one titled analysis-agent – . Both use correct agent name, not the same one. **Fail signal:** Both entries show the same agent name (e.g. both say "analysis-agent") → output save is using frontend selectbox state instead of backend registry. Fixed in commit 2afe202.

SECTION 7 – TICKETS PAGE

Navigate to: Tickets

7.1 Create a Ticket

- 1. Click **Create** tab
- 2. Fill:
 - Title: QA Test Ticket
 - Description: Testing ticket creation during QA
 - Category: bug
 - Priority: medium
 - Namespace: global
- 3. Submit
- 4. **Expected:** Success, ticket appears in Browse tab

7.2 Browse Tickets

- 1. **Browse** tab
- 2. **Expected:** QA Test Ticket visible, with SLA due date, status=open
- 3. Status filter works (filter by open)
- 4. Priority filter works

7.3 Advance Ticket Status

- 1. Click on QA Test Ticket
- 2. Change status: open → assigned → work_in_progress → completed
- 3. **Expected:** Each transition saves successfully

7.4 My Tickets Tab

- 1. Click **My Tickets**
- 2. **Expected:** QA Test Ticket appears (you are creator)

7.5 Bulk Delete

- 1. Browse tab → select QA Test Ticket via checkbox
- 2. Click **Delete Selected**
- 3. Confirm
- 4. **Expected:** Ticket removed

SECTION 8 – OBSERVABILITY PAGE

Navigate to: Observability

(Only visible to admin and operator roles)

8.1 Quality Scores Tab

- 1. **Expected:** Bar chart of per-agent quality averages (0-5 scale)

- 2. Scores from agent runs in Section 2 should appear here
- 3. Agents with 0 runs show 0 or are absent

8.2 Latency Tab

- 1. **Expected:** Table showing p50/p95/p99 latency per agent
- 2. Agents run in Section 2 should have values

8.3 Token Cost Tab

- 1. **Expected:** Token usage breakdown per agent, cost estimate in USD

8.4 Memory Health Tab

- 1. **Expected:**
 - Total memory entries count
 - Stale entries count
 - Consolidation status (last run time)
 - Suggestion to run consolidation if stale entries > threshold

8.5 Namespace Usage Tab

- 1. **Expected:** Tab visible (admin/operator only)
- 2. Table showing per-namespace: runs count, input tokens, output tokens, estimated USD cost, avg quality score, memory entries
- 3. Stacked bar chart (plotly) comparing token usage across namespaces
- 4. Data based on up to 500 most recent runs – no error on low-run systems (zeros acceptable)

SECTION 9 – SETTINGS PAGE

Navigate to: Settings

9.1 Email / Notification Config

- 1. **Expected:** SMTP fields visible (host, port, from, to)
- 2. Values should match .env (smtp.gmail.com, port 587)
- 3. Edit a field → Save → Reload page → value persists

9.2 Supabase Sync Status

- 1. **Expected:** Status badge visible
- 2. If Supabase is configured: click **Test Connection** → should return success or clear error
- 3. Click **Manual Push** → status updates
- 4. If Supabase not configured: badge shows "not configured" or "disabled" → mark SKIP

9.3 Sync Log – Single Entry Delete

- 1. Scroll to **Sync Log** section (last 50 runs)
- 2. Find any row in the Individual delete list
- 3. Click the  button on that row
- 4. **Expected:** Success toast, row disappears on rerun
- 5. **Fail signal:** 404 (entry ID missing) or 500 (delete query error)

9.4 Sync Log – Bulk Select & Delete

- 1. In the Sync Log st.data_editor, tick the ☒ checkbox on 2-3 rows
- 2. **Expected:** "Delete Selected (N)" button becomes enabled, label updates with count
- 3. Click **Delete Selected (N)**
- 4. **Expected:** Success toast "Deleted N entries", table refreshes with those rows gone
- 5. Try clicking **Select All** – **Expected:** editor state clears and all rows become selected on next render
- 6. Click Delete Selected with 0 rows checked – **Expected:** button is disabled, no action possible

SECTION 10 – ADMIN PAGE

Navigate to: Admin

(Admin role required)

10.1 Users Tab

- 1. **Expected:** Table of all users with role, namespace, active status
- 2. Admin user (yourself) visible
- 3. Click **Create User:**
 - Username: qa_test_user
 - Password: TestUser123!
 - Role: viewer
 - Namespace: global
- 4. **Expected:** User appears in table

10.2 API Keys Tab

- 1. Click **Create API Key**
- 2. Name: QA Test Key, Permissions: read, Namespace: global
- 3. **Expected:** Key created, token displayed (copy it – shown only once)
- 4. Test the key:

```
`powershell
```

```
Invoke-WebRequest -Uri "http://localhost:5000/api/v1/health"
```

```
-Headers @{ "X-API-Key" = "" }
```

```
`
```

- 5. **Expected:** 200 OK

10.3 Audit Log Tab

- 1. **Expected:** Table of recent events (login_success, user_created, etc.)
- 2. Actions from this test session should appear
- 3. Filter by event type login_success → only login events shown

10.4 Sessions Tab

- 1. **Expected:** List of active sessions with IP, user-agent, expiry
- 2. Your current session visible
- 3. Revoke the qa_test_user session if one exists → no error

10.5 Security Settings Tab

- 1. **Expected:** Fields for:
 - Max failed attempts (default: 5)
 - Lockout minutes (default: 15)
 - Access token TTL minutes (default: 60)
 - Allow self-registration (toggle)
- 2. Change a value → Save → **Expected:** Success message, value persists on refresh

10.6 Edit User

- 1. In Users tab, select any non-admin user from the dropdown
- 2. Click  **Edit** button
- 3. **Expected:** Dialog opens with current values pre-filled (role, namespace, email, active, force-pw)
- 4. Change Role to viewer, tick **Force password change on next login**
- 5. Click **Save changes**
- 6. **Expected:** Toast "User updated", dialog closes, table reflects new values
- 7. Reopen Edit → verify saved values persist

10.7 Delete User (Permanent)

- 1. Create a fresh test user qa_delete_test / TestUser123! / role=viewer
- 2. Select it from the Users dropdown
- 3. Click  **Delete** button
- 4. **Expected:** Dialog opens: "Permanently delete qa_delete_test?"
- 5. Click **Yes, delete permanently**
- 6. **Expected:** Toast "User permanently deleted", dialog closes, user absent from table
- 7. Verify: try to log in as qa_delete_test → **Expected:** "Invalid credentials" (user gone from DB)

10.8 Cleanup test data

- 1. Delete qa_test_user from Users tab (if not already deleted in 10.7)

- 2. Revoke QA Test Key from API Keys tab

10.9 Client Onboarding Tab

- 1. Click **Client Onboarding** tab (6th tab in Admin Panel)
- 2. **Expected:** Dropdown of client namespaces (not global/personal – client-type only)
- 3. Select a namespace → 14 fields appear (business name, industry, primary goals, brand tone, SLA tier, contact name, contact email, timezone, preferred language, custom instructions, etc.)
- 4. Fill in 2-3 fields → click **Save**
- 5. **Expected:** Success message; navigate away and return – values persist

10.10 Admin Unlock (Context-Aware)

- 1. In Users tab, find a user that is NOT locked
- 2. **Expected:** No "Unlock" button visible for unlocked users (button only appears when locked)
- 3. Lock a test account by logging in with wrong password 5 times (from Section 0.4)
- 4. Return to Admin → Users → find the locked user
- 5. **Expected:** Lock warning with expiry time AND a prominent Unlock button visible
- 6. Click Unlock → **Expected:** Lock cleared immediately, user can log in

SECTION 12 – USAGE DASHBOARD (client/viewer only)

Login as a client or viewer role user first.

Navigate to: **Usage** (■ in sidebar)

> This page is NOT visible to admin/operator/staff. If logged in as admin, you will see an info message redirecting you to Observability.

12.1 KPI Grid

- 1. **Expected:** Six metric cards visible: AI Runs (30d), Tokens In, Tokens Out, Est. Cost, Avg Quality, Outputs
- 2. All values load without error (0 is acceptable, error banners are NOT)

12.2 Namespace Pulse Score

- 1. **Expected:** Circular SVG gauge visible showing a score 0-100
- 2. Label below gauge shows rating: Excellent (≥85) / Good (≥70) / Fair (≥50) / Needs Attention (<50) / Getting Started (no data)
- 3. Score breakdown table below gauge shows 4 dimensions with weights: Quality Score (40%), Ticket Resolve (30%), Memory Fresh (20%), Workflow OK (10%)

12.3 Recent Activity Feed

- 1. **Expected:** List of recent AI runs for this namespace – agent name (human-readable, not UUID), status badge, timestamp
- 2. If no runs: empty state message, no error

12.4 Memory Summary

- 1. **Expected:** Memory entry count and freshness indicator visible

SECTION 13 – NAMESPACE BRANDING (admin)

Navigate to: Admin → Branding tab (7th tab)

13.1 Branding Tab Visible

- 1. **Expected:** Branding tab is the 7th tab in Admin Panel
- 2. Dropdown of client namespaces visible (not global)

13.2 Set Namespace Brand

- 1. Select a client namespace
- 2. Fill in: Company Name = QA Test Co, Icon = ■, Primary Color = #2563EB, Accent Color = #3B82F6
- 3. Click **Save**
- 4. **Expected:** Success message

13.3 Client Sees Branded Sidebar

- 1. Log out, log in as a client user assigned to that namespace
- 2. **Expected:** Sidebar logo area shows ■ QA Test Co instead of raw namespace slug
- 3. **Expected:** Pill color in aurora hero header matches brand color (approximately)

13.4 Cleanup

- 1. Log back in as admin
- 2. Admin → Branding → select namespace → clear Company Name and Icon → Save

SECTION 11 – CROSS-CUTTING CHECKS

These apply to ALL pages.

11.1 Role Scoping

- 1. Login as qa_test_user (viewer role, created in 10.1 – recreate if deleted)
- 2. **Expected nav visible:** Overview, Agents, Memory, Projects, Outputs, Tickets, **Usage (■)**
- 3. **Expected nav HIDDEN:** Workflows, Observability, Settings, Admin
- 4. Verify Usage page loads with Pulse Score and KPI grid (not an error page)
- 5. Try navigating directly to Admin → should redirect to login or show "Access denied"
- 6. Logout, re-login as admin
- 7. **Admin nav visible:** Overview, Agents, Memory, Workflows, Projects, Outputs, Tickets, Observability, Settings, Admin
- 8. **Admin nav HIDDEN:** Usage (admin uses Observability instead)

11.2 Dark/Light Mode

- 1. Click the circular toggle button (bottom area, fixed at left:220px – clears sidebar text)
- 2. **Expected:** Entire dashboard switches theme – background, text, cards, sidebar all update
- 3. Switch back – state persists during session

11.2a Toolbar Header Icons (visual regression)

Check the Streamlit native header bar (top-right: Stop / Deploy / ■ menu) in **both** themes.

```
|-----|-----|-----|
```

Fail signal: A solid colored square appears next to "Deploy". Root cause: CSS fill override on the MoreVert SVG bounding-box path. Fix: ensure brand.py path selectors use `:not([fill="none"])` and JS checks `getAttribute('fill') === 'none'` before setting fill.

11.5 Onboarding Tour (first-time user)

- 1. Create a brand-new user with role client or viewer (tour ONLY shows for these two roles – admin/operator/staff skip it entirely)
- 2. Log in as that user for the first time
- 3. **Expected:** Onboarding tour/modal appears with 5 slides (Welcome, Agents, Memory, Tickets, Usage)
- 4. Click through or dismiss it
- 5. Log out, log back in
- 6. **Expected:** Onboarding does NOT appear again (persisted via onboarding_done DB column)
- 7. **If tour doesn't appear:** Check role – must be client or viewer. Admin can fix via Users tab → ■ Edit → change role

11.3 Error Handling

For each page, check:

- No red Python tracebacks visible to user (internal errors should show friendly message)
- No NoneType or KeyError stack traces in the UI

11.4 API Key Auth (alternative to JWT)

```
`powershell
```

Replace with actual API key from Section 10.2

```
$key = ""
```

```
Invoke-WebRequest "http://localhost:5000/api/v1/agents" -Headers @{ "X-API-Key" = $key }
```

```
` Expected: 200 with agents list
```

KNOWN ISSUES TO VERIFY FIXED

```
|-----|-----|-----|
```

Check	How	Expected	
Flask alive	Browser → http://localhost:5000/api/v1/health	{"status":"ok"}	
Streamlit alive	Browser → http://localhost:8501	Login page loads	
DB exists	File exists: data/claudeos.db	File present, non-zero size	
ChromaDB exists	Folder exists: data/chromadb	Folder present	
Element	Dark Mode Expected	Light Mode Expected	
Header background	Dark green #0A1F0A	White #ffffff	
"Deploy" button text	Light #E8F5E8	Dark #1A1A1A	
■ menu button	Three visible dots, transparent bg	Three visible dots, transparent bg	
No solid squares	No filled square anywhere in header	No filled square anywhere in header	
Issue	Fix Commit	How to Verify	
Images not sent to agent chat	291eece	Section 2.3 – image analysis works	
Overview stats failed on non-main thread	bed94f7	Section 1.1 – KPI cards load without error	
Browser refresh loses active page	64c4140	Navigate to Agents, press F5 – stays on Agents	
XSS escaping / security hardening	63a83d6	Inputs accept text; no script injection renders	
Voice input widget not clearing on conversation reset	208d58b	Section 2.5 – after Clear, microphone widget resets	
Analysis agent namespace scope warning in logs	8a36d10	Run analysis-agent – no scope warning in Flask terminal	
Workflow run delete broken	8a36d10	Section 4.3 – delete a run history entry, no 500 error	

Theme toggle overlapping sidebar text	86bbade	Section 11.2 – toggle at bottom-left (left:220px), clears sidebar	
Onboarding shows again after logout/re-login	03366f6	Complete onboarding, logout, log back in – tour does NOT appear again	
Memory namespace list hardcoded to local path	5423ba2	Memory page namespace filter populates from API, not error	
Context tiers duplicated when namespace==global	70860f2	Run agent in global namespace – no duplicate context in prompt	
Admin unlock button always visible (not context-aware)	eba9751	Section 10.10 – Unlock only shown for actually-locked users	
Delete User broken (session-state confirm + nested columns)	528346c	Section 10.7 – Delete dialog opens, permanent delete works	
Edit User missing	528346c	Section 10.6 – Edit dialog opens, all fields save correctly	
must_change_password silently dropped on PATCH	528346c	Section 10.6 – Force password change toggle saves via Edit dialog	
Reactivate user broken (api_post PATCH)	528346c	Section 10.1 – Deactivate then Reactivate works without error	
Output delete silently fails on older SQLite	0cad72	Section 6.1 – Delete output, confirm it disappears from list	
Output timestamps date-only (no time)	0cad72	Section 6.1 – Timestamps show YYYY-MM-DD HH:MM not just date	
Activity feed shows UUID not agent name	552e5b3	Section 1.5 – Feed shows readable agent names, not truncated UUIDs	

Analysis agent fabricates data when given nothing	49c6631	Ask analysis-agent a vague question with no data – it must ask clarifying questions, not invent results	
Agents hallucinate when input missing	b1211e5	Ask briefing/research/writing agents with no context – must request specific inputs, not produce generic output	
Analysis/client-manager agents use training data for business facts	87815fb	Ask analysis-agent "what cities does X deliver to?" with no data – must trigger MISSING INPUT PROTOCOL, not answer from training knowledge; ask client-manager to draft an email – must respond with one-line redirect only	
Evaluator penalizes correct scope refusals (task_completion: 0.0)	11f51e5	Run client-manager-agent on an out-of-scope prompt (e.g. "draft an email") – Observability Quality Scores must show ≥ 4.0 , not near 0	
Sync log delete returns "Delete failed"	26d1d38	Section 9.3 – delete a sync log entry, confirm it disappears. Was false 404 due to SELECT changes() resetting after commit	
Voice widget not resetting on Clear Conversation	b969309	Section 2.5 – After Clear, microphone widget resets to default state	
Both outputs from different agents show same agent name	2afe202	Section 6.5 – run research-agent then analysis-agent with save; outputs must show correct agent names	

Stream error message flashes and disappears on rerun	2afe202	Run any agent when API is down/exhausted – error must appear as a persistent red message in chat history, not flash once and vanish	
Output not saving after streaming completes	2afe202	Section 6.5 – saved outputs appear in Outputs page immediately after stream finishes; no silent drop	

PASS/FAIL SUMMARY SHEET

Copy this to track results:

SECTION 0 – AUTH

0.1 Login []

0.2 Token refresh []

0.3 Logout []

0.4 Lockout []

SECTION 1 – OVERVIEW

1.1 KPI Cards []

1.2 System Status []

1.3 Memory Breakdown []

1.4 Quick Dispatch []

1.5 Activity Feed []

1.6 Auto-refresh []

SECTION 2 – AGENTS

2.1 Catalog []

2.2 Basic Chat []

2.3 Image Upload []

2.4 Multi-turn []

2.5 Clear Conversation []

2.6 A2A Agent Card []

2.7 Run History []

2.8 Voice Input [SKIP if no whisper]

SECTION 3 – MEMORY

3.1 Add Entry []

3.2 Browse []

3.3 Text Search []

3.4 Semantic Search []

3.5 Hybrid Search []

3.6 Delete Entry []

SECTION 4 – WORKFLOWS

4.1 List []

4.2 Manual Trigger []

4.3 Run History []

4.4 Scheduler []

4.5 Webhooks []

SECTION 5 – PROJECTS

5.1 Namespace List []

5.2 Workspace Stats []

5.3 Projects Tab []

5.4 Create Project []

5.5 Context Files []

SECTION 6 – OUTPUTS

6.1 Browse []

6.2 Search []

6.3 Export []

6.4 Stats []

6.5 Agent Attribution []

SECTION 7 – TICKETS

7.1 Create []

7.2 Browse + Filter []

7.3 Status Transitions []

7.4 My Tickets []

7.5 Bulk Delete []

SECTION 8 – OBSERVABILITY

8.1 Quality Scores []

8.2 Latency []

8.3 Token Cost []

8.4 Memory Health []

8.5 Namespace Usage []

SECTION 9 – SETTINGS

9.1 Email Config []

9.2 Supabase Sync [SKIP if not configured]

9.3 Sync Log Single Delete []

9.4 Sync Log Bulk Delete []

SECTION 10 – ADMIN

10.1 Users []

10.2 API Keys []

10.3 Audit Log []

10.4 Sessions []

10.5 Security Settings []

10.6 Edit User (dialog) []

10.7 Delete User (permanent) []

10.8 Cleanup []

10.9 Client Onboarding Tab []

10.10 Admin Unlock (ctx-aware)[]

SECTION 11 – CROSS-CUTTING

11.1 Role Scoping []

11.2 Dark/Light Mode []

11.3 Error Handling []

11.4 API Key Auth []

11.5 Onboarding Tour []

SECTION 12 – USAGE DASHBOARD

12.1 KPI Grid []

12.2 Pulse Score []

12.3 Activity Feed []

12.4 Memory Summary []

SECTION 13 – NAMESPACE BRANDING

13.1 Branding Tab Visible []

13.2 Set Namespace Brand []

13.3 Client Sees Branding []

13.4 Cleanup []

SECTION 14 – COMMERCIAL PACKAGE

14.1 Build Distribution ZIP []

14.2 ZIP Contents Integrity []

14.3 Dev Scripts Excluded []

14.4 Handbook PDF Integrity []

14.5 Landing Pages Load []

`

SECTION 14 – COMMERCIAL PACKAGE

14.1 Build Distribution ZIP

`powershell

python scripts/build_package.py

` **Expected output:**

- dist/FaiykeOS-v17.0.zip created (~475 KB, ~153 files)
- Console shows: Secret leaks: NONE, file count, size

Fail signals: Python error, zip not created, size 0 KB

14.2 ZIP Contents Integrity

`powershell

python -c "

import zipfile

z = zipfile.ZipFile('dist/FaiykeOS-v17.0.zip')

names = z.namelist()

bad = [n for n in names if '.env' in n and 'example' not in n]

print('Secret leaks:', bad if bad else 'NONE')

print('Has handbook:', any('FaiykeOS_Handbook' in n for n in names))

```
print('Has landing:', any('landing/index.html' in n for n in names))

print('Has requirements:', any('requirements.txt' in n for n in names))

"
```

` **Expected:**

- Secret leaks: NONE – .env not in ZIP
- Has handbook: True
- Has landing: True
- Has requirements: True

14.3 Dev Scripts Excluded

```
`powershell

python -c "

import zipfile

z = zipfile.ZipFile('dist/FaiykeOS-v17.0.zip')

dev = [n for n in z.namelist() if any(s in n for s in
['debug_namespaces', 'delete_faiyke', 'fix_faiyke', 'seed_faiyke', 'build_package'])]

print('Dev scripts leaked:', dev if dev else 'NONE')

"
```

` **Expected:** Dev scripts leaked: NONE

14.4 Handbook PDF Integrity

- 1. Open docs/FaiykeOS_Handbook_faiyke-ai.pdf
- 2. **Expected:** Cover page shows **FaiykeOS** (not ClaudeOS)
- 3. Footer shows FaiykeOS v17.0 · faiyke-ai
- 4. No duplicate footer on last page

14.5 Landing Pages Load

- 1. Open docs/landing/index.html in browser (double-click or start)
- 2. **Expected:** Hero loads with green gradient, "FaiykeOS" heading visible, no broken CSS
- 3. Open docs/landing/pricing.html`
- 4. **Expected:** 3 pricing cards visible (\$197 / \$997+\$147mo / \$497+\$97mo), comparison table renders

REPORTING A FAILURE

When a test fails, note:

- 1. **Section + step number** (e.g. "3.4 Semantic Search")
- 2. **Exact error message** shown in UI
- 3. **Flask terminal output** – any Python traceback at the time of the failure

- 4. **Browser console errors** (F12 → Console tab)

This gives enough info to diagnose and fix quickly.