

UNIX / LINUX - NETWORK COMMUNICATION UTILITIES

<http://www.tutorialspoint.com/unix/unix-communication.htm>

Copyright © tutorialspoint.com

Advertisements

In this chapter, we will discuss in detail about network communication utilities in Unix. When you work in a distributed environment, you need to communicate with remote users and you also need to access remote Unix machines.

There are several Unix utilities that help users compute in a networked, distributed environment. This chapter lists a few of them.

The ping Utility

The **ping** command sends an echo request to a host available on the network. Using this command, you can check if your remote host is responding well or not.

The ping command is useful for the following –

- Tracking and isolating hardware and software problems.
- Determining the status of the network and various foreign hosts.
- Testing, measuring, and managing networks.

Syntax

Following is the simple syntax to use the ping command –

```
$ping hostname or ip-address
```

The above command starts printing a response after every second. To come out of the command, you can terminate it by pressing **CNTRL + C** keys.

Example

Following is an example to check the availability of a host available on the network –

```
$ping google.com
PING google.com (74.125.67.100) 56(84) bytes of data.
64 bytes from 74.125.67.100: icmp_seq = 1 ttl = 54 time = 39.4 ms
64 bytes from 74.125.67.100: icmp_seq = 2 ttl = 54 time = 39.9 ms
64 bytes from 74.125.67.100: icmp_seq = 3 ttl = 54 time = 39.3 ms
64 bytes from 74.125.67.100: icmp_seq = 4 ttl = 54 time = 39.1 ms
64 bytes from 74.125.67.100: icmp_seq = 5 ttl = 54 time = 38.8 ms
--- google.com ping statistics ---
22 packets transmitted, 22 received, 0% packet loss, time 21017ms
rtt min/avg/max/mdev = 38.867/39.334/39.900/0.396 ms
$
```

If a host does not exist, you will receive the following output –

```
$ping giiiiiiigle.com
ping: unknown host giiiiiiigle.com
$
```

The ftp Utility

Here, **ftp** stands for **F**ile **T**ransfer **P**rotocol. This utility helps you upload and download your file from one computer to another computer.

The ftp utility has its own set of Unix-like commands. These commands help you perform tasks such as –

- Connect and login to a remote host.
- Navigate directories.
- List directory contents.
- Put and get files.
- Transfer files as **ascii**, **ebcdic** or **binary**.

Syntax

Following is the simple syntax to use the ping command –

```
$ftp hostname or ip-address
```

The above command would prompt you for the login ID and the password. Once you are authenticated, you can access the home directory of the login account and you would be able to perform various commands.

The following tables lists out a few important commands –

Sr.No.	Command & Description
1	put filename Uploads filename from the local machine to the remote machine.
2	get filename Downloads filename from the remote machine to the local machine.
3	mput file list Uploads more than one file from the local machine to the remote machine.
4	mget file list Downloads more than one file from the remote machine to the local machine.
5	prompt off Turns the prompt off. By default, you will receive a prompt to upload or download files using mput or mget commands.
6	prompt on Turns the prompt on.
7	

	dir Lists all the files available in the current directory of the remote machine.
8	cd dirname Changes directory to dirname on the remote machine.
9	lcd dirname Changes directory to dirname on the local machine.
10	quit Helps logout from the current login.

It should be noted that all the files would be downloaded or uploaded to or from the current directories. If you want to upload your files in a particular directory, you need to first change to that directory and then upload the required files.

Example

Following is the example to show the working of a few commands –

```
$ftp amrood.com
Connected to amrood.com.
220 amrood.com FTP server (Ver 4.9 Thu Sep 2 20:35:07 CDT 2009)
Name (amrood.com:amrood): amrood
331 Password required for amrood.
Password:
230 User amrood logged in.
ftp> dir
200 PORT command successful.
150 Opening data connection for /bin/ls.
total 1464
drwxr-sr-x    3 amrood   group        1024 Mar 11 20:04 Mail
drwxr-sr-x    2 amrood   group        1536 Mar  3 18:07 Misc
drwxr-sr-x    5 amrood   group         512 Dec  7 10:59 OldStuff
drwxr-sr-x    2 amrood   group       1024 Mar 11 15:24 bin
drwxr-sr-x    5 amrood   group       3072 Mar 13 16:10 mpl
-rw-r--r--    1 amrood   group     209671 Mar 15 10:57 myfile.out
drwxr-sr-x    3 amrood   group         512 Jan  5 13:32 public
drwxr-sr-x    3 amrood   group         512 Feb 10 10:17 pvm3
226 Transfer complete.
ftp> cd mpl
250 CWD command successful.
ftp> dir
200 PORT command successful.
150 Opening data connection for /bin/ls.
total 7320
-rw-r--r--    1 amrood   group        1630 Aug  8 1994  dboard.f
-rw-r-----   1 amrood   group        4340 Jul 17 1994  vttest.c
-rwxr-xr-x    1 amrood   group     525574 Feb 15 11:52  wave_shift
-rw-r--r--    1 amrood   group        1648 Aug  5 1994  wide.list
-rwxr-xr-x    1 amrood   group        4019 Feb 14 16:26  fix.c
226 Transfer complete.
ftp> get wave_shift
```

```
200 PORT command successful.
150 Opening data connection for wave_shift (525574 bytes).
226 Transfer complete.
528454 bytes received in 1.296 seconds (398.1 Kbytes/s)
ftp> quit
221 Goodbye.
$
```

The telnet Utility

There are times when we are required to connect to a remote Unix machine and work on that machine remotely. **Telnet** is a utility that allows a computer user at one site to make a connection, login and then conduct work on a computer at another site.

Once you login using Telnet, you can perform all the activities on your remotely connected machine. The following is an example of Telnet session –

```
C:>telnet amrood.com
Trying...
Connected to amrood.com.
Escape character is '^]'.

login: amrood
amrood's Password:
*****
*                                                                    *
*                                                                    *
*      WELCOME TO AMROOD.COM                                         *
*                                                                    *
*                                                                    *
*****

Last unsuccessful login: Fri Mar  3 12:01:09 IST 2009
Last login: Wed Mar  8 18:33:27 IST 2009 on pts/10

    {  do your work  }

$ logout
Connection closed.
C:>
```

The finger Utility

The **finger** command displays information about users on a given host. The host can be either local or remote.

Finger may be disabled on other systems for security reasons.

Following is the simple syntax to use the finger command –

Check all the logged-in users on the local machine –

```
$ finger
Login      Name      Tty      Idle   Login Time   Office
amrood                pts/0                Jun 25 08:03 (62.61.164.115)
```

Get information about a specific user available on the local machine –

```
$ finger amrood
Login: amrood                Name: (null)
Directory: /home/amrood      Shell: /bin/bash
On since Thu Jun 25 08:03 (MST) on pts/0 from 62.61.164.115
No mail.
No Plan.
```

Check all the logged-in users on the remote machine –

```
$ finger @avtar.com
Login      Name      Tty      Idle    Login Time    Office
amrood          pts/0          Jun 25 08:03 (62.61.164.115)
```

Get the information about a specific user available on the remote machine –

```
$ finger amrood@avtar.com
Login: amrood                      Name: (null)
Directory: /home/amrood           Shell: /bin/bash
On since Thu Jun 25 08:03 (MST) on pts/0 from 62.61.164.115
No mail.
No Plan.
```