

https://github.com/t-o-k/Maxima-bezier/bezier_basis_functions.wmxm

Copyright (c) 2020 Tor Olav Kristensen, <http://subcube.com>

Use of this source code is governed by the GNU Lesser General Public License version 3, which can be found in the LICENSE file.

```
(%i1) kill(all)$
```

```
(%i2) load("draw")$  
load("bezier")$
```

```
(%i3) set_draw_defaults(  
  xrange = [ 0, 1 ],  
  yrange = [ 0, 1 ],  
  xlabel = "s",  
  ylabel = "",  
  grid = true  
)$
```

```
(%i4) degree_s: 3$
```


```
(%i5) define(bf_1a(s), basis_functions_1a(degree_s, s));
```

```
(%o5) bf_1a(s):=
$$\begin{pmatrix} (1-s)^3 & 3(1-s)^2 s & 3(1-s)s^2 & s^3 \end{pmatrix}$$

```

```
(%i6) wxdraw2d(
    color = red,
    parametric(s, bf_1a(s)[1, 1], s, 0, 1),
    color = green,
    parametric(s, bf_1a(s)[1, 2], s, 0, 1),
    color = blue,
    parametric(s, bf_1a(s)[1, 3], s, 0, 1),
    color = magenta,
    parametric(s, bf_1a(s)[1, 4], s, 0, 1)
)$
```

(%t6)



```
(%i7) set_draw_defaults(
    xrange = [ 0, 1 ],
    yrange = [ 0, 1 ],
    zrange = [ 0, 1 ],
    cbrange = [ 0, 1 ],
    colorbox = false,
    xu_grid = 15,
    yv_grid = 15,
    xlabel = "u",
    ylabel = "v",
    zlabel = "",
    grid = true,
    color = gray,
    wired_surface = true,
    surface_hide = false,
    enhanced3d = true,
    view = [ 80, 10 ]
)$
```

```
(%i9) degree_u: 2$
       degree_v: 2$
```

```
(%i10) define(bf_2a(u, v), basis_functions_2a(degree_u, degree_v, u, v));
```

```
(%o10) bf_2a(u, v) :=
```


$$\begin{pmatrix} (1-u)^2(1-v)^2 & 2(1-u)u(1-v)^2 & u^2(1-v)^2 \\ 2(1-u)^2(1-v)v & 4(1-u)u(1-v)v & 2u^2(1-v)v \\ (1-u)^2v^2 & 2(1-u)uv^2 & u^2v^2 \end{pmatrix}$$

```
(%i11) bf_2a(u, v)[2, 1];
```

```
(%o11) 2 (1-u)^2 (1-v) v
```

```
(%i12) wxdraw3d(
  title = "Basis function [2, 1]",
  parametric_surface(
    u,
    v,
    bf_2a(u, v)[2, 1],
    u, 0, 1,
    v, 0, 1
  )
)$
```

```
(%t12)
```




```
(%i13) bf_2a(u, v)[2, 2];
```

```
(%o13) 4 (1-u) u (1-v) v
```

```
(%i14) wxdraw3d(
    title = "Basis function [2, 2]",
    parametric_surface(
        u,
        v,
        bf_2a(u, v)[2, 2],
        u, 0, 1,
        v, 0, 1
    )
)$
```

(%t14)




```
(%i15) bf_2a(u, v)[3, 3];
```

```
(%o15) 
$$u^2 v^2$$

```

```
(%i16) wxdraw3d(  
    title = "Basis function [3, 3]",  
    parametric_surface(  
        u,  
        v,  
        bf_2a(u, v)[3, 3],  
        u, 0, 1,  
        v, 0, 1  
    )  
);
```

(%t16)



(%o16)