Wire record: ASSUMED-HYDRO

The tension member's history log across cruises (RVSS Appendix A, A.5.2.1), from ASSUMED-HYDRO/: the deployments of every cruise merged in, and the operator's events (events.toml): break tests, cutbacks, spooling, lubrication, test results and terminations. Written by winch-data-processing 0.1.0.

The tension member

NSF identifier	ASSUMED-HYDRO
Kind	cable
Description	assumed: 0.322 in. 3-conductor EM cable
Nominal breaking load	10000 lbf
Factor of safety, selected	2.5
Break test	2023-11-15: 10200 lbf

Maintenance

Length	7,970.0 m: 8,000.0 m spooled on 2023-06-20, 30.0 m cut back since
Last lubrication	2024-01-10: illustrative lubricant, 2,500.0 m; illustrative: the outer 2,500 m, in port
Last termination	2024-02-05: illustrative mechanical termination, proof tested to 4000 lbf; illustrative: proof tested to the SWT
Last test: resistance	2024-02-06: illustrative: conductors within specification

Deployments

	Deployments	Hours	Deepest [m]	Highest tension [lbf]	Lowest FS	Cruises
Since the last break test (2023-11-15)	1	0.5	499.8	3593	2.78	1
Over the record	1	0.5	499.8	3593	2.78	1

Since the last break test counts the deployments that started on or after its date (a test has a date, not a time). Each FS is with its cruise's ABL.

By cruise

Cruise	Vessel	Winch	Dates	Deployments	Hours	Deepest [m]	Highest tension [lbf]
RR2403	Roger Revelle	hydro	2024-04-06 to 2024-04-06	1	0.5	499.8	3593

Since the last break test (2023-11-15)

Cruise	Winch	#	Start (UTC)	Duration [s]	Max payout [m]	Max tension [lbf]	Min FS
RR2403	hydro	1	2024-04-06 21:58:25	1850.5	499.8	3593	2.78

Events

Date	Event	Details
2023-06-20	Spooling	8,000.0 m on the drum, hydro; illustrative: new wire spooled
2023-11-15	Break test	TBL 10200 lbf; illustrative: TBL above the NBL, so the ABL stays the NBL
2024-01-10	Lubrication	illustrative lubricant, 2,500.0 m; illustrative: the outer 2,500 m, in port
2024-02-05	Cutback	30.0 m cut (re-terminating); illustrative
2024-02-05	Termination	illustrative mechanical termination, proof tested to 4000 lbf; illustrative: proof tested to the SWT
2024-02-06	Test	resistance: illustrative: conductors within specification; after re-terminating