Ch 7: Loops in Python

Sometimes we need to repeat a set of instructions in our program.
eg - print 1 to 100

```
print(1)
print(2)
  ⋮                  → This is a dumb way.
print(100)
```

We use loops to make this easier.

→ for loop
→ while loop

```
while <condition>:   ← Syntax
    # Code #
```
(True/False)

The code inside while loop will only be executed if the condition is True. The loop terminates once the condition is False.

```
while (4>3):          → True
    print("loop")     → "loop" will be printed infinite times

while (7==8):         → False
    print("loop")     → "loop" will not be printed as the condition gets False
```

```
i = 0
while (i<10):
    i = i+1
    print("this is good", i)  → this is good 1
                                this is good 2
                                =====
                                this is good 10
```

As soon as the condition becomes False [i=10 & 10≠10] the loop stops executing.

Q→ Write a program to print first n natural numbers in reverse order.

- break keyword - This instructs a loop to stop.

```
i = 0
while (i<10):
    i += 1
    print(i)
    if (i==6):
        break  → 1
                 2
                 3
                 4
                 5
                 6
```

- continue keyword - Helps you to skip the current instruction.

```
i = 0
while (i<10):
    i += 1
    if (i==6):
        continue
    print(i) → 1
               2
               3
               4
               5
               7   } → skipped 6
               8
               9
               10
```

- pass keyword - This instructs a program to do nothing

```
if (10==1):
    print("Good")
```

↳ "Good" will be printed

```
if (10>=1):
    pass
```

↳ This will do nothing

For loop

for loops can be used in lists, tuples, sets.

```
li = ['Python', 10, True]
for i in li
    print(i) → Python
               10
               True
```

range() function

This is used to generate a sequence of numbers.

range (starting integer, stop)

range (100) → [0, 1, 2, 3, 4, ---------99]

→ start is by default 0
→ last number not included

range (1, 101) → [1, 2, 3, 4, 5 - - - - 98, 99, 100]

- for loop with else

```
for i in [2,4,9,6]:
    print(i)
else:
    print("Task completed!")
```

→ The else is executed only when for loop completes it's process.

If the for loop breaks, else won't be executed.

range (1, 101, 4) → [1, 5, 9, 13, 17, ------, 93, 97]

step size

+4 +4 +4 +4