

The kinshipsymbols package*

Alejandro Ochoa
<https://ochoalab.github.io/>

December 11, 2025

Abstract

This package defines consistent mathematical symbols for statistical genetics, particularly relating to the kinship model and F_{ST} . In addition to providing a long list of symbols, the package has two options that alter the behavior of some of the most common symbols. Option `color` highlights genotypes (blue), kinship coefficients (dark green), and the standard ancestral allele frequency estimator (red), which is useful for Beamer presentations. Option `noT` removes the ancestral population T superscript from all symbols that contain it (for simpler presentations).

Contents

1	Introduction	2
2	Implementation	7
2.1	Dependencies	7
2.2	Initializing variables, modify depending on options	7
2.3	Commands for math operators	8
2.4	Genotypes	9
2.5	Ancestral allele frequencies	9
2.6	Wright's F_{ST}	10
2.7	Inbreeding coefficients	11
2.8	Kinship coefficients	11
2.9	Review of previous work	13
2.10	Convergence arrows	13
2.11	F_{ST} estimators for independent subpopulations	14
2.12	Estimators based on the standard kinship	14
2.13	New kinship and F_{ST} estimators	16
2.14	Estimates from Beagle	18
2.15	Measures of association and related problems	18
2.16	Cartoon genotype matrix	18
3	Acknowledgments	19

*This document corresponds to kinshipsymbols v1.06, dated 2025/12/11.

Command	Symbol	Description
<code>\xij</code>	x_{ij}	Genotype
<code>\x</code>	\mathbf{x}_i	Genotype vector
<code>\X</code>	\mathbf{X}	Genotype matrix
<code>\pit</code>	p_i^T	Ancestral allele frequency
<code>\pith</code>	\hat{p}_i^T	Sample p_i^T estimator
<code>\kt</code>	φ_{jk}^T	Kinship coefficient
<code>\kinMat</code>	Φ^T	Kinship matrix
<code>\ft</code>	f_j^T	Inbreeding coefficient
<code>\Fst</code>	F_{ST}	(Wright's) Fixation index

Table 1: Commands for the most common statistical genetics quantities.

Command	Symbol	Description
<code>\f{A}{B}</code>	f_B^A	Inbreeding of pop. B relative to pop. A
<code>\fl</code>	$f_j^{L_j}$	Local inbreeding coefficient
<code>\fs</code>	$f_{L_j}^T$	Structural inbreeding coefficient
<code>\kl</code>	$\varphi_{jk}^{L_{jk}}$	Local kinship coefficient
<code>\ks</code>	$f_{L_{jk}}^T$	Structural kinship coefficient
<code>\fpw</code>	$f_{L_j}^{L_{jk}}$	Individual pairwise F_{ST} component
<code>\mav</code>	$\overline{p(1-p)}^T$	Mean ancestral variance

Table 2: Commands for more rare statistical genetics quantities.

1 Introduction

This package provides macros for many common symbols involving the genotypes, kinship coefficients, and F_{ST} . Each of Tables 1 to 5 and 8 pairs a command to its symbol and its common description in the field. Note that these symbols work even when not in math mode, so it is not necessary to write `\Fst` inline, `\Fst` works! This is achieved through use of `\ensuremath{\dots}\xspace` in each of these definitions.

Some of these symbols accept arguments for limited flexibility. For example, `\xij` produces x_{ij} , but `\xij[k]` produces x_{ik} . Similarly, `\kt` produces φ_{jk}^T , but `\kt[1]` produces φ_{jl}^T . See the implementation section below for details for each command.

Additionally, Tables 6 and 7 lists some math operators and convergence arrows defined by this package (absent in `amsmath`). These commands do require math mode to work.

Lastly, the package provides `\sampleGenMat`, which generates the cartoon genotype table shown in Fig. 1. Note that this technically generates a “tabular” table. It is meant to be used in Beamer presentations, but works in standard documents too.

The effects of the package options `color` and `noT` are visualized in Figs. 2 to 5. Each of those figures generated the symbols with a particular combination of options:

Command	Symbol	Description
<code>\ktHat</code>	$\hat{\varphi}_{jk}^T$	Unnamed kinship estimator
<code>\kinMatHat</code>	$\hat{\Phi}^T$	Unnamed kinship matrix estimator
<code>\ftHat</code>	\hat{f}_j^T	Unnamed inbreeding estimator
<code>\ktHatNamed{example}</code>	$\hat{\varphi}_{jk}^{T,\text{example}}$	Named kinship estimator
<code>\ftHatNamed{example}</code>	$\hat{f}_j^{T,\text{example}}$	Named inbreeding estimator
<code>\ktHatStd</code>	$\hat{\varphi}_{jk}^{T,\text{std}}$	Standard kinship estimator
<code>\ftHatStd</code>	$\hat{f}_j^{T,\text{std}}$	Standard inbreeding estimator (I)
<code>\ftHatStdII</code>	$\hat{f}_j^{T,\text{stdII}}$	Alternate inbreeding estimator (II)
<code>\ftHatStdIII</code>	$\hat{f}_j^{T,\text{stdIII}}$	Alternate inbreeding estimator (III)
<code>\ktHatNew</code>	$\hat{\varphi}_{jk}^{T,\text{new}}$	New kinship estimator
<code>\ktHatNewMin</code>	$\hat{\varphi}_{\min}^{T,\text{new}}$	Estimator of the asymptotic minimum $\hat{\varphi}_{jk}^{T,\text{new}}$
<code>\ftHatNew</code>	$\hat{f}_j^{T,\text{new}}$	New inbreeding estimator
<code>\klHatBeagle</code>	$\hat{\varphi}_{jk}^{L_{jk},\text{beagle}}$	Beagle-based kinship estimator
<code>\flHatBeagle</code>	$\hat{f}_j^{L_j,\text{beagle}}$	Beagle-based inbreeding estimator
<code>\Ajk</code>	A_{jk}	New kinship-related statistic
<code>\AMinHat</code>	\hat{A}_{\min}	Estimator of the asymptotic minimum A_{jk}

Table 3: Commands for miscellaneous kinship and inbreeding estimators.

Command	Symbol	Description
<code>\FstHatSample</code>	$\hat{F}_{\text{ST},i}^{\text{sample}}$	Sample F_{ST} estimator (one locus)
<code>\FstHat</code>	\hat{F}_{ST}	Unnamed F_{ST} estimator
<code>\FstHatNamed{example}</code>	$\hat{F}_{\text{ST}}^{\text{example}}$	Named F_{ST} estimator
<code>\FstHatWc</code>	$\hat{F}_{\text{ST}}^{\text{WC}}$	Weir-Cockerham F_{ST} estimator
<code>\FstHatHudson</code>	$\hat{F}_{\text{ST}}^{\text{Hudson}}$	Hudson Pairwise F_{ST} estimator
<code>\FstHatHudsonK</code>	$\hat{F}_{\text{ST}}^{\text{HudsonK}}$	Generalized Hudson F_{ST} estimator
<code>\FstHatIs</code>	$\hat{F}_{\text{ST}}^{\text{indep}}$	Asymptotic F_{ST} estimator for indep. subpops.
<code>\FstHatStd</code>	$\hat{F}_{\text{ST}}^{\text{std}}$	Standard F_{ST} estimator (based on $\hat{\varphi}_{jk}^{T,\text{std}}$)
<code>\FstHatStdPrime</code>	\hat{F}_{ST}'	Standard F_{ST} estimator adjusted 1
<code>\FstHatStdPrimeDb1</code>	\hat{F}_{ST}''	Standard F_{ST} estimator adjusted 2
<code>\FstHatNew</code>	$\hat{F}_{\text{ST}}^{\text{new}}$	New F_{ST} estimator

Table 4: Commands for miscellaneous F_{ST} estimators.

Command	Symbol	Description
<code>\Fit</code>	F_{IT}	Wright's total inbreeding
<code>\Fis</code>	F_{IS}	Wright's local inbreeding
<code>\Gst</code>	G_{ST}	Nei's genetic diversity measure
<code>\GstPrime</code>	G_{ST}'	Normalized G_{ST}
<code>\Rst</code>	R_{ST}	F_{ST} estimator for microsatellites
<code>\PhiSt</code>	ϕ_{ST}	AMOVA-based differentiation measure

Table 5: Commands for historical quantities in statistical genetics.

Command	Symbol	Description
<code>\E</code>	E	Expectation
<code>\Var</code>	Var	Variance
<code>\Cov</code>	Cov	Covariance
<code>\round</code>	round	Rounding function
<code>\sgn</code>	sgn	Sign function
<code>\logit</code>	logit	Logit function

Table 6: Commands for math operators.

Command	Symbol	Description
<code>\toas</code>	$\xrightarrow[m \rightarrow \infty]{a.s.}$	Almost sure convergence as m goes to ∞
<code>\toN</code>	$\xrightarrow{n \rightarrow \infty}$	Limit as n goes to ∞
<code>\toasNM</code>	$\xrightarrow[n, m \rightarrow \infty]{a.s.}$	Almost sure convergence as both m and n go to ∞

Table 7: Commands for math convergence arrows.

Command	Symbol	Description
<code>\srmsdp</code>	SRMSD_p	Signed root mean square deviation for null p-values
<code>\aucpr</code>	AUC_{PR}	Area under the precision-recall curve

Table 8: Commands for miscellaneous measures.




Figure 1: The cartoon genotype matrix generated by `\sampleGenMat`




Figure 2: The vanilla version of the symbols (no colors and no omission of ancestral population T in superscripts)

- Fig. 2: `\usepackage{kinshipsymbols}` "vanilla" version (no options). This version shows symbols completely (without omitting the ancestral population T from superscripts) and without color.
- Fig. 3: `\usepackage[color]{kinshipsymbols}` version. Same as the vanilla version except a few common symbols gain colors:
 - The genotypes (x_{ij} , \mathbf{x}_i , \mathbf{X}) become blue (and also the cartoon genotype matrix drawn by `\sampleGenMat`). Highlighted since this is the observed data from which inferences are drawn.
 - The kinship coefficients (φ_{jk}^T , Φ^T) become dark green. Highlighted since these are the main unknown parameters we wish to estimate.
 - The standard ancestral allele frequency estimator (\hat{p}_i^T) becomes red. Highlighted since this is a particularly problematic estimator that leads to biases in common approaches.
- Fig. 4: `\usepackage[noT]{kinshipsymbols}` version. Same as the vanilla version except the ancestral population T is omitted in the superscript of several symbols (p_i^T , \hat{p}_i^T , f_j^T , $f_{L_j}^T$, φ_{jk}^T , Φ^T , $\hat{\Phi}^T$, $f_{L_{jk}}^T$, $\hat{\varphi}_{jk}^T$, \hat{f}_j^T , $\hat{\varphi}_{jk}^{T,std}$, $\hat{f}_j^{T,std}$, $\hat{f}_j^{T,stdII}$, $\hat{f}_j^{T,stdIII}$, $\hat{\varphi}_{jk}^{T,new}$, $\hat{\varphi}_{min}^{T,new}$, $\hat{f}_j^{T,new}$, and $\overline{p(1-p)}^T$). This option is provided to simplify the heavy notation in a context where T is implicit or fixed.
- Fig. 5: `\usepackage[color,noT]{kinshipsymbols}` version. A straightforward combination of the color and `noT` options described above.




Figure 3: The color version of the symbols (with no omission of ancestral population T in superscripts)




Figure 4: The noT version of the symbols (no color, with omission of ancestral population T in superscripts as appropriate)




Figure 5: The `color, noT` version of the symbols (with color and omission of ancestral population T in superscripts as appropriate)

2 Implementation

2.1 Dependencies

This package requires `amsmath` to define the various math symbols and operators, `xspace` to allow inline math symbols to have appropriate spacings when used outside math mode, `xcolor` for color management and tricks, and `colortbl` and `multirow` for the cartoon genotype matrix.

```

1 \RequirePackage{amsmath}
2 \RequirePackage{xspace}
3 \RequirePackage{xcolor}
4 \RequirePackage{colortbl}
5 \RequirePackage{multirow}

```

2.2 Initializing variables, modify depending on options

Then we define the special colors we want to use (in a way that is easy to tweak later if needed).

`\ifcolor` LaTeX boolean for whether color option is on or off.

```

6 \newif\ifcolor%
7 \colorfalse% default is false

```

`genColor` The hardcoded “genotype color” is blue, applied if the `color` package option is set.

```

8 \colorlet{genColor}{blue}

```

`kinColor` The hardcoded “kinship color” is a dark green, applied if the `color` package option is set.

`\sgn` The sign function.

```
26 \DeclareMathOperator{\sgn}{sgn}
```

`\logit` The logit function.

```
27 \DeclareMathOperator{\logit}{logit}
```

2.4 Genotypes

`\xij` x_{ij} : Genotype variable at locus i of individual j (default). The optional argument allows setting other individuals (`\xij[k]` gives x_{ik} for individual k). If the package option `color` is passed, then this symbol turns the color `genColor` (default blue).

```
28 \newcommand{\xij}[1][j]{%
29   \ensuremath{%
30     \ifcolor \textcolor{genColor}{\fi%
31       x_{i#1}%
32     \ifcolor } \fi%
33   }%
34   \xspace%
35 }%
```

`\x` \mathbf{x}_i : Genotype vector at locus i (default). The optional argument allows setting other loci (`\x[i']` gives $\mathbf{x}_{i'}$ for locus i'). If the package option `color` is passed, then this symbol turns the color `genColor` (default blue).

```
36 \newcommand{\x}[1][i]{%
37   \ensuremath{%
38     \ifcolor \textcolor{genColor}{\fi%
39       \mathbf{x}_{#1}%
40     \ifcolor } \fi%
41   }%
42   \xspace%
43 }%
```

`\X` \mathbf{X} : Genotype matrix. If the package option `color` is passed, then this symbol turns the color `genColor` (default blue).

```
44 \newcommand{\X}{%
45   \ensuremath{%
46     \ifcolor \textcolor{genColor}{\fi%
47       \mathbf{X}%
48     \ifcolor } \fi%
49   }%
50   \xspace%
51 }%
```

2.5 Ancestral allele frequencies

`\pit` p_i^T : The ancestral allele frequency at locus i (default). The optional argument allows setting other loci (`\pit[i']` gives $p_{i'}^T$ for locus i'). This parameter has a value that depends on the ancestral population T , which is by default denoted in the superscript, but which gets omitted if the package option `noT` is passed.

```
52 \newcommand{\pit}[1][i]{%
53   \ensuremath{%
54     p_{#1}\kinshipsymbols@T%
```

```

55 }%
56 \xspace%
57 }%

```

`\pith` \hat{p}_i^T : The sample estimator of the ancestral allele frequency at locus i (default). The optional argument allows setting other loci (`\pith[i']` gives $\hat{p}_{i'}^T$ for locus i'). The parameter being estimated has a value that depends on the ancestral population T , which is by default denoted in the superscript, but which gets omitted if the package option `noT` is passed. If the package option `color` is passed, then this symbol turns the color `pithColor` (default red).

```

58 \newcommand{\pith}[1][i]{%
59   \ensuremath{%
60     \ifcolor \textcolor{pithColor}{\fi%
61       \hat{p}_{#1}\kinshipsymbols@T%
62     \ifcolor } \fi%
63   }%
64   \xspace%
65 }%

```

2.6 Wright's F_{ST}

`\Fst` F_{ST} : Wright's Fixation index. Although the T in the subscript technically refers to the ancestral population T , in this case it is never omitted (even if the package option `noT` is passed) to always match the more traditional and highly recognizable notation.

```

66 \newcommand{\Fst}{%
67   \ensuremath{%
68     F_{\text{ST}}}%
69   }%
70   \xspace%
71 }%

```

`\Fit` F_{IT} : Wright's total inbreeding coefficient. Although the T in the subscript technically refers to the ancestral population T , in this case it is never omitted (even if the package option `noT` is passed) to always match the more traditional and highly recognizable notation.

```

72 \newcommand{\Fit}{%
73   \ensuremath{%
74     F_{\text{IT}}}%
75   }%
76   \xspace%
77 }%

```

`\Fis` F_{IS} : Wright's local inbreeding coefficient.

```

78 \newcommand{\Fis}{%
79   \ensuremath{%
80     F_{\text{IS}}}%
81   }%
82   \xspace%
83 }%

```

2.7 Inbreeding coefficients

`\f` f_B^A : The inbreeding coefficient (of F_{ST}) of population B relative to an ancestral population A . Note that this command has two mandatory arguments.

```
84 \newcommand{\f}[2]{%
85   \ensuremath{%
86     f^{\#1}_{\#2}%
87   }%
88   \xspace%
89 }
```

`\ft` f_j^T : The (total) inbreeding coefficient of individual j (default). The optional argument allows setting other individuals (`\ft[k]` gives f_k^T for individual k). This parameter has a value that depends on the ancestral population T , which is by default denoted in the superscript, but which gets omitted if the package option `noT` is passed.

```
90 \newcommand{\ft}[1][j]{%
91   \ensuremath{%
92     f_{\#1}\kinshipsymbols@T%
93   }%
94   \xspace%
95 }
```

`\fl` $f_j^{L_j}$: The local inbreeding coefficient of individual j (default). The optional argument allows setting other individuals (`\fl[k]` gives $f_k^{L_k}$ for individual k).

```
96 \newcommand{\fl}[1][j]{%
97   \ensuremath{%
98     f_{\#1}^{L_{\#1}}%
99   }%
100   \xspace%
101 }
```

`\fs` $f_{L_j}^T$: The structural inbreeding coefficient of individual j (default). The optional argument allows setting other individuals (`\fs[k]` gives $f_{L_k}^T$ for individual k). This parameter has a value that depends on the ancestral population T , which is by default denoted in the superscript, but which gets omitted if the package option `noT` is passed.

```
102 \newcommand{\fs}[1][j]{%
103   \ensuremath{%
104     f_{L_{\#1}}\kinshipsymbols@T%
105   }%
106   \xspace%
107 }
```

2.8 Kinship coefficients

`\kt` φ_{jk}^T : The (total) kinship coefficient between the pair of individuals j and k (default). The optional argument allows setting another second individual (`\kt[l]` gives φ_{jl}^T for a second individual l). This parameter has a value that depends on the ancestral population T , which is by default denoted in the superscript, but which gets omitted if the package option `noT` is passed. If the package option `color` is passed, then this symbol turns the color `kinColor` (default dark green).

```

108 \newcommand{\kt}[1][k]{%
109   \ensuremath{%
110     \ifcolor \textcolor{kinColor}{\fi%
111       \varphi_{j#1}\kinshipsymbols@T%
112     \ifcolor } \fi%
113   }%
114   \xspace%
115 }%

\kinMat  $\Phi^T$ : The matrix of (total) kinship coefficients between every pair of individuals.
This parameter has a value that depends on the ancestral population  $T$ , which is
by default denoted in the superscript, but which gets omitted if the package option
noT is passed. If the package option color is passed, then this symbol turns the
color kinColor (default dark green).

116 \newcommand{\kinMat}{%
117   \ensuremath{%
118     \ifcolor \textcolor{kinColor}{\fi%
119       \boldsymbol{\Phi}\kinshipsymbols@T%
120     \ifcolor } \fi%
121   }%
122   \xspace%
123 }%

\kl  $\varphi_{jk}^{L_{jk}}$ : The local kinship coefficient between the pair of individuals  $j$  and  $k$ .

124 \newcommand{\kl}{%
125   \ensuremath{%
126     \varphi_{jk}^{L_{jk}}%
127   }%
128   \xspace%
129 }%

\ks  $f_{L_{jk}}^T$ : The structural kinship coefficient between the pair of individuals  $j$  and  $k$ .
This parameter has a value that depends on the ancestral population  $T$ , which
is by default denoted in the superscript, but which gets omitted if the package
option noT is passed.

130 \newcommand{\ks}{%
131   \ensuremath{%
132     f_{L_{jk}}%
133   }%
134   \xspace%
135 }%

\fpw  $f_{L_j}^{L_{jk}}$ : A component of the pairwise  $F_{ST}$  between a pair of individuals  $j$  and  $k$ 
(default). The optional argument changes the individual in the subscript only (so
\fpw[k] gives  $f_{L_k}^{L_{jk}}$ , and is obviously intended to be used for  $k$  only). Note that
the actual pairwise  $F_{ST}$  between  $j$  and  $k$  is given by the average of  $f_{L_j}^{L_{jk}}$  and  $f_{L_k}^{L_{jk}}$ .

136 \newcommand{\fpw}[1][j]{%
137   \f_{L_{#1}}^{L_{jk}}%
138 }%

```

2.9 Review of previous work

`\Rst` R_{ST} : An F_{ST} estimator developed for microsatellites.

```

139 \newcommand{\Rst}{%
140   \ensuremath{%
141     R_{\text{ST}}}%
142   }%
143   \xspace%
144 }%
```

`\PhiSt` ϕ_{ST} : An F_{ST} -like estimate based on AMOVA.

```

145 \newcommand{\PhiSt}{%
146   \ensuremath{%
147     \phi_{\text{ST}}}%
148   }%
149   \xspace%
150 }%
```

`\Gst` G_{ST} : Nei's genetic diversity measure.

```

151 \newcommand{\Gst}{%
152   \ensuremath{%
153     G_{\text{ST}}}%
154   }%
155   \xspace%
156 }%
```

`\GstPrime` G'_{ST} : A normalized G_{ST} statistic.

```

157 \newcommand{\GstPrime}{%
158   \ensuremath{%
159     G_{\text{ST}}'}%
160   }%
161   \xspace%
162 }%
```

`\FstHatSample` $\hat{F}_{ST,i}^{\text{sample}}$: A sample F_{ST} estimator for a single locus i .

```

163 \newcommand{\FstHatSample}{%
164   \ensuremath{%
165     \hat{F}_{\text{ST},i}^{\text{sample}}}%
166   }%
167   \xspace%
168 }%
```

2.10 Convergence arrows

`\toas` $\xrightarrow[m \rightarrow \infty]{\text{a.s.}}$: Almost sure convergence as m goes to ∞ . Optional argument changes the variable name (`\toas[n]` gives $\xrightarrow[n \rightarrow \infty]{\text{a.s.}}$).

```

169 \newcommand{\toas}[1][m]{%
170   \xrightarrow[#1]{\infty}{\text{a.s.}}%
171 }%
```

`\toN` $\xrightarrow[n \rightarrow \infty]$: The limit as n goes to ∞ . Optional argument changes the variable name (`\toN[m]` gives $\xrightarrow[m \rightarrow \infty]$).

```

172 \newcommand{\toN}[1][n]{%
173   \xrightarrow[#1]{\rightarrow \infty}}{}%
174 }%

\toasNM  $\xrightarrow[n, m \rightarrow \infty]{\text{a.s.}}$ : Almost sure convergence as both  $n$  and  $m$  go to  $\infty$ .
175 \newcommand{\toasNM}{%
176   \xrightarrow[n, m]{\rightarrow \infty}{\text{a.s.}}}{}%
177 }%

```

2.11 F_{ST} estimators for independent subpopulations

```

\FstHat  $\hat{F}_{ST}$ : Unnamed  $F_{ST}$  estimator.
178 \newcommand{\FstHat}{%
179   \ensuremath{%
180     \hat{F}_{\text{ST}}}%
181   }%
182   \xspace%
183 }%

\FstHatNamed  $\hat{F}_{ST}^{\text{example}}$ : Base command for a named  $F_{ST}$  estimator. Takes on one mandatory
argument—the name of the estimator—which is rendered as text.
184 \newcommand{\FstHatNamed}[1]{%
185   \ensuremath{%
186     \hat{F}_{\text{ST}}^{\text{\text{\#1}}}%
187   }%
188   \xspace%
189 }%

\FstHatIs  $\hat{F}_{ST}^{\text{indep}}$ : Asymptotic  $F_{ST}$  estimator for independent subpopulations.
190 \newcommand{\FstHatIs}{\FstHatNamed{indep}}

\FstHatWc  $\hat{F}_{ST}^{\text{WC}}$ : Weir-Cockerham  $F_{ST}$  estimator.
191 \newcommand{\FstHatWc}{\FstHatNamed{WC}}

\FstHatHudson  $\hat{F}_{ST}^{\text{Hudson}}$ : Hudson pairwise  $F_{ST}$  estimator.
192 \newcommand{\FstHatHudson}{\FstHatNamed{Hudson}}

\FstHatHudsonK  $\hat{F}_{ST}^{\text{HudsonK}}$ : Generalized Hudson  $F_{ST}$  estimator (for  $K$  subpopulations).
193 \newcommand{\FstHatHudsonK}{\FstHatNamed{HudsonK}}

```

2.12 Estimators based on the standard kinship

```

\ktHat  $\hat{\varphi}_{jk}^T$ : An unnamed kinship estimator for individuals  $j$  and  $k$  (default). The optional
argument allows setting another second individual ( $\ktHat[1]$  gives  $\hat{\varphi}_{jl}^T$  for a
second individual  $l$ ). The estimated parameter has a value that depends on the
ancestral population  $T$ , which is by default denoted in the superscript, but which
gets omitted if the package option noT is passed.
194 \newcommand{\ktHat}[1][k]{%
195   \ensuremath{%
196     \hat{\varphi}_{\text{\#1}}^{\text{kinshipsymbols@T}}%
197   }%
198   \xspace%
199 }%

```

`\ktHatNamed` $\hat{\varphi}_{jk}^{T,\text{example}}$: A generic named kinship estimator for individuals j and k (default). Mandatory argument is the name, rendered as text. The optional argument allows setting another second individual (`\ktHatNamed[1]{example}` gives $\hat{\varphi}_{jl}^{T,\text{example}}$ for a second individual l). The estimated parameter has a value that depends on the ancestral population T , which is by default denoted in the superscript, but which gets omitted if the package option `noT` is passed.

```

200 \newcommand{\ktHatNamed}[2][k]{%
201   \ensuremath{%
202     \hat{\varphi}_{\#1}\kinshipsymbols@Ts{\#2}%
203   }%
204   \xspace%
205 }%
```

`\kinMatHat` $\hat{\Phi}^T$: The unnamed (total) kinship matrix estimator between every pair of individuals. This parameter has a value that depends on the ancestral population T , which is by default denoted in the superscript, but which gets omitted if the package option `noT` is passed.

```

206 \newcommand{\kinMatHat}{%
207   \ensuremath{%
208     \boldsymbol{\hat{\Phi}}\kinshipsymbols@T%
209   }%
210   \xspace%
211 }%
```

`\ktHatStd` $\hat{\varphi}_{jk}^{T,\text{std}}$: Standard kinship estimator for individuals j and k (default). The optional argument allows setting another second individual (`\ktHatStd[1]` gives $\hat{\varphi}_{jl}^{T,\text{std}}$ for a second individual l). The estimated parameter has a value that depends on the ancestral population T , which is by default denoted in the superscript, but which gets omitted if the package option `noT` is passed.

```

212 \newcommand{\ktHatStd}[1][k]{\ktHatNamed[\#1]{std}}
```

`\ftHat` \hat{f}_j^T : Unnamed inbreeding coefficient estimator for individual j (default). The optional argument allows setting another individual (`\ftHat[k]` gives \hat{f}_k^T for individual k). The estimated parameter has a value that depends on the ancestral population T , which is by default denoted in the superscript, but which gets omitted if the package option `noT` is passed.

```

213 \newcommand{\ftHat}[1][j]{%
214   \ensuremath{%
215     \hat{f}_{\#1}\kinshipsymbols@T%
216   }%
217   \xspace%
218 }%
```

`\ftHatNamed` $\hat{f}_j^{T,\text{example}}$: Named inbreeding coefficient estimator for individual j (default). Mandatory argument is the name, rendered as text. The optional argument allows setting another individual (`\ftHatNamed[k]{example}` gives $\hat{f}_k^{T,\text{example}}$ for individual k). The estimated parameter has a value that depends on the ancestral population T , which is by default denoted in the superscript, but which gets omitted if the package option `noT` is passed.

```

219 \newcommand{\ftHatNamed}[2][j]{%
220   \ensuremath{%
```

```

221     \hat{f}_{\#1}\kinshipsymbols@Ts{\#2}%
222   }%
223   \xspace%
224 }%

```

\ftHatStd $\hat{f}_j^{T,\text{std}}$: Standard inbreeding coefficient estimator (I) for individual j . The estimated parameter has a value that depends on the ancestral population T , which is by default denoted in the superscript, but which gets omitted if the package option `noT` is passed.

```

225 \newcommand{\ftHatStd}{\ftHatNamed{std}}

```

\ftHatStdII $\hat{f}_j^{T,\text{stdII}}$: Alternate inbreeding coefficient estimator (II) for individual j . The estimated parameter has a value that depends on the ancestral population T , which is by default denoted in the superscript, but which gets omitted if the package option `noT` is passed.

```

226 \newcommand{\ftHatStdII}{\ftHatNamed{stdII}}

```

\ftHatStdIII $\hat{f}_j^{T,\text{stdIII}}$: Alternate inbreeding coefficient estimator (III) for individual j . The estimated parameter has a value that depends on the ancestral population T , which is by default denoted in the superscript, but which gets omitted if the package option `noT` is passed.

```

227 \newcommand{\ftHatStdIII}{\ftHatNamed{stdIII}}

```

\FstHatStd $\hat{F}_{\text{ST}}^{\text{std}}$: Standard F_{ST} estimator (based on the standard kinship estimator).

```

228 \newcommand{\FstHatStd}{\FstHatNamed{std}}

```

\FstHatStdPrime \hat{F}_{ST}' : Standard F_{ST} estimator adjusted 1.

```

229 \newcommand{\FstHatStdPrime}{%
230   \ensuremath{%
231     \hat{F}_{\text{ST}}'%
232   }%
233   \xspace%
234 }%

```

\FstHatStdPrimeDbl \hat{F}_{ST}'' : Standard F_{ST} estimator adjusted 2.

```

235 \newcommand{\FstHatStdPrimeDbl}{%
236   \ensuremath{%
237     \hat{F}_{\text{ST}}''%
238   }%
239   \xspace%
240 }%

```

2.13 New kinship and F_{ST} estimators

\ktHatNew $\hat{\varphi}_{jk}^{T,\text{new}}$: New kinship estimator for the pair of individuals j and k (default). The optional argument allows setting another second individual (`\ktHatNew[1]` gives $\hat{\varphi}_{jl}^{T,\text{new}}$ for a second individual l). The estimated parameter has a value that depends on the ancestral population T , which is by default denoted in the superscript, but which gets omitted if the package option `noT` is passed.

```

241 \newcommand{\ktHatNew}[1][k]{\ktHatNamed{\#1}{new}}

```


`\ktHatNewMin` $\hat{\varphi}_{\min}^{T,\text{new}}$: Estimator of the limit of the minimum value of the expectation of $\hat{\varphi}_{jk}^{T,\text{new}}$ across all pairs of individuals. The estimated parameter has a value that depends on the ancestral population T , which is by default denoted in the superscript, but which gets omitted if the package option `noT` is passed.

```

242 \newcommand{\ktHatNewMin}{%
243   \ensuremath{%
244     \hat{\varphi}_{\text{min}}\kinshipsymbols@Ts{new}%
245   }%
246   \xspace%
247 }%

```

`\ftHatNew` $\hat{f}_j^{T,\text{new}}$: New inbreeding estimator for individual j (default). The optional argument allows setting other individuals (`\ftHatNew[k]` gives $\hat{f}_k^{T,\text{new}}$ for individual k). The estimated parameter has a value that depends on the ancestral population T , which is by default denoted in the superscript, but which gets omitted if the package option `noT` is passed.

```

248 \newcommand{\ftHatNew}[1][j]{\ftHatNamed[#1]{new}}

```

`\fstHatNew` $\hat{F}_{\text{ST}}^{\text{new}}$: New F_{ST} estimator.

```

249 \newcommand{\fstHatNew}{\fstHatNamed{new}}

```

`\Ajk` A_{jk} : A new statistic proportional in expectation to $\varphi_{jk}^T - 1$ for the pair of individuals j and k (default). The optional argument allows setting another second individual (`\Ajk[l]` gives A_{jl} for a second individual l).

```

250 \newcommand{\Ajk}[1][k]{%
251   \ensuremath{%
252     A_{j\#1}%
253   }%
254   \xspace%
255 }%

```

`\AMinHat` \hat{A}_{\min} : Estimator of the limit of the minimum value of the expectation of A_{jk} across all pairs of individuals.

```

256 \newcommand{\AMinHat}{%
257   \ensuremath{%
258     \hat{A}_{\text{min}}%
259   }%
260   \xspace%
261 }%

```

`\AAvgHat` \hat{A}_{avg} : Estimator of the limit of the average value of the expectation of A_{jk} across all pairs of individuals.

```

262 \newcommand{\AAvgHat}{%
263   \ensuremath{%
264     \hat{A}_{\text{avg}}%
265   }%
266   \xspace%
267 }%

```

`\mav` $\overline{p(1-p)}^T$: Mean ancestral variance. This parameter has a value that depends on the ancestral population T , which is by default denoted in the superscript, but which gets omitted if the package option `noT` is passed.

```

268 \newcommand{\mav}{\%
269   \ensuremath{\%
270     \overline{p(1-p)}}\kinshipsymbols@T%
271   }%
272   \xspace%
273 }%

```

2.14 Estimates from Beagle

`\klHatBeagle` $\hat{\varphi}_{jk}^{L_{jk}, \text{beagle}}$: Local kinship estimator based on Beagle, for the pair of individuals j and k .

```

274 \newcommand{\klHatBeagle}{\%
275   \ensuremath{\%
276     \hat{\varphi}_{jk}^{L_{jk}, \text{beagle}}}%
277   }%
278   \xspace%
279 }%

```

`\flHatBeagle` $\hat{f}_j^{L_j, \text{beagle}}$: Local inbreeding estimator based on Beagle, for individual j (default). The optional argument allows setting other individuals (`\flHatBeagle[k]` gives $\hat{f}_k^{L_k, \text{beagle}}$ for individual k).

```

280 \newcommand{\flHatBeagle}[1][j]{\%
281   \ensuremath{\%
282     \hat{f}_{\text{\#1}}^{L_{\text{\#1}}, \text{beagle}}}%
283   }%
284   \xspace%
285 }%

```

2.15 Measures of association and related problems

`\srmsdp` SRMSD_p : The Signed Root Mean Square Deviation (SRMSD) of null p-values from their expectation that they have uniform quantiles.

```

286 \newcommand{\srmsdp}{\%
287   \ensuremath{\%
288     \text{SRMSD}_p}%
289   }%
290   \xspace%
291 }%

```

`\aucpr` AUC_{PR} : The Area Under the Curve (AUC) for precision-recall (PR) curves, which is a proxy measure for calibrated power.

```

292 \newcommand{\aucpr}{\%
293   \ensuremath{\%
294     \text{AUC}_{\text{PR}}}%
295   }%
296   \xspace%
297 }%

```

2.16 Cartoon genotype matrix

I use this cartoon genotype matrix often in Beamer presentations. Unfortunately I also use the `color kinshipsymbols` package option in my presentations,

but due to a strange bug the colors do not show up in Beamer. This solution was found online: <https://tex.stackexchange.com/questions/159378/cline-disappears-in-beamer>

```

298 % after package colortbl is loaded
299 \makeatletter
300 \@ifclassloaded{beamer}{%
301   \patchcmd\@cline
302     {\arrayrulewidth\hfill}% search
303     {\arrayrulewidth\hfill\kern\z@}% replace
304     {}% success
305     {\errmessage{Patching \string\@cline\space failed}}% failure
306 }{%
307   % nothing to do here?
308 }
309 \makeatother

```

`\sampleGenMat` This is the bulky code used to generate the cartoon genotype matrix shown in Fig. 1.

```

310 \newcommand{\sampleGenMat}{%
311   \begin{tabular}{cc}%
312     & Individuals \\
313     \ifcolor \arrayrulecolor{genColor} \fi% % gets applied to whole table
314     \cline{2-2}%
315     \multirow{10}{*}{\rotatebox[origin=c]{90}{Loci}}%
316     & \multicolumn{1}{|l|}{0 2 2 1 1 0 1} \\
317     & \multicolumn{1}{|l|}{0 2 1 0 1 } \\
318     & \multicolumn{1}{|l|}{2 ... } \\
319     & \multicolumn{1}{|l|}{ } \\
320     & \multicolumn{1}{|l|}{ } \\
321     & \multicolumn{1}{|l|}{ } \\
322     & \multicolumn{1}{|l|}{ } \\
323     & \multicolumn{1}{|l|}{ } \\
324     & \multicolumn{1}{|l|}{ } \\
325     & \multicolumn{1}{|l|}{ } \\
326     \cline{2-2}%
327     & \\
328     & X \\
329   \end{tabular}%
330 }%

```

3 Acknowledgments

The symbols in this package were originally designed with John D. Storey (Alex Ochoa's postdoctoral adviser and coauthor of several papers about kinship and F_{ST}).

The package was written following Scott Pakin's guide [How to Package Your L^AT_EX package](#).

Change History

v1.00	estimator name)	1	
General: Initial version	1	v1.04	
v1.01	General: Added NEWS, README, and symbols A_{jk} , \hat{A}_{avg} , and *Std versions	1	General: Added option to change variable name in $\xrightarrow[\text{a.s.}]{m \rightarrow \infty}$
		1	
v1.02	General: Added $\hat{\varphi}_{\text{min}}^{T,\text{new}}$ symbol . . .	1	v1.05
General: Added $\hat{\varphi}_{\text{min}}^{T,\text{new}}$ symbol . . .	1		General: Added Φ^T , \mathbf{x}_i , \mathbf{X} , SRMSD _p , AUC _{PR} , and locus subscript options for p_i^T , \hat{p}_i^T . . .
v1.03	General: Added unnamed \hat{F}_{ST} , $\hat{\varphi}_{jk}^T$, and \hat{f}_j^T symbols (without		1
		v1.06	
			General: Added $\hat{\Phi}^T$
			1

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

A	K
\AAvgHat 262	\kinColor 9
\Ajk 250	\kinMat 116
\AMinHat 256	\kinMatHat 206
\aucpr 292	\kinshipsymbols@T 11 , 17 , 54 , 61 , 92 , 104 , 111 , 119 , 132 , 196 , 208 , 215 , 270
B	\kinshipsymbols@Ts 12 , 18 , 202 , 221 , 244
\boldsymbol 119 , 208	\kl 124
C	\klHatBeagle 274
\colorfalse 7	\ks 130
\colortrue 14	\kt 108
\Cov 24	\ktHat 194
E	\ktHatNamed 200 , 212 , 241
\E 22	\ktHatNew 241
F	\ktHatNewMin 242
\f 84 , 137	\ktHatStd 212
\fi 30 , 32 , 38 , 40 , 46 , 48 , 60 , 62 , 110 , 112 , 118 , 120 , 313	L
\Fis 78	\logit 27
\Fit 72	M
\fl 96	\mav 268
\flHatBeagle 280	N
\fpw 136	\newif 6
\fs 102	P
\Fst 66	\Phi 119 , 208
\FstHat 178	
\FstHatHudson 192	
\FstHatHudsonK 193	
\FstHatIs 190	
\FstHatNamed 184 , 190 , 191 , 192 , 193 , 228 , 249	
\FstHatNew 249	
\FstHatSample 163	
\FstHatStd 228	
\FstHatStdPrime 229	
\FstHatStdPrimeDbl 235	
\FstHatWc 191	
\ft 90	
\ftHat 213	
\ftHatNamed 219 , 225 , 226 , 227 , 248	
\ftHatNew 248	
\ftHatStd 225	
\ftHatStdII 226	
\ftHatStdIII 227	
G	
\genColor 8	
\Gst 151	
\GstPrime 157	
I	
\ifcolor 6 , 30 , 32 , 38 , 40 , 46 , 48 , 60 , 62 , 110 , 112 , 118 , 120 , 313	

\PhiSt	145	S	V
\pit	52	\sampleGenMat	310
\pith	58	\sgn	26
\pithColor	10	\srmsdp	286
		X	
R		T	
\round	25	\toas	169
\Rst	139	\toasNM	175
		\toN	172
		\X	44 , 328
		\x	36
		\xij	28