# SOP-IT-003 · Observer dashboards: local by default, remote access on purpose

SOP IT-003 | Status draft | Changed 2026-11-01 | For Stewards

**Department:** IT · **ID:** 003 · **Status:** draft (approved when tagged) · **Owner:** whoever runs an observer on their machine · **Last changed:** 2026-11-01

## Purpose

A bot or observer that serves a dashboard from someone's computer must not answer the whole network by accident. This procedure says what "local by default" means, what changes for the people who used to open the page from another device, and how to give remote access back deliberately.


## Scope

Every observer in the fleet that serves a page or an API from a person's machine. The worked example is a bot dashboard on port `<port>` that used to listen on every interface and now listens on loopback only.

## What changes when a dashboard becomes local-only, and what you will notice

| Before | After the monitor's next restart |
|---|---|
| The server listened on **all interfaces**, so a phone or laptop on the home or VPN network could open `http://<this-machine>:<port>` | It listens on **127.0.0.1** only. From any other device the page **times out and looks "down"** |
| Only POST routes checked who was calling; configuration, trades, logs, the journal and the alert history answered anyone | **Every** `/api` route and the live **WebSocket** refuse a caller that is not local (or not carrying the token, below) |
| `/api/config` showed the whole configuration | `/api/config` is **redacted**: keys, URLs and wallet fields no longer appear, even locally |
| — | `http://localhost:<port>` **on the machine itself works unchanged**; the **public GitHub Pages copy is unaffected** (it reads the nightly snapshot, not this server) |

### Three ways to reach the dashboard




## Steps: give remote access back, on purpose

1. Decide that a second device really needs the live page. *You should see:* a reason you could write in one line. If it is just a glance, the public copy or a screenshot is enough.
2. **Preferred:** reach it through the Mac instead of widening the server: from the other device `ssh -L <port>:localhost:<port> <user>@<this-machine>`, then open `http://localhost:<port>` there. *You should see:* the dashboard, with nothing on the network changed.
3. **If the server itself must listen wider:** add both `BIND_HOST=0.0.0.0` **and** `BOT_API_TOKEN=<a long random value>` to the bot's `.env` (helpers never read `.env`; you edit it yourself), then restart the monitor (`sh scripts/edge-monitor-service.sh restart`). *You should see:* the log line `Server listening on 0.0.0.0:<port>`.
4. From the other device, send the token as a header: `Authorization: Bearer <value>` (a script, or a browser extension that sets headers). A `?token=` in the address bar also works but stays in the browser's history; use it only on your own device and clear it after. *You should see:* live data. Without the token the page shell loads but every API call and the socket are refused.
5. Never widen the binding without the token, never paste the token into a chat, an Issue or a commit, and remove both lines from `.env` when the need ends. *You should see:* the log line back to `127.0.0.1:<port>` after a restart.

## Verification

From this machine, `curl -s localhost:<port>/api/edge/stats` answers. From another device without the token, the port times out (default) or `/api/edge/stats` returns 401 (widened). `curl -s localhost:<port>/api/config` shows no key, URL or wallet field.

## Troubleshooting

| Symptom | Likely cause | What to do |
|---|---|---|
| The dashboard "went down" on the phone after a restart | local-by-default, as designed | use step 2, or steps 3–4 on purpose |
| `401 Unauthorized` from another device | widened without the token, or the token is wrong | send the Bearer header; check `.env` |

| | | |
|---|---|---|
| The page loads but shows no data from another device | the token is not reaching the API or socket | prefer the SSH tunnel (step 2); otherwise check the header |

## Where the heads-up came from: the "You should know" reader

The exposure was first spelled out by Claude Code's built-in **You should know** plugin ( `cc-plugin-you-should-know@builtin` ), a second reader that runs beside the main agent in a session. Its own heads-up on 2026-10-31 said what it is; keep these four points in mind whenever a helper works on an observer:

| What it is | What it means for you |
|---|---|
| Turned on with `/plugin enable cc-plugin-you-should-know@builtin`. Reloading plugins is enough: **no `/restart` is needed**, so a restart refused because background work is running does not matter | to know it runs, look for its **Heads up** note in the session; that note is its own verification |
| A **second reader with no tools**: it cannot open files, check GitHub or confirm a deploy. It only re-reads the conversation and flags what may have been missed | a heads-up is a reason to check, never a check done. The main agent's requirements ledger, and this procedure's **Verification**, stay the real checklist |
| **Each check is an extra model request** on the same weekly allowance the session already uses | expect a small, steady cost while long sessions run; switch it off from `/plugin` when the allowance is tight |
| Its note offers three answers: **Understood**, **Chat in main session** (hands the point to the main agent), **Dismiss** | choose *Chat in main session* when the point needs a file opened or a command run: only the main agent can do that |

## Related

- SOP-IT-001 (VPN and DNS stalls), SOP-IT-002 (reading room and helper access)
- The observer's own runbook; the heads-up that first explained this change came from the session's "You should know" reader on 2026-10-31

## Change log

| Date | Change | By |
|---|---|---|
| 2026-10-31 | Drafted from the dashboard gate and the second reader's heads-up | Alfred |
| 2026-10-31 | The "You should know" reader recorded from its own heads-up (Christopher's screenshot): how to tell it runs, no tools, what it costs, its three answers | Alfred |
| 2026-11-01 | Lucid pass: Lucide icons, the three ways to reach a dashboard in Mermaid; the reader's next heads-up (base permission) is recorded in SOP-GOV-002 | Alfred |
| 2026-11-01 | ORG's copy brought level with my-template: Lucide icons in emerald, Mermaid where a picture explains, ORG's own facts kept; the lab's own dashboard example now lives in the lab's copy, this one is the generic procedure | Alfred |

*Part of the fleet's procedures. The master copies and the legend live in my-template.*