

VPN Site a Site

Conf Marseille

IPsec Tunnels										
	ID	IKE	Remote Gateway	Auth/Mode	P1 Protocol	P1 Transforms	P1 DH-Group	P1 Description	Actions	
☐	Disable	1	V2	WAN 192.168.150.65	Mutual PSK -	AES (256 bits)	SHA256	14 (2048 bit)	VPN Lille	
	ID	Mode	Local Subnet	Remote Subnet	P2 Protocol	P2 Transforms	P2 Auth Methods	Description	P2 actions	
☐	Disable	1	tunnel	10.0.0.0/26	192.168.110.0/28	ESP	AES (256 bits)	SHA256	Vlan 110	
☐	Disable	2	tunnel	10.0.0.0/26	192.168.120.0/28	ESP	AES (256 bits)	SHA256	Vlan 120	
☐	Disable	3	tunnel	10.0.0.0/26	192.168.130.0/28	ESP	AES (256 bits)	SHA256	Vlan 130	
☐	Disable	4	tunnel	10.0.0.0/26	172.16.3.0/24	ESP	AES (256 bits)	SHA256	Vlan 400	
☐	Disable	5	tunnel	192.168.10.0/24	172.16.3.0/24	ESP	AES (256 bits)	SHA256	Vlan 400	
☐	Disable	6	tunnel	192.168.11.0/24	172.16.3.0/24	ESP	AES (256 bits)	SHA256	Vlan 400	
☐	Disable	7	tunnel	192.168.12.0/24	172.16.3.0/24	ESP	AES (256 bits)	SHA256	Vlan 400	
☐	Disable	8	tunnel	192.168.13.0/24	172.16.3.0/24	ESP	AES (256 bits)	SHA256	Vlan 400	
☐	Disable	9	tunnel	192.168.14.0/24	172.16.3.0/24	ESP	AES (256 bits)	SHA256	Vlan 400	
☐	Disable	10	tunnel	172.16.0.0/24	172.16.3.0/24	ESP	AES (256 bits)	SHA256	Vlan 400	
☐	Disable	11	tunnel	172.16.2.0/24	172.16.3.0/24	ESP	AES (256 bits)	SHA256	Vlan 400	
+ Add P2										

Pour chaque pair il faut autoriser le transfert du local vers le remote par exemple:
la première ligne permet le transfert de 10.0.0.0/26 vers 192.168.110.0 donc du
VLAN server de Marseille vers le vlan 110 de Lille il faut faire de même pour les
autre VLAN et cela des deux coté.

Phase 1 Proposal (Authentication)	
Authentication Method	Mutual PSK Must match the setting chosen on the remote side.
My identifier	IP address 192.168.150.54
Peer identifier	Peer IP address
Pre-Shared Key	f8be3dcd7823ac36a977aeea676bdc0777d2eb187ac6f6a4e15ba458 Enter the Pre-Shared Key string. This key must match on both peers. This key should be long and random to protect the tunnel and its contents. A weak Pre-Shared Key can lead to a tunnel compromise. Generate new Pre-Shared Key

Il faut préciser que le Pfsense est derriere un NAT ici derriere 192.168.150.54

Il faut aussi configurer des routes statiques pour que les requêtes faites vers Lille passent par le Pfsense:

```
ip forward -protocol nd
ip route 0.0.0.0 0.0.0.0 192.168.150.1
ip route 172.16.3.0 255.255.255.0 10.0.0.11
ip route 192.168.110.0 255.255.255.240 10.0.0.11
ip route 192.168.120.0 255.255.255.240 10.0.0.11
ip route 192.168.130.0 255.255.255.240 10.0.0.11
```

Conf Lille

IPsec Tunnels									
	ID	IKE	Remote Gateway	Auth/Mode	P1 Protocol	P1 Transforms	P1 DH-Group	P1 Description	Actions
☐  Disable	1	V2	WAN 192.168.150.54	Mutual PSK -	AES (256 bits)	SHA256	14 (2048 bit)	VPN Marseille	  
	ID	Mode	Local Subnet	Remote Subnet	P2 Protocol	P2 Transforms	P2 Auth Methods	Description	P2 actions
☐  Disable	1	tunnel	VLAN110	10.0.0.0/26	ESP	AES (256 bits)	SHA256	Vlan 110	  
☐  Disable	2	tunnel	VLAN120	10.0.0.0/26	ESP	AES (256 bits)	SHA256	Vlan 120	  
☐  Disable	3	tunnel	VLAN130	10.0.0.0/26	ESP	AES (256 bits)	SHA256	Vlan 130	  
☐  Disable	4	tunnel	VLAN400SERVEURS	10.0.0.0/26	ESP	AES (256 bits)	SHA256	Vlan 400	  
☐  Disable	5	tunnel	VLAN400SERVEURS	192.168.10.0/24	ESP	AES (256 bits)	SHA256	Vlan 400	  
☐  Disable	6	tunnel	VLAN400SERVEURS	192.168.11.0/24	ESP	AES (256 bits)	SHA256	Vlan 400	  
☐  Disable	7	tunnel	VLAN400SERVEURS	192.168.12.0/24	ESP	AES (256 bits)	SHA256	Vlan 400	  
☐  Disable	8	tunnel	VLAN400SERVEURS	192.168.13.0/24	ESP	AES (256 bits)	SHA256	Vlan 400	  
☐  Disable	9	tunnel	VLAN400SERVEURS	192.168.14.0/24	ESP	AES (256 bits)	SHA256	Vlan 400	  
☐  Disable	10	tunnel	VLAN400SERVEURS	172.16.0.0/24	ESP	AES (256 bits)	SHA256	Vlan 400	  
☐  Disable	11	tunnel	VLAN400SERVEURS	172.16.2.0/24	ESP	AES (256 bits)	SHA256	Vlan 400	  
 Add P2									