




deeplearning.ai

One hidden layer  
Neural Network

---

Derivatives of  
activation functions

# Sigmoid activation function



$$\underline{g(z) = \frac{1}{1 + e^{-z}}}$$

$$a = g(z) = \frac{1}{1 + e^{-z}}$$

$$\begin{aligned} \boxed{g'(z)} &= \boxed{\frac{d}{dz} g(z)} = \text{slope of } g(z) \text{ at } z \\ &= \frac{1}{1 + e^{-z}} \left( 1 - \frac{1}{1 + e^{-z}} \right) \\ &= g(z) (1 - g(z)) \leftarrow \\ &= \boxed{a(1-a)} \quad \left| \begin{array}{l} g'(z) = a(1-a) \\ \uparrow \\ a \end{array} \right. \end{aligned}$$

$$z = 10. \quad g(z) \approx 1$$

$$\frac{d}{dz} g(z) \approx 1(1-1) \approx 0$$


$$z = -10 \quad g(z) \approx 0$$

$$\frac{d}{dz} g(z) \approx 0 \cdot (1-0) \approx 0$$

$$z = 0 \quad g(z) = \frac{1}{2}$$

$$\frac{d}{dz} g(z) = \frac{1}{2} \left( 1 - \frac{1}{2} \right) = \frac{1}{4}$$

# Tanh activation function



$$g(z) = \tanh(z) = \frac{e^z - e^{-z}}{e^z + e^{-z}}$$


$$g'(z) = \frac{d}{dz} g(z) = \text{slope of } g(z) \text{ at } z = \underline{1 - (\tanh(z))^2} \leftarrow$$

$$a = g(z), \quad g'(z) = 1 - a^2$$

↑                      ↑

$$\left| \begin{array}{ll} z=10 & \tanh(z) \approx 1 \\ & g'(z) \approx 0 \\ z=-10 & \tanh(z) \approx -1 \\ & g'(z) \approx 0 \\ z=0 & \tanh(z) = 0 \\ & g'(z) = 1 \end{array} \right.$$


# ReLU and Leaky ReLU



# ReLU

$$g(z) = \max(0, z)$$

$\rightarrow g'(z) = \begin{cases} 0 & \text{if } z < 0 \\ 1 & \text{if } z \geq 0 \end{cases}$   
 ~~$undefined \text{ if } z = 0$~~   
 $z = 0.0000 \dots 0$



# Leaky ReLU

$$g(z) = \max(0.01z, z)$$
$$g'(z) = \begin{cases} 0.01 & \text{if } z < 0 \\ 1 & \text{if } z \geq 0 \end{cases}$$