

RTR-COD:

- В настоящий момент имеет:
 - **te0** - порт в сторону **ISP**
 - **te1** - порт в сторону **SW-COD**

```
ecorouter>show port brief
```

Name	Physical	Admin	Lacp	Last Change	Description

te0	UP	UP	*	02h:17m:24s ago	
te1	UP	UP	*	02h:17m:24s ago	

```
ecorouter>
```

- Базовая настройка:
 - имя
 - адресация в соответствие с L3
 - требуемый пользователь

```
enable
configure terminal
hostname rtr-cod
ip domain-name au.team

username net_admin
password P@ssw0rd
role admin
exit

interface int0
description "Connect-to-ISP"
ip address 34.95.33.33/24
exit

port te0
service-instance te0/int0
encapsulation untagged
connect ip interface int0
exit
exit

interface int1
description "Connect-to-SW-COD"
ip address 172.16.1.254/23
exit

port te1
service-instance te1/int1
encapsulation untagged
connect ip interface int1
exit
exit

write memory
```

- Проверить:

```

rtr-cod#show hostname
rtr-cod
rtr-cod#show run | include ip domain-name
ip domain-name au.team
rtr-cod#show users localdb
User: admin
  Description: Administrator User
  Docker socket access: disabled
  VR:
    pvr
  Roles:
    admin
User: daemon
  Description: The user is used to get configuration data
  Docker socket access: disabled
  VR:
    pvr
  Roles:
    daemon
User: net_admin
  Description:
  Docker socket access: disabled
  VR:
    pvr
  Roles:
    admin
rtr-cod#show ip int br

```

Interface	IP-Address	Status	VRF
int0	34.95.33.33/24	up	default
int1	172.16.1.254/23	up	default

```

rtr-cod#ping 34.95.33.254
PING 34.95.33.254 (34.95.33.254) 56(84) bytes of data.
64 bytes from 34.95.33.254: icmp_seq=1 ttl=64 time=14.7 ms
64 bytes from 34.95.33.254: icmp_seq=2 ttl=64 time=13.7 ms
64 bytes from 34.95.33.254: icmp_seq=3 ttl=64 time=12.9 ms

--- 34.95.33.254 ping statistics ---
3 packets transmitted, 3 received, 0% packet loss, time 2002ms
rtt min/avg/max/mdev = 12.866/13.725/14.654/0.731 ms
rtr-cod#

```

- Настройка BGP:

```
conf t
```

```
router bgp 64499
```

```
bgp router-id 34.95.33.33
```

```
neighbor 34.95.33.254 remote-as 64499
```

```
exit
```

```
write memory
```

- Проверить:

```

rtr-cod#show ip bgp summary
BGP router identifier 34.95.33.33, local AS number 64499
BGP table version is 2
1 BGP AS-PATH entries
0 BGP community entries

Neighbor      V    AS    MsgRcv   MsgSen   TblVer   InQ    OutQ    Up/Down
-----
34.95.33.254  4    64499   5         2         2         0         0      00:00:19

Total number of neighbors 1

Total number of Established sessions 1
rtr-cod#show ip route
Codes: C - connected, S - static, R - RIP, B - BGP
       O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS inter area
       * - candidate default

IP Route Table for VRF "default"
Gateway of last resort is 34.95.33.254 to network 0.0.0.0

B*      0.0.0.0/0 [200/0] via 34.95.33.254, int0, 00:00:16
C       34.95.33.0/24 is directly connected, int0
B       100.64.0.0/16 [200/0] via 34.95.33.254, int0, 00:00:16
C       172.16.0.0/23 is directly connected, int1
rtr-cod#ping 77.88.8.8
PING 77.88.8.8 (77.88.8.8) 56(84) bytes of data.
64 bytes from 77.88.8.8: icmp_seq=1 ttl=55 time=40.1 ms
64 bytes from 77.88.8.8: icmp_seq=2 ttl=55 time=31.9 ms
64 bytes from 77.88.8.8: icmp_seq=3 ttl=55 time=38.7 ms

--- 77.88.8.8 ping statistics ---
3 packets transmitted, 3 received, 0% packet loss, time 2001ms
rtt min/avg/max/mdev = 31.865/36.882/40.050/3.588 ms
rtr-cod#

```

- Настройка NAT:

```
conf t
```

```
interface int0  
ip nat outside  
exit
```

```
interface int1  
ip nat inside  
exit
```

```
ip nat pool COD 172.16.0.1-172.16.1.254
```

```
ip nat source dynamic inside-to-outside pool COD overload interface int0  
write memory
```