

Admin User Management Build Comparison

Previous version vs. enhanced build - 14 September 2026

Executive summary

The user-management page has been upgraded from a read-heavy CRM view with permanent deletion into an operational control center. Administrators can now grant or remove course access, ban or unban accounts, revoke sessions when banning, search phone numbers reliably despite formatting, filter banned users, inspect login activity, and review an audit trail of sensitive actions.

Area	Previous version	Enhanced build
Search	Name, email, mobile and course text	Same coverage plus normalized phone-number matching and deferred filtering for responsive typing
Subscription	Status display and filter only	Grant or extend 1-3650 days; remove app access immediately; expiry visible
Account access	Active state displayed; deletion available	Ban/unban controls, mandatory ban reason, immediate session and device-token revocation
Safety	Delete confirmation	Confirmations for all sensitive actions, required reasons, bounded input, protected APIs
Auditability	No user action history	Latest 25 admin access/subscription actions with previous and next state
Operations	Subscription filter and CRM segments	Added active/banned account filter, login count, last-login date, ban reason and subscription end date

Feature details

Grant or extend subscription access

An administrator chooses a duration in days and records a required reason. The backend creates or updates the Subscription record, synchronizes the User status and expiry, and records the change.

Remove subscription access

Access is expired immediately in both the User and Subscription records. The interface explicitly warns that this does not cancel an external payment mandate; payment-provider cancellation remains a separate operational responsibility.

Ban and unban

Banning requires a reason, sets the account inactive, records the timestamp and reason, clears active web/mobile sessions, and removes the device token. Existing authentication middleware already rejects inactive users. Unban restores sign-in eligibility.

Enhanced search and filters

Search covers user name, email, mobile number, subscription status, demographic values and course titles. Phone matching ignores punctuation and country-code formatting. An account-access filter isolates active or banned users.

Operational account detail

Expanded records now show subscription expiry, last login, login count, ban reason, learning progress, watch time and verification status.

Admin action history

The latest 25 ban, unban, grant and revoke actions are available inside each user record. Entries retain reason, admin subject, previous state, next state and timestamp.

Existing capabilities retained

CRM segments, subscription filters, sorting, pagination, CSV export, course-progress drill-down, deletion requests, refresh and permanent deletion remain available.

Code and data changes

Component	Change
User model	Added bannedAt and bounded banReason fields.
AdminUserAction model	New immutable-style audit collection for sensitive account operations.
Backend API	Added protected access, subscription and action-history endpoints.
Admin React page	Added controls, responsive search, filters, detail fields, warnings and action history.
Admin stylesheet	Added layouts for management controls, alerts and audit rows.
Tests	Added targeted checks for authorization, required reason, session revocation, duration bounds and audit metadata.

Verification

Check	Result
Backend JavaScript syntax	Pass
Targeted admin/auth/session tests	10 passed, 0 failed
Frontend production build	Pass - 116 modules transformed
Dependency vulnerability audit	0 vulnerabilities reported during npm install
Interactive browser QA	Not run: browser-control runtime was unavailable in this session

Operational note

Manual subscription removal controls application access only. If the customer has a live PhonePe or Razorpay recurring mandate, cancel that mandate through the payment-provider workflow as well. No database migration is required for the new optional user fields; MongoDB will populate them when an action occurs.