

[Microsoft-Teams-Samples/samples/app-anonymous-users/csharp at main · OfficeDev/Microsoft-Teams-Samples · GitHub](https://github.com/microsoft/OfficeDev/Tree/main/OfficeDev/Microsoft-Teams-Samples/samples/app-anonymous-users/csharp)

Online Meeting / Get Teams App Settings

GET `https://graph.microsoft.com/beta/teamwork/teamsappsettings`

Params Authorization Headers (9) Body Pre-request Script Tests Settings

Type Bearer Token

Heads up! These parameters hold sensitive data. To keep this data secure while working in a collaborative environment, we recommend using variables.

The authorization header will be automatically generated when you send the request. Learn more about authorization.

Token `{{UserAccessToken}}`

Body Cookies Headers (10) Test Results Status: 200 OK Time

```
1 {
2   "@odata.context": "https://graph.microsoft.com/beta/$metadata#teamwork/teamsAppSettings/$entity",
3   "id": "a6218add-62d4-4c65-a992-da1ec5d85e38",
4   "allowUserRequestsForAppAccess": true,
5   "isChatResourceSpecificConsentEnabled": true
6 }
```

Meeting settings

Meeting settings are used to control whether anonymous people can join Teams meetings and what is included in the meeting invitations. You can also enable Quality of Service (QoS) and set the ports for real-time traffic. These settings are used for all Teams meetings that people schedule in your organization. [Learn more](#)

Participants

- Anonymous users can join a meeting
This setting is also controlled at Meetings > Meeting policies and Meetings > Live events policies On
- Anonymous users can interact with apps in meetings On

