

Video-15

Topics to cover:

- Joins in SQL
 - 5. CROSS JOIN
 - 6. SELF JOIN

5. CROSS JOIN: Produces the Cartesian product of both tables.

Every row from the first table combines with every row from the second.

Syntax:

```
SELECT column_list  
FROM table1  
CROSS JOIN table2;
```

Note: If 3 employees and 4 departments exist, result = 12 rows

Example Tables

1. Students Table

```
CREATE TABLE Students (  
    student_id INT PRIMARY KEY,  
    student_name VARCHAR(50)  
);  
INSERT INTO Students (student_id, student_name) VALUES  
(1, 'Alice'),  
(2, 'Bob');
```

2. Courses Table

```
CREATE TABLE Courses (  
    course_id INT PRIMARY KEY,  
    course_name VARCHAR(50)  
);  
INSERT INTO Courses (course_id, course_name) VALUES  
(101, 'Math'),  
(102, 'Science');
```

CROSS JOIN Example

```
SELECT student_id, student_name, course_name  
FROM Students  
CROSS JOIN Courses;
```

6. SELF JOIN: A self join is simply a regular join where a table is joined to itself. You must use aliases to differentiate the two instances of the same table.

Syntax:

```
SELECT a.column_list, b.column_list  
FROM table_name a  
JOIN table_name b  
ON a.common_column = b.common_column;
```

```
CREATE TABLE employees (  
    emp_id INT PRIMARY KEY AUTO_INCREMENT,  
    name VARCHAR(50) NOT NULL,  
    manager_id INT,  
    FOREIGN KEY (manager_id) REFERENCES employees(emp_id)  
);
```

```
INSERT INTO employees (name, manager_id)  
VALUES  
    ('Amit', NULL), -- Amit is the top-level manager (no manager)  
    ('Priya', 1),   -- Priya reports to Amit  
    ('Ravi', 1),    -- Ravi reports to Amit  
    ('Sneha', 2),   -- Sneha reports to Priya  
    ('Arjun', 3);   -- Arjun reports to Ravi
```

```
SELECT * FROM employees;
```

```
SELECT e1.emp_id, e1.name AS Employee, e2.name AS Manager  
FROM employees e1  
LEFT JOIN employees e2  
ON e1.manager_id = e2.emp_id;
```