

# Notes 6

---

## mkdir (Make Directory)

---

Definition: The mkdir command is used to create new directories (**folders**) in the Linux file system. By default, it creates directories within the current working directory unless an absolute path is specified.

### Usage/Formula:

```
mkdir [OPTION]... DIRECTORY_NAME...
```

## Examples:

---

Create a single directory named Test in the current location:

```
mkdir Test
```

Create multiple directories (dir1, dir2, dir3) at once:

```
mkdir dir1 dir2 dir3
```

## touch

---

Definition: The touch command is primarily used to change a file's access and modification timestamps to the current time. If the specified file does not exist, touch will create a new, empty file with that name.

### Usage/Formula:

```
touch [OPTION]... FILE_NAME...
```

### Examples:

Create a single empty file named newfile.txt:

```
touch newfile.txt
```

Create multiple empty files simultaneously:

```
touch file1.txt file2.txt
```

## rm (Remove)

---

Definition: The rm command is used to delete files and directories permanently from the file system. Files removed with rm are not sent to a recycle bin and cannot be easily recovered.

### Usage/Formula:

```
rm [OPTION]... FILE/DIRECTORY_NAME...
```

### Examples:

Delete a single file named myfile.txt: `rm myfile.txt`

Interactively prompt for confirmation before deleting each file using the -i option:

```
rm -i unwanted_file.txt
```

## cp (Copy)

---

Definition: The cp command is used to duplicate files or directories from a source to a destination.

### Usage/Formula:

```
cp [OPTION]... SOURCE DESTINATION
```

### Examples:

Copy a file named file1.txt to a new file named file2.txt in the same directory:

```
cp file1.txt file2.txt
```

Copy a file named report.pdf into a different directory named Documents (keeping the same filename):

```
cp report.pdf Documents/
```

## mv (Move)

---

Definition: The mv command is used to move or rename files and directories from one location to another. Moving a file effectively renames it if the destination is in the same directory and has a different name.

### Usage/Formula:

```
mv [OPTION]... SOURCE DESTINATION
```

### Examples:

Rename a file named oldname.txt to newname.txt:

```
mv oldname.txt newname.txt
```

Move a file named data.txt into a different directory named Documents:

```
mv data.txt Documents/
```