

# "High Frequency Ceramic Solutions"

## 2.4GHz Mini Antenna, SMT


P/N 2450AT18A100

Detail Specification: 7/9/2018

Page 1 of 5

Let us help you with the antenna design, optimization, and tuning!

### General Specifications

|                         |                   |  |                |
|-------------------------|-------------------|--|----------------|
| Part Number             | 2450AT18A100      |  |                |
| Frequency (MHz)         | 2400 - 2500       |  |                |
| Avg. Rad Efficiency*    | 76%               |  |                |
| Peak Gain (dBi typ.)    | 0.5               |  |                |
| Average Gain (dBi typ.) | -0.5              |  |                |
| Return Loss (dB)        | 9.5 min.          | Storage Period   | 18 months max. |
| Impedance               | 50 $\Omega$       | Storage Temperature  | -40 to +125°C  |
| Input Power             | 2 Watts max. (CW) | Operating Temperature  | -40 to +125°C  |
|                         |                   | Reel Quantity  | 3000           |


\*Efficiency based on Johanson's standard evaluation board

### Part Number Explanation

|            |                  |   |                 |                           |
|------------|------------------|---|-----------------|---------------------------|
| P/N Suffix | Packing Style    | Bulk (loose)                                  | Suffix = S      | e.g. 2450AT18A100S        |
|            |                  | T & R   | Suffix = E      | e.g. 2450AT18A100E        |
|            |                  | 100% Tin                                      | Suffix = E or S | e.g. 2450AT18A100(E or S) |
|            | Evaluation Board | 2450AT18A100-EBSMA (see page 2&3 for details) |                 |                           |

### Mechanical Dimensions


|   | In                | mm             |
|---|-------------------|----------------|
| L | 0.126 $\pm$ 0.008 | 3.20 $\pm$ 0.2 |
| W | 0.063 $\pm$ 0.008 | 1.60 $\pm$ 0.2 |
| T | 0.051 +.004/-.008 | 1.30 +0.1/-0.2 |
| a | 0.020 $\pm$ 0.012 | 0.50 $\pm$ 0.3 |



Want the layout file? Request it at: [www.johansontechnology.com/ask-a-question](http://www.johansontechnology.com/ask-a-question)

### Terminal Configuration

| No. | Function |
|-----|----------|
| 1   | FEED     |
| 2   | NC       |



Johanson Technology, Inc. reserves the right to make design changes without notice.  
All sales are subject to Johanson Technology, Inc. terms and conditions.



[www.johansontechnology.com](http://www.johansontechnology.com)  
4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821  
Ver. 3.0 2018 Johanson Technology, Inc. All Rights Reserved

# "High Frequency Ceramic Solutions"



## 2.4GHz Mini Antenna, SMT

Detail Specification: 7/9/2018

P/N 2450AT18A100

Page 2 of 5

### Mounting Considerations 1: Evaluation Board



JTI P/N for Matching Circuit: Cap  
(1.0pF): 500R07S1R0BV4T  
Inductor (2.7nH): L-07C2N7SV6T  
Inductor (3.9nH): L-07C3N9SV6T

To order a pre-tuned 50Ω EVB with a female SMA connector click  
here: [www.johansontechnology.com/request-a-sample](http://www.johansontechnology.com/request-a-sample)

Reference p/n: 2450AT18A100-EBSMA

Johanson Technology, Inc. reserves the right to make design changes without notice.  
All sales are subject to Johanson Technology, Inc. terms and conditions.



Ver. 3.0

[www.johansontechnology.com](http://www.johansontechnology.com)

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

2018 Johanson Technology, Inc. All Rights Reserved

# "High Frequency Ceramic Solutions"

## 2.4GHz Mini Antenna, SMT




P/N 2450AT18A100

Detail Specification: 7/9/2018

Page 3 of 5

### Mounting Considerations 1: Typical Electrical Performance (T=25°C)

Return Loss with matching circuit @ +25C VSWR with matching circuit @ +25C and +125C



m1  
freq=2.400GHz  
VSWR\_25=1.386  
m2  
freq=2.500GHz  
VSWR\_25=1.219

m4  
freq=2.400GHz  
VSWR\_125=1.606  
m3  
freq=2.500GHz  
VSWR\_125=1.332

Johanson Technology, Inc. reserves the right to make design changes without notice.  
All sales are subject to Johanson Technology, Inc. terms and conditions.



Ver. 3.0

[www.johansontechnology.com](http://www.johansontechnology.com)

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

2018 Johanson Technology, Inc. All Rights Reserved

# "High Frequency Ceramic Solutions"

## 2.4GHz Mini Antenna, SMT


Detail Specification: 7/9/2018

P/N 2450AT18A100

Page 4 of 5

### Mounting Considerations 1: Antenna Performance

Typical 2D radiation patterns @ 2.44GHz



Johanson Technology, Inc. reserves the right to make design changes without notice.  
All sales are subject to Johanson Technology, Inc. terms and conditions.



Ver. 3.0

[www.johansontechnology.com](http://www.johansontechnology.com)

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

2018 Johanson Technology, Inc. All Rights Reserved

## "High Frequency Ceramic Solutions"

2.4GHz Mini Antenna, SMT

P/N 2450AT18A100

Detail Specification: 7/9/2018

Page 5 of 5

### Antenna tuning, optimization, and validation services:

[www.johansontechnology.com/ipc-antenna-services](http://www.johansontechnology.com/ipc-antenna-services)

### For more antennas and to download measured S-parameters, go to:

[www.johansontechnology.com/antennas](http://www.johansontechnology.com/antennas)

### Soldering Information

[www.johansontechnology.com/ipcsoldering-profile](http://www.johansontechnology.com/ipcsoldering-profile)

### MSL Info

[www.johansontechnology.com/msl-rating](http://www.johansontechnology.com/msl-rating)

### Packaging information

[www.johansontechnology.com/tape-reel-packaging](http://www.johansontechnology.com/tape-reel-packaging)

### For layout review contact our Applications Team at:

[www.johansontechnology.com/ask-a-question](http://www.johansontechnology.com/ask-a-question)

### RoHS Compliance

[www.johansontechnology.com/rohs-compliance](http://www.johansontechnology.com/rohs-compliance)

Need help designing the antenna in? Use our antenna design services!

[www.johansontechnology.com/ipc-antenna-services](http://www.johansontechnology.com/ipc-antenna-services)

We provide 2 free layout reviews and if you need us to tune and characterize the antenna on your product (inside anechoic chamber) we can do that too. Small lab fee may apply for the latter.

Johanson Technology, Inc. reserves the right to make design changes without notice.  
All sales are subject to Johanson Technology, Inc. terms and conditions.



[www.johansontechnology.com](http://www.johansontechnology.com)  
4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821  
Ver. 3.0 2018 Johanson Technology, Inc. All Rights Reserved

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Johanson:

2450AT18A100E