Architectural Framework for an Intelligent Urban Flash Flood Early Warning and Evacuation System in Kenya

1. Introduction to Urban Flash Flood Dynamics in Equatorial East Africa

Equatorial East Africa (EEA) is characterized by highly variable climate dynamics that frequently culminate in severe hydro-meteorological hazards. The region exhibits a pronounced teleconnection to global climate phenomena, notably the Madden-Julian Oscillation (MJO), which has been empirically linked to extreme weekly rainfall events and subsequent fluvial and pluvial flood risks.[1] Within this climatic context, rapidly urbanizing centers like Nairobi face an escalating threat from flash floods. Unplanned urban expansion, deteriorating natural drainage corridors, and the proliferation of informal settlements have fundamentally altered the hydrological response of local watersheds.[2]

In Nairobi, where approximately 4.4 million residents are densely concentrated, an estimated 27% of the total city area is classified as flood-prone.[3] The vulnerability is acutely spatial; the density of built-up structures correlates directly with exposure. Analysis reveals that 35% of Nairobi's built-up areas are exposed to flood hazards, with informal settlements such as Kibera, Mathare, Mukuru, and Kariobangi bearing disproportionate risk due to their proximity to riparian zones and inadequate pervious surfaces.[3] The Nairobi River, stretching approximately 390 kilometers and acting as the primary drainage artery for the Athi Catchment Basin, is severely compromised by solid waste accumulation, notably in Kibera, which impedes hydraulic conveyance and exacerbates localized inundation.[4] Over the last few decades, rapid land-use changes have further compounded these vulnerabilities. For instance, in the neighboring Mavoko Municipality, built-up areas that are largely impervious increased from 24.6% in 1989 to 37.0% in 2018, resulting in 76% of the annual precipitation being converted directly into surface runoff.[4]

Traditional early warning systems in the region have historically relied on broad, synoptic-scale forecasts with lead times of several days, which are fundamentally inadequate for the rapid onset of flash floods.[1] Convective rainfall can cause dangerous flash floods in less than six hours, demanding systems capable of real-time nowcasting and immediate automated response.[6] Furthermore, global flood forecasting models, such as GloFAS, while highly sophisticated, frequently fail to capture the micro-topographical nuances of urban drainage

networks, resulting in false alarm rates exceeding 50% for localized basins like the Nzoia River.[1]

Current institutional frameworks also suffer from dissemination bottlenecks. Despite the generation of seasonal, monthly, and daily forecast information by the Kenya Meteorological Department (KMD), this critical intelligence often fails to reach vulnerable communities systematically.[8] Assessments of the Eastern Nile Flash Flood Early Warning System (EN-FFEWS) during the 2023 long rains demonstrated that while technical agencies accurately predicted flooding in Kenya's Lake Victoria basin a week in advance, the warnings were not translated into actionable public advisories.[9] Conversely, neighboring nations like Rwanda have successfully converted technical forecasts into accessible public warnings via mobile channels.[9]

To address these systemic deficiencies, an effective urban flash flood early warning system (FFEWS) requires a paradigm shift. It must synthesize hyper-local, real-time meteorological data, high-resolution hydrological modeling, dynamic routing algorithms, and multi-channel, impact-based dissemination protocols to deliver actionable evacuation intelligence to vulnerable populations.[10] This report delineates the architecture of a comprehensive flash flood early warning and dynamic evacuation system tailored for Kenyan cities, transitioning from atmospheric observation to citizen-level evacuation routing.

2. Meteorological Data Acquisition and Nowcasting Integration

The foundational layer of the FFEWS is the continuous ingestion and synthesis of high-fidelity meteorological data. Relying exclusively on sparse terrestrial rain gauges is insufficient for capturing the spatial heterogeneity of convective storms that drive urban flash floods. Therefore, a hybrid approach combining open-source weather Application Programming Interfaces (APIs), satellite-derived estimations, and localized terrestrial sensor networks is strictly required to feed the hydrological models.

2.1 Open-Source Weather APIs and Numerical Weather Prediction (NWP)

Modern open-source weather APIs aggregate data from diverse global and mesoscale models, providing essential inputs for rainfall-runoff simulation. The integration of multiple NWP sources allows the system to utilize ensemble forecasting, minimizing the inherent uncertainties of meteorological prediction.

Open-Meteo provides a highly capable open-source API that leverages a sophisticated ensemble of global (11 km resolution) and localized mesoscale (1 km resolution) models from esteemed national weather services.[12] By providing hourly resolution data and updating its local models hourly via rain radar assimilation, Open-Meteo ensures that rapid changes in convective storm intensity are captured.[12] Additionally, it offers up to 80 years of historical data,

which is invaluable for establishing climatic baselines and training predictive algorithms.[12]

Alternatively, OpenWeatherMap's One Call API 3.0 delivers minute-by-minute precipitation forecasts for the immediate hour, alongside hourly forecasts extending 48 hours ahead and daily forecasts up to 8 days.[14] Crucially, it integrates government-issued national severe weather alerts (e.g., NOAA, EUMETNET), providing an additional layer of macro-level situational awareness.[14]

Other robust alternatives include the Tomorrow.io API, which offers ultra-accurate, hyperlocal data up to 14 days ahead, alongside high-resolution map tiles that can be integrated directly into geographic information systems (GIS) using libraries like Mapbox or Leaflet.[15] Meteosource presents another specialized option, utilizing machine learning algorithms to minimize NWP errors by aggregating multiple models, thereby providing specific hourly and daily rain probabilities tailored for coordinates in Nairobi.[16]

API Provider	Spatial Resolution	Update Frequency	Key Hydrological Features
Open-Meteo	Up to 1 km	Hourly	Assimilates rain radar; provides historical data up to 80 years; completely open-source for non-commercial use.[12]
OpenWeatherMap	Hyperlocal	Minutely	1-minute precision for the next hour; integrates government alerts; 40 years of historical data.[14]
Tomorrow.io	Hyperlocal	Minutely/Hourly	Custom weather monitoring conditions; dynamic weather map tiles for UI integration; 20 years historical.[15]

Meteosource	Point-based	Real-time	Machine learning error minimization; detailed hourly precipitation out to 7 days.[16]

2.2 Terrestrial Sensor Networks and National Datasets

While satellite and API data provide expansive coverage, their estimations must be continuously ground-truthed against local telemetry to correct bias and improve algorithmic accuracy. The Trans-African Hydro-Meteorological Observatory (TAHMO) operates a dense network of automated weather stations across the continent, providing rigorously quality-controlled daily and hourly observations.[17]

Through the TAHMO API (accessible via endpoints supporting JSON, Pandas DataFrames, or CSV formats), the system can extract critical hydrological parameters that dictate flood initiation.[18] These parameters include soilmoisture (volumetric water content, θ), soiltemperature, waterlevel in local rivers, discharge rates, and even lightningevents to gauge storm severity.[19] To facilitate rapid deployment, developers can utilize open-source Python modules such as filter-stations, which interface directly with the TAHMO API and retrieve unified weather datasets hosted on platforms like HuggingFace.[20] When parsing TAHMO data, the precip_quality_flag parameter is critical; values must be strictly greater than zero to be admitted into the simulation pipeline, ensuring that only verified observations influence the evacuation logic.[17]

Furthermore, the system must interface with the official datasets maintained by the Kenya Meteorological Department (KMD). The KMD provides dekadal (10-day) rainfall indicators derived from CHIRPS-GEFS satellite imagery combined with in-situ station data.[21] This dataset encompasses 1-month and 3-month rolling aggregations, as well as their long-term averages.[22] These rolling aggregations are indispensable for calculating long-term soil saturation and antecedent moisture conditions prior to an acute storm event, allowing the system to accurately predict how much rainfall will be absorbed versus how much will become surface runoff.[22] KMD data can be accessed programmatically or requested via the Kenyan e-citizen portal, ensuring alignment with national meteorological protocols.[23]

3. Hydrological Modeling and Rainfall-Runoff Transformation

Transforming meteorological precipitation forecasts into precise volumetric runoff metrics requires the deployment of robust hydrological models. While regional-scale systems might employ the Weather Research and Forecasting Hydrological modeling system (WRF-Hydro) to

simulate continuous spatial patterns [24], urban flash flood systems demand highly parameterized models capable of accounting for intense imperviousness and artificial drainage.

3.1 The SCS-CN Method for Urban Catchments

The Soil Conservation Service Curve Number (SCS-CN) method remains the premier empirical model for estimating direct surface runoff from effective rainfall. The method relies heavily on local land use cover, soil pedology, and antecedent moisture conditions to determine the infiltration capacity of the watershed. The fundamental equation governing the SCS-CN model is expressed mathematically as:

$$Q = \frac{(P - I_a)^2}{P - I_a + S}$$

Where Q represents the accumulated direct runoff depth (mm), P is the accumulated rainfall depth (mm), I_a is the initial abstraction representing the sum of canopy interception, surface depression storage, and infiltration prior to runoff, and S is the potential maximum retention of the soil. Empirical studies typically approximate initial abstraction as $I_a = 0.2S$.[25] The potential maximum retention S is directly derived from the dimensionless Curve Number (CN) via the relationship $S = \frac{25400}{CN} - 254$.

In the context of the Nairobi watershed, empirical investigations utilizing the Hydrologic Engineering Center's Hydrologic Modeling System (HEC-HMS) reveal alarming metrics. The Nairobi watershed exhibits a composite Curve Number of 89 and is characterized by a staggering 55% imperviousness.[2] Furthermore, soil survey data indicates that the watershed is predominantly overlain by soils classified under Hydrological Soil Group (HSG) C, denoting slow infiltration rates when thoroughly wetted and a high runoff potential.[2]

This extreme imperviousness, combined with poor natural infiltration, significantly reduces the lag time between peak rainfall and peak discharge. Sensitivity analyses demonstrate that as urbanization increases pavements and buildings, the SCS lag time drops precipitously, engineering a system uniquely primed for catastrophic flash flooding.[2] Consequently, even moderate convective storms over Nairobi yield massive volumes of rapid surface water.[2]

3.2 Dynamic Flash Flood Thresholds and Trigger Mechanisms

A deterministic FFEWS must operate on predefined threshold criteria to automate the transition from environmental monitoring to public alert dissemination. Relying purely on total

rainfall depth is insufficient; the rate of precipitation and the preexisting state of the soil dictate the hazard level.

3.2.1 Empirical Rainfall Intensity-Duration (I-D) Thresholds

Flash floods in urban environments are predominantly driven by short-duration, high-intensity storms. The general Intensity-Duration (I-D) threshold is mathematically defined as $I = \alpha D^{-\gamma}$, where I is the rainfall intensity (mm/hr), D is the duration, and α and γ are empirical regional parameters.[28]

For East Africa, a broad operational definition often classifies heavy, flood-inducing rainfall as exceeding 50 mm in a single event.[29] However, precise extreme value analysis utilizing Generalized Pareto Distribution (GPD) models applied to Nairobi's historical precipitation data indicates critical intraday thresholds. Using Maximum Likelihood Estimation (MLE), researchers have statistically isolated a threshold of 34.5 mm/hr as a highly predictive indicator of urban flash flooding in the Nairobi basin.[6] When open-source APIs forecast precipitation intensities approaching this 34.5 mm/hr limit, the system's heuristic engines are primed for alert generation.

3.2.2 The Antecedent Rainfall Index (ARI)

Rainfall intensity alone does not provide a complete picture; the pre-existing saturation of the catchment dictates the true runoff coefficient. The Antecedent Rainfall Index (ARI) quantifies this pre-event soil moisture state, acting as a dynamic multiplier for flood risk.[30] A specific disaster index, β, can be defined as the ratio of antecedent rainfall to intraday rainfall. Studies have shown that when β exceeds a critical threshold (e.g., $\beta = 5$), the correlation with flood initiation approaches certainty.[28]

By continuously calculating the ARI via the rolling 1-month and 3-month precipitation aggregates provided by the KMD [22], combined with real-time soilmoisture telemetry from TAHMO [19], the system dynamically adjusts the I-D trigger thresholds. For instance, if the catchment is fully saturated following weeks of seasonal rain (driving the operational CN toward 98), a mere 15 mm/hr rainfall event may breach the flood initiation threshold. Conversely, a completely dry catchment ($CN \approx 75$) may comfortably absorb 30 mm/hr without initiating overland flow.[25]

Catchment Condition	Soil Moisture Profile	Operational CN	Adjusted Rainfall Threshold

Dry (AMC I)	Below wilting point	~75	> 45.0 mm/hr
Average (AMC II)	Moderate saturation	~89	> 34.5 mm/hr
Wet (AMC III)	Near field capacity	~98	> 15.0 mm/hr

4. Hydraulic Modeling and Topographical Processing

Once the hydrological parameters compute the expected runoff volume, the system must simulate the spatial propagation of the flood wave across the urban topography to determine exactly which streets, neighborhoods, and bridges will be submerged.

4.1 2D Hydraulic Routing via HEC-RAS

The industry standard for simulating floodplain inundation is the Hydrologic Engineering Center's River Analysis System (HEC-RAS). By coupling the 1D surface hydrology outputs from models like HEC-HMS or PCSWMM with a 2D HEC-RAS model, the system can solve the diffusive wave or full shallow water equations.[33] This process generates contiguous raster grids representing water depth, velocity, and hazard classification across the city.[34]

The accuracy of this hydraulic simulation is entirely contingent upon the resolution and quality of the underlying Digital Elevation Model (DEM). Global datasets, such as the 30-meter resolution Copernicus DEM or SRTM data, are freely available and easily ingested via APIs.[38] However, studies focused on Nairobi have demonstrated that raw global DEMs frequently fail to account for dense urban structures, walls, and road embankments, leading to misrepresentations of actual street-level drainage paths.[3] Utilizing urban-corrected DEMs that algorithmically adjust for building density dramatically improves the skill of the inundation mapping, yielding highly accurate flood extent and depth predictions.[37]

In highly informal settlements like Kibera, where formal drainage networks are virtually non-existent and unmapped, high-resolution topographical models combined with local community data provide the only reliable predictive capability.[3] Platforms such as FlyPix AI can process UAV imagery, satellite data, and LiDAR to generate incredibly precise terrain elevations and automated hydrodynamic models, facilitating micro-level watershed management without requiring extensive manual coding.[40] For a programmatic open-source approach, developers can deploy Python packages like HybridUrb, which is specifically designed for fast, probabilistic urban pluvial flood prediction, significantly reducing the heavy computational overhead

typically associated with standalone HEC-RAS instances.[41]

4.2 Automated Raster-to-Vector Geoprocessing

To generate actionable evacuation advisories, the system must translate the hydraulic model outputs—which exist as continuous raster grids of water depth—into navigable vector geometries (GeoJSON polygons) that routing algorithms can comprehend and process.[42]

Using open-source Python geospatial libraries such as GDAL, rasterio, and geopandas, the pipeline automates the extraction of dangerous flood zones.[42] The 2D depth grids generated by the hydraulic simulation are first statistically reclassified. For instance, any raster pixel exhibiting a water depth exceeding 0.3 meters (the approximate depth at which a standard vehicle loses traction and individuals face severe wading difficulty) is classified as an impassable obstacle.

The GDAL Polygonize function is then invoked to convert these thresholded raster pixels into continuous, mathematically defined vector polygons.[45]

Python

```python
# Conceptual Python/GDAL implementation for raster polygonization
from osgeo import gdal, ogr
import sys

gdal.UseExceptions()

# Open the 2D depth raster generated by the hydraulic model
src_ds = gdal.Open("nairobi_flood_depth.tif")
srcband = src_ds.GetRasterBand(1)

# Create the GeoJSON output datasource
dst_layername = "impassable_flood_zones"
drv = ogr.GetDriverByName("GeoJSON")
dst_ds = drv.CreateDataSource("flood_zones.geojson")
dst_layer = dst_ds.CreateLayer(dst_layername, srs=None)

# Execute the polygonize algorithm
gdal.Polygonize(srcband, None, dst_layer, -1,, callback=None)
```

This automated Python workflow allows the system to continuously update the spatial bounds

of the disaster zone in near real-time, instantly converting evolving flood waters into distinct geographical boundaries that can be shared across web interfaces and APIs.[39]

4.3 OpenStreetMap Integration and Heuristic Validation

The generated GeoJSON flood polygons are systematically overlaid onto OpenStreetMap (OSM) highway and waterway data. The Kenyan OSM community, active since the 2018 FOSS4G conference, has comprehensively mapped extensive drainage and road networks, specifically tagging historical flood zones with the flood_prone=yes attribute.[47] This tagging is primarily applied to vulnerable infrastructure such as low-lying bridges, culverts, and underpasses.[48]

Integrating these heuristic tags provides a crucial secondary validation layer for the FFEWS. If a simulated flood polygon generated by the hydraulic model intersects an OSM segment tagged flood_prone=yes, or aligns with known World Resources Institute (WRI) drainage basins [49], the statistical confidence interval of the alert is heavily reinforced.[48] This synthesis of machine-generated hydrodynamic data with human-verified, crowd-sourced intelligence creates a highly robust hazard map.

5. Geospatial Intelligence and Dynamic Routing Algorithms

Providing an early warning without outlining a safe egress path frequently causes panic, leading populations to evacuate directly into the path of the flood wave or become trapped in congested bottlenecks. The integration of the generated GeoJSON flood polygons into open-source routing engines guarantees that the advised evacuation routes actively circumvent impassable terrain.[51]

5.1 Routing Engine Selection: OSRM vs. GraphHopper

The Open Source Routing Machine (OSRM) and GraphHopper are the preeminent open-source routing frameworks globally, both utilizing state-of-the-art graph algorithms (such as Dijkstra, A*, and Contraction Hierarchies) to compute routes across vast street networks within milliseconds.[53]

However, they diverge fundamentally in their mathematical capacity to handle real-time, dynamic roadblocks—such as the sudden appearance of flood polygons. OSRM relies heavily on aggressive pre-computation via Contraction Hierarchies (CH) or Multi-Level Dijkstra (MLD) to achieve its speed.[55] Attempting to extract alternative routes that dynamically avoid specific road segments in OSRM without rebuilding the entire graph requires highly complex and unstable parameter tuning. For instance, modifying variables like kSearchSpaceOverlapFactor, kAlternativesToUnpackFactor, and kAtMostLongerBy frequently results in algorithms returning zero alternatives, or generating illogical paths that still share nodes with the flooded road

segments.[55] While tools built on OSRM, like openrouteservice, have implemented avoid_polygons features for disaster scenarios (such as the 2013 Magdeburg floods using Twitter data) [56], OSRM's core architecture is inherently rigid.

Conversely, GraphHopper natively supports "Customizable Routing" (CR) through custom weighting profiles defined via JSON payloads submitted exactly at query time.[57] GraphHopper explicitly permits the definition of restricted geospatial zones using GeoJSON polygons without necessitating a complete rebuild of the underlying road graph.[58]

5.2 Implementation of Dynamic Area Avoidance in GraphHopper

Using GraphHopper, the early warning system ingests the flood_zones.geojson generated by the Python/GDAL pipeline. A custom routing profile is instantiated where the priority (edge weight) of any road segment falling within the geographical bounds of the flood polygon is mathematically reduced to zero. This operation algorithmically eliminates those flooded edges from the shortest-path graph calculation.[58]

JSON

```
{
 "priority": [{
  "if": "in_flood_zone",
  "multiply_by": "0"
 }],
 "areas": {
  "flood_zone": {
   "type": "Feature",
   "properties": {},
   "geometry": {
    "type": "Polygon",
    "coordinates": [[[36.78, -1.31], [36.82, -1.31], [36.82, -1.28], [36.78, -1.28], [36.78, -1.31]]]
   }
  }
 }
}
```

By querying the GraphHopper API with the citizen's current GPS coordinates (origin) and the nearest designated higher-ground safe zone (destination), the A* algorithm computes the optimal path that strictly adheres to the non-flooded topological network.[58] This safe route geometry—including turn-by-turn instructions and specific roads to avoid—is then serialized

and passed directly to the dissemination architecture.

6. Multi-Channel Alert Dissemination Architecture

The efficacy of a technical early warning system is ultimately governed by its last-mile delivery mechanism. Relying solely on smartphone applications or high-bandwidth web portals is fundamentally unviable in regions exhibiting vast disparities in digital equity. The communication architecture must be multi-tiered, resilient to network degradation (which frequently occurs during severe convective storms), and highly localized to prevent generalized warning fatigue.[9]

The ICPAC Husika platform exemplifies this multi-channel philosophy, emphasizing smart tagging, precision geo-targeting, and structured approval workflows to ensure that early warnings reach the intended demographic accurately.[62] As demonstrated during disaster risk reduction efforts in Busia County, Husika dismantled communication silos by targeting specific wards in appropriate local languages, thereby ensuring alerts were highly actionable.[62] Building upon these principles, the proposed dissemination framework employs three primary protocols: USSD/SMS, the WhatsApp Business API, and Telegram Bots.

6.1 USSD and SMS via Telecommunications APIs

Unstructured Supplementary Service Data (USSD) and Short Message Service (SMS) remain the most robust, universally accessible communication channels in Kenya. They function flawlessly on basic feature phones and operate entirely independent of 3G/4G cellular data access, which is crucial during power outages or broadband failures.[63] Platforms such as Africa's Talking and SMSLeopard provide RESTful APIs that interface directly with major Kenyan Mobile Network Operators (MNOs) like Safaricom, Airtel, Equitel, and Telkom.[64]

When the system triggers a localized flood alert, an SMS broadcast is instantly pushed to all registered MSISDNs (phone numbers) within the geo-fenced danger zone.[68] The SMS contains a concise hazard warning and prompts the user to dial a specific USSD code (e.g., *483*123#) for personalized evacuation instructions and safe routing.[67]

Upon the citizen dialing the code, the USSD application initiates a synchronous, interactive session. The Africa's Talking API sends a POST request (encoded as application/x-www-form-urlencoded) containing the user's sessionId, phoneNumber, networkCode (e.g., 63902 for Safaricom Kenya), and user input to the system's Python Flask webhook.[66] The system cross-references the user's known or inputted location, retrieves the dynamic GraphHopper safe-route text instructions, and returns the sequential evacuation steps directly to the user's screen in real-time.[70]

Dissemination Mechanism	Primary Advantage	Technical Limitation	Use Case
SMS Broadcast	Immediate, universal reach; 98% open rate.[64]	Limited to 160 characters; no rich media; no read receipts.[73]	Initial rapid alert and call to action.
USSD Session	Interactive, real-time querying without internet data.[71]	Prone to session timeouts; strict character limits per menu.[66]	Interactive step-by-step evacuation routing.

6.2 The WhatsApp Business API for Rich Media Dissemination

While USSD handles basic text logic for feature phones, WhatsApp dominates the Kenyan smartphone demographic. Organizations like Turn.io leverage the WhatsApp Business API to deliver high-impact, rich-media social services at immense scale, as seen in projects like MomConnect and Sauti East Africa.[74]

For the FFEWS, WhatsApp's critical technological advantage is the capacity to bypass the 160-character limit of SMS (WhatsApp supports up to 65,536 characters) and send high-resolution raster maps or GeoJSON visualizations of the flood zones directly to the citizen.[73] Furthermore, unlike SMS, which lacks delivery transparency and is subject to arbitrary carrier filtering, WhatsApp provides cryptographic end-to-end encryption and definitive read-receipts.[73] This allows disaster management coordinators to accurately track the penetration rate of the evacuation order in real-time.[73]

Additionally, utilizing platforms like Turn.io allows for conversational AI integration and vital feedback loops. Citizens can reply with geospatial pins of their location, photos of rising water levels for verification, or specific requests for emergency extraction, creating a powerful two-way communication channel.[61]

6.3 Telegram Bot Integration for Operational Coordination

To facilitate rapid, automated updates among disaster response teams, government officials, NGOs, and local community leaders, the system employs Python-based Telegram bots.[79] Utilizing libraries such as python-telegram-bot or telethon and authenticating via the Telegram Bot API (BotFather), the central Python orchestrator automatically broadcasts severe weather threshold breaches directly into designated public channels or private encrypted groups.[79]

Python

```python
# Conceptual Python Telegram Bot Broadcast Implementation
from telegram import Bot

# Authenticate via BotFather Token
TOKEN = "1234567890:ABCdefGHIjkIMNOpqrSTUvwxYZ"
CHANNEL_USERNAME = "@Nairobi_Flood_Alerts"
bot = Bot(token=TOKEN)

# Dispatch immediate alert to first responders
bot.send_message(
    chat_id=CHANNEL_USERNAME,
    text="🚨 FLASH FLOOD WARNING: Kibera Sectors 3 & 4. Water levels exceeding 0.5m. Immediate evacuation required via Route A. Avoid River Road."
)
```

Telegram bots deliver messages with extreme latency efficiency (studies indicate an average delivery time of just 4.07 seconds per dispatch) and, crucially, incur zero per-message cost.[83] This renders Telegram the optimal protocol for high-frequency internal operational updates and localized neighborhood watch groups.[82]

7. Participatory Mapping and Community Feedback Loops

Top-down dissemination of technological alerts is frequently insufficient without ground-level community integration. Sustainable water governance and disaster risk reduction require active multi-stakeholder engagement.[84]

In Kenya, the integration of local knowledge has proven highly effective. For example, in Tana River County, local "water scouts" from herder communities were recruited and trained as data stewards. Utilizing mobile applications like Open Data Kit (ODK) and platforms like KoboToolbox, these scouts map water infrastructure, creating critical datasets that aid in anticipating water scarcity and planning migratory routes.[84] A similar methodology is essential for the FFEWS. By integrating open-source tools like the Sketch Map Tool and MapSwipe, local communities can actively harness geographic knowledge, identifying hyper-local blockages in drainage networks that satellite models cannot resolve.[85]

The value of this participatory intelligence was explicitly demonstrated by the Kenya Red Cross in Garissa during the April 2024 floods. Volunteer reports provided crucial early warnings of rising river levels three days before major flooding occurred, giving communities precious time

to evacuate livestock and valuables.[9] This network of human sensors is invaluable in remote or highly informal areas where automated monitoring equipment is absent or frequently vandalized.[9] Through the feedback loops inherent in the Husika and WhatsApp platforms, citizens transition from passive recipients of alerts to active nodes in the early warning network.[61]

8. Economic and Operational Sustainability

The long-term viability of an intelligent FFEWS is heavily dependent on the economic constraints of operating the telecommunications infrastructure. A comprehensive cost-benefit analysis dictates the optimal routing of outgoing messages based on the urgency of the alert and the socio-economic profile of the recipient.

Acquiring a dedicated 3-digit or 4-digit USSD code (e.g., *123#) through a provider in Kenya carries significant capital expenditure. For instance, setup fees on Safaricom and Airtel range from KES 140,000 to KES 190,000, accompanied by recurring monthly maintenance fees of approximately KES 50,000 to KES 70,000 per Mobile Network Operator.[71] For a resource-constrained disaster management agency or NGO, these fixed costs are punitive and difficult to sustain.[88]

Consequently, utilizing a Shared USSD code (e.g., *483*X#) is the fiscally prudent architectural choice. Shared codes drastically reduce setup fees to zero or KES 15,000, with monthly maintenance dropping to a manageable KES 5,000 - KES 15,000.[71] The operational expenditure is therefore shifted to post-paid session costs, ranging from KES 1.00 to KES 4.90 per user interaction.[67] By bearing the post-paid session costs, the central system ensures that citizens with zero airtime balances can still access critical evacuation intelligence free of charge.[87]

USSD Code Type	**Setup Fee (KES)**	**Monthly Maintenance (KES)**	**Session Cost (KES)**
**Dedicated (e.g., 123#)*	140,000 - 190,000	50,000 - 70,000	1.00 - 4.90
Shared (e.g., *483X#*)	0 - 15,000	5,000 - 15,000	1.00 - 4.90

Data derived from Kenyan USSD providers including VasPro, Citycloud, and WinguSMS.[71]

For outbound notifications, WhatsApp Business API pricing is highly competitive and often

more efficient than SMS. Under Meta's 2025 pricing model, utility and authentication messages (which encompass critical disaster alerts) represent a highly transparent per-category cost.[72] While a standard international or high-volume SMS incurs variable costs depending on the aggregator, WhatsApp provides 24-hour conversational windows where all subsequent inbound and outbound messages between the system and the citizen are entirely free.[72] This economic structure heavily incentivizes the use of WhatsApp for citizens with data access, reserving the more expensive, character-limited SMS and USSD channels exclusively as fallbacks for populations relying on feature phones.[72]

To ensure seamless system behavior and eliminate financial risk during development, software engineers can utilize the Africa's Talking Sandbox environment. This free simulator allows developers to construct the complete 2-way SMS logic, test USSD channel routing, and debug callback webhook integrations via simulated handsets without incurring actual MNO charges.[91]

9. System Integration and Algorithmic Workflow

The final deployed architecture operates as a continuously cycling, highly automated, event-driven pipeline:

1. **Ingestion & Monitoring:** The Python backend routinely fetches 1-minute to hourly precipitation data from APIs like Open-Meteo, Tomorrow.io, and local TAHMO stations via HuggingFace datasets.[12] Concurrently, it queries the KMD's rolling monthly rainfall aggregates to determine the Antecedent Rainfall Index (ARI) and baseline soil saturation.[7]
2. **Hydrologic Trigger Evaluation:** The empirical parameters (e.g., Nairobi's composite Curve Number of 89 and HSG C soil classifications) are loaded.[2] If the real-time intensity-duration metric exceeds the computed safety threshold (e.g., >34.5 mm/hr adjusted by the disaster index β), the system initiates the hydraulic simulation.[2]
3. **Hydraulic Simulation:** A lightweight, automated hydraulic model (such as HybridUrb or an automated HEC-RAS 2D instance) projects the flood wave over an urban-corrected Copernicus DEM, factoring in the severe imperviousness of the environment.[4]
4. **Vectorization & Routing Adjustment:** Python scripts utilizing rasterio and osgeo.gdal isolate pixels where water depth exceeds safe limits (e.g., > 0.3 meters) and execute gdal.Polygonize to generate precise GeoJSON boundaries.[42] These polygons are instantly passed to the GraphHopper API via a custom weighting profile, mathematically nullifying the priority of all intersected road edges and generating safe egress paths.[42]
5. **Multi-Channel Dissemination:**
   - *Telegram Bots* immediately alert municipal coordinators, Red Cross volunteers, and emergency responders with zero latency.[9]
   - *SMS* is broadcasted to MSISDNs in the affected geospatial bounds as a primary siren.[64]
   - *WhatsApp Business API* (via platforms like Turn.io) dispatches rich-media hazard maps, conversational AI prompts, and safe-routing links directly to smartphones.[78]

- Citizens using feature phones dial the *Shared USSD code* to navigate an interactive menu, pulling specific, turn-by-turn evacuation instructions that reflect the dynamically updated, safe GraphHopper routes.[67]

6. **Feedback Loop & Adaptation:** Citizens report back via WhatsApp or USSD with visual confirmations or requests for aid, enriching the dataset and allowing human operators to manually update the danger zones if the automated models fail to capture localized debris blockages.[61]

10. Conclusion

The mitigation of mass casualties and systemic socio-economic disruption resulting from urban flash floods in Kenya relies entirely on shrinking the temporal gap between hazard detection and citizen action. By transitioning away from broad, static meteorological warnings with days of lead time, and adopting a highly integrated, deterministic computational framework capable of intra-hour responsiveness, municipalities can provide actionable, life-saving intelligence.

The synthesis of high-resolution numerical weather models (Open-Meteo, Tomorrow.io), accurate hydrological transformations (SCS-CN, ARI indices), rapid hydraulic vectorization (GDAL, Python geospatial libraries), and dynamic spatial routing (GraphHopper) establishes an exceptionally robust technological core.[2] However, the success of this architecture is cemented by its multi-modal dissemination strategy. Recognizing the stark digital divide, the simultaneous deployment of feature-phone compatible USSD and SMS, alongside rich-media WhatsApp interactions and instantaneous Telegram alerts, ensures that the generated intelligence penetrates the deepest and most vulnerable stratums of the urban population.[63]

Through this orchestrated alignment of open-source meteorological data, geographic information systems, participatory community mapping, and resilient telecommunication APIs, it is entirely feasible to deploy a highly resilient, automated, and economically sustainable flash flood early warning and dynamic evacuation system across Equatorial East Africa.

Works cited

1. Drivers and Subseasonal Predictability of Heavy Rainfall in Equatorial East Africa and Relationship with Flood Risk in - AMS Journals, accessed on March 8, 2026, https://journals.ametsoc.org/view/journals/hydr/22/4/JHM-D-20-0211.1.xml
2. Rainfall-runoff flood modelling in Nairobi urban watershed, Kenya - DSpace Repository, accessed on March 8, 2026, https://ir-library.ku.ac.ke/items/f8372889-598d-410d-bc4d-bb4156d4d768
3. DIAGNOSTIC OF URBAN FLOODING IN NAIROBI Report 2024 - University of Twente Research Information, accessed on March 8, 2026, https://research.utwente.nl/files/483486672/FloodExposure_Report_Nairobi_Space4All_1_.pdf
4. Runoff Estimation for an Urban Area using SCS-CN Method, Remote Sensing and

Geographic Information Systems Approach: A Case Study of Mavoko Municipality, Kenya - ResearchGate, accessed on March 8, 2026, https://www.researchgate.net/publication/341204351_Runoff_Estimation_for_an_Urban_Area_using_SCS-CN_Method_Remote_Sensing_and_Geographic_Information_Systems_Approach_A_Case_Study_of_Mavoko_Municipality_Kenya
5. Nairobi River: A Lifeline or Wasteland? - ArcGIS StoryMaps, accessed on March 8, 2026, https://storymaps.arcgis.com/stories/74594bbf43b14bd7add2293f6b73bb67
6. ASSESSMENT OF FLASH FLOODS IN THE STREETS OF NAIROBI CITY, THEIR RELATIONSHIPWITH RAINFALL AND SURFACE RUNOFF DRAINAGE AND THEIR, accessed on March 8, 2026, https://meteorology.uonbi.ac.ke/sites/default/files/cbps/sps/meteorology/Silvia.pdf
7. Rainfall Threshold for Flash Flood Warning Based on Model Output of Soil Moisture: Case Study Wernersbach, Germany - MDPI, accessed on March 8, 2026, https://www.mdpi.com/2073-4441/13/8/1061
8. Early Warning Communication for Enhanced Anticipatory Disaster Risk - Anticipation Hub, accessed on March 8, 2026, https://www.anticipation-hub.org/Documents/Analysis/Early_Warning_Communication_for_Enhanced_Anticipatory_Disaster_Risk_Management_June_2021.pdf
9. Early warning systems: Bridging tech and tradition to protect communities | Daily Nation, accessed on March 8, 2026, https://nation.africa/kenya/health/early-warning-systems-bridging-tech-and-tradition-to-protect-communities-5054162
10. Designing Effective Flood Early Warning Systems: A Review of Barriers, Best Practices, and Key Characteristics - the NOAA Institutional Repository, accessed on March 8, 2026, https://repository.library.noaa.gov/view/noaa/72059/noaa_72059_DS1.pdf
11. A Conceptual Flash Flood Early Warning System for Africa, Based on Terrestrial Microwave Links and Flash Flood Guidance - MDPI, accessed on March 8, 2026, https://www.mdpi.com/2220-9964/3/2/584
12. Open-Meteo.com: 🌤️ Free Open-Source Weather API, accessed on March 8, 2026, https://open-meteo.com/
13. Features | Open-Meteo.com, accessed on March 8, 2026, https://open-meteo.com/en/features
14. Weather API - OpenWeather, accessed on March 8, 2026, https://openweathermap.org/api
15. Free Weather API - 60+ Data Layers, 99.9% Uptime | Tomorrow.io, accessed on March 8, 2026, https://www.tomorrow.io/weather-api/
16. weather forecast data for Nairobi, Kenya - Global Weather API, accessed on March 8, 2026, https://www.meteosource.com/api-weather-forecast-nairobi
17. Climate Data - TAHMO, accessed on March 8, 2026, https://tahmo.org/climate-data/
18. TAHMO Server API - ZENTRA Cloud Help Documentation, accessed on March 8, 2026, https://docs.zentracloud.com/l/en/article/x5mqp9ry4b-api-v-3-0-tahmo
19. TAHMO API V1, accessed on March 8, 2026,

https://tahmo.org/docs/TAHMO_API_documentation_latest.pdf
20. filter-stations - PyPI, accessed on March 8, 2026, https://pypi.org/project/filter-stations/
21. ENACTS datasets at Kenya Meteorological Department (KMD) - CGSpace, accessed on March 8, 2026, https://cgspace.cgiar.org/bitstreams/56b5aa3d-f5c6-41cf-98a7-c325ebf9473e/download
22. Kenya: Rainfall Indicators at Subnational Level | Humanitarian Dataset | HDX, accessed on March 8, 2026, https://data.humdata.org/dataset/ken-rainfall-subnational
23. Climate Data Management - Kenya Meteorological Department, accessed on March 8, 2026, https://meteo.go.ke/Services/climate-data-management/
24. Towards Improved Flash Flood Forecasting over Dire Dawa, Ethiopia Using WRF-Hydro, accessed on March 8, 2026, https://www.mdpi.com/2073-4441/15/18/3262
25. Appendix D – NRCS Table of Curve Numbers Time of Concentration Calculation, accessed on March 8, 2026, https://www.medfordoregon.gov/files/assets/public/public-works/engineering/documents/design-standards/rogue-valley-sw-design-manual/appendix-d-tr55.pdf
26. Infiltration Methods - Hydrologic Engineering Center, accessed on March 8, 2026, https://www.hec.usace.army.mil/confluence/rasdocs/r2dum/6.5/developing-a-terrain-model-and-geospatial-layers/infiltration-methods
27. The Application and Applicability of HEC-HMS Model in Flood Simulation under the Condition of River Basin Urbanization - ResearchGate, accessed on March 8, 2026, https://www.researchgate.net/publication/371659377_The_Application_and_Applicability_of_HEC-HMS_Model_in_Flood_Simulation_under_the_Condition_of_River_Basin_Urbanization
28. Rainfall Threshold Triggering Floods - African Institute for Mathematical Sciences Library, accessed on March 8, 2026, https://library.nexteinstein.org/wp-content/uploads/2023/03/mediatrice_iradukunda_essay2022_final.pdf
29. Are Kenya Meteorological Department heavy rainfall advisories useful for forecast-based early action and early preparedness for - NHESS, accessed on March 8, 2026, https://nhess.copernicus.org/articles/21/261/2021/nhess-21-261-2021.pdf
30. Using rainfall thresholds and ensemble precipitation forecasts to issue and improve urban inundation alerts - HESS, accessed on March 8, 2026, https://hess.copernicus.org/preprints/hess-2016-340/hess-2016-340-manuscript-version4.pdf
31. A literature review: rainfall thresholds as flash flood monitoring for an early warning system, accessed on March 8, 2026, https://www.researchgate.net/publication/385350671_A_literature_review_rainfall_thresholds_as_flash_flood_monitoring_for_an_early_warning_system
32. Green and blue water resources and assessment of soil and water management

scenarios using an integrated modelling framework - ISRIC, accessed on March 8, 2026, https://files.isric.org/public/documents/isric_gwc_report_k3.pdf
33. Urban flash floods modeling in Mzuzu City, Malawi based on Sentinel and MODIS data, accessed on March 8, 2026, https://www.frontiersin.org/journals/climate/articles/10.3389/fclim.2024.1284437/full
34. A study of urban flooding mitigation using PCSWMM and HEC-RAS 2D - ICWMM, accessed on March 8, 2026, https://www.icwmm.org/Archive/2022-C031-11/a-study-of-urban-flooding-mitigation-using-pcswmm-and-hec-ras-2d
35. Coupling HEC-RAS and HEC-HMS in Precipitation Runoff Modelling and Evaluating Flood Plain Inundation Map - OAsis Research Repository - University of Nevada, Las Vegas, accessed on March 8, 2026, https://oasis.library.unlv.edu/cgi/viewcontent.cgi?article=1449&context=fac_articles
36. Rainfall-runoff modeling of urban floods using GIS and HEC-HMS - PMC - NIH, accessed on March 8, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC12226067/
37. City-scale Modelling of Factors Affecting Urban Pluvial Flood Hazard in Rapidly Developing Cities Using Global Data, accessed on March 8, 2026, https://etheses.whiterose.ac.uk/id/eprint/31459/
38. Nairobi: elevation — download elevation (topography) map - NextGIS Data, accessed on March 8, 2026, https://data.nextgis.com/en/region/KE-30/dem/
39. Simulating Flood Inundation with Python and Elevation Data: A Beginner's Guide, accessed on March 8, 2026, https://towardsdatascience.com/simulating-flood-inundation-with-python-and-elevation-data-a-beginners-guide/
40. Best Floodplain Mapping Tools for Accurate Risk Assessment - Flypix, accessed on March 8, 2026, https://flypix.ai/floodplain-mapping-tools/
41. HybridUrb: a Python package to perform hybrid urban flood modelling - GitHub, accessed on March 8, 2026, https://github.com/xldeltares/hybridurb
42. 12 Essential Python Libraries for Geospatial Data Analysis (with Hands-On Examples), accessed on March 8, 2026, https://www.geoapify.com/python-geospatial-data-analysis/
43. Learning resources for GIS in Python with cloud-native geospatial, PostGIS and more, accessed on March 8, 2026, https://blog.rtwilson.com/learning-resources-for-gis-in-python-with-cloud-native-geospatial-postgis-and-more/
44. Introduction to Python and Geopandas for Flooded Area Analysis - Tutorial - Hatari Labs, accessed on March 8, 2026, https://hatarilabs.com/ih-en/introduction-to-python-and-geopandas-for-flooded-area-analysis-tutorial
45. How to apply GDAL polygonize? - python - GIS StackExchange, accessed on March 8, 2026, https://gis.stackexchange.com/questions/417383/how-to-apply-gdal-polygonize
46. GeoJSON — GDAL documentation, accessed on March 8, 2026,

https://gdal.org/en/stable/drivers/vector/geojson.html
47. OSM Kenya - OpenStreetMap Wiki, accessed on March 8, 2026, https://wiki.openstreetmap.org/wiki/OSM_Kenya
48. Tag:flood_prone=yes - OpenStreetMap Wiki, accessed on March 8, 2026, https://wiki.openstreetmap.org/wiki/Tag:flood_prone%3Dyes
49. Basins and sub-basins in Kenya - Datasets - Data | World Resources Institute, accessed on March 8, 2026, https://old-datasets.wri.org/dataset/basins-and-sub-basins-in-kenya
50. WikiProject Kenya - OpenStreetMap Wiki, accessed on March 8, 2026, https://wiki.openstreetmap.org/wiki/WikiProject_Kenya
51. Integrating Spatial Analytics and Routing Algorithms for Flood Response: The FIRS Approach - Data for Public Good - CDPG, accessed on March 8, 2026, https://dataforpublicgood.org.in/blog/integrating-spatial-analytics-and-routing-algorithms-for-flood-response-the-firs-approach/
52. A Web-based Decision Support Framework for Optimizing Road Network Accessibility and Emergency Facility Allocation During Flood - EarthArXiv, accessed on March 8, 2026, https://eartharxiv.org/repository/object/5759/download/11246/
53. Routing with OSRM and GraphHopper - Geofabrik, accessed on March 8, 2026, https://www.geofabrik.de/data/routing.html
54. tutorials/general/foss_routing_engines_overview.md at master - GitHub, accessed on March 8, 2026, https://github.com/gis-ops/tutorials/blob/master/general/foss_routing_engines_overview.md
55. Using alternatives as a way to dynamically avoid specific roads · Issue #5581 · Project-OSRM/osrm-backend - GitHub, accessed on March 8, 2026, https://github.com/Project-OSRM/osrm-backend/issues/5581
56. Example: Avoid flooded Areas with ORS - openrouteservice, accessed on March 8, 2026, https://openrouteservice.org/example-avoid-flooded-areas-with-ors/
57. Limit rules to certain areas - GraphHopper Directions API, accessed on March 8, 2026, https://docs.graphhopper.com/openapi/custom-model/limit-rules-to-certain-areas
58. Examples For Customizable Routing - GraphHopper Directions API, accessed on March 8, 2026, https://www.graphhopper.com/blog/2020/05/31/examples-for-customizable-routing/
59. Custom routing with areas to block road - GraphHopper Forum, accessed on March 8, 2026, https://discuss.graphhopper.com/t/custom-routing-with-areas-to-block-road/6328
60. Routing Alternatives With Custom Spatial Data | by İbrahim Sarıçiçek - Medium, accessed on March 8, 2026, https://ibrahimsaricicek.medium.com/routing-alternatives-with-custom-spatial-data-dbb2a9175ef2

61. Early warning - Husika, accessed on March 8, 2026, https://husika.icpac.net/about
62. Forging a Resilient Future: ICPAC Champions Strategic Engagement in Early Warning at Busia DRR Symposium and IDDRR 2025, accessed on March 8, 2026, https://icpac.medium.com/forging-a-resilient-future-icpac-champions-strategic-engagement-in-early-warning-at-busia-drr-481bd0ecbace
63. Early warning, accessed on March 8, 2026, https://husika.icpac.net/
64. Emergency Alerts and Crisis Communications: How to Stay Prepared. - Bulk SMS Kenya – Reliable Messaging with SMSLeopard | SMS Leopard, accessed on March 8, 2026, https://smsleopard.com/blogs/emergency-alerts-and-crisis-communications-how-to-stay-prepared
65. USSD - Developer Documentation - Africa's Talking, accessed on March 8, 2026, https://developers.africastalking.com/docs/ussd/overview
66. USSD Notifications - Africa's Talking, accessed on March 8, 2026, https://developers.africastalking.com/docs/ussd/notifications
67. Countries supported by Africa's Talking USSD API and Pricing - HelloDuty, accessed on March 8, 2026, https://helloduty.com/blogs/countries-supported-by-africas-talking-ussd-api
68. SMS Notifications - Developer Documentation - Africa's Talking, accessed on March 8, 2026, https://developers.africastalking.com/docs/sms/notifications
69. darthlotu5/AT-PYTHON-TUTORIAL: A repository of code samples demonstrating how to use Africas Talking APIs(Voice, airtime, sms, payments, ussd) with Python and The Flask micro-framework - GitHub, accessed on March 8, 2026, https://github.com/darthlotu5/AT-PYTHON-TUTORIAL
70. Building a SMS app with Africa's Talking and Python - YouTube, accessed on March 8, 2026, https://www.youtube.com/watch?v=B8UusMzYI7g
71. USSD - Bulk SMS | SMS, USSD, Survey, Mobile Payments Gateway in Africa | VasPro, accessed on March 8, 2026, https://www.vaspro.co/ussd.html
72. SMS vs. WhatsApp API 2026: Cost, ROI & Engagement | Chatarmin, accessed on March 8, 2026, https://chatarmin.com/en/blog/sms-whatsapp-api
73. SMS vs WhatsApp: A Comparison for Business - Respond.io, accessed on March 8, 2026, https://respond.io/blog/sms-vs-whatsapp
74. Use Cases for Serving Smallholder Farmers Across Africa - Mercy Corps AgriFin, accessed on March 8, 2026, https://www.mercycorpsagrifin.org/wp-content/uploads/2021/04/WA4B.pdf
75. Turn.io: Chat for impact, accessed on March 8, 2026, https://www.turn.io/
76. Turn.io Announces the Six organisations selected for the Chat for Women's Livelihoods Accelerator, accessed on March 8, 2026, https://www.turn.io/news/cwl-cohort-announcement
77. Chat for Impact Accelerator 2022 Cohort Announced - Turn.io, accessed on March 8, 2026, https://www.turn.io/news/chat-for-impact-accelerator-2022-cohort-announcement
78. Ten New Health Chatbots Launched, Paving the Way to Improve Millions of Lives - Turn.io, accessed on March 8, 2026,

https://www.turn.io/news/chat-for-impact-2023-demo-day
79. austinsw/Telegram-Flood-Bot: A Telegram bot for sending out bulk messages, made in 2021 - GitHub, accessed on March 8, 2026, https://github.com/austinsw/Telegram-Flood-Bot
80. Sending telegram notifications from your Python codes in a simple way via telenotif library, accessed on March 8, 2026, https://www.youtube.com/watch?v=UTRoUfv4xaI
81. Send Alerts In A Telegram Channel Using Python - Tradehull, accessed on March 8, 2026, https://tradehull.com/send-alerts-in-a-telegram-channel-using-python/
82. How to send notifications to Telegram with Python | by Andrei Kushniarou - Medium, accessed on March 8, 2026, https://andrewkushnerov.medium.com/how-to-send-notifications-to-telegram-with-python-9ea9b8657bfb
83. Telegram bot-based Flood Early Warning System with WSN Integration - Semantic Scholar, accessed on March 8, 2026, https://pdfs.semanticscholar.org/5947/70248fc61808b105f1eec0731e91a05025c5.pdf
84. Mapping water sources in Kenya | United Nations Development Programme, accessed on March 8, 2026, https://www.undp.org/acceleratorlabs/untapped/case-studies/mapping-water-sources-in-Kenya
85. Five open-source tools to harness geographic knowledge for disaster management - HeiGIT, accessed on March 8, 2026, https://heigit.org/five-open-source-tools-to-harness-geographic-knowledge-for-disaster-management/
86. How much is a dedicated USSD code? - Africa's Talking Help Center, accessed on March 8, 2026, http://help.africastalking.com/en/articles/1163556-how-much-is-a-dedicated-ussd-code
87. USSD - Citycloud ERP & CRM Solutions, accessed on March 8, 2026, https://citycloudtech.com/skills/ussd.php
88. This startup wants to bring Bitcoin to Africans who can't afford the Internet - TechCabal, accessed on March 8, 2026, https://techcabal.com/2026/03/04/machankuras-solution-for-crypto-transactions/
89. USSD Services Kenya | Best USSD Provider Nairobi - Wingu SMS, accessed on March 8, 2026, https://wingusms.com/ussd-bulk-sms-services/
90. WhatsApp Business API Pricing 2026: Complete Cost Guide with Country Rates - Flowcall, accessed on March 8, 2026, https://flowcall.co/blog/whatsapp-business-api-pricing-2026
91. SandBox Set Up · Mobile Communication Apis - Africastalking Ltd, accessed on March 8, 2026, https://africastalkingltd.gitbooks.io/mobile-communication-apis/content/sandbox-set-up.html
92. USSD Kenya -Airtel, Safaricom, - Apps on Google Play, accessed on March 8,

2026, https://play.google.com/store/apps/details?id=com.eladeforwa.ussdkenya&hl=en_US
93. PHP package for a mobile money solution on USSD - CodeSandbox, accessed on March 8, 2026, https://codesandbox.io/p/github/amadoucheik/ussd-mobile-money-php/main
94. WhatsApp Business API vs SMS API: The Ultimate 2025 Comparison Guide, accessed on March 8, 2026, https://www.smsgatewaycenter.com/blog/whatsapp-business-api-vs-sms-api-2025/