

BQMail
User Manual
Version 2.3.0

Mijian Xu^{1,*}

¹*School of Earth Science and Engineering, Nanjing University*

**Email: gomijianxu@gmail.com*

September 23, 2015

Contents

1	Introduction	2
2	Installation	3
2.1	Dependencies	3
2.2	Installation	3
2.2.1	Download BQMail	3
2.2.2	Install BQMail	3
3	Tutorial	4
3.1	bqmail	4
3.1.1	Synopsis	4
3.1.2	Required Arguments	4
3.1.3	Optional Arguments	5
3.1.4	Example	5
3.2	bqmail_raw	5
3.2.1	Synopsis	5
3.2.2	Required Arguments	5
3.2.3	Optional Arguments	6
3.2.4	Example	6
3.3	searchDMC	6
3.3.1	Synopsis	6
3.3.2	Arguments	6
3.3.3	Example	7
3.4	updateCatalog	7
3.4.1	Synopsis	7
3.4.2	Required Arguments	7
3.4.3	Optional Arguments	7
3.4.4	Example	7

1 Introduction

BQMail is an open source software package for requesting seismic data from Incorporated Research Institutions for Seismology (IRIS) Data Management Center (DMC) with the BREQ_FAST service (http://ds.iris.edu/ds/nodes/dmc/manuals/breq_fast/). BREQ_FAST is a popular method for accessing to the IRIS DMC archive via electronically mailings. Users first set parameters (e.g., station name, date range, file format) in command lines, and then create formatted files and send to the IRIS DMC automatically with the BQMail package. Meanwhile, users can use it for searching stations with necessary parameters in command lines.

Scripts in the BQMail package were developed with Python programming language (<https://www.python.org>) on OSX 10.10 platform. They are compatible with both Python 2.7 and Python 3.x. The BQMail package runs on OSX and Linux/Unix platform, but is not tested under Windows. It is distributed under the GNU General Public License Version 3 (GPLv3) as published by the Free Software Foundation (<http://www.gnu.org/licenses/gpl.html>).

2 Installation

2.1 Dependencies

BQMail depends on standard libraries of Python 2.7 or higher versions, which include datetime, os, re, smtplib, urllib, sys, getopt, glob, ConfigParser/configParser and math.

2.2 Installation

2.2.1 Download BQMail

After opening a terminal, run the following commands:

```
git clone git://github.com/xumi1993/bqmail.git
```

2.2.2 Install BQMail

In the root directory of BQMail, users may use the package by running the scripts. To use it in any other directory, just run:

```
cd bqmail  
./install.sh
```

3 Tutorial

3.1 bqmail

bqmail - Request seismic waveform data.

3.1.1 Synopsis

bqmail [*configfile*] **-N***network* **-S***station* **-Y***ymin/mmin/dmin/ymax/mmax/dmax*
-B*sec_before/sec_after* [**-C***channel*] [**-L***location*] [**-c***datetimefile*] [**-F***[seed|miniseed]*]

3.1.2 Required Arguments

configfile Specify directory of config file, which contains a events list, BREQ_FAST options, and information of electronic mail server. The table 3.1 lists options in the config file.

-Nnetwork Specify network code.

-Sstation Select a station of specified network by **-N**

-Yymin/mmin/dmin/ymax/mmax/dmax Select a date range during the archive time.

Table 3.1: Options in config file

Option	Function
eventlst	Directory of the formatted events list.
NAME	Folder name at IRIS DMC ftp site.
INST	Institution.
EMAIL	Email address to send and receive related mail.
MEDIA	Media for accessing data. [Default is Electronic (FTP).]
hosts	Host name of SMTP server.
port	Port of the SMTP server. [Default is 25.]
passwd	Clear text password of the EMAIL .

-Bsec_before/sec_after Set time duration of each seismogram from *sec_before* before to *sec_after* after event time in seconds

3.1.3 Optional Arguments

-Cchannel Specify channels like *"?H?"* or *"HHZ"*. [Default is *"BH?"*].

-Llocation Location identifier

-cdatetimefile If this argument is specified, **-Y** will be futile. The time range will be specified in a table file with 12 column as: [*year1 month1 day1 hour1 minute1 sec1 year2 month2 day2 hour2 minute2 sec2*].

-F[seed|miniseed] Select a format (seed or miniseed) to retrieve [Default is *seed*].

3.1.4 Example

To request waveform data by events of CB.NJ2 station from 2013 to 2014, try:

```
bqmail head.cfg -NCB -SNJ2 -Y2013/1/1/2014/12/31 -B0/3600
```

3.2 bqmail_raw

bqmail_raw - Request continuous seismic waveform data by hours.

3.2.1 Synopsis

bqmail_raw [*configfile*] **-Istationlist** **-Yymin/mmin/dmin/ymax/mmax/dmax** **-Hhours** [**-Cchannel**] [**-F[seed|miniseed]**]

3.2.2 Required Arguments

configfile Specify directory of config file. The config file contains a events list, BREQ_FAST options, and information of electronic mail server. Table [3.1](#) lists options in the config file.

-Istationlist Select a text file including network & station information as:[*network station [location]*]

-Yymin/mmin/dmin/ymax/mmax/dmax Select a date range during the archive time.

-Hhours Specify a time duration of each retrieving data file in hours.

3.2.3 Optional Arguments

-Cchannel Specify channels like *"?H?"* or *"HHZ"*. [Default is *"BH?"*].

-F[seed|miniseed] Select a format (seed or miniseed) of retrieving data file. [Default is *seed*].

3.2.4 Example

To request continuous seismic waveform data with format of miniseed from 1 Jan. 2015 to 1 Jan. 2015 every 1 day, try:

```
bqmail_raw head.cfg -Ista.lst -Y2015/1/1/2015/1/5 -H24 \
-Fminiseed
```

this is a record of the *sta.lst*

```
CB NJ2
CB TNC
IC BJT 00
```

3.3 searchDMC

searchDMC - Find stations in IRIS DMC. Stations defined by different criterions. First, using **-R** to find stations in a box region. Second, using **-D** to find stations in a specified region by epicentral distance. Third, using **-N [-S]** to find stations under a specified network.

3.3.1 Synopsis

```
searchDMC [-Nnetwork] [-Sstation] [-Rlonmin/lonmax/latmin/latmax]
[-Dlon/lat/discrimin/dimax] [-Yymin/mmin/dmin/ymax/mmax/dmax] [-Cchannel] [-K]
```

3.3.2 Arguments

-Nnetwork Specify a network code.

-Sstation Select a station under the specified network by **-N**

-Rlonmin/lonmax/latmin/latmax Limits stations in a box region. Latitude is from -90° to 90° and longitude is from -180° to 180°.

-Dlon/lat/discrimin/dimax Limits station in a specified region by epicentral distance between *discrimin* and *dimax* from a center at *lat*, *lon*. The distance is from 0 to 180 degrees.

- Ymin/mmin/dmin/ymax/mmax/dmax** Select a date range during the archive time.
- Cchannel** Specify a channel like "BHZ". This argument with unsupported wild-card is different from that in **bqmail** (or **bqmail_raw**).
- K** Generates a KML file in current directory. which is used by Google Earth to display stations and related information based on IRIS DMC metadata. The argument of **-D** does not support this function.

3.3.3 Example

To find stations in a box region from 2002 to 2004, use

```
searchDMC -R90/100/20/30 -Y2002/1/1/2004/12/31
```

To find stations in the region with epicentral distance between 0° and 10° from a center at 25°N and 100°E, use

```
searchDMC -D100/25/0/10
```

To find stations under network IC with channel of HHZ and Generate a KML file, use

```
searchDMC -NIC -CHHZ -K
```

3.4 updateCatalog

updateCatalog - Automatically update the events list from Harvard CMT Catalog.

3.4.1 Synopsis

updateCatalog *-inputfile* [*-Ooutputfile*]

3.4.2 Required Arguments

-inputfile Specify the directory of events list.

3.4.3 Optional Arguments

-Ooutputfile Specify a directory of the updated events list. If it is not specified, the *inputfile* will be overwritten as a updated events list.

3.4.4 Example

To update the the events list, use

```
updateCatalog -I~/work/EventCMT.dat -O/tmp/Newlist.dat
```