


McLab Tutorial

www.sable.mcgill.ca/mclab



Part 3 – McLab Frontend

- Frontend organization
- Introduction to Beaver
- Introduction to JastAdd

6/4/2011

McLab Tutorial, Laurie Hendren, Rahul Garg and Nurudeen Lameed

Frontend-1

McLab Frontend

- Tools to parse MATLAB-type languages
 - Quickly experiment with language extensions
 - Tested on a lot of real-world Matlab code
- Parser generates ASTs
- Some tools for computing attributes of ASTs
- A number of static analyses and utilities
 - Example: Printing XML representation of AST

6/4/2011

McLab Tutorial, Laurie Hendren, Rahul Garg and Nurudeen Lameed

Frontend-2

Tools used


- Written in Java (JDK 6)
- MetaLexer and JFlex for scanner
- Beaver parser generator
- JastAdd “compiler-generator” for computations of AST attributes
- Ant based builds
- We typically use Eclipse for development
 - Or Vim 😊

6/4/2011

McLab Tutorial, Laurie Hendren, Rahul Garg and Nurudeen Lameed

Frontend-3

Look! Notes!



Natlab


- Natlab is a clean subset of MATLAB
 - Not a trivial subset though
 - Covers a lot of “sane” MATLAB code
- MATLAB to Natlab translation tool available
 - Written using ANTLR
 - Outside the scope of this tutorial
- Forms the basis of much of our semantics and static analysis research

6/4/2011

McLab Tutorial, Laurie Hendren, Rahul Garg and Nurudeen Lameed

Frontend-5

Derivatives such as AspectMatlab use the work done in Natlab.



How is Natlab organized?

- Scanner specifications
 - src/metalexer/shared_keywords.mlc
- Grammar files
 - src/parser/natlab.parser
- AST computations based on JastAdd
 - src/natlab.ast
 - src/*jadd, src/*jrag
- Other Java files
 - src/*java

6/4/2011

McLab Tutorial, Laurie Hendren, Rahul Garg and Nurudeen Lameed

Frontend-7

MetaLexer

- A system for writing extensible scanner specifications
- Scanner specifications can be modularized, reused and extended
- Generates JFlex code
 - Which then generates Java code for the lexer/scanner
- Syntax is similar to most other lexers
- Reference: “MetaLexer: A Modular Lexical Specification Language. Andrew Casey, Laurie Hendren” by Casey, Hendren at AOSD 2011.

6/4/2011

McLab Tutorial, Laurie Hendren, Rahul Garg and Nurudeen Lameed

Frontend-8

**If you already know
Beaver and JstAdd...**

**Then take a break.
Play Angry Birds.
Or Fruit Ninja.**

Frontend-9

Beaver

- Beaver is a LALR parser generator
- Familiar syntax (EBNF based)
- Allows embedding of Java code for semantic actions
- Usage in Natlab: Simply generate appropriate AST node as semantic action

6/4/2011

McLab Tutorial, Laurie Hendren, Rahul Garg and Nurudeen Lameed

Frontend-10

Beaver Example

```
Stmt stmt =  
    expr.e {: return new ExprStmt(e); :}  
|   BREAK {: return new BreakStmt(); :}  
|   FOR  for_assign.a stmt_seq.s END  
        {: return new ForStmt(a,s); :}
```

6/4/2011

McLab Tutorial, Laurie Hendren, Rahul Garg and Nurudeen Lameed

Frontend-11

Example is a simplified grammar

Beaver Example

Java type

```
Stmt stmt =  
    expr.e {: return new ExprStmt(e); :}  
|    BREAK {: return new BreakStmt(); :}  
|    FOR  for_assign.a stmt_seq.s END  
        {: return new ForStmt(a,s); :}
```

6/4/2011

McLab Tutorial, Laurie Hendren, Rahul Garg and Nurudeen Lameed

Frontend-12

The Java types must be declared/defined/imported by the programmer.

Beaver Example

Node name in grammar

Stmt **stmt** =

```
    expr.e {: return new ExprStmt(e); :}  
  |  
    BREAK {: return new BreakStmt(); :}  
  |  
    FOR  for_assign.a stmt_seq.s END  
        {: return new ForStmt(a,s); :}
```

Beaver Example

```

Stmt s: Identifier for node
      |   expr.e { : return new ExprStmt(e); :}
      |   BREAK { : return new BreakStmt(); :}
      |   FOR   for_assign.a stmt_seq.s END
              { : return new ForStmt(a,s); :}

```

6/4/2011

McLab Tutorial, Laurie Hendren, Rahul Garg and Nurudeen Lameed

Frontend-14

The name given to a node can then be used inside the semantic action.

Beaver Example

Stmt stmt =

Java code for semantic
action

```
    expr.e { : return new ExprStmt(e); :}  
|    BREAK { : return new BreakStmt(); :}  
|    FOR  for_assign.a stmt_seq.s END  
        { : return new ForStmt(a,s); :}
```

JastAdd: Motivation

- You have an AST
- Each AST node type represented by a class
- Want to compute attributes of the AST
 - Example: String representation of a node
- Attributes might be either:
 - Inherited from parents
 - Synthesized from children

6/4/2011

McLab Tutorial, Laurie Hendren, Rahul Garg and Nurudeen Lameed

Frontend-16

JastAdd

- JastAdd is a system for specifying:
 - Each attribute computation specified as an aspect
 - Attributes can be inherited or synthesized
 - Can also rewrite trees
 - Declarative philosophy
 - Java-like syntax with added keywords
- Generates Java code
- Based upon “Reference attribute grammars”

6/4/2011

McLab Tutorial, Laurie Hendren, Rahul Garg and Nurudeen Lameed

Frontend-17

How does everything fit?

- JastAdd requires two types of files:
 - .ast file which specifies an AST grammar
 - .jrag/.jadd files which specify attribute computations
- For each node type specified in AST grammar:
 - JastAdd generates a class derived from ASTNode
- For each aspect:
 - JastAdd adds a method to the relevant node classes

6/4/2011

McLab Tutorial, Laurie Hendren, Rahul Garg and Nurudeen Lameed

Frontend-18

JastAdd AST File example

```
abstract BinaryExpr: Expr ::=
    LHS:Expr RHS:Expr
PlusExpr: BinaryExpr;
MinusExpr: BinaryExpr;
MTimesExpr: BinaryExpr;
```

6/4/2011

McLab Tutorial, Laurie Hendren, Rahul Garg and Nurudeen Lameed

Frontend-19

JastAdd XML generation aspect

```
aspect AST2XML{  
  ..  
  eq BinaryExpr.getXML(Document d, Element e){  
    Element v = d.getElement(nameOfExpr);  
    getRHS().getXML(d,v);  
    getLHS().getXML(d,v);  
    e.add(v);  
    return true;  
  }  
  ...  
}
```

6/4/2011

McLab Tutorial, Laurie Hendren, Rahul Garg and Nurudeen Lameed

Frontend-20

Code has been simplified to suit the purposes of the tutorial. Actual code will do a little more bookkeeping of line numbers etc.

Aspect
declaration

```
aspect AST2XML{  
..  
eq BinaryExpr.getXML(Document d, Element e){  
    Element v = d.getElement(nameOfExpr);  
    getRHS().getXML(d,v);  
    getLHS().getXML(d,v);  
    e.add(v);  
    return true;  
}  
...
```

6/4/2011

McLab Tutorial, Laurie Hendren, Rahul Garg and Nurudeen Lameed

Frontend-21

Code has been simplified to suit the purposes of the tutorial. Actual code will do a little more bookkeeping of line numbers etc.

```
aspect AST2XML{
```

"Equation" for an
attribute


```
eq BinaryExpr.getXML(Document d, Element e){  
    Element v = d.getElement(nameOfExpr);  
    getRHS().getXML(d,v);  
    getLHS().getXML(d,v);  
    e.add(v);  
    return true;  
}  
...
```

6/4/2011

McLab Tutorial, Laurie Hendren, Rahul Garg and Nurudeen Lameed

Frontend-22

Code has been simplified to suit the purposes of the tutorial. Actual code will do a little more bookkeeping of line numbers etc.

```
aspect AST2XML{  
  ..   
  eq BinaryExpr.getXML(Document d, Element e){  
    Element v = d.getElement(nameOfExpr);  
    getRHS().getXML(d,v);  
    getLHS().getXML(d,v);  
    e.add(v);  
    return true;  
  }  
  ...  
}
```

6/4/2011

McLab Tutorial, Laurie Hendren, Rahul Garg and Nurudeen Lameed

Frontend-23

Code has been simplified to suit the purposes of the tutorial. Actual code will do a little more bookkeeping of line numbers etc.

```
aspect AST2XML{  
  ..  
  eq BinaryExpr.getXML(Document d, Element e){  
    Element v = d.getElement(nameOfExpr);  
    getRHS().getXML(d,v);  
    getLHS().getXML(d,v);  
    e.add(v);  
    return true;  
  }  
  ...  
}
```

Method name to be
added

6/4/2011

McLab Tutorial, Laurie Hendren, Rahul Garg and Nurudeen Lameed

Frontend-24

Code has been simplified to suit the purposes of the tutorial. Actual code will do a little more bookkeeping of line numbers etc.


```
aspect AST2XML{  
  ..  
  eq BinaryExpr.getXML(Document d, Element e){  
    Element v = d.getElement(nameOfExpr);  
    getRHS().getXML(d,v);  
    getLHS().getXML(d,v);  
    e.add(v);  
    return true;  
  }  
  ...  
}
```

Attributes can be parameterized

6/4/2011

McLab Tutorial, Laurie Hendren, Rahul Garg and Nurudeen Lameed

Frontend-25

Code has been simplified to suit the purposes of the tutorial. Actual code will do a little more bookkeeping of line numbers etc.


```
aspect AST2XML{  
  ..  
  eq BinaryOp.Document d, Element e){  
    Element v = Element(nameOfExpr);  
    Compute for children  
    getRHS().getXML(d,v);  
    getLHS().getXML(d,v);  
    e.add(v);  
    return true;  
  }  
  ...  
}
```

6/4/2011

McLab Tutorial, Laurie Hendren, Rahul Garg and Nurudeen Lameed

Frontend-26

Code has been simplified to suit the purposes of the tutorial. Actual code will do a little more bookkeeping of line numbers etc.



Overall picture recap

- Scanner converts text into a stream of tokens
- Tokens consumed by Beaver-generated parser
- Parser constructs an AST
- AST classes were generated by JastAdd
- AST classes already contain code for computing attributes as methods
- Code for computing attributes was weaved into classes by JastAdd from aspect files

6/4/2011

McLab Tutorial, Laurie Hendren, Rahul Garg and Nurudeen Lameed

Frontend-28

Adding a node

- Let's assume you want to experiment with a new language construct:
- Example: parallel-for loop construct
 - `parfor i=1:10 a(i) = f(i) end;`
- How do you extend Matlab to handle this?
- You can either:
 - Choose to add to Matlab source itself
 - (Preferred) Setup a project that inherits code from Matlab source directory

6/4/2011

McLab Tutorial, Laurie Hendren, Rahul Garg and Nurudeen Lameed

Frontend-29

Steps

- Write the following in your project:
 - Lexer rule for “parfor”
 - Beaver grammar rule for parfor statement type
 - AST grammar rule for PforStmt
 - attributes for PforStmt according to your requirement
 - eg. getXML() for PforStmt in a JastAdd aspect
 - Buildfile that correctly passes the Natlab source files and your own source files to tools
 - Custom main method and jar entrypoints

6/4/2011

McLab Tutorial, Laurie Hendren, Rahul Garg and Nurudeen Lameed

Frontend-30