

Tower Parts Physical Count List

Generated: 2026-03-09 12:28:53

Scope: consolidated from maintenance templates, current orders, inventory records, and manuals/datasheet references.

Total unique parts	60
High confidence	43
Medium confidence	0
Low confidence (manual name hints)	17

Part	Used For (sample)	Component(s)	Manual Ref(s)	Confidence	Qty Counted	Count Notes
63mm Furnace Manual Soreq rev 22 Jul 20 AD	Manual/datasheet reference	-	-	Low		
Air filter element	UV Curing System PSU dust removal + filter check 3-Month; UV Curing System – PSU Every 3 months: remove dust from PSU units and replace air filters if required 3-Month	UV Curing System; UV Curing System – PSU	Ultra Violet Curing System (F600S - I606/P600M) Manual p.12; Ultra Violet Curing System – F600S / I606 / P600M p.12	High		
Analysis of coating thickness variation during optical fiber Processing	Manual/datasheet reference	-	-	Low		
Applicator seal kit	Pressurised Coating System Monthly: lubricate applicator gimbals and X adjustment mechanism Monthly; Wet-on-Dry Coating System Applicator alignment to tower axis check Routine; Wet-on-Dry Coating System Applicator/delivery block levelness check R	Pressurised Coating System; Wet-on-Dry Coating System	Generic Lubrication Schedule – Fibre Draw Tower (TD0141) p.7; Wet on Dry Coating System Manual (Soreq) p.27; Wet on Dry Coating System Manua	High		
Bearing set	Bottom Centering Pulley + Break Detector Weekly: check pulley rotates freely, bearing play, and clean V-groove Weekly; Capstan System Every 3 months: check bearings are not worn (sealed for life) 3-Month; Guide Pulley + Fibre Tension Gauge Weekly: ch	Bottom Centering Pulley + Break Detector; Capstan System; Guide Pulley + Fibre Tension Gauge	Bottom Centering Pulley with Break Detector (SG Controls) p.4; Capstan Manual (Capstan V2) p.7; Guide Pulley & Tension Gauge (SG Controls) p	High		
Bottom sleeve top cap	63mm Furnace System On-condition: inspect/replace bottom sleeve top cap when eroded (e.g., length reduction >3 mm) On-Condition	63mm Furnace System	63mm Furnace Manual (Soreq) p.17	High		
Cane Puller Manual Soreq rev 05 Aug 2020	Manual/datasheet reference	-	-	Low		
Capstan V2	Manual/datasheet reference	-	-	Low		
Centering Pulley & break detector	Manual/datasheet reference	-	-	Low		
Clean Air System	Manual/datasheet reference	-	-	Low		
cleaning cloth	63mm Furnace System After every run: clean furnace entry disc (remove soot, wipe with IPA) Per-Draw/Startup; 63mm Furnace System Before operation: check top sleeve + water-cooled top ring for soot; clean if needed Per-Draw/Startup; 63mm Furnace System	63mm Furnace System; Bottom Centering Pulley + Break Detector; Cane / Rod Puller (Caterpillar); Capstan System; Clean Ai	63mm Furnace Manual (Soreq) p.22; 63mm Furnace Manual (Soreq) p.9; Bottom Centering Pulley with Break Detector (SG Controls) p.4; Cane / Rod	High		
cleaning kit	63mm Furnace System Every 3 months OR 1500 operating hours: check pyrometer alignment & window cleanliness 3-Month	63mm Furnace System	63mm Furnace Manual (Soreq) p.22	High		

Part	Used For (sample)	Component(s)	Manual Ref(s)	Confidence	Qty Counted	Count Notes
coating DS	Order details: tiger project need	Tiger	-	High		
coating OF	Order details: tiger project need	Tiger	-	High		
Coating::Coating_KS_1-002	Inventory note: Auto sync from consumables (warehouse + containers); Order details: Auto-created from low stock alert	Consumables; Maintenance	-	High		
Coating::Coating_KS_2-002	Inventory note: Auto sync from consumables (warehouse + containers)	Consumables	-	High		
Coating::Coating_OF_136	Inventory note: Auto sync from consumables (warehouse + containers); Order details: Auto-created from low stock alert	Consumables; Maintenance	-	High		
Coating::DP-1032	Inventory note: Auto sync from consumables (warehouse + containers)	Consumables	-	High		
Coating::DS-2015	Inventory note: Auto sync from consumables (warehouse + containers); Order details: Auto-created from low stock alert	Consumables; Maintenance	-	High		
Coating::DS-2042	Inventory note: Auto sync from consumables (warehouse + containers); Order details: Auto-created from low stock alert	Consumables; Maintenance	-	High		
Datasheet DeSoliteDP1032PrimaryOpticalFiberCoatingUVCure1kg COV DP 1032 1KG fiberopticcenter REV1	Manual/datasheet reference	-	-	Low		
DeSoliteDS2042SecondaryOpticalFiberCoatingUVCure1kg COV DS 2042 1KG fiberopticcenter	Manual/datasheet reference	-	-	Low		
Die 140	Inventory note: Auto from received order; Order details: the first 140 is stuck	63mm Furnace System	-	High		
Drive belt	Capstan System As needed: adjust urethane belt tension (cam plate) On-Condition; Take Up Winder Every 6 months: inspect drive train (belt tension + contamination/wear/damage) 6-Month	Capstan System; Take Up Winder	Capstan Manual (Capstan V2) p.7; Take Up Winder (Traversing Drum Type) p.6	High		
Entry sleeve	63mm Furnace System Before operation: select correct entry sleeve and clean Per-Draw/Startup	63mm Furnace System	63mm Furnace Manual (Soreq) p.22	High		
Furnace bottom door set	63mm Furnace System Monthly: inspect bottom doors for distortion/damage; replace if needed Monthly	63mm Furnace System	63mm Furnace Manual (Soreq) p.22	High		
Furnace heating element	63mm Furnace System On-condition: replace heating element when voltage trend increases (e.g., >2 V above new) 3-Month	63mm Furnace System	63mm Furnace Manual (Soreq) p.16	High		
gasket	Clean Air System (HEPA + Pre-filter + Fan Cabinet) As needed: replace HEPA filter element (front face access; tighten nuts diagonally) On-Condition; Clean Air System (HEPA + Pre-filter + Fan Cabinet) As needed: replace pre-filter element (with seal inspe	Clean Air System (HEPA + Pre-filter + Fan Cabinet)	Clean Air System (SG Controls) p.3; Clean Air System (SG Controls) p.4; Clean Air System (SG Controls) p.5; Clean Air System (SG Controls) p	High		
Generic Lubrication Schedule	Manual/datasheet reference	-	-	Low		
Graphite set	63mm Furnace System Before operation: inspect graphite set; clean/replace if needed Per-Draw/Startup; 63mm Furnace System Every 3 months OR 1500 operating hours: inspect graphite insulation/radiation shield; replace if needed 3-Month	63mm Furnace System	63mm Furnace Manual (Soreq) p.22	High		
Grease (NLGI-2)	Dual Drum Winder 3■monthly: grease drum bearing housings 3-Month; Inventory record; Preform Feed Assembly 3-monthly: grease ball screw 3-Month; Preform Feed Assembly 3-monthly: grease linear rails 3-Month; Preform Feed Module 3■monthly: grease li	Dual Drum Winder; Preform Feed Assembly; Preform Feed Module; Take Up Winder	Generic Lubrication Schedule – Fibre Draw Tower (TD0141) p.6; Generic Lubrication Schedule – Fibre Draw Tower (TD0141) p.9; Preform Feed Ass	High		

Part	Used For (sample)	Component(s)	Manual Ref(s)	Confidence	Qty Counted	Count Notes
Guide Pulley & Tension Gauge	Manual/datasheet reference	-	-	Low		
HEPA filter element	Clean Air System (HEPA + Pre-filter + Fan Cabinet) As needed: replace HEPA filter element (front face access; tighten nuts diagonally) On-Condition; Clean Air System (HEPA + Pre-filter + Fan Cabinet) As needed: replace pre-filter element (with seal inspe	Clean Air System (HEPA + Pre-filter + Fan Cabinet)	Clean Air System (SG Controls) p.6; Clean Air System (SG Controls) p.7	High		
HEPA gasket	Clean Air System (HEPA + Pre-filter + Fan Cabinet) As needed: replace HEPA filter element (front face access; tighten nuts diagonally) On-Condition; Clean Air System (HEPA + Pre-filter + Fan Cabinet) As needed: replace pre-filter element (with seal inspe	Clean Air System (HEPA + Pre-filter + Fan Cabinet)	Clean Air System (SG Controls) p.6; Clean Air System (SG Controls) p.7	High		
insulation parts	63mm Furnace System Before operation: inspect graphite set; clean/replace if needed Per-Draw/Startup; 63mm Furnace System Every 3 months OR 1500 operating hours: inspect graphite insulation/radiation shield; replace if needed 3-Month	63mm Furnace System	63mm Furnace Manual (Soreq) p.22	High		
IPA wipes	63mm Furnace System After every run: clean furnace entry disc (remove soot, wipe with IPA) Per-Draw/Startup; 63mm Furnace System Before operation: check top sleeve + water-cooled top ring for soot; clean if needed Per-Draw/Startup; 63mm Furnace System	63mm Furnace System; Bottom Centering Pulley + Break Detector; Cane / Rod Puller (Caterpillar); Capstan System; Clean Ai	63mm Furnace Manual (Soreq) p.22; 63mm Furnace Manual (Soreq) p.9; Bottom Centering Pulley with Break Detector (SG Controls) p.4; Cane / Rod	High		
Light machine oil	Cane / Rod Puller (Caterpillar) Periodic: check carriage movement, belt tension, and lubricate drive linkages Routine; Dual Drum Winder Monthly: lubricate clamps, guide pulleys, layering arm pulleys Monthly; General Tower Shafts & Slideways Monthly:	Cane / Rod Puller (Caterpillar); Dual Drum Winder; General Tower Components; General Tower Shafts & Slideways; Helium Co	Cane / Rod Puller Manual (Soreq) p.9; Generic Lubrication Schedule – Fibre Draw Tower (TD0141) p.6; Generic Lubrication Schedule – Fibre Dra	High		
line flush consumables	63mm Furnace System Before use: if storage vacuum rose >0.03 bar since last use, perform cyclic purge Per-Draw/Startup; 63mm Furnace System Cyclic purge after atmosphere exposure (minimum 5 cycles; end in vacuum) Routine; Wet-on-Dry Coating System De	63mm Furnace System; Wet-on-Dry Coating System	63mm Furnace Manual (Soreq) p.12; 63mm Furnace Manual (Soreq) p.14; Wet on Dry Coating System Manual (Soreq) p.27; Wet on Dry Coating System	High		
Load cell service	Guide Pulley + Fibre Tension Gauge On-condition: return load cell to manufacturer if erratic / cannot calibrate On-Condition	Guide Pulley + Fibre Tension Gauge	Guide Pulley & Tension Gauge (SG Controls) p.10	High		
Mini Capstan	Manual/datasheet reference	-	-	Low		
Optics wipes	UV Curing System Every 500 operating hours: clean lamp module, reflector, bulb and RF screen 3-Month; UV Curing System Module surface + optics cleaning 3-Month	UV Curing System	Ultra Violet Curing System (F600S - I606/P600M) Manual p.12; Ultra Violet Curing System – F600S / I606 / P600M p.12	High		
Pre-filter element	Clean Air System (HEPA + Pre-filter + Fan Cabinet) As needed: replace HEPA filter element (front face access; tighten nuts diagonally) On-Condition; Clean Air System (HEPA + Pre-filter + Fan Cabinet) As needed: replace pre-filter element (with seal inspe	Clean Air System (HEPA + Pre-filter + Fan Cabinet)	Clean Air System (SG Controls) p.3; Clean Air System (SG Controls) p.4; Clean Air System (SG Controls) p.5; Clean Air System (SG Controls) p	High		
Pre-filter seal	Clean Air System (HEPA + Pre-filter + Fan Cabinet) As needed: replace HEPA filter element (front face access; tighten nuts diagonally) On-Condition; Clean Air System (HEPA + Pre-filter + Fan Cabinet) As needed: replace pre-filter element (with seal inspe	Clean Air System (HEPA + Pre-filter + Fan Cabinet)	Clean Air System (SG Controls) p.3; Clean Air System (SG Controls) p.4; Clean Air System (SG Controls) p.5; Clean Air System (SG Controls) p	High		
Preform Feed Assembly	Manual/datasheet reference	-	-	Low		

Part	Used For (sample)	Component(s)	Manual Ref(s)	Confidence	Qty Counted	Count Notes
Purge gas	63mm Furnace System Before use: if storage vacuum rose >0.03 bar since last use, perform cyclic purge Per-Draw/Startup; 63mm Furnace System Cyclic purge after atmosphere exposure (minimum 5 cycles; end in vacuum) Routine; Wet-on-Dry Coating System De	63mm Furnace System; Wet-on-Dry Coating System	63mm Furnace Manual (Soreq) p.12; 63mm Furnace Manual (Soreq) p.14; Wet on Dry Coating System Manual (Soreq) p.27; Wet on Dry Coating System	High		
Pyrometer window	63mm Furnace System Every 3 months OR 1500 operating hours: check pyrometer alignment & window cleanliness 3-Month	63mm Furnace System	63mm Furnace Manual (Soreq) p.22	High		
Quartz liner tube	UV Curing System After full preform draw: inspect quartz liner tube for discolouration (replace if needed) Routine; UV Curing System Quartz tube discoloration check Routine	UV Curing System	Ultra Violet Curing System (F600S - I606/P600M) Manual p.12; Ultra Violet Curing System – F600S / I606 / P600M p.12	High		
replacement	Guide Pulley + Fibre Tension Gauge On-condition: return load cell to manufacturer if erratic / cannot calibrate On-Condition	Guide Pulley + Fibre Tension Gauge	Guide Pulley & Tension Gauge (SG Controls) p.10	High		
Resin line cleaning solvent	Coating System (Resin Delivery Block) Align coating resin delivery block to fibre line; record X/Y micrometer readings Routine; Wet-on-Dry Coating System Resin level & vessel cleanliness check Per-Draw/Startup; Wet-on-Dry Coating System Resin line pu	Coating System (Resin Delivery Block); Wet-on-Dry Coating System	Fibre Draw Tower Alignment Manual p.16; Wet on Dry Coating System Manual (Soreq) p.31; Wet on Dry Coating System Manual (Soreq) p.32	High		
Resin line seals	Coating System (Resin Delivery Block) Align coating resin delivery block to fibre line; record X/Y micrometer readings Routine; Wet-on-Dry Coating System Resin level & vessel cleanliness check Per-Draw/Startup; Wet-on-Dry Coating System Resin line pu	Coating System (Resin Delivery Block); Wet-on-Dry Coating System	Fibre Draw Tower Alignment Manual p.16; Wet on Dry Coating System Manual (Soreq) p.31; Wet on Dry Coating System Manual (Soreq) p.32	High		
seal	Clean Air System (HEPA + Pre-filter + Fan Cabinet) As needed: replace HEPA filter element (front face access; tighten nuts diagonally) On-Condition; Clean Air System (HEPA + Pre-filter + Fan Cabinet) As needed: replace pre-filter element (with seal inspe	Clean Air System (HEPA + Pre-filter + Fan Cabinet)	Clean Air System (SG Controls) p.6; Clean Air System (SG Controls) p.7	High		
Take Up Winder	Manual/datasheet reference	-	-	Low		
Top sleeve	63mm Furnace System Before operation: check top sleeve + water-cooled top ring for soot; clean if needed Per-Draw/Startup	63mm Furnace System	63mm Furnace Manual (Soreq) p.22	High		
Tower Alignment Manual	Manual/datasheet reference	-	-	Low		
Ultra Violet Curing System	Manual/datasheet reference	-	-	Low		
Urethane belt	Capstan System As needed: adjust urethane belt tension (cam plate) On-Condition	Capstan System	Capstan Manual (Capstan V2) p.7	High		
UV lamp cleaning kit	UV Curing System Every 500 operating hours: clean lamp module, reflector, bulb and RF screen 3-Month; UV Curing System Module surface + optics cleaning 3-Month	UV Curing System	Ultra Violet Curing System (F600S - I606/P600M) Manual p.12; Ultra Violet Curing System – F600S / I606 / P600M p.12	High		
Wet on Dry Coating System Manual Soreq FINAL	Manual/datasheet reference	-	-	Low		
■■■■■ ■■■■■	Order history	Tiger	-	High		
■■■■■ ■■■■■ ■■■■	Manual/datasheet reference	-	-	Low		