

LAB-3

Array and Structure Operations in C

Q1) Write a program to find the second largest element in an integer array without sorting the array. Consider the array may contain duplicate values.

```
#include <stdio.h>
#include <limits.h>

int main(){
    int n;
    long long x;
    long long max=LLONG_MIN;
    long long secondmax=LLONG_MIN;
    scanf("%d",&n);
    for(int i=0;i<n;i++){
        scanf("%lld",&x);
        if(x>max){
            secondmax=max;
            max=x;
        }
        else if(secondmax<x && secondmax!=max){
            secondmax=x;
        }
    }
    printf("The Second maximum element in array is : %lld",secondmax);
    return 0;
}
```

Sample Input

4

12 34 20 6

Your Output

The Second maximum element in array is : 20

Q2) Given an array of integers, write a program to check if there exists a contiguous subarray whose sum equals a given value S. If it exists, print the starting and ending indices of such subarray.

```
#include <stdio.h>
#include <stdbool.h>
#include <limits.h>

int main(){
    int n;
    long long S;
    scanf("%d%lld",&n,&S);

    long long arr[n];
    for(int i=0;i<n;i++){
        long long x;
        scanf("%lld",&x);
        arr[i]=x;
    }

    int ans[2];
    bool isit=false;

    for(int i=0;i<n;i++){
        long long sum=0;
        for(int j=i;j<n;j++){
            sum+=arr[j];
            if(sum==S){
                isit=true;
                ans[0]=i;
                ans[1]=j;
                break;
            }
        }
        if(isit){
            break;
        }
    }

    if(isit){
        printf("Yes There is contiguous subarray whose sum equals to S\n");
        printf("The following starting and ending indices of subarray : %d %d\n",
```

```

ans[0], ans[1]);
    }
    else{
        printf("No Such subarray found\n");
    }

    return 0;
}

```

Sample Input

5
54
20 34 6 12 24

Your Output

Yes There is contiguous subarray whose sum equals to S
The following starting and ending indices of subarray : 0 1

Q3) Write a function to rotate an array of n elements to the right by k positions. For example, for array [1, 2, 3, 4, 5] and k = 2, the rotated array should be [4, 5, 1, 2, 3]. Try to do in O(n) time complexity

```

#include <stdio.h>
#include <stdbool.h>
#include <limits.h>

int main(){
    int n;
    long long k;
    scanf("%d%lld",&n,&k);

    long long arr[n];
    for(int i=0;i<n;i++){
        long long x;
        scanf("%lld",&x);
        arr[i]=x;
    }
    long long RotatedArr[n];

```

```

int j=0;
for(int i=(n-k);i<n;i++){
    RotatedArr[j++]=arr[i];
}
for(int i=0;i<(n-k);i++){
    RotatedArr[j++]=arr[i];
}
printf("The Rotated Array after k positions are : ");
for(int i=0;i<n;i++){
    printf("%lld ", RotatedArr[i]);
}
printf("\n");
return 0;
}

```

Sample Input

5

3

20 34 6 12 24

Your Output

The Rotated Array after k positions are : 6 12 24 20 34

Q4) Define a structure Student with fields name, rollNumber, and marks. Write a program to input details of n students and then display the details of the student with the highest marks.

```

#include <stdio.h>
#include <string.h>

```

```

struct Student{
    char name[50];
    int rollNumber;
    float marks;
};

```

```

int main(){
    int n;

```

```

printf("Enter number of students: ");
scanf("%d",&n);

struct Student students[n];

for(int i=0;i<n;i++){
    printf("Enter details of student %d:\n", i+1);
    printf("Name: ");
    scanf(" %[^\\n]s", students[i].name);
    printf("Roll Number: ");
    scanf("%d", &students[i].rollNumber);
    printf("Marks: ");
    scanf("%f", &students[i].marks);
}

int maxIndex = 0;

for(int i=1;i<n;i++){
    if(students[i].marks > students[maxIndex].marks){
        maxIndex = i;
    }
}

printf("\nStudent with highest marks:\n");
printf("Name: %s\n", students[maxIndex].name);
printf("Roll Number: %d\n", students[maxIndex].rollNumber);
printf("Marks: %.2f\n", students[maxIndex].marks);

return 0;
}

```

Sample Input

```

3
Ohi
34
92
Tiger
37
86

```

Veer

48

68

Your Output

Enter number of students: Enter details of student 1:

Name: Roll Number: Marks: Enter details of student 2:

Name: Roll Number: Marks: Enter details of student 3:

Name: Roll Number: Marks:

Student with highest marks:

Name: Ohi

Roll Number: 34

Marks: 92.00

Q5) Define a structure Employee with fields id, name, salary, and department. Write a program to increase the salary of all employees in the "IT" department by 10%.

```
#include <stdio.h>
#include <string.h>

struct Employee{
    int id;
    char name[50];
    float salary;
    char department[20];
};

int main(){
    int n;
    printf("Enter number of employees: ");
    scanf("%d",&n);

    struct Employee employe[n];

    for(int i=0;i<n;i++){
```

```

    printf("Enter details of Employee %d:\n", i+1);
    printf("Employee ID: ");
    scanf("%d", &employee[i].id);
    printf("Name: ");
    scanf(" %[^\\n]s", employee[i].name);
    printf("Salary: ");
    scanf("%f", &employee[i].salary);
    printf("Department: ");
    scanf(" %[^\\n]s", employee[i].department);
}

for(int i=0;i<n;i++){
    if(strcmp(employee[i].department, "IT") == 0){
        employee[i].salary *= 1.10;
    }
}

printf("\nEmployee details after salary update:\n");
for(int i=0;i<n;i++){
    printf("ID: %d\n", employee[i].id);
    printf("Name: %s\n", employee[i].name);
    printf("Salary: %.2f\n", employee[i].salary);
    printf("Department: %s\n\n", employee[i].department);
}

return 0;
}

```

Sample Input

```

3
34
Ohi
92000
AI
37
Tiger
88000
CSE
48

```

Veer

68000

IT

Your Output

Enter number of employees: Enter details of Employee 1:

Employee ID: Name: Salary: Department: Enter details of Employee 2:

Employee ID: Name: Salary: Department: Enter details of Employee 3:

Employee ID: Name: Salary: Department:

Employee details after salary update:

ID: 34

Name: Ohi

Salary: 92000.00

Department: AI

ID: 37

Name: Tiger

Salary: 88000.00

Department: CSE

ID: 48

Name: Veer

Salary: 74800.00

Department: IT

Q6) Define a structure Book with fields title, author, and price. Input details for n books and then display all books whose price is above a given value.

```
#include <stdio.h>
#include <string.h>
```

```
struct Book {
    char title[100];
```



```

    char author[50];
    float price;
};

int main() {
    int n;
    scanf("%d", &n);
    printf("Enter number of books: %d",n);

    struct Book books[n];
    printf("\nEnter details of Book\n");
    for(int i = 0; i < n; i++) {
        scanf(" %[^\n]", books[i].title);
        scanf(" %[^\n]", books[i].author);
        scanf("%f", &books[i].price);
    }

    float limit;
    printf("\nEnter price limit");
    scanf("%f", &limit);

    printf("\nBooks with price above %.2f:\n", limit);
    int found = 0;
    for(int i = 0; i < n; i++) {
        if(books[i].price > limit) {
            printf("Title: %s\n", books[i].title);
            printf("Author: %s\n", books[i].author);
            printf("Price: %.2f\n\n", books[i].price);
            found = 1;
        }
    }

    if(!found) {
        printf("No books found above %.2f\n", limit);
    }

    return 0;
}

```

Sample Input

3

Arc Fault Dedection

Ohi

200

IOT Optimization

Tiger

220

Drone Technology

Veer

180

199

Your Output

Enter number of books: 3

Enter details of Book

Enter price limit

Books with price above 199.00:

Title: Arc Fault Dedection

Author: Ohi

Price: 200.00

Title: IOT Optimization

Author: Tiger

Price: 220.00

Q7) Define a structure Date with fields day, month, and year. Write a program to input two dates and determine which date is earlier.

```
#include <stdio.h>
```

```
struct Date {  
    int day;  
    int month;
```

```

    int year;
};

int main() {
    struct Date d1, d2;

    printf("Enter first date (day month year): ");
    scanf("%d %d %d", &d1.day, &d1.month, &d1.year);

    printf("Enter second date (day month year): ");
    scanf("%d %d %d", &d2.day, &d2.month, &d2.year);

    printf("\nFirst Date: %02d-%02d-%04d", d1.day, d1.month, d1.year);
    printf("\nSecond Date: %02d-%02d-%04d\n", d2.day, d2.month, d2.year);

    if(d1.year < d2.year ||
       (d1.year == d2.year && d1.month < d2.month) ||
       (d1.year == d2.year && d1.month == d2.month && d1.day < d2.day)) {
        printf("\nThe earlier date is: %02d-%02d-%04d\n", d1.day, d1.month,
d1.year);
    }
    else if(d1.year == d2.year && d1.month == d2.month && d1.day == d2.day) {
        printf("\nBoth dates are the same.\n");
    }
    else {
        printf("The earlier date is: %02d-%02d-%04d\n", d2.day, d2.month,
d2.year);
    }

    return 0;
}

```

Sample Input

12 5 2023

25 4 2023

Your Output

Enter first date (day month year): Enter second date (day month year):

First Date: 12-05-2023

Second Date: 25-04-2023

The earlier date is: 25-04-2023

Q8) Given an array of integers nums and an integer target, return indices of the two numbers such that they add up to target.

```
#include <stdio.h>
#include <stdbool.h>

int main() {
    int n;
    long long target;

    scanf("%d", &n);
    scanf("%lld", &target);

    int arr[n];
    for(int i = 0; i < n; i++){
        scanf("%d", &arr[i]);
    }

    int start = -1;
    int end = -1;
    bool isit = false;

    int number = 0;
    for(int i = 0; i < n; i++){
        int check = target - arr[i];
        for(int j = 0; j < n; j++){
            if(j != i && arr[j] == check){
                start = i;
                end = j;
                isit = true;
                break;
            }
        }
        if(isit) break;
    }

    if(isit){
        printf("The indices of elements are: %d , %d\n", start, end);
    }
}
```

```
else{
    printf("No such pair exists.\n");
}
return 0;
}
```

Sample Input

```
4
54
20 24 6 34
```

Your Output

The indices of elements are: 0 , 3

Q9) Write a function to find the longest common prefix string amongst an array of strings.

```
#include <stdio.h>
#include <string.h>
#include <stdbool.h>

int main() {
    int n;
    scanf("%d", &n);

    char arr[n][34];
    for(int i = 0; i < n; i++) {
        scanf(" %[^\\n]", arr[i]);
    }

    char str[34] = "";
    char prev[34];
    strcpy(prev, arr[0]);

    int shortestStrLength = strlen(prev);

    for(int i = 0; i < shortestStrLength; i++) {
        char curr = prev[i];
```

```
bool isit = true;

for(int j = 1; j < n; j++) {
    if(arr[j][i] != curr) {
        isit = false;
        break;
    }
}

if(isit) {
    int len = strlen(str);
    str[len] = curr;
    str[len+1] = '\0';
} else {
    break;
}
}

if(strlen(str) > 0) {
    printf("%s\n", str);
} else {
    printf("\n");
}

return 0;
}
```

Sample Input

4

Ohi

OhiTiger

OhiVeer

OhiUippto

Your Output

Ohi

Q10) Given an integer array nums, return true if any value appears at least twice in the array, and return false if every element is distinct.

```
#include <stdio.h>
#include <stdbool.h>

int main() {
    int n;
    scanf("%d", &n);

    int arr[n];
    for(int i = 0; i < n; i++){
        scanf("%d", &arr[i]);
    }

    bool isit = false;
    int count = 0;

    for(int i = 0; i < n; i++){
        int num = arr[i];
        for(int j = 0; j < n; j++){
            if(i != j && num == arr[j]){
                count++;
            }
            if(count > 0){
                isit = true;
                break;
            }
        }
        count = 0;
        if(isit) break;
    }

    if(isit){
        printf("TRUE");
    }
    else{
        printf("FALSE");
    }
    return 0;
}
```

Sample Input

4

34 20 34 12

Your Output

TRUE