Total NDT
Non-Destructive Specialist

Company Name: SAChem
Location: 2311 Pipeline Rd Cleburn, Tx 76033
Inspection Date: 9/24/2025
Technician: Damon Crain

ULTRASONIC THICKNESS READINGS ON: 54-11-005 Ethyl Chloride Storage

Noz.	Desc.	Size (in)	tmin*	0°	90°	180°	270°				
1	Manway	16	0.328								
2	Vent	4	0.207	0.247	0.247	0.261	0.245				
3	Fill	2	0.135	0.163	0.168	0.163	0.177				
4	Drain	2	0.135	0.143	0.141	0.148	0.149				
5	Spare	3	0.189	0.212	0.221	0.212	0.219				
6	Level Gauge	1	0.116	0.131	0.132	0.14	0.135				
7	Level Gauge	1	0.116	0.17	0.177	0.166	0.157				
8	Bottom Nozzle	2	0.135	0.212	0.221	0.212	0.221				

Skecth/Drawing: See 54-11-005 Report

Technician: Damon Crain Assistant: Date: 9/24/2025

Total NDT
Non-Destructive Specialist

Company Name: SAChem
Location: 2311 Pipeline Rd Cleburn, Tx 76033
Inspection Date: 9/22/2025
Technician: Damon Crain

ULTRASONIC THICKNESS READINGS ON: 54-11-005 Ethyl Chloride Storage

Noz.	Desc.	Size (in)	tmin*	0°	90°	180°	270°				
1	Manway	16	0.328								
2	Vent	4	0.207								
3	Fill	2	0.135								
4	Drain	2	0.135	0.143	0.141	0.148	0.149				
5	Spare	3	0.189	0.212	0.221	0.212	0.219				
6	Level Gauge	1	0.116	0.131	0.132	0.14	0.135				
7	Level Gauge	1	0.116	0.17	0.177	0.166	0.157				
8	Bottom Nozzle	2	0.135	0.212	0.221	0.212	0.221				

Skecth/Drawing:

Technician: Damon Crain Assistant: Date: 9/22/2025

Total NDT
Non-Destructive Specialist

Company Name: SAChem
Location: 2311 Pipeline Rd Cleburn, Tx 76033
Inspection Date: 9/24/2025
Technician: Damon Crain

ULTRASONIC THICKNESS READINGS ON: 54-11-005 Ethyl Chloride Storage

CML	Desc.	0°	45°	90°	135°	180°	224°	270°	315°		
1	2" from Seam w/East Head	0.47	0.419	0.468	0.46	0.462	0.463	0.464	0.465		
2	2'	0.477	0.476	0.475	0.468	0.466	0.471	0.472	0.475		
3	4'	0.475	0.475	0.478	0.471	0.463	0.471	0.473	0.469		
4	6'	0.468	0.468	0.469	0.464	0.455	0.465	0.467	0.476		
5	8'	0.455	0.461	0.471	0.467	0.464	0.471	0.475	0.46		
6	10'	0.458	0.466	0.464	0.469	0.459	0.472	0.476	0.463		
7	12'	0.461	0.468	0.472	0.466	0.466	0.47	0.475	0.465		
8	14'	0.456	0.461	0.471	0.467	0.465	0.471	0.473	0.46		
9	16'	0.471	0.475	0.473	0.468	0.46	0.47	0.472	0.475		
10	18'		0.478	0.476	0.473	0.465	0.473	0.478	0.478		
11	20'		0.478	0.478	0.475	0.471	0.475	0.477	0.478		
12	2" from Seam w/West Head	0.472	0.476	0.473	0.47	0.462	0.473	0.474	0.472		
23	2" from Seam w/West Head	0.61	0.601	0.577	0.572	0.567	0.575	0.565	0.59		
24	2" from Seam w/East Head	0.61	0.616	0.592	0.576	0.555	0.582	0.581	0.597		
13	East Head 12 O'Clock	0.566									
14	East Head Center	0.523									
15	East Head 3 O'Clock	0.536									
16	East Head 6 O'Clock	0.535									
17	East Head 9 O'Clock	0.539									
18	West Head 12 O'Clock	0.523									
19	West Head Center	0.49									
20	West Head 3 O'Clock	0.518									
21	West Head 6 O'Clock	0.519									
22	West Head 9 O'Clock	0.521									

Skecth/Drawing: See 54-11-005 Report

Technician: Damon Crain Assistant: Date: 9/24/2025

Total NDT
Non-Destructive Specialist

Company Name: SAChem
Location: 2311 Pipeline Rd Cleburn, Tx 76033
Inspection Date: 9/22/2025
Technician: Damon Crain

ULTRASONIC THICKNESS READINGS ON: 54-11-005 Ethyl Chloride Storage

CML	Desc.	0°	45°	90°	135°	180°	224°	270°	315°		
1	2" from Seam w/East Head			0.468	0.46	0.462	0.463	0.464			
2	2'			0.475	0.468	0.466	0.471	0.472			
3	4'			0.478	0.471	0.463	0.471	0.473			
4	6'			0.469	0.464	0.455	0.465	0.467			
5	8'			0.471	0.467	0.464	0.471	0.475			
6	10'			0.464	0.469	0.459	0.472	0.476			
7	12'			0.472	0.466	0.466	0.47	0.475			
8	14'										
9	16'			0.473	0.468	0.46	0.47	0.472			
10	18'			0.476	0.473	0.465	0.473	0.478			
11	20'			0.478	0.475	0.471	0.475	0.477			
12	2" from Seam w/West Head			0.473	0.47	0.462	0.473	0.474			
23	2" from Seam w/West Head			0.577	0.572	0.567	0.575	0.565			
24	2" from Seam w/East Head			0.592	0.576	0.555	0.582	0.581			
13	East Head 12 O'Clock	0.566									
14	East Head Center	0.523									
15	East Head 3 O'Clock	0.536									
16	East Head 6 O'Clock	0.535									
17	East Head 9 O'Clock	0.539									
18	West Head 12 O'Clock	0.523									
19	West Head Center	0.49									
20	West Head 3 O'Clock	0.518									
21	West Head 6 O'Clock	0.519									
22	West Head 9 O'Clock	0.521									

Skecth/Drawing:

Technician: Damon Crain Assistant: Date: 9/22/2025