

Transfinite games and the sequoidal exponential

John Gowers

October 27, 2016

Abstract

Laird [Lai02] introduces the concept of a *sequoidal category*, an augmentation of a monoidal category by a new operation \otimes (the sequoid) that has a natural model constructed using game semantics. The sequoid operator \otimes in this game-semantic model allows us to present the exponential connective $A \mapsto !A$ of [Hyl97] and [AJM00] as a final coalgebra. Under further assumptions, one can prove coalgebraically that this final coalgebra $!A$ is the carrier for a cofree commutative comonoid on A , and is therefore a suitable model for the exponential from linear logic. The authors of [CLM13] note that it does not seem to be possible to construct cofree commutative comonoids using the sequoidal category axioms alone. I shall show that this is indeed impossible by presenting a sequoidal category of transfinite games in which the final coalgebra $!A$ admits no comonoid structure. I shall discuss ways in which this transfinite model can inform our study of the usual finitary model.

References

- [AJM00] Samson Abramsky, Radha Jagadeesan, and Pasquale Malacaria. Full abstraction for PCF. *Information and Computation*, 163(2):409 – 470, 2000.
- [CLM13] Martin Churchill, Jim Laird, and Guy McCusker. Imperative programs as proofs via game semantics. *CoRR*, abs/1307.2004, 2013.
- [Hyl97] Martin Hyland. Game semantics. *Semantics and logics of computation*, 14:131, 1997.
- [Lai02] J. Laird. A categorical semantics of higher-order store. In *Proceedings of CTCS '02*, number 69 in ENTCS. Elsevier, 2002.