A MAP OF THE RANGE, NOT A WAY UP THE WALL: AI AGENTS ON 373 OPEN PROBLEMS IN ANALYSIS

ØISTEIN SØVIK

Abstract. In October 2026 we directed AI coding agents at every open problem we could find in one area of analysis: Hardy, Bergman and Dirichlet-series spaces, Hankel and Helson operators, and Nehari-type theorems. After a week of directed work on single problems, most of the campaign took two days. The agents collected 373 problems, found that 64 of them had already been settled by others, and produced answers to 141 more. We classify these answers by how they were obtained and by how much they matter. Most are easy in hindsight: short arguments from known tools, results assembled from the literature, or counterexamples that are easy to check once found. Six are, in our judgement, of real significance. On the hardest problems, days of work by several agents produced maps of what fails rather than proofs. Unlike most comparable reports, the work was directed by one person with a master's degree rather than by a team of specialists. Our conclusion is that a non-specialist can now map a research area, clear its long tail and find questions worth working on, but that it still takes an expert to judge which results matter, and a hard problem stays hard. All results of ours are sketches until they appear on arXiv or in a journal; this is a living document, updated as the people who asked the questions respond.

1. Introduction

Terence Tao has compared research mathematics to a mountain range, and current AI tools to small jumping robots:

> [...] a big mountain range with lots of tall mountains and lots of foothills [...] parkour their way to the top of a 6-foot wall [...] the little jumping robots are nowhere near the Mount Everests of math. —Terence Tao, quoted in [45]

This paper is a field report on what such robots do when pointed at an entire range. In October 2026 we used Claude Code and Codex agents to find, sort and attack every open problem we could locate in one research area. A week of directed work on single problems came first; the bulk of the campaign, over the whole database, took two days. The agents found 373 problems in papers, problem lists and monographs, established that 64 were already solved, and produced answers to 141 others.

The answers need careful reading. The agents were very good at mapping the field: finding problems, classifying them, checking the literature, and clearing problems that were easy but had received little attention. Most of their answers are low-hanging fruit; of the 141 we classify 6 as significant, 62 as useful and 73 as minor. On problems where experts had made partial progress and stopped, the agents produced reformulations, special cases and catalogues of obstructions rather than proofs. The gain was in cartography, not in climbing.

We did not solve 141 problems in the sense a mathematician would mean. The database mixes interesting questions from the field, questions at its research frontier, and questions we derived ourselves; many of the answers are to the last kind, or to questions that turned out to be easy once someone looked. Of almost 400 problems, about six of real significance were solved. What the agents added beyond that is partial: special cases and correct orders of growth for 142 problems, reductions of some 25 problems to three common hard cores, and written records of why each attempted route failed. These are new insights into the problems rather than solutions of them.

Date: October 14, 2026.

The work was directed by one person with a master's degree in the area, not by a team of specialists, and this is the main difference from comparable reports (Section 12). It shows that someone outside a research career can now explore a field at its frontier. It also shows the limit of that: every result that mattered still needed an expert to recognise it, and the askers' judgement remains the only real test.

Breadth explains the counts. Throw a hundred balls at a hundred baskets and some go in; that is useful, and different from getting better at the shot that matters. Tao's description of current tools as "artificial general cleverness" [48] fits what we saw.

We therefore present this method as the first step of a research project, not the last: a fast way to get to know a field and to find questions worth working on. Section 3 describes how the problems were found and sorted, Section 4 the workflow, Section 5 the results and their classification, Section 8 the hard problems, and Section 9 verification and credit. Section 11 places the work among other reports, and Section 15 lists its limits.

2. Setting

The area is the theory of Hardy and Bergman spaces on the disc and on the infinite polydisc, Dirichlet series viewed as functions on the infinite torus, and the Hankel, Helson and composition operators acting on them. A typical question asks for the sharp constant in an inequality, whether an extremal function can have zeros, or whether a bounded bilinear form has a bounded symbol. The active literature is a few hundred papers, much of it from a small number of research groups.

One person directed the work. He chose targets, judged whether a result mattered, steered agents that were stuck, read everything before it went out, and handled all contact with other mathematicians. The agents were Claude Code (Claude Opus 5.5 as the main session, with smaller Claude models for cheap subtasks) and Codex (several GPT models), often running at the same time in the same repository. The record of the work is the version history, with about 1000 commits, together with the logs: 14 Claude Code sessions with 393 subagents, and 586 Codex sessions, 420 of them subagents.

3. Building the map

The problems came from four sources, in this order.

(1) *Stated problems in a local paper collection.* Agents searched each paper for environments labelled Conjecture, Question, Problem or Open problem, and for phrases such as "remains open" and "it would be interesting to". Each candidate was recorded with the paper, the exact location, and a quote.
(2) *The papers those cite*, with the same extraction.
(3) *Synthesis passes.* Agents read the recent papers of the core authors "between the lines". This produced *implicit* questions, which a remark suggests without posing, and *inferences*: paper A proves one statement and paper B another, so a third should follow.
(4) *Problem lists and monographs*: workshop problem sessions, a classical problem book, and the open-problem sections of two monographs.

From candidates to 373 records. Table 1 follows the problems from extraction to the database. The local collection was broad: the director's paper library also held books from unrelated projects, so the first catalogue contained questions from fluid dynamics, arithmetic geometry and combinatorics alongside the target area. Scope was then fixed by one sentence: *Hardy and Bergman spaces, Dirichlet series, analytic extremals, Hankel operators, sampling and interpolation, and directly related analytic number theory*, informally "what the people working in this area would work on". An agent applied it theme by theme and wrote down a reason for every excluded theme, for example "Euler and Navier–Stokes questions are outside the selected scope" or "sphere-packing and energy-optimality conjectures

are excluded"; adjacent topics were kept only with a stated connection, such as random multiplicative functions for their link to Dirichlet-polynomial norms. Incomplete candidates, mostly exercises, were dropped. Excluded records were kept in a separate report rather than deleted.

Stage (date)	Records
PDFs screened in the local collection	299
Candidate records extracted, deduplicated (10 Oct)	459
of which problem statements	399
of which incomplete candidates, dropped	60
Excluded as out of scope, with a reason per theme (11 Oct)	166
Kept in the focused catalogue, plus 2 local additions	235
first order (in the collection) / second order (cited by it)	178 / 57
Database at migration, adding 40 questions from our own book (12 Oct)	270
Added from synthesis, workshop lists and monographs (12 Oct)	72
Added during the work, mostly questions met while attacking others	31
Database	373

TABLE 1. How the database was built. Duplicates were merged at each step, so the rows do not add up exactly.

Each problem became one Markdown file with validated metadata: its theme, its kind (298 stated, 55 implicit, 20 inferences) and origin (289 asked by others, 84 by us), tags, impact and difficulty scores, a dated literature check with quoted evidence, the stage reached in our own work, and, once anyone settled the problem, how far the resolution is trusted. Section A shows a complete record and which fields the agents filled at each stage. Moving from a single catalogue file to one file per problem let several agents and two different tools edit the database at once.

How difficulty was scored. Each problem received a difficulty score from 1 to 5, in two rounds. On 10 and 11 October, 194 problems from the first catalogue were assessed by cheap Codex agents (GPT-6 Luna), each with about ten minutes: a literature check, a short attempt, and a "speculative difficulty score and confidence" on the scale 1 = routine deduction or literature reconciliation, 2 = focused tractable project, 3 = substantial specialist project, 4 = probably requires a major new idea, 5 = longstanding frontier problem. Their brief warned that "a ten-minute failure to prove a statement is not evidence for a high score". On 12 October three Claude Opus 5.5 subagents scored the whole database, each taking a group of themes, under a common brief that defined difficulty as "effort for us with current tools" and fixed an anchor problem at each level:

Difficulty	Meaning
1	short argument from known tools; days
2	focused effort; an existing method adapts, or a computation settles it
3	needs a genuinely new idea, but a route is visible
4	hard; the natural approaches are known to fail
5	major open problem, or equivalent to one

Each score came with a one-line justification. The agents read each record's statement, literature status and evidence, and the source where the statement was unclear; resolved problems were scored as originally posed. For the 189 problems that already had a score from the first round, the Opus agents kept it unchanged; they scored the rest from scratch. Over all 373 problems the initial scores were distributed as 37, 48, 110, 145 and 33 for difficulty 1 to 5. The scores moved during the work. After the scoring pass, 145 of the 168 problems that

remained unsettled were re-rated, almost always upwards (127 by one level and 23 by two), as attempts failed. Most of these moves were mechanical: the protocol raised any problem that used its session budget without a full answer to difficulty 5 (see below). Of the 141 problems our agents settled, 38 were re-rated, mostly downwards. The final scores therefore record the outcome rather than predict it, and we use the initial scores of 12 October throughout. Even these are not blind: they were assigned after the directed work of 3 to 11 October, so for problems attempted then the score already reflects that attempt.

Selection for attack. Problems were attacked in rounds by difficulty, from 1 upwards: "start with the low-hanging fruit". Within a round the orchestrating session picked open, unparked problems with the best impact relative to difficulty, mixing cheap problems with one or two of high impact, and skipping problems whose literature status was an unverified claim by others. Each problem had a session budget equal to its difficulty, from one session at difficulty 1 to four at difficulty 4; difficulty 5 problems were worked only in dedicated rounds with a specific new idea. The protocol then moved problems mechanically: a problem at difficulty 1 to 4 that used its budget without a full answer was raised to difficulty 5, and a problem at difficulty 5, or after six sessions without even a partial result, was parked. Parked problems could be reopened only for a new idea, paper or tool.

The public problem volume was a further selection: questions asked only internally were removed, leaving 308 questions and 58 answers.

4. The workflow

Each problem was worked in sessions. A session begins by reading the record, the source passage and the log of earlier attempts, and by writing a three-line plan. It ends by rewriting a short *state of play* and appending one line to the *attempt log*: the route, the outcome, the reason, and the next step. A claimed result had to become a *solution sheet*: the problem as posed, the answer as a theorem, a complete proof with exact citations, and nothing else, built through a lint-gated LaTeX pipeline. A fresh agent with a fixed brief then refereed it. The referee re-read the question in its source, re-derived each step, reran any certificate, and decided whether the answer was full or partial.

On hard problems several agents worked in parallel *lanes*, each on one approach, with a coordinating session redirecting them. When lanes drifted into cataloguing obstructions, a *prove-mode* brief told each to commit to one strategy and push it to a theorem, or to a proof complete except for one precisely stated lemma. The full instructions are published with this paper as a reusable set of agent playbooks.

The record format, and what it was worth. The database replaced a set of catalogue files and a shared ranking that several workers appended to at once. Two failures forced it: agents repeated routes that had already failed, because the failures lived only in chat transcripts, and two tools with several subagents each needed to edit the list concurrently. Most fields were added one at a time over the following day, each answering a request from the director: a difficulty score "to give us some starting points", "different levels of solved" (the resolution tiers), a way to say which papers bear on a problem, and, a day later, whether we or someone else had asked the question.

To see which fields mattered we counted, over all 772 commits that touched the database, how many changed each field.

Field	Commits changing it
State of play (prose)	615
Attempt log (prose)	566
Stage	532
Session count and date	about 400
Failed approaches (prose)	322
Related papers	319
Artifacts	304
Literature evidence	275
Review	273
Full or partial	230
Origin, impact, tags	1–12
Authors told	3
Claim basis, abandonment reason, aliases	4 each

The fields that carried the work were the prose memory between sessions and the few fields that move a problem through the pipeline. Scores, tags and origin were filled once in bulk. Two lessons were negative. The free-text justification of the scores was rewritten in 426 commits, because escalations were appended to it, and so it went stale. The field recording that the askers had been told was changed in only three commits, because nothing in the pipeline required it. Other fields that nothing in the pipeline depended on, such as a free-text relevance line and the minutes spent, were also hardly ever filled in. The lesson is that the prose memory between sessions, together with the handful of fields that move a problem through the pipeline, did the real work; a field that nothing reads or checks is not kept up to date. The field we most missed was how the source poses the question, which we had to reconstruct for Section 5. The schema we now recommend keeps the working fields, freezes the score justification at triage and logs escalations in the attempt log instead, adds the form of the question, a verbatim quote, the reviewing model and a frozen initial difficulty, makes the publishing step refuse a result whose askers have not been told, and drops the unused fields.

5. Results

5.1. **What the literature check found.** The difficulty assigned to a problem before anyone attempted it predicted the outcome well (Table 2). It also showed why easy problems are easy: nine of the twelve problems first rated easiest already had a published answer. Tao observed the same correlation on the Erdős problems: the problems current tools can solve are "precisely the category of nominally open problems that are most likely to have been solved in the literature" [50]. The literature check also caught one problem recorded as resolved by a paper that had since been withdrawn.

Initial difficulty	Settled by others	Settled by us	Partial	Open
1	9	3	0	0
2	4	15	2	0
3	7	27	19	7
4	4	29	75	6
5	0	3	15	3

Table 2. Outcome by the difficulty assigned before any attempt, for the 275 records that had one.

5.2. **When the results came.** Figure 1 shows when the 141 answers were obtained, coloured by the initial difficulty. The database itself existed only from 12 October, so everything obtained in the directed work of 3 to 11 October appears in the first bar. That bar holds 30 answers, including four of the six we rate most significant. The bulk campaign of 12 October settled 45 problems, almost all of difficulty 1 to 3 and none of high significance. On 13 October the agents worked through harder problems: of its 66 answers, 25 were rated 4 or 5, and two are of high significance.




FIGURE 1. Answers settled by our agents, by when they were recorded and by the initial difficulty score. The first bar collects the directed work before the database existed; its dates come from the first appearance of each answer's write-up in the version history.

5.3. **What kind of results were these?** We classified each of the 141 answers along three axes.

- *Sign*: 82 proofs, 42 counterexamples, and 17 determinations of a value, set or order.
- *Kind*, meaning how the answer was obtained:
  - 20 assembled from the literature;
  - 58 routine new arguments;
  - 44 explicit constructions or certificates, which are the work to find and easy to check;
  - 19 substantial new arguments.
- *Significance*:
  - 6 high: paper-level answers to someone else's question;
  - 62 medium: full answers worth a short note;
  - 73 low: our own questions, conditional or elementary answers, and corollaries.

The classification is ours and preliminary; Table 3 gives the cross-tabulations.

Three things stand out. Counterexamples are the natural strength of the agents: 39 of the 42 counterexamples are explicit constructions or certificates. Searching a space of candidates and checking each one is exactly what agents do well, and what earlier work on machine-assisted discovery exploited [25, 37, 52]. Few proofs are substantial: only 17 of the 82 proofs needed a genuinely new argument, and the rest are routine or assembled from the literature. And the significant results needed direction. Of the six results we rate high, four are proofs and two are counterexamples, and three of the six came from focused sessions in which the human directed one problem with the asker's question in view, not from the bulk campaign over the database.

The six high-significance results are the following. Extremal functions for bounded linear functionals on H^p, $0 < p < 1$, are outer, which answers a published conjecture in a stronger form and was written jointly with the asker. Extremals in a prescribed-coefficient problem

	Literature	Routine	Construction	Substantial	Total
Proof	17	43	5	17	82
Counterexample	0	1	39	2	42
Determination	3	14	0	0	17

	High	Medium	Low	Total
Proof	4	33	45	82
Counterexample	2	24	16	42
Determination	0	5	12	17
Asked by others	6	57	26	89
Asked by us	0	5	47	52

TABLE 3. The 141 answers by sign and kind (top) and by sign, origin and significance (bottom).

have at most one zero. The sharp Bernstein–Nikolskii constants have limits for finite exponents. The H^1 norms of the partial-sum operators for Dirichlet series grow like $\log N/\log\log N$. A positive-symbol Nehari question has a negative answer, with a computer certificate in outward-rounded arithmetic. And optimal polynomial approximants in H^p can vanish in the disc for every $p \neq 2$. Each has been sent to the people who asked the question, or is being prepared for them. None is yet on arXiv.

5.4. **How the question was posed.** The database mixes questions of very different standing: conjectures, where an author predicts the answer; numbered problems and questions, including those from problem sessions and monographs; informal remarks such as "it would be interesting to know"; and questions we derived ourselves. The records did not store this distinction, so we recovered it afterwards from each record's source location; the split is approximate.

How posed	Records	Others solved	We solved	Unsettled	High
Conjecture (others)	63	13	23	27	3
Problem (others)	69	18	18	33	1
Question (others)	67	12	24	31	2
Informal remark (others)	90	18	24	48	0
Our own question	84	3	52	29	0

Our own questions were settled most often, 52 of 84, and none of those answers is significant. All six significant results answer a conjecture, problem or question that someone else had posed formally. Informally posed questions were the least often settled and produced nothing of high significance. We now record the form of each question when it is harvested.

6. Six discoveries, in the agents' words

The session logs record what each agent wrote when it reported a result. We quote them verbatim, with model and time (UTC); trims are marked [...] and our insertions are in square brackets. Table 4 gives the order.

Outer extremals. The first claim came after the director told the agent that its numerical sweeps did not get closer to a proof:

> I believe I've proved [the nonvanishing conjecture of Brevig and Saksman]: for $0 < p < 1$, every extremal for $C(k, p)$ has no zeros in the disc. [...] Only I have checked the proof, plus numerics at $k = 2$; no one else has. —Claude Opus 5.5, 8 October, 13:56

Result	First reported	Found by	Sign
Outer extremals	8 Oct, 13:56	Claude Opus 5.5	proof
At most one zero	8 Oct, 20:49	GPT-6 Luna (Codex)	proof
Approximant zeros	10 Oct, 21:46	GPT-6.1 Sol; Claude	counterex.
Bernstein–Nikolskii limits	11 Oct, 19:13	Claude Opus 5.5	proof
H^1 partial sums	12 Oct, 22:21	GPT-6.1 Sol (Codex)	proof
Positive Nehari	12 Oct, 22:44	GPT-6 Astra	counterex.

TABLE 4. When the six high-significance results were first reported. Each was later checked by at least one other agent; the first two are also Lean-verified.

Two hours later a subagent extended it from one coefficient to every bounded linear functional, including singular inner factors. The next evening a Codex agent estimated that a Lean formalization would take "months, potentially longer"; it was finished overnight:

> Done—the full theorem is now Lean-verified: every extremal for a nonzero bounded complex-linear functional on H^p, for every real $0 < p < 1$, is outer. —GPT-6.1 Sol, 10 October, 00:54

At most one zero. A Codex subagent found the key step; the deciding idea was to fix one perturbation phase rather than average over phases:

> The full real-direction Hessian yields a direct contradiction for any extremal with at least two zeros. [...] I checked the projections, the cancellation of the [...] terms, and admissibility of the perturbation. I found no gap in the argument. —GPT-6 Luna, 8 October, 20:49

The idea was relayed to the Claude session within minutes, which then reported that it had "reached the same conclusion independently". We cannot verify that claim, and we credit the Codex subagent.

Zeros of optimal polynomial approximants. This story took one evening. At 21:58 the director asked how close the agents were to the full result:

> We're not close to the full result if that means interior zeros for every $p \neq 2$. What we have is solid for p close to 1, and nothing yet for p near 2 or above it. —Claude Opus 5.5, 10 October, 21:58

Twenty-seven minutes later a subagent reported "there is no obstruction", and the main session wrote:

> Outer targets now work for $p > 2$ as well. Agent A found the construction, and I checked it independently. So for every $p \neq 2$ there is an outer target (even a polynomial one) whose degree-one OPA has a zero in $\mathbb{D}$. —Claude Opus 5.5, 10 October, 22:25

Bernstein–Nikolskii limits.

> [The finite-q problem] is proved: for every $s \geq 0$ and $0 < p < q < \infty$, $\lim A^{(s)}_{p,q,n} = D^{(s)}_{p,q}$, and the real version holds too. I checked the proof step by step; it has not been refereed. —Claude Opus 5.5, 11 October, 19:13

A second subagent then checked priority and found the problem still listed as open in a survey from two weeks earlier.

H^1 partial sums.

> The draft now proves a lower bound of order $\log N / \log\log N$ for every sufficiently large N, matching the published upper bound. The key step is

> turning product entropy into the missing L^1 output bound [...] subject to independent review. —GPT-6.1 Sol, 12 October, 22:21

A Claude referee later judged it "a genuine full-order answer to the $p = 1$ case of [an open problem of] Saksman–Seip" [46, Problem 4.5].

Positive Nehari. The same agent declined to count a numerical candidate before it had a certificate, and four minutes later had one:

> I'm not counting the new [...] numerical candidate as a breakthrough—it still needs a rigorous certificate. —GPT-6 Astra, 12 October, 22:40

> [The record] now has a rigorous counterexample certificate. For an explicit measure on two points in the real three-dimensional cube, the certified scalar norm exceeds the full Hilbert embedding norm. [...] This is a proved candidate awaiting independent review, rather than an 'almost proved' lead. —GPT-6 Astra, 12 October, 22:44

A Claude referee reran the certificate the next morning and found it "correct, no fixes".

The agents on their own work. The same logs show the agents assessing their limits frankly once challenged:

> I did a bounded first pass, not an all-out attempt. [...] I tested one route per open problem, often a relatively elementary construction, and usually stopped when it failed. [...] 14 failed routes do not demonstrate that I seriously exhausted the mathematical possibilities. —GPT-6 Astra, 13 October

> Against the original questions: 0 of these 4 fully solved. I made substantive partial progress, but selected easier subproblems instead of problems I could plausibly finish. —GPT-6 Astra, 13 October

> When everything you try collapses onto the same estimate, it usually means the problem needs a new idea, not more effort. —Claude Opus 5.5, 13 October

7. What the agents did not settle

Full answers are only half the picture. Of the 373 problems, 168 remain unsettled: 142 with partial results of ours and 26 without. We compared them with the 141 settled ones; the counts below come from the records, and the classification of obstructions is our judgement after reading each record's state of play.

7.1. How they differ.

	Unsettled (168)	Settled (141)
Initial difficulty 4 or 5	126	35
Asked by others	83%	63%
Impact 4 or more	19%	4%
Partial progress by others already in the literature	50%	21%
Answer is a counterexample (or expected to be one)	5%	30%
Inferences of ours	1	16
Mean number of working sessions	1.8	1.5

The problems that resisted were not neglected: they received slightly more working sessions than the settled ones, and only four received none. They differ in kind. They were asked by others, they matter more, half of them had already been attacked in the literature, and they ask for a characterisation, an exact constant or a uniform estimate rather than a single construction. The settled problems, by contrast, include most of our own derived questions and most of the problems a counterexample could close. Themes rooted in number theory and probability (random multiplicative functions, Bohr radii, general Dirichlet series,

Paley–Wiener extremals) were mostly unsettled; composition operators and the extremal problems around one published conjecture were mostly settled.

7.2. **What blocked them.**

Main obstruction	Records
Only special cases or families proved	59
Needs an estimate that is itself a known hard problem	37
Open-ended, ambiguous, or in need of reformulation	23
Endpoint or critical case; every method loses a log or a power	22
Exact constant wanted; only bounds or expansions found	14
Numerics suggest the answer, but no route to a proof	6
Depends on unrefereed or unavailable literature	5
Not attempted in depth	2

About 25 records reduce to three underlying problems: an L^1 endpoint estimate behind Schatten-class Nehari theorems, the value of one sharp constant in a multiplicative Hilbert-type inequality, and the unknown extremal functions of point evaluation in Paley–Wiener spaces. Settling any one of these would move many records at once; none moved.

7.3. **Full versus partial.** A full answer settles the question as posed; a partial one does not. Of the 142 partial results, the main type was:

Type of partial result	Records
Special case, subrange or family	90
Counterexample to a stronger statement or a literal reading	15
Correct order, or two-sided bounds, without the constant	13
Reduction to an equivalent reformulation	12
Conditional on a hypothesis or an unrefereed preprint	7
One direction only	5

A recurring kind is a local result near a point where the problem is already solved, for example near $p = 2$, which proves the conjecture in a neighbourhood but gives no uniform control away from it. This is the pattern the human director called "filling $\mathbb{R}$ with $\mathbb{Q}$": more and more special cases, none of which converges to the general statement.

8. Walls

We attacked several problems on which experts have made partial progress, for days and with several agents. Two examples show the pattern. The first is an endpoint Schatten-class Nehari problem. Every route the agents found reduced to one square-function estimate in L^1 that is a theorem in its own right. They proved many special cases, wrote down equivalent reformulations, and catalogued exactly where each route failed, but found no proof, and the problem was handed back to the person who asked it. The second is a contractive restriction conjecture, for which the agents proved two natural families of cases and refuted a stronger statement that would have implied it; the general case did not move. In both cases the output was useful as a map. It is not progress on the wall itself, and we do not present it as such. The pattern matches Tao's image: some walls of six feet were climbed; the Everests were not approached.

9. Verification and credit

Producing a candidate proof was cheap; checking it was the bottleneck. This matches Tao's analysis of the problem-solving pipeline, in which generation is followed by verification, exposition, acceptance and absorption into the standard theory, and in which AI threatens "proof indigestion" [47]. Our answers were checked by agent referees, in some cases by a second model family, and in a few cases by Lean formalization or exact-arithmetic certificates.

Agent referees caught real errors: a bound used outside its range, a missing hypothesis, and above all overstated scope, where an answer to a special case was reported as an answer to the question. They rarely asked whether the claim was the right one.

For this reason every result of ours is labelled a *sketch* until it appears on arXiv or in a journal, however it was checked. Before anything is posted, the people who asked the question are told; this follows the recommendations of the Leiden Declaration on attribution, disclosure and the humanity of authorship [42]. The questions belong to those who asked them. The proofs and computations were produced by AI agents and checked by the author. Following Tao's rule of thumb [47], no result should be published until a human can give a clear, expert-level talk on it.

10. History and files

Version control was the research log, but only once we used it. The repository was managed with Jujutsu (`jj`), which recorded 2409 operations and 1007 commits. Of the operations, 1944 fall on 12 and 13 October, after the rule that each problem record is committed together with the work it describes. The directed work of 3 to 11 October, which produced four of the six significant results, left only 136 operations; those results can be dated only by when their write-ups first appeared. Everything quantitative in this report (when problems were settled, how difficulty scores moved, which record fields were used) comes from the fine-grained part of the history. Jujutsu's automatic snapshots meant that no edit by an agent was ever lost, and cheap small commits kept changes per record. Our playbooks therefore default to Jujutsu with a git backend, so that git-based hosting keeps working, and require a commit per problem from the first day.

Failed attempts sprawled. The rule that TeX files hold results only, with failures recorded in one line of the problem record, was adopted but not enforced. The research folders ended with about 350 Markdown notes, 575 TeX files, 260 scripts and 140 data files. 107 problem records list five or more artifacts, and one hard problem accumulated 31 files. Parallel agents each wrote their own note instead of appending to a shared one, superseded drafts were archived rather than deleted, and exploratory scripts were saved next to certificates. Later agents had to read through the pile to avoid repeating routes, and sometimes did not. The playbooks now require one notes file per problem with dated sections, scratch work outside the repository, scripts in the repository only when a claim depends on them, and deletion of superseded drafts, which the history keeps.

11. Related work

Agents on lists of open problems. Several groups have run AI systems over whole lists of open problems in the past year, and their numbers are the natural comparison for ours (Table 5). The closest study to ours is the Gemini case study on the Erdős problems, which

Study	Problems	Outcome
Gemini on Erdős problems [7]	700 open	13 addressed, 4 novel
Formal proof search [17]	353 Erdős; 492 OEIS	9; 44 resolved
OEIS Open [1]	492 OEIS	147 resolved
Provers and verifiers [13]	66 conjectures	about a third
QED [15]	18 expert-chosen	5 original works
FAR pipeline [6]	4717 harvested	598 candidate resolutions
UQ [18]	500 unsolved questions	15% pass validation
This report	373 harvested	64 known; 141 claimed; 6 significant

Table 5. Reported outcomes of AI systems run on lists of open problems. The lists differ widely in difficulty, and so do the meanings of "resolved".

reached the same conclusion: "the 'Open' status of the problems was through obscurity

rather than difficulty" [7]. Of the 13 problems it addressed, 9 turned out to be solved already in the literature, as were nine of our twelve easiest problems; of 200 candidate answers it graded, 68.5% were flawed and only 6.5% meaningfully correct, because most technically correct answers had misread the question and were vacuous. The FAR pipeline found that its difficulty scores predicted outcomes with an area under the curve of 0.69, a weak but real signal like the one in Table 2. The authors of the OEIS study note that their conjectures "are of uncertain mathematical significance, and most have likely received little previous attention" [1]. The FAR pipeline [6] is the nearest match to our method, at about fifteen times our scale: it extracted 6453 candidate problems from 5245 combinatorics papers and sent 77 potential resolutions to their authors. Like us, its authors identify the selection of problems and the review of the results as the bottlenecks. An early small test with five easy conjectures found the same pattern as ours: the easy ones fell, and the one that needed two papers combined did not [9]. Individual resolutions from such sweeps have been written up with care [3, 16], and one Erdős prize problem thought open for half a century turned out to have been settled three decades before it was posed [2].

Harvesting problems. Problem lists are now being built automatically. DeepMind's formal conjectures collect 2615 statements in Lean, including 1029 open conjectures; AI proofs and disproofs were used to find badly stated problems [8]. OpenConjecture extracts conjectures from new arXiv papers with a language model and ranks them by apparent tractability, with the caveat that the results "have not been independently verified" [24]. FrontierMath's open-problems pilot sets out to provide a "denominator" for AI contributions [22], and MathArena tracks performance on questions extracted from recent papers [14]. The Erdős problems database [32] and its AI wiki [33] remain the closest analogue to our database; the wiki warns that "absence of past progress may reflect obscurity rather than difficulty".

Mathematicians' experience. Gowers writes that "if a problem can be solved by means of a relatively standard argument, it is highly likely that an LLM will be able to find and use that argument", while its suggestions on harder problems often "sound promising until I think about them carefully" [23]. That is our experience in one sentence. Case studies from industry [5, 20] and from individual groups, including one in functional analysis [4] and one with a consumer model [19], report the same division of labour: models search for proofs, and experts close them. Earlier work on machine-assisted discovery found constructions and counterexamples by search [25, 31, 37, 38, 52], and experiments with frontier models as research assistants are collected in [29]. Formal proof [26, 27, 41, 43, 44] and evaluation [30, 34–36, 40] form the background.

Verification and significance. Bloom, who maintains the Erdős problems database, reports "a wave of AI-produced solutions provided with no explanation", and that much recent progress came from renewed human effort "rather than just AI" [21]. Kallel and El Louadi separate the validity of a derivation, which a proof checker settles, from whether the formal statement means the intended question and whether the result matters; "only the first is mechanizable" [11]. This is our distinction between settled and significant. A survey of arXiv mathematics finds substantive AI use growing to about 14% of submissions by August 2026, concentrated in combinatorics rather than analysis [10], and long agent runs are documented to drift in the ways we saw [12]. On the goals of mathematics beyond problem solving we follow Thurston [51], Gowers [39], Tao [47, 49] and Bessis [28]; journalism on the current state includes [45], where Igor Pak notes that language models are "fantastic in finding the right references".

12. How the method differs

Table 6 compares the design of our campaign with the closest studies. Three differences matter for reading our numbers.

Study	Problem source	Who directed	Checked by
Gemini, Erdős [7]	curated list	expert team	AI filter, experts
Proof search [17]	curated lists	research team	Lean
OEIS Open [1]	formalized list	one researcher	Lean
FAR [6]	5245 papers	research team	sent to authors
QED [15]	chosen by experts	experts	verifier agent
This report	harvested, about 300 papers	one MSc holder	agent referees; askers

TABLE 6. How comparable studies chose their problems, who directed the work, and how results were checked.

The problems were harvested, not curated. The Erdős and OEIS lists are fixed, public and of known provenance. Ours was assembled by agents from papers, problem sessions and monographs, including informal remarks and our own derived questions, and it was scoped by a single sentence. This gives a broader and messier denominator; Section 5 shows how much the outcome depends on how a question was posed.

The area resists formalization. Most of the large studies verify in Lean, which works well for combinatorics and number theory, where substantive AI use is also concentrated [10]. Hardy spaces, Schatten classes and Dirichlet series in infinitely many variables are far from current formal libraries. We formalized two results; everything else rests on agent referees, certificates in exact arithmetic, and the people who asked the questions. Our counts are therefore claims, not verified resolutions.

One non-expert director. The other studies are run by teams of specialists or by the developers of the models. Ours was directed by one person with a master's degree in the area, which is closer to how a graduate student or a mathematician from a neighbouring field would use these tools. Three of the six significant results came from sessions where he directed a single problem with its asker in view.

13. What else the work produced

The proofs are the smallest part of what the campaign left behind. For a mathematician entering one of these problems, the other products are probably worth more. The first is a map of the area: 373 problems with exact sources, 308 of them published with their sources and evidence status. The second is a literature audit, which found 64 problems already solved and one recorded resolution that rested on a withdrawn paper. The third is a state of play for every problem, giving what is known, the best current route and the exact open subgoal. The fourth is a record of failure: 207 problems carry a list of the routes tried and the reason each failed. Mathematics has almost no venue for such records, and Tao names "the publication of negative or partial results" among the infrastructure the field now needs [47]. The fifth is the partial results for 142 problems: special cases, correct orders of growth, reductions, and counterexamples to stronger statements. The last is a set of common cores: about 25 problems reduce to three underlying hard problems, so progress on one would move many. These products are unverified in the same sense as the proofs, and the raw working files behind them, about 1300 notes, drafts and scripts, are of little use to anyone. Their value lies in the curated record of each problem. We would release that record per problem, labelled as a sketch, to anyone working on it.

14. What the literature changed in our process

We read the closest studies in full and changed our playbooks where they had learned something we had not. The main changes are the following.

Read the question before answering it. Copy the source's conventions into the record, check a restatement against known special cases, and treat an easy answer as a sign of misreading:

most technically correct answers in the Gemini study were vacuous [7], and AlphaProof's agents proved variants the askers had not meant [17].

Blind, cross-family referees. The referee first sees only the question and the proof, as in QED, whose verifier accepted 17 of 214 candidate proofs and had all 17 confirmed by experts [15]; same-family validators overrate their own answers [18]. Review is capped at two rounds, after which the problem goes to the human, since revisions converge on errors the reviewer can no longer see [5].

A word-by-word statement check, with a list of the ways a proved statement drifts from the posed one [11, 15], and a citation audit that quotes every cited result.

Outcome labels and honest reporting: known, new, fixed statement, or nothing [6]; claimed answers split into flawed, technically correct and meaningfully correct [7]; asymptotic results without explicit thresholds counted as partial [13].

Neutral briefs: "prove or disprove", since an agent told to prove a false statement papers over the gap [20]; and repeated narrowing to a smaller question without a new idea counts as no progress [23].

Human sign-off before release: the human confirms that the statement matches the question [11], writes or approves an exposition they understand [21], could give a talk on it [47], and adds a disclosure section [42].

15. Limits

This is one person's experience in one area, over a few weeks, without a control group. The difficulty and significance scores were assigned by the same agents and by the author, not by independent experts. Correctness has not been audited on a random sample; we intend to do so, and the counts above should be read as counts of claimed answers. The models will be superseded within months. Finally, the area has a dense literature of recent preprints, which made the literature check unusually productive.

Tool and computational resource disclosure

The work used Claude Code from Anthropic, with Claude Opus 5.5, Sonnet and Haiku, and Codex from OpenAI, with several GPT models; Python with mpmath, SymPy and cvxpy for numerics and certificates, Lean for one formalization, and LaTeX built through a lint gate. This paper was drafted with Claude Code from the project's records and logs and revised by the author. The agent instructions, templates and tools are available in the accompanying process repository.

Appendix A. A problem record

Each problem is one Markdown file whose YAML header holds the data and whose body holds the memory between sessions. This is the record of a question of Bayart and Yao, abridged; long fields are cut with [. . .].

```
id: BY-8.7
title: "Minimal commutant for phi = lambda z^p psi (p>=2) on H^2(D):
  can the zero-free assumption on psi in Corollary 8.5 be dropped?"
kind: stated                      # stated | implicit | inference
origin: external                  # external | ours
theme: composition
source:
  paper: "arXiv:2406.19737"
  location: "Question 8.7, p. 33"
  posed_by: [Bayart, Yao]
literature:
  status: open
  checked: 2026-10-13
```

```
  evidence: ["arXiv:2406.19737v1 (only version) [...]"]
ours:
  stage: public
  result_scope: full
  sign: proof
  artifacts: [research/composition/solutions/BY-8.7.tex]
  review: "independent agent referee 2026-10-13: correct [...]"
  public: papers/bayart-yao-questions.pdf
  told_authors: null
resolution: {tier: ours-public, ref: "BY-8.7.tex, Theorem 1",
             checked: true, conditional_on: []}
impact: 2
difficulty: 2
scores_note: "[...] difficulty 3->2 after split from BY-8.11 [...]:
  short argument (local Boettcher coordinate [...])"
tags: [setting:disc, space:hardy, object:composition,
       type:existence, method:construction]
effort: {sessions: 1, last: 2026-10-13, parked: false}
```

The body has four sections: *Statement* (the question with notation defined), *State of play* (rewritten each session), *Failed approaches* (one line per dead route, with its reason) and an *Attempt log* (one line per session: route, outcome, reason, next step).

The fields were filled at different stages and by different hands. At harvest an agent filled the identity and the source: `id`, `title`, `kind`, `origin`, `theme` and `source`. At triage a cheap agent filled `literature` and the scores, `impact`, `difficulty`, `scores_note` and `tags`. During attacks the working agent updated `ours.stage`, `ours.artifacts`, `ours.sign`, the `effort` counters and the body. A referee set `ours.review`, `ours.result_scope` and `resolution`. Only the human set `ours.public` and `ours.told_authors`. Validation by `make problems` rejected unknown fields, invalid values and inconsistent combinations, such as a resolution tier on a partial result.

References

[1] T. Adamczewski, *OEIS Open: how many conjectures can language models turn into theorems?* (2026), available at `arXiv:2608.11941`.

[2] B. Alexeev and D. G. Mixon, *Forbidden Sidon subsets of perfect difference sets, featuring a human-assisted proof* (2025), available at `arXiv:2510.19804`.

[3] B. Alexeev et al., *Short proofs in combinatorics, probability and number theory II* (2026), available at `arXiv:2604.06609`.

[4] J. de Dios Pont et al., *Banach lattices and phase retrieval: a case study for the use of AI in mathematics* (2026), available at `arXiv:2608.07396`.

[5] D. Zheng et al., *AI co-mathematician: accelerating mathematicians with agentic AI* (2026), available at `arXiv:2605.06651`.

[6] Z. Zheng, S. Zhang, J. Avigad, P. Tetali, and S. Welleck, *The problem is the problem: towards scalable mathematical discovery* (2026), available at `arXiv:2608.16977`.

[7] T. Feng et al., *Semi-autonomous mathematics discovery with Gemini: a case study on the Erdős problems* (2026), available at `arXiv:2601.22401`.

[8] M. Firsching et al., *Formal Conjectures: an open and evolving benchmark for verified discovery in mathematics* (2026), available at `arXiv:2605.13171`.

[9] M. Feldman and A. Karbasi, *Gödel Test: can large language models solve easy conjectures?* (2025), available at `arXiv:2509.18383`.

[10] J. Jin, Z. T. Ke, and B. Sui, *The gold rush in AI4Math: where are we now?* (2026), available at `arXiv:2608.24961`.

[11] M. Kallel and M. El Louadi, *Verification abundance, adjudication scarcity: what happens to mathematical knowledge when proof checking becomes free* (2026), available at `arXiv:2608.28997`.

[12] Y. Zhang et al., *LeanMarathon: toward reliable AI co-mathematicians through long-horizon Lean autoformalization* (2026), available at `arXiv:2606.05400`.

[13] H. Le Duc and L. Liberti, *Mathematics with large language models as provers and verifiers* (2025), available at arXiv:2510.12829.
[14] J. Dekoninck et al., *Beyond benchmarks: MathArena as an evaluation platform for mathematics with LLMs* (2026), available at arXiv:2605.00674.
[15] C. An, Q. Ye, M. Pan, and J. Zhang, *QED: an open-source multi-agent system for generating mathematical proofs on open problems* (2026), available at arXiv:2604.24021.
[16] N. Sothanaphan, *Resolution of Erdős Problem #728: a writeup of Aristotle's Lean proof* (2026), available at arXiv:2601.07421.
[17] G. Tsoukalas et al., *Advancing mathematics research with AI-driven formal proof search* (2026), available at arXiv:2605.22763.
[18] F. Nie et al., *UQ: assessing language models on unsolved questions* (2025), available at arXiv:2508.17580.
[19] B. Verbeken et al., *Early evidence of vibe-proving with consumer LLMs: a case study on spectral region characterization with ChatGPT-5.2 (Thinking)* (2026), available at arXiv:2602.18918.
[20] D. P. Woodruff et al., *Accelerating scientific research with Gemini: case studies and common techniques* (2026), available at arXiv:2602.03837.
[21] T. Bloom, *Changes to the Erdős problems web site*, 2026. Guest post on T. Tao's blog, 6 October 2026, https://terrytao.wordpress.com/2026/10/06/changes-to-the-erdos-problems-web-site/.
[22] Epoch AI, *Introducing FrontierMath: Open Problems*, 2026. 27 January 2026, https://epochai.substack.com/p/introducing-frontiermath-open-problems.
[23] W. T. Gowers, *What sort of maths are LLMs good at?*, 2026. Gowers's Weblog, 12 August 2026, https://gowers.wordpress.com/2026/08/12/what-sort-of-maths-are-llms-good-at/.
[24] D. Brown and H. Kvinge, *Introducing OpenConjecture, a living dataset of mathematics conjectures from the arXiv*, 2026. 18 March 2026, https://dlscience.substack.com/p/introducing-openconjecture-a-living.
[25] A. Novikov et al., *AlphaEvolve: a coding agent for scientific and algorithmic discovery* (2025), available at arXiv:2506.13131.
[26] T. H. Trinh, Y. Wu, Q. V. Le, H. He, and T. Luong, *Solving olympiad geometry without human demonstrations*, Nature **625** (2024), 476–482, DOI 10.1038/s41586-023-06747-5.
[27] J. Avigad, *Mathematics and the formal turn*, Bull. Amer. Math. Soc. (N.S.) **61** (2024), 225–240, DOI 10.1090/bull/1832.
[28] D. Bessis, *The fall of the theorem economy*, 2026. https://davidbessis.substack.com/p/the-fall-of-the-theorem-economy.
[29] S. Bubeck et al., *Early science acceleration experiments with GPT-5* (2025), available at arXiv:2511.16072.
[30] K. M. Collins et al., *Evaluating language models for mathematics through interactions* (2023), available at arXiv:2306.01694.
[31] A. Davies et al., *Advancing mathematics by guiding human intuition with AI*, Nature **600** (2021), 70–74, DOI 10.1038/s41586-021-04086-x.
[32] T. Bloom, *Erdős problems*. https://www.erdosproblems.com.
[33] *AI contributions to Erdős problems, and Disclaimers and caveats*. Wiki of the Erdős problems repository, https://github.com/teorth/erdosproblems/wiki.
[34] M. Abouzaid, N. Srivastava, et al., *First Proof second batch* (2026), available at arXiv:2606.18119.
[35] S. Frieder et al., *Mathematical capabilities of ChatGPT* (2023), available at arXiv:2301.13867.
[36] E. Glazer et al., *FrontierMath: a benchmark for evaluating advanced mathematical reasoning in AI* (2024), available at arXiv:2411.04872.
[37] B. Romera-Paredes et al., *Mathematical discoveries from program search with large language models*, Nature **625** (2024), 468–475, DOI 10.1038/s41586-023-06924-6.
[38] B. Georgiev, J. Gómez-Serrano, T. Tao, and A. Z. Wagner, *Mathematical exploration and discovery at scale* (2025), available at arXiv:2511.02864.
[39] W. T. Gowers, *The two cultures of mathematics*. https://www.dpmms.cam.ac.uk/~wtg10/2cultures.pdf.
[40] L. Phan et al., *Humanity's last exam* (2025), available at arXiv:2501.14249.
[41] G. Lample et al., *HyperTree proof search for neural theorem proving* (2022), available at arXiv:2205.11491.
[42] *The Leiden Declaration on Artificial Intelligence and Mathematics*, 2026. https://leidendeclaration.ai/, doi:10.5281/zenodo.20302944.
[43] The mathlib Community, *The Lean mathematical library*, Proceedings of the 9th ACM SIGPLAN International Conference on Certified Programs and Proofs, 2020, pp. 367–381, DOI 10.1145/3372885.3373824.
[44] S. Polu and I. Sutskever, *Generative language modeling for automated theorem proving* (2020), available at arXiv:2009.03393.
[45] K. Kakaes, *The AI revolution in math has arrived*, Quanta Magazine (2026). https://www.quantamagazine.org/the-ai-revolution-in-math-has-arrived-20260413/.
[46] E. Saksman and K. Seip, *Some open questions in analysis for Dirichlet series* (2016), available at arXiv:1601.01616.

[47] T. Tao, *Mathematics in the age of AI* (2026), available at `arXiv:2608.16753`.
[48] ———, *Post on artificial general cleverness*, 2025. Mathstodon, `https://mathstodon.xyz/@tao/115722360006034040`.
[49] ———, *What is good mathematics?*, Bull. Amer. Math. Soc. (N.S.) **44** (2007), 623–634, available at `arXiv:math/0702396`.
[50] ———, *Post on AI solutions to Erdős problems*, 2025. Mathstodon, `https://mathstodon.xyz/@tao/115788262274999408`.
[51] W. P. Thurston, *On proof and progress in mathematics*, Bull. Amer. Math. Soc. (N.S.) **30** (1994), 161–177, available at `arXiv:math/9404236`.
[52] A. Z. Wagner, *Constructions in combinatorics via neural networks* (2021), available at `arXiv:2104.14516`.