

Cryptographic Hash Functions: SHA-256 Analysis and Security Properties

Cryptography Research Laboratory

December 11, 2025

Abstract

This report presents a comprehensive computational analysis of cryptographic hash functions, with focus on the SHA-256 algorithm and its security properties. We examine the three fundamental requirements of cryptographic hash functions: preimage resistance, second preimage resistance, and collision resistance. Through computational experiments, we demonstrate the avalanche effect where single-bit input changes produce dramatically different hash outputs, analyze birthday attack probabilities for collision finding, and explore applications in digital signatures, blockchain technology, and password hashing. Results confirm SHA-256's strong security properties including 50% bit flip probability under minimal input perturbation.

1 Introduction

Cryptographic hash functions serve as fundamental building blocks in modern information security, providing data integrity verification, digital signature schemes, and secure password storage. A cryptographic hash function transforms arbitrary-length input messages into fixed-length digest values, designed to make finding two inputs with identical outputs computationally infeasible.

Definition 1.1 (Cryptographic Hash Function) *A cryptographic hash function $H : \{0, 1\}^* \rightarrow \{0, 1\}^n$ maps arbitrary-length bit strings to fixed-length n -bit outputs (digests), satisfying three security properties:*

1. **Preimage resistance:** *Given hash value h , computationally infeasible to find m such that $H(m) = h$*
2. **Second preimage resistance:** *Given m_1 , infeasible to find $m_2 \neq m_1$ with $H(m_1) = H(m_2)$*
3. **Collision resistance:** *Infeasible to find any pair (m_1, m_2) with $m_1 \neq m_2$ and $H(m_1) = H(m_2)$*

2 Theoretical Framework

2.1 SHA-256 Construction

The Secure Hash Algorithm 256-bit (SHA-256) employs the Merkle-Damgård construction, processing the input message in 512-bit blocks through iterative compression. The algorithm initializes eight 32-bit working variables with predetermined constants, then updates these values through 64 rounds of bitwise operations including rotations, XOR, AND, and modular addition.

Theorem 2.1 (Merkle-Damgård Construction) *Let $f : \{0, 1\}^{n+m} \rightarrow \{0, 1\}^n$ be a collision-resistant compression function. The iterated hash function H constructed by padding the input, partitioning into m -bit blocks, and iteratively applying f is also collision-resistant. A collision in H implies a collision in f .*

2.2 Avalanche Effect

Property 2.1 (Strict Avalanche Criterion) *A cryptographic hash function exhibits the avalanche effect if changing a single input bit causes each output bit to flip with probability ≈ 0.5 . For an ideal n -bit hash function, a one-bit input change should produce an expected Hamming distance of $n/2$ bits in the output.*

The avalanche effect ensures that similar messages produce dramatically different hash values, preventing attackers from deducing relationships between inputs based on hash similarity. SHA-256’s compression function achieves excellent avalanche propagation through its round structure combining non-linear Boolean functions with bit rotations.

2.3 Birthday Attack Complexity

Theorem 2.2 (Birthday Bound) *For a hash function outputting n -bit digests, the expected number of random hash evaluations required to find a collision is approximately $\sqrt{2^n} = 2^{n/2}$. This follows from the birthday paradox: among k randomly selected values from a set of size N , the collision probability approaches 0.5 when $k \approx 1.177\sqrt{N}$.*

For SHA-256 with 256-bit output, birthday attacks require approximately 2^{128} hash evaluations to find a collision with 50% probability—a computationally infeasible number even for state-of-the-art computing clusters.

Example 2.1 (Birthday Paradox) *The probability that among k people, at least two share a birthday (365 possible dates):*

$$P(\text{collision}) = 1 - \frac{365!}{(365 - k)! \cdot 365^k} \approx 1 - e^{-k^2/(2 \cdot 365)} \quad (1)$$

With $k = 23$ people, $P(\text{collision}) \approx 0.507$. For hash functions with $N = 2^n$ possible outputs, collisions become likely after $\sqrt{N}$ samples.

3 Computational Analysis

We implement simplified hash function demonstrations and analyze SHA-256’s cryptographic properties through computational experiments. The following analysis examines message digest computation, avalanche effect quantification, and birthday attack probability modeling.

4 Results

4.1 SHA-256 Hash Examples

We demonstrate SHA-256 digest computation for sample messages and analyze the dramatic output changes resulting from minimal input perturbations. The hexadecimal hash values illustrate the unpredictability and avalanche properties essential for cryptographic security.

Table 1: SHA-256 Hash Digest Examples

Input Message	SHA-256 Digest (Hexadecimal)
Hello, World!	df6d6021bb2bd5b0af676290809ec3a53191dd81c7f70a4b28688a362182986f
Hello, world!	315f5bdb76d078c43b8ac0064e4a0164612b1fce77c869345bfc94c75894edd3
Blockchain	625da44e4eaf58d61cf048d168aa6f5e492dea166d8bb54ec06c30de07db57e1
blockchain	ef7797e13d3a75526946a3bcf00daec9fc9c9c4d51ddc7cc5df888f74dd434d1
Cryptographic hash functions e...	629babf9ee1de3298927993d283c26f760c4f35cc67c1774cc6a06cfaa02120a

4.2 Avalanche Effect Quantification

The avalanche effect is quantified by measuring the Hamming distance between hash outputs when a single input bit is modified. For cryptographically strong hash functions, this distance should approximate 50% of the output bits, indicating complete decorrelation between similar inputs.




Figure 1: Comprehensive cryptographic hash function analysis: (a) Avalanche effect demonstration showing Hamming distances between original and perturbed message hashes, confirming near-ideal 128-bit average change for single-bit input modifications; (b) Distribution of output bit flip percentages across multiple perturbations, clustering near the ideal 50% mark; (c) Birthday attack collision probabilities for hash functions of varying bit lengths, illustrating the $2^{n/2}$ security bound; (d) Output distribution uniformity of a simplified polynomial hash function; (e) Computational work factor comparison between preimage attacks (2^n complexity) and birthday attacks ($2^{n/2}$ complexity); (f) Entropy visualization of SHA-256 digests for similar input messages; (g) Per-bit flip frequency analysis demonstrating uniform avalanche propagation across all 256 output bits; (h) Required hash evaluations to achieve 50% collision probability as a function of hash length; (i) Fixed-length output property showing constant 256-bit digests regardless of input message size.

Table 2: Avalanche Effect Analysis for SHA-256

Metric	Value	Ideal Value
Mean Hamming distance	128.0 bits	128 bits
Std. deviation	6.2 bits	—
Mean bit flip percentage	50.00%	50.00%
Min bit flip percentage	46.88%	—
Max bit flip percentage	55.08%	—

4.3 Birthday Attack Security Analysis

For hash functions with varying output lengths, we calculate the number of hash evaluations required to achieve a 50% collision probability under birthday attack conditions. These values demonstrate why 256-bit hashes provide adequate security margins against current and foreseeable computational capabilities.

Table 3: Birthday Attack Work Factors

Hash Length (bits)	$2^{n/2}$ Bound	Evaluations for 50% Collision	Security Assessment
64	32	2^{32}	Broken
128	64	2^{64}	Weak
160	80	2^{80}	Marginal
256	128	2^{128}	Strong
512	256	2^{256}	Very Strong

5 Discussion

5.1 Security Properties

Example 5.1 (Preimage Attack Resistance) *Given the hash digest `243263afe491d9d7...`, finding an input message that produces this digest requires an expected $2^{256} \approx 10^{77}$ hash evaluations—vastly exceeding the computational capacity of all computers on Earth combined.*

Example 5.2 (Collision Resistance) *Finding two distinct messages with identical SHA-256 hashes requires approximately $2^{128} \approx 3.4 \times 10^{38}$ hash evaluations under birthday attack conditions. At 1 billion hashes per second, this would take 10^{22} years, far exceeding the age of the universe.*

5.2 Applications in Modern Cryptography

Digital Signatures: Hash functions enable efficient signing of arbitrary-length messages. Instead of signing the entire document, cryptographic signature schemes sign the fixed-length hash digest, providing integrity verification and non-repudiation.

Blockchain and Merkle Trees: Bitcoin and other cryptocurrencies use SHA-256 extensively. Each block header contains the hash of the previous block, creating an immutable chain. Merkle trees allow efficient verification of transaction inclusion using logarithmic-space hash proofs.

Password Hashing: Secure password storage uses specialized hash functions (e.g., bcrypt, scrypt, Argon2) derived from cryptographic hash primitives. These functions incorporate salt values and computational cost parameters to resist rainbow table and brute-force attacks.

Message Authentication Codes: HMAC (Hash-based Message Authentication Code) combines a secret key with a hash function to provide both authenticity and integrity verification. HMAC-SHA256 is widely deployed in TLS, IPsec, and API authentication.

5.3 Avalanche Effect Implications

Our experimental results show SHA-256 achieves a mean bit flip percentage of 50.00%, closely approximating the ideal 50% threshold. This strong avalanche property ensures that even minor input changes—typos in passwords, single-bit transmission errors, or malicious document modifications—produce completely different hash values, enabling reliable integrity verification.

The per-bit analysis (Figure 1g) reveals uniform flip frequencies across all 256 output bit positions, confirming that avalanche propagation does not exhibit positional bias. This uniformity prevents attackers from exploiting predictable bit patterns or correlations between input and output.

6 Conclusions

This computational analysis demonstrates the fundamental security properties of cryptographic hash functions using SHA-256 as the primary exemplar:

1. SHA-256 produces 256-bit hexadecimal digests such as 243263afe491d9d7... for the input message "Cryptographic hash functions e..."
2. Changing a single character from "hash" to "Hash" results in 120 bit flips (46.9% of output), confirming strong avalanche effect
3. Birthday attack analysis shows $2^{128} \approx 3.4 \times 10^{38}$ hash evaluations required for 50% collision probability, providing robust security

4. Preimage attack resistance requires 2^{256} work, computationally infeasible with current or foreseeable technology
5. Avalanche effect analysis across 9 single-bit perturbations yields mean bit flip percentage of 50.00%, closely matching the ideal 50%
6. Per-bit flip frequency analysis shows uniform distribution across all 256 output bit positions, with no positional bias

These properties establish SHA-256 as suitable for digital signatures, blockchain applications, and integrity verification in modern cryptographic protocols. The 2^{128} birthday bound provides adequate security margin against collision attacks, while the avalanche effect ensures that similar messages cannot be distinguished through hash analysis.

References

1. National Institute of Standards and Technology (NIST). *Secure Hash Standard (SHS)*, FIPS PUB 180-4, 2015.
2. Ferguson, N., Schneier, B., and Kohno, T. *Cryptography Engineering: Design Principles and Practical Applications*, Wiley, 2010.
3. Menezes, A., van Oorschot, P., and Vanstone, S. *Handbook of Applied Cryptography*, CRC Press, 1996.
4. Katz, J. and Lindell, Y. *Introduction to Modern Cryptography*, 2nd ed., Chapman & Hall/CRC, 2014.
5. Bellare, M. and Rogaway, P. "Collision-Resistant Hashing: Towards Making UOWHFs Practical", *CRYPTO 1997*.
6. Preneel, B. "Cryptographic Hash Functions", *European Transactions on Telecommunications*, 5(4):431-448, 1994.
7. Damgård, I. "A Design Principle for Hash Functions", *CRYPTO 1989*, pp. 416-427.
8. Merkle, R. "One Way Hash Functions and DES", *CRYPTO 1989*, pp. 428-446.
9. Stevens, M. et al. "The First Collision for Full SHA-1", *CRYPTO 2017*, pp. 570-596.
10. Wang, X. and Yu, H. "How to Break MD5 and Other Hash Functions", *EUROCRYPT 2005*.

11. Narayanan, A. et al. *Bitcoin and Cryptocurrency Technologies*, Princeton University Press, 2016.
12. Boneh, D. and Shoup, V. *A Graduate Course in Applied Cryptography*, version 0.5, 2020.
13. Rogaway, P. and Shrimpton, T. "Cryptographic Hash-Function Basics", *FSE 2004*.
14. Aumasson, J.-P. *Serious Cryptography: A Practical Introduction to Modern Encryption*, No Starch Press, 2017.
15. Stinson, D. and Paterson, M. *Cryptography: Theory and Practice*, 4th ed., CRC Press, 2018.