

Package ‘okalaR’

June 5, 2025

Type Package

Title API wrapper around the okala dashboard interface

Version 1.1.4

Description Allows basic reading and writing of data to and from your project on the okala dashboard

License Apache License 2.0

Encoding UTF-8

RoxygenNote 7.3.2

Imports httr2, jsonlite, jsonify, leaflet, geojsonsf, tibble, dplyr,
sf, scales

NeedsCompilation no

Author Adam Varley [aut, cre]

Maintainer Adam Varley <adam@okala.io>

R topics documented:

add_IUCN_labels	2
add_project_labels	2
auth_headers	3
auth_headers_dev	4
getIUCNLabels	4
get_key	5
get_media_assets	6
get_project	6
get_project_labels	7
get_station_info	8
okalaR	8
plot_stations	9
push_new_labels	9
push_new_timestamps	10
Index	11

add_IUCN_labels	<i>Add labels from the wider IUCN database (all species)</i>
-----------------	--

Description

Add labels from the wider IUCN database in chunks.

Usage

```
add_IUCN_labels(hdr, labels, chunksize)
```

Arguments

hdr	A base URL provided and valid API key returned by the function auth_headers
labels	A data frame of labels to add
chunksize	An integer specifying the chunk size for the submission

Value

A success message as a list

Author(s)

Adam Varley

Examples

```
## Not run:
  add_IUCN_labels(headers, labels=my_labels, chunksize=200)

## End(Not run)
```

add_project_labels	<i>Add project labels for either bioacoustics or camera</i>
--------------------	---

Description

Add labels so labellers have access to them in the Dashboard. Labels are derived by using either suggested labels on the platform or by manually adding labels from the wider database.

Usage

```
add_project_labels(hdr, labeltype = c("Bioacoustic", "Camera"), labels)
```

Arguments

hdr	A base URL provided and valid API key returned by the function auth_headers
labeltype	A character vector specifying the label type ('Bioacoustic' or 'Camera')
labels	A label object list specifying the labels to be added

Value

A success message as a list

Author(s)

Adam Varley

Examples

```
## Not run:  
  add_project_labels(headers, labeltype='Camera', labels=my_labels)  
  
## End(Not run)
```

auth_headers	<i>Initiate root URL with API key</i>
--------------	---------------------------------------

Description

Creates a base URL object that can be used as a root to call endpoints. This requires a project API key, which can be obtained directly from the Okala dashboard.

Usage

```
auth_headers(api_key, okala_url = "https://api.dashboard.okala.io/api/")
```

Arguments

api_key	A valid API key
okala_url	The base URL for the Okala API (default: production)

Value

A list containing the root URL and the API key

Author(s)

Adam Varley

Examples

```
## Not run:  
  headers <- auth_headers("your_api_key")  
  
## End(Not run)
```

auth_headers_dev	<i>Initiate root URL with API key (Development)</i>
------------------	---

Description

Creates a base URL object for the development Okala API. Requires a project API key.

Usage

```
auth_headers_dev(
  api_key,
  okala_url = "https://dev.api.dashboard.okala.io/api/"
)
```

Arguments

api_key	A valid API key
okala_url	The base URL for the Okala dev API (default: dev)

Value

A list containing the root URL and the API key

Author(s)

Adam Varley

Examples

```
## Not run:
headers <- auth_headers_dev("your_api_key")

## End(Not run)
```

getIUCNLabels	<i>Get labels from the wider IUCN database (all species)</i>
---------------	--

Description

Retrieve labels from the wider IUCN database, optionally filtered by a search term.

Usage

```
getIUCNLabels(hdr, offset, limit, search_term = NULL)
```

Arguments

hdr	A base URL provided and valid API key returned by the function auth_headers
offset	An integer specifying the offset for the query
limit	An integer specifying the limit for the query
search_term	A character vector specifying the search term to be used (optional)

Value

A list containing tabular data and pagination information for iterative calls

Author(s)

Adam Varley

Examples

```
## Not run:
  getIUCNLabels(headers, offset=0, limit=100, search_term="horse")

## End(Not run)
```

get_key

Get API key from environment variable

Description

Retrieves the API key from the environment variable OKALA_API_KEY. If the variable is not set, an error is raised.

Usage

```
get_key()
```

Value

The API key as a character string

Author(s)

Adam Varley

Examples

```
## Not run:
  api_key <- get_key()

## End(Not run)
```

get_media_assets	<i>Retrieve media assets for a given project system record ID</i>
------------------	---

Description

Get all of the station data associated with your project. For data types c("video","audio","image")

Usage

```
get_media_assets(hdr, datatype = c("video", "audio", "image", "eDNA"), psrID)
```

Arguments

hdr	A base URL provided and valid API key returned by the function auth_headers
datatype	A character vector of data types c("video","audio","image","eDNA")
psrID	Unique project system ID for which the media assets will be retrieved

Value

A tibble of media assets for the specified project system record

Author(s)

Adam Varley

Examples

```
## Not run:
  assets <- get_media_assets(headers, datatype="video", psrID=123)

## End(Not run)
```

get_project	<i>Get Project Information</i>
-------------	--------------------------------

Description

Retrieves information about the active project associated with the provided API key and sets it as the active project.

Usage

```
get_project(hdr = headers)
```

Arguments

hdr	A list containing the root URL and API key, as returned by auth_headers .
-----	---

Value

No return value. Displays a message indicating the active project name.

Author(s)

Adam Varley

Examples

```
## Not run:  
  headers <- auth_headers("your_api_key")  
  get_project(headers)  
  
## End(Not run)
```

get_project_labels	<i>Get project labels for either bioacoustics or camera</i>
--------------------	---

Description

Labels are derived by using either suggested labels on the platform or by manually adding labels from the wider database.

Usage

```
get_project_labels(hdr, labeltype = c("Bioacoustic", "Camera"))
```

Arguments

hdr	A base URL provided and valid API key returned by the function auth_headers
labeltype	A character vector specifying the label type ('Bioacoustic' or 'Camera')

Value

A tibble containing project labels

Author(s)

Adam Varley

Examples

```
## Not run:  
  labels <- get_project_labels(headers, labeltype='Camera')  
  
## End(Not run)
```

get_station_info	<i>Get project station metadata</i>
------------------	-------------------------------------

Description

Retrieve all of the station data associated with your project, including video, audio, image, and eDNA data types.

Usage

```
get_station_info(hdr, datatype = c("video", "audio", "image", "eDNA"))
```

Arguments

hdr	A base URL provided and valid API key returned by the function auth_headers
datatype	A character vector of data types c("video","audio","image","eDNA")

Value

An sf object containing station metadata and geometry

Author(s)

Adam Varley

Examples

```
## Not run:
stations <- get_station_info(headers, datatype="video")

## End(Not run)
```

okalaR	<i>okalaR: API wrapper for the Okala dashboard</i>
--------	--

Description

Provides functions to interact with the Okala dashboard API, including project, station, media, and label management.

Author(s)

Maintainer: Adam Varley <adam@okala.io>

plot_stations	<i>Plot stations on a leaflet map</i>
---------------	---------------------------------------

Description

Plots station locations using leaflet, with circle markers sized by record count.

Usage

```
plot_stations(geojson_response)
```

Arguments

geojson_response
An sf object containing station metadata and geometry

Value

A leaflet map widget

Author(s)

Adam Varley

Examples

```
## Not run:  
plot_stations(stations)  
  
## End(Not run)
```

push_new_labels	<i>Push new labels using a chunked process</i>
-----------------	--

Description

Push new labels to the platform in chunks.

Usage

```
push_new_labels(hdr, submission_records, chunksize)
```

Arguments

hdr A base URL provided and valid API key returned by the function [auth_headers](#)
submission_records A tibble containing the records to be submitted
chunksize An integer specifying the chunk size for the submission

Value

A list containing tabular data and pagination information for iterative calls

Author(s)

Adam Varley

Examples

```
## Not run:
  push_new_labels(headers, submission_records, chunksize=30)

## End(Not run)
```

push_new_timestamps	<i>Push new timestamps to the platform in chunks</i>
---------------------	--

Description

Push new timestamps to the platform in chunks.

Usage

```
push_new_timestamps(hdr, media_metadata, chunksize)
```

Arguments

hdr	A base URL provided and valid API key returned by the function auth_headers
media_metadata	A tibble containing the media metadata to be submitted
chunksize	An integer specifying the chunk size for the submission

Value

A success message as a list

Author(s)

Adam Varley

Examples

```
## Not run:
  push_new_timestamps(headers, media_metadata, chunksize=100)

## End(Not run)
```

Index

`add_IUCN_labels`, [2](#)
`add_project_labels`, [2](#)
`auth_headers`, [2](#), [3](#), [5–10](#)
`auth_headers_dev`, [4](#)

`get_key`, [5](#)
`get_media_assets`, [6](#)
`get_project`, [6](#)
`get_project_labels`, [7](#)
`get_station_info`, [8](#)
`getIUCNLabels`, [4](#)

`okalaR`, [8](#)
`okalaR-package (okalaR)`, [8](#)

`plot_stations`, [9](#)
`push_new_labels`, [9](#)
`push_new_timestamps`, [10](#)