Tables

Table I. Mentions and direct named qualification expressions

Task and technology	Ads B	Mention M	General G	R	Direct Q/N	U	Q/mentions %
Robot learning: Python	105	73	40	2	42/88	17	57.5
Robot learning: PyTorch	105	83	20	3	23/97	8	27.7
Robot runtime: C++	87	80	38	0	38/64	23	47.5
Robot runtime: Linux	87	52	47	0	47/86	1	90.4
Board circuitry: Altium	56	24	5	0	5/56	0	20.8
Board circuitry: EMC/SI/PI	56	36	15	0	15/56	0	41.7

Notes: Robot learning denotes robot learning and model development. M is any mention; G and R are unconditional general and required qualification positives. Q is their advertisement-level union. N excludes unresolved states; B includes them. No G/R positive overlaps occur in these six cells. R adds five pairs in four advertisements. The final column conditions on M. B, M, G, R and U are counts on the task base; Q/N reports positives over evaluable cases and excludes U. The EMC/SI/PI family includes electromagnetic compatibility, signal integrity and power integrity. Technologies within a task share advertisements and must not be treated as independent samples. Source: calculations from the captured job-advertisement corpus.

Table II. Coverage and state matches in the source-reading diagnostic

Task and technology	Pairs	G matches	R matches	Q matches	Q differs	Example clarifications
Robot learning: Python	20	16	19	17	3	0
Robot learning: PyTorch	20	15	20	15	5	3
Robot runtime: C++	20	17	19	17	3	0
Robot runtime: Linux	15	13	15	13	2	0
Board circuitry: Altium	15	14	12	14	1	0
Board circuitry: EMC/SI/PI	15	13	15	13	2	0

Notes: The 105 pairs cover 94 distinct advertisements. Matches compare the frozen original state with the fresh reader output, before adjudication. Sampling used prior-state strata and is not a probability sample for estimating coding accuracy. Prior row labels were withheld, but high-level project history was visible. The reader was a model; these counts are neither human intercoder reliability nor validation against a gold standard. Three explicit examples are U-to-Z clarifications; ten Q differences remain contestable and three reflect unsupported fresh scope readings. Source: calculations from the captured job-advertisement corpus.

Table III. Eligible firm comparisons
Panel A Minimum common denominator of 10

Task and technology	Eligible firms	Pairs	M to Q reversals	G to Q reversals	Disjoint Q bounds
Robot learning: Python	2	1	0	0	1
Robot learning: PyTorch	2	1	1	0	0
Robot runtime: C++	1	0	0	0	0
Robot runtime: Linux	2	1	0	0	1
Board circuitry: Altium	1	0	0	0	0
Board circuitry: EMC/SI/PI	1	0	0	0	0

Notes: Each firm must meet the stated minimum separately for M, G and Q. All eligible unordered pairs are retained; zero pairs means fewer than two eligible firms. Pair outcomes are dependent because they share firms and advertisements. At ten, all three pairs compare Galbot and XSquare. At five, 32 pairs include those three comparisons; the panels are not separate replications. Bounds assign all recorded unknowns to each endpoint and are not confidence intervals. Source: calculations from the captured job-advertisement corpus.

Table III. Eligible firm comparisons
Panel B Minimum common denominator of 5

Task and technology	Eligible firms	Pairs	M to Q reversals	G to Q reversals	Disjoint Q bounds
Robot learning: Python	4	6	3	0	5
Robot learning: PyTorch	4	6	2	0	4
Robot runtime: C++	3	3	2	0	1
Robot runtime: Linux	6	15	1	0	15
Board circuitry: Altium	2	1	0	0	1
Board circuitry: EMC/SI/PI	2	1	0	0	1

Notes: Each firm must meet the stated minimum separately for M, G and Q. All eligible unordered pairs are retained; zero pairs means fewer than two eligible firms. Pair outcomes are dependent because they share firms and advertisements. At ten, all three pairs compare Galbot and XSquare. At five, 32 pairs include those three comparisons; the panels are not separate replications. Bounds assign all recorded unknowns to each endpoint and are not confidence intervals. Source: calculations from the captured job-advertisement corpus.