

# MVP Product Flow & Architecture Brief

Version 1.0 · Draft for architect review · Confidential

**Version:** 1.0 (draft for architect review) **Audience:** System architect / founding engineer **Launch vehicle:** Brand Laureate award & conference event, Kuala Lumpur, followed by co-working space partnerships in the same city.

## 1. What the product is

Ol-ga is a real-time professional availability and intent-matching layer. A user declares (a) that they are open to meeting right now, and (b) what they are trying to achieve. Ol-ga surfaces a small number of nearby, also-available professionals whose declared intent complements theirs, and tells the user *why* each person appeared.

It is explicitly **not** a profile directory, not a CRM, and not a cold-outreach tool.

Three design principles govern every decision below:

1. **Nothing is visible unless the user has switched it on.** Presence is opt-in, scoped, and expires by itself.
2. **Every match carries a human-readable reason.** If the system cannot explain a match in one sentence, it does not show the match.
3. **The loop must close.** Every connection ends with a one-tap outcome capture. This is the only source of proprietary data the product will ever have.

## 2. Core concepts

| Concept    | Definition                                                                                                                                                                                                        |
|------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| User       | A verified individual professional.                                                                                                                                                                               |
| Context    | A bounded space-time container in which people can be visible to each other: an EVENT, a VENUE (co-working space, cafe), or an ORG (corporate campus / multi-office employer). Visibility never crosses contexts. |
| Intent     | A short, expiring declaration of what a user is currently seeking. The primary matching input.                                                                                                                    |
| Presence   | A time-boxed "I am live in this context" state. Ephemeral.                                                                                                                                                        |
| Match      | A system-generated candidate pairing within a context, with a score and a reason.                                                                                                                                 |
| Connection | A mutually accepted request between two users. Unlocks messaging.                                                                                                                                                 |
| Meeting    | A confirmed real-world interaction with an outcome rating.                                                                                                                                                        |
| Ledger     | The user's private record of who they met, what those people wanted, and what is outstanding. Works at zero network density.                                                                                      |

## 3. Data model (indicative)

```

User
  id, phone_e164 (verified), display_name, headline, photo_url,
  voice_intro_url (nullable, post-v1 capture), created_at,
  status (ACTIVE | SUSPENDED | DELETED)

Context
  id, type (EVENT | VENUE | ORG), name, partner_id,
  geofence (polygon or centre+radius), starts_at, ends_at (nullable for VENUE/ORG),
  join_method (CODE | QR | GEO | INVITE), status

ContextMembership
  id, user_id, context_id, joined_at, role (ATTENDEE | SPEAKER | STAFF | SEED)

Intent
  id, user_id, context_id (nullable = general),
  category (enum), free_text (<=140 chars),
  created_at, expires_at, status (ACTIVE | EXPIRED | FULFILLED | WITHDRAWN)

Presence
  id, user_id, context_id, went_live_at, expires_at,
  visibility (CONTEXT_ONLY | CONTEXT_PLUS_CONNECTIONS)
  -- NO coordinate history is persisted. See §7.

Match
  id, context_id, user_a_id, user_b_id, score,
  reason_code[], reason_text, generated_at, shown_at (nullable)

ConnectionRequest
  id, from_user_id, to_user_id, match_id (nullable), note (<=200 chars),
  status (PENDING | ACCEPTED | DECLINED | EXPIRED),
  created_at, responded_at, expires_at

Conversation / Message
  conversation_id, connection_id, sender_id, body, sent_at, delivered_at

Meeting
  id, connection_id, context_id,
  happened (bool, per-user), usefulness (1..3, per-user),
  captured_at

FollowUp
  id, owner_user_id, about_user_id, text, due_at,
  status (OPEN | DONE | DISMISSED)

SafetyEvent
  id, reporter_id, subject_id, context_id, type (BLOCK | REPORT),
  reason_code, notes, created_at, resolution

```

**Ledger** is a derived read-model, not a table — assembled from Connection, Meeting, Intent snapshots, and FollowUp. Intent must be **snapshotted onto the Connection at acceptance time**, because the live Intent record expires and the ledger needs to show what the person wanted *when you met them*.

## 4. Screen flow

### Onboarding (target: under 60 seconds)

1. **Join** — phone number + OTP. Primary and only required auth path.
2. **Profile** — display name, headline (role @ company), photo. Three fields. Nothing else is mandatory.
3. **Declare intent** — category pick-list plus one free-text line. Default expiry: end of current context, or 7 days for a general intent.
4. **Context join** — via event code, QR, or geofence detection.

Onboarding may be completed **asynchronously and in advance** (from a ticket confirmation email), and this is the expected primary path for the Brand Laureate launch. Steps 1–3 must be completable outside the venue, with step 4 occurring on arrival.

### Core loop

5. **Home** — the ledger by default, with a prominent Go Live control. Home is *not* a social feed.
6. **Go Live** — one tap. Sets Presence with an auto-expiry (default 2 hours, user-adjustable).
7. **Live view** — a ranked list of 3–7 matches, each showing name, headline, and the reason sentence. Never an unfiltered roster.
8. **Profile detail** — full profile plus their declared intent, and a Request button with an optional short note.
9. **Requests** — inbox of incoming requests; accept or decline.
10. **Conversation** — text messaging, unlocked only on mutual acceptance.
11. **Outcome capture** — triggered at context end or 12 hours after acceptance. Two taps: did you meet, was it useful.
12. **Ledger** — people met, their intent snapshot, outcomes, open follow-ups, and cooling-relationship nudges.
13. **Events nearby** — upcoming events in the user's city, each showing an **intent-density preview**: "20 of 100 registered attendees share your intent." This is a priority feature, not a nice-to-have.
14. **Settings** — visibility, notifications, block list, data export, account deletion.

## 5. State machines

### Intent

|                                                        |
|--------------------------------------------------------|
| DRAFT -> ACTIVE -> { EXPIRED   FULFILLED   WITHDRAWN } |
|--------------------------------------------------------|

- ACTIVE intents are the only ones eligible for matching.
- Expiry is mandatory. There is no permanent intent.
- On expiry, prompt the user to renew or replace. Do not silently auto-renew.

### Presence

|                            |
|----------------------------|
| OFFLINE -> LIVE -> OFFLINE |
|----------------------------|

- LIVE always carries an `expires_at`. Auto-expiry is non-negotiable.
- Leaving the geofence ends LIVE for a VENUE/EVENT context.
- A user must be LIVE **and** hold an ACTIVE intent to appear to anyone.

### Connection

|                                                                                 |
|---------------------------------------------------------------------------------|
| PENDING -> { ACCEPTED -> MET_UNKNOWN -> { MET   NOT_MET } , DECLINED, EXPIRED } |
|---------------------------------------------------------------------------------|

- PENDING requests expire at context end, or after 24 hours for a general context.
- Messaging is gated on ACCEPTED.
- Declines are silent to the sender (shown as expired), to avoid status damage.

## 6. Matching (v1)

**Build this rule-based. Do not build a learned model for v1.** There is no training data yet, and outcome capture is what will generate it.

Candidate set: users in the same context, currently LIVE, with an ACTIVE intent, not blocked, not already connected.

Score components (indicative weights, tunable via config, not code):

| Signal                                                                                                         | Weight |
|----------------------------------------------------------------------------------------------------------------|--------|
| Intent complementarity (category pair from a curated matrix, e.g. SEEKING_DISTRIBUTOR ↔ OFFERING_DISTRIBUTION) | 0.40   |
| Free-text semantic similarity (embedding cosine)                                                               | 0.25   |
| Industry / function adjacency                                                                                  | 0.15   |
| Seniority compatibility (avoid large mismatches in both directions)                                            | 0.10   |
| Freshness of presence                                                                                          | 0.10   |

**Hard requirement:** every surfaced match must produce a `reason_text` assembled from `reason_code[]`. If no reason can be generated, suppress the match. Show a smaller list rather than an unexplained one.

**Volume cap:** maximum 7 matches shown per live session. Scarcity is a feature — it drives action and avoids the paradox of choice at an event.

**Manual override:** staff must be able to inject a curated match during a live event (see §9). Model this as a `Match` row with `source = MANUAL` and a staff-authored reason.

## 7. Privacy & compliance — non-negotiable

Governing regimes: Malaysia PDPA 2010, and India DPDP Act 2023 if the India market proceeds.

- Never persist coordinate history.** Geolocation is used transiently to resolve context membership and is discarded. Store `ContextMembership` and `Presence`, not a location trail. This must be true in the schema, not just in policy — it is a marketing claim and a legal position.
- Visibility is context-scoped by default.** A user visible at a co-working space is not visible to the general public or to other contexts.
- Double opt-in before any identity is exchanged beyond name, headline, photo.** Full profile and contact details unlock only on ACCEPTED.
- Block and report available from every profile surface**, including inside conversations. Shipped in v1.
- Public-venue default.** Meeting suggestions default to the shared public context. Do not build features that route users to private addresses in v1.
- Data export and hard account deletion** in v1 settings.

## 8. Non-functional requirements

**Event-grade offline resilience is the highest technical risk in this build.** Several hundred users on a single hotel access point behind a

captive portal is the most common failure mode for event apps.

- Cache the context roster and candidate set locally on context join.
- Run matching client-side against the cached set when the network is unavailable.
- Queue connection requests, acceptances, and outcome captures locally; sync on reconnect with idempotent server-side handling.
- Degrade visibly but gracefully — show a clear offline state, never a spinner or an empty list.

Other: - Mobile-first. Native or cross-platform native (React Native / Flutter) — a web app will not deliver acceptable geofence, push, or offline behaviour. - Push notifications required for request received, request accepted, and outcome prompt. - Target: live view renders in under 2 seconds on a mid-range Android device over 3G. - Feature flags on matching weights, match count cap, and expiry durations — these will be tuned live during the launch event.

## 9. Launch-specific requirements (Brand Laureate)

- **Pre-event onboarding link** embedded in ticket confirmation and reminder emails, deep-linking to steps 1–3.
- **Seeded profiles:** speakers, judges, sponsors and organising committee onboarded in advance with real intents and consent, so the first user to open the app never sees an empty list. Model as `ContextMembership.role = SEED`.
- **Staff console** (can be internal/admin-only, minimal UI): view live users, inject manual matches, monitor sign-up and activation counters in real time.
- **Event-end outcome push** timed to the close of the programme.
- **Live ops dashboard** for the funnel metrics in §11.

## 10. Explicitly out of scope for v1

Deferred deliberately. Do not build these:

- CRM / sales-funnel integrations (Salesforce, HubSpot). Ship CSV export instead.
- Voice intro capture during onboarding. Capture is deferred to post-first-connection in a later release.
- Any public "social capital" score, points, streaks, badges, or leaderboards. The audience is senior professionals; gamification damages positioning.
- File exchange, video calling, calendar integration.
- LinkedIn or X authentication. LinkedIn's API is restrictive and its terms are unstable for adjacent products; phone OTP is the only v1 auth path. Optional LinkedIn *enrichment* may be evaluated later.
- Group or multi-party matching.
- Cross-context / city-wide public discovery.

## 11. Success metrics

Instrument from day one. Targets are for a captive, organiser-endorsed event audience.

| Metric                               | Target      |
|--------------------------------------|-------------|
| Sign-up rate (of attendees)          | 30–40%      |
| Intent declared (of sign-ups)        | 70%+        |
| Went live during event (of sign-ups) | 60%+        |
| Request acceptance rate              | 50%+        |
| Meetings confirmed (of accepted)     | 30%+        |
| <b>Day-7 return rate</b>             | <b>25%+</b> |

The first five measure whether the *event* worked. **Day-7 return measures whether the product works** and is the single number that decides whether to scale co-working partnerships or return to design.

## 12. Open decisions for the architect

1. **Launch market** — Malaysia (Brand Laureate points to KL) versus the earlier India-first framing. This affects compliance regime, phone verification provider, and venue partnership strategy. Recommend a single market, saturated.
2. **Ledger in v1** — recommended yes. It is the only surface with value at zero network density and is the primary defence against day-7 churn.
3. **Native versus cross-platform** — trade-off between geofence/background-presence fidelity and build speed.
4. **Embedding provider** for free-text intent similarity, and whether it must run offline for the event scenario.
5. **Context join method priority** — QR versus geofence for the launch event.

### 13. Suggested build sequence

---

1. Auth, profile, intent, context join — the onboarding path, completable asynchronously.
2. Presence, matching engine with reason generation, live view, request/accept, messaging.
3. Offline cache and sync queue. **Harden before the event, not after.**
4. Outcome capture and ledger.
5. Staff console and seeded profiles.
6. Events-nearby with intent-density preview.

Steps 1-5 constitute the minimum shippable set for the launch event. Step 6 is the highest-value addition immediately after.