

Labs

Instructions:

1. Login to killercoda using your gmail account.
2. Choose kubernetes playground.

<https://killercoda.com/playgrounds/scenario/kubernetes>

Chapter 5:

1. Create a **named volume “mysql_data”** and list all volumes to make sure that the volume is created.
2. Create a container named **“my_sql”** in the background using the **mysql:8.0** image. Set the root credentials by passing the environment variable **-e MYSQL_ROOT_PASSWORD=root123**, and use the volume **mysql_data** to persist MySQL data mount for **/var/lib/mysql** inside the container.
3. Go inside the container then connect to the database using **mysql -u root -p** and create a sample table using this command **CREATE DATABASE school**; and make sure the table is created using **SHOW DATABASES**;
4. Delete the container.
5. Create another container same as no.2 named **“my_sql2”**.
6. Go inside the container then connect to the database using **mysql -u root -p** and check if DB school is already exist using **SHOW DATABASES**;
7. Delete my_sql2 container and delete **mysql_data** volume.
9. Create a new directory on your local machine named **“my_data”**. Then Create a file named **“index.html”** and write inside the file **“Hello \$YourName”**.
10. Create a new container with the following parameters:
 - Name: httpd-container
 - Image: registry.access.redhat.com/ubi8/httpd-24:latest
 - Ports: Route traffic from port 8082 on your machine to port 8080 inside of the container
 - Run container in detached mode
 - Mounts an existing host folder **“mydata”** into the container **“/var/www/html”**
11. Go inside the container then list all the files **/var/www/html**
12. verify that you see the message exist in index.html