

Tenants Table — Field Reference

The `tenants` table is the root of multi-tenancy in the platform. **One row = one organization (a customer company)**. Almost every other table carries a `tenantId` pointing back here, which is how data is kept isolated between companies.

This document explains every field defined on the `Tenant` model in `apps/api/prisma/schema.prisma`.

Important distinction: Only the **scalar columns** below physically exist as columns in the `tenants` table. The **relations** listed further down are *not* columns here — they are links Prisma exposes for convenience, but the actual foreign keys live on the other tables (each child row stores a `tenantId`).

Actual columns in the `tenants` table

Column	Type	Required	Default	What it means
<code>id</code>	String (CUID)	Yes	auto-generated	Primary key. A unique, collision-resistant ID created automatically when the organization is onboarded. Used everywhere as <code>tenantId</code> .
<code>name</code>	String	Yes	—	The organization's display name (e.g. "Acme Contact Centre"). Shown in the platform console and used as the default branding name.
<code>slug</code>	String	Yes (unique)	—	A URL-safe short identifier derived from the name (e.g. <code>acme-contact-centre</code>). Must be unique across all tenants. Used for per-tenant branding lookups on the login page and tenant-specific URLs.
<code>active</code>	Boolean	Yes	<code>true</code>	Master on/off switch for the organization. When <code>false</code> , the tenant is treated as disabled. Kept in sync with <code>status</code> (suspending sets this to <code>false</code>).
<code>status</code>	String	Yes	<code>"active"</code>	Lifecycle state of the account. Expected values: <code>trial</code> (evaluating), <code>active</code> (live, paying), <code>suspended</code> (disabled, e.g. for non-payment). Drives access and billing behaviour.
<code>planId</code>	String (nullable)	No	<code>null</code>	Foreign key to the <code>plans</code> table — which subscription plan this organization is on. <code>null</code> means no plan assigned yet. If the plan is deleted, this is set back to <code>null</code> (SetNull).
<code>limits</code>	JSON (nullable)	No	<code>null</code>	Per-tenant overrides of the plan's limits. Shape: <code>{ maxExtensions, maxConcurrentCalls, maxCampaigns }</code> . When set, these take precedence over the plan's defaults — used to give a specific customer a custom cap. <code>null</code> means "use the plan's limits".
<code>branding</code>	JSON (nullable)	No	<code>null</code>	White-label appearance for this organization. Shape: <code>{ name, logoUrl, color }</code> . Used to theme the login page and UI per tenant. Defaults to <code>{ name }</code> at onboarding.
<code>createdAt</code>	DateTime	Yes	<code>now()</code>	Timestamp the organization was created. Set automatically.
<code>updatedAt</code>	DateTime	Yes	<code>auto</code>	Timestamp of the last change to this row. Updated automatically on every write.

Relations (not columns on this table)

These appear on the `Tenant` model so you can navigate from a tenant to its related records, but the foreign key (`tenantId`) is stored on the **child** table, not here. They are listed for completeness.

Relation	Points to	Meaning
plan	plans	The plan referenced by <code>planId</code> (the one real outbound FK).
subscriptions	subscriptions	Billing subscription history for this org.
invoices	invoices	Invoices generated for this org.
managerRoles	manager_roles	Named RBAC permission sets (roles) defined for this org.
managers	managers	Back-office / admin users of this org.
userRoles	user_roles	Roles assignable to agent-level users.
userGroups	user_groups	Groupings of users.
users	users	Agent-level user accounts.
outgoingRules	outgoing_rules	Outbound call routing rules.
dataRecords	data_records	Generic per-tenant data records.
auditLogs	audit_logs	Audit trail of actions in this org.
extensions	extensions	SIP/phone extensions provisioned for this org.
trunks	trunks	SIP trunks (carrier connections).
ringGroups	ring_groups	Groups of extensions that ring together.
inboundRoutes	inbound_routes	Rules mapping incoming numbers (DIDs) to destinations.
ivr	ivr	Interactive voice menus.
queues	queues	Call-centre queues.
timeConditions	time_conditions	Time-of-day routing conditions.
dispositions	dispositions	Call outcome / wrap-up codes.
dncEntries	dnc	Do-Not-Call list entries.
leadGroups	lead_groups	Groupings of dialer leads.
leads	leads	Outbound dialer leads.
campaigns	outbound_campaigns	Outbound dialing campaigns.
callAttempts	call_attempts	Individual outbound call attempts.
callbacks	callbacks	Scheduled callbacks.
contacts	contacts	CRM contacts.

Relation	Points to	Meaning
<code>conversations</code>	<code>conversations</code>	Omnichannel inbox conversations.
<code>messages</code>	<code>messages</code>	Individual messages within conversations.
<code>cannedResponses</code>	<code>canned_responses</code>	Saved reply templates for the inbox.

How a tenant is created

New organizations are created by a platform super-admin via `POST /platform/tenants` (`onboardTenant` in `billing.service.ts`), which sets `name` , `slug` , `status: "active"` , an optional `planId` , and a default `branding` of `{ name }` . It also creates the first "Administrator" role and the first admin user for the organization.