SCIENTIST-CONTROLLED DOCKING

Ankora

The illustrated user guide

Version 0.1.0 · Windows 11 Beta & Linux x86_64 RC
12 November 2026 edition

A guided docking campaign, from a PDB accession to a citable record.

SERPINE1 / PAI-1 · PDB 7AQF · RV2

Samael Olascoaga · ORCID 0009-0008-5522-7938

MIT licence · github.com/Olascoaga/Ankora

Ankora - User guide

Version 0.1.0 · Windows 11 Beta & Linux x86_64 Release Candidate · Illustrated edition, 2026-11-12

This guide walks one complete docking campaign from a PDB accession to an exported, citable record. It uses **7AQF and RV2 throughout**, real application captures and a preserved ligand-to-export tutorial recorded on 9 October 2026. This edition reopens its exact records in the current interface; no figure is a mock-up and no docking or preparation was rerun to update the visuals. The prepared receptor and CPU/GPU redocking examples are preserved historical records; they were not recomputed just to obtain attractive screenshots.

The case is **SERPINE1 (PAI-1), PDB 7AQF**, redocking its co-crystallized inhibitor **RV2**. It was chosen for a reason that will become clear in §6: both AutoDock backends find the crystallographic pose and then rank the wrong one first. A guided tour that only showed a clean result would teach you nothing about what this tool is for.

> **How to use this edition.** Follow the numbered actions, then use the tables and figures to check your decisions. This edition uses the current desktop interface with an isolated copy of the recorded reference project. A read-only capture layer reopens saved stages; it does not execute the preparation buttons. It is not another clean-machine installer test or a promise of identical results on your computer. Historical examples come from the frozen SERPINE1 evidence matrix. Its CPU run used neutral RV2; its Vina and GPU runs used anionic RV2. They are separate historical examples, not a controlled comparison of engines.

Contents

1. What Ankora is, and what it is not
2. Before you start
3. Structure → Receptor: preparing 7AQF
4. Ligand: preparing RV2
5. Binding site and docking
6. Validation: did the engine find the crystal pose?
7. Results, interactions and figures
8. The Methods section
9. What Ankora will not do for you
10. How to read a docking score
11. If something goes wrong
12. From one ligand to virtual screening

---

1. What Ankora is, and what it is not

Ankora is a local desktop workbench for **Windows 11 x64** (`private_beta`) and **Linux x86_64** (`release_candidate` , Ubuntu 24.04 LTS reference) that runs **AutoDock Vina** `1.2.7` , **AutoDock4** `4.2.6` , **AutoDock-GPU** `1.6` and—on Linux—**GNINA** `1.3.3` through a guided interface, and records what it did precisely enough to write your Methods section afterwards.

It does not implement a new scoring function or a new search algorithm. The numbers come from the engines you already know. What Ankora adds is everything around them: the original file is never modified, each chemical decision is made by you and recorded, every artifact carries a SHA-256, and the campaign can be exported as evidence somebody else can check.

The design rule behind every screen is a single sentence: **nothing is asserted that was not recorded.** When Ankora cannot establish something, it says so rather than filling the gap with a reasonable default.

---

2. Before you start

Supported platforms: Windows 11 x64 (`private_beta`) and **Linux x86_64** (`release_candidate` , Ubuntu 24.04 LTS reference; awaiting final bare-metal physical workstation attestation under Gate `D6`). macOS is out of scope for v0.1. See the Platform & Engine Status matrix for the full capability breakdown.

Required community experience: install Ankora and start the supported workflow. Self-contained offline packaging supplies Python 3.12, preparation tools (`RDKit` , `PDBFixer` / `OpenMM` , `PDB2PQR` / `PROPKA` , `Meeko` , `Dimorphite-DL` , `ProLIF`), `AutoDock Vina 1.2.7` , `AutoGrid4` / `AutoDock4 4.2.6` , `AutoDock-GPU 1.6` , and `P2Rank 2.5.1` with its private Temurin Java 21 runtime. No separate Conda environment, terminal commands or manual path configuration are required. See the complete-installer contract and the Linux modular offline distribution contract.

Distribution status: Windows packaging includes the bundled Core engines, P2Rank, private Java and offline WebView2 (see the Windows installed acceptance record and latest slim candidate record). That Windows slim candidate passed staged-payload checks; its new NSIS installation was not retested because the existing registered installation was deliberately preserved. Linux packaging passes clean-room offline verification on WSL2/WSLg with real CUDA GPU execution (Linux offline package smoke), with physical non-WSL workstation attestation tracked separately in Gate `D6` . Do not conflate source, staged-payload and installed-machine checks; code signing and public release authorization remain distinct gates. The manual captures demonstrate the workflow; installation evidence is recorded separately.

Installing

- **Windows 11 x64 (`private_beta`):** Install `Ankora_0.1.0_x64-setup.exe` (`407.16 MiB` slim offline NSIS installer, paired with `Ankora_0.1.0_x64-sources-companion.zip`). Use only the exact candidate supplied for review, with its matching SHA-256 checksum. This guide does not assert that a signed public download is already available.
- **Linux x86_64 (`release_candidate`):** Install the double-click Debian package `Ankora_0.1.0_amd64.deb` (`272.34 MiB`) on Ubuntu 24.04 LTS derivatives, or extract the zero- `sudo` portable bundle `Ankora_0.1.0_linux_x86_64.tar.zst` (`313.97 MiB` , paired with `Ankora_0.1.0_linux-sources-`

`companion.zip`) and launch `ankora-desktop`. Both carry the complete `10/10` Core scientific payload offline.

- **Linux 1-click offline GNINA CUDA 12.8 pack (optional):** Because `GNINA 1.3.3` and its isolated CUDA 12.8 / cuDNN 9 user-space libraries weigh `2.55 GiB` (`2,610.34 MiB`), they are distributed as a separate hash-locked archive (`Ankora_0.1.0_gnina-cuda12-pack.tar.zst`). Open **Tools → Scientific tool readiness**, click **Import offline GNINA pack…**, and select the `.tar.zst` file: Ankora verifies every SHA-256 digest and installs the toolchain into your per-user data directory with **zero `sudo` and zero terminal commands**, scoping `LD_LIBRARY_PATH` strictly to GNINA child processes (`11/11` tools ready).

> **Candidate security status.** Current private-beta and release-candidate artifacts are unsigned. Operating-system or institutional policy may block unsigned installers. Do not disable security controls to install Ankora; ask the maintainer for a verified hash, signed release or approved testing arrangement.

After installation, open **Tools → Scientific tool readiness** to inspect available tools. Finding `AutoDock-GPU` or `GNINA` on disk does not establish GPU compatibility: GPU execution also requires a supported graphics device and host vendor driver (`OpenCL` on Windows; `NVIDIA` kernel driver for `CUDA 12` on Linux, since user-space packages never install kernel drivers). CPU docking remains the path for machines without suitable GPU hardware; choosing a different engine or compute backend always remains explicit.




Figure 1. Tool discovery in the isolated Windows documentation runtime. The eleven entries include ten supported Core tools and explicitly deferred GNINA (versions belong to this runtime, not automatically to every installed beta). On Linux x86_64, importing the offline GNINA CUDA 12.8 pack transitions GNINA 1.3.3 to ready (11/11). Executable discovery alone does not prove GPU compatibility.

The workbench

The window has three parts: the **workflow** on the left - eight numbered steps in three groups, *Prepare*, *Define & run* and *Review* - the **workspace** in the middle, and the **inspector** on the right. The status bar at the bottom shows machine load, warnings, provenance and background activity.

Preparation and execution steps unlock as their inputs exist. You cannot dock before there is a receptor, a ligand and a box - not as a restriction, but because a docking run without those is not a defined experiment.

Results, Validation and Export can reopen saved project evidence even when no structure is currently loaded. Validation measures a completed individual docking result; it does not start the search itself.

A quick route through your first project

Step	Before continuing
Structure	Confirm the correct entry, model, chains and source
Receptor	Resolve structural decisions and review selected protonation states
Ligand	Preserve the crystal reference separately from the prepared docking state
Binding site	Preview, inspect and explicitly save the final search box
Docking	Confirm the exact receptor, ligand state, site and engine protocol
Validation	Measure a completed individual result against the original reference
Results	Inspect the exact pose, chemical plausibility and interaction evidence
Export	Check written files, Methods gaps, identities and sharing scope

For a virtual screen, start with library filtering and preparation in §12. Do not mistake selecting a table row for selecting a whole library to dock.

On a laptop, use the panel-collapse buttons to give the workspace more room, or drag a panel divider. **View** offers theme and density controls. Long interaction reviews have a workspace scrollbar; wide tables have their own horizontal bar. An off-screen **Save** control is not a disabled capability: scroll the workspace, not the 3D canvas. Figure 2 shows the same shell with a structure loaded.

Projects. Use **File → Project workspace…** to create or switch projects. Inputs, campaigns and exports belong to the selected project. Reopen a saved receptor with **File → Reopen latest receptor**; this loads the accepted derivative without rerunning preparation. The migrated `default` project remains a real project, not disposable demonstration data.

---

3. Structure → Receptor: preparing 7AQF

3.1 Import the structure

Step **1 · Structure**. Choose **Fetch a structure** (RCSB PDB · AlphaFold DB), choose **RCSB PDB**, enter `7AQF` and confirm. The same action is available in **Open structure** and the **File** menu. For a local structure, choose a PDB, CIF or mmCIF file instead. An AlphaFold accession is not a PDB ID and does not provide a co-crystallized experimental ligand.

Ankora downloads the deposited mmCIF, hashes it, and inspects it **without changing a single coordinate**. You should see:

Method	X-RAY DIFFRACTION
Resolution	1.77 Å
Models	1
Atoms	6266
Residues	1218
Missing residues	22
Missing atoms	123

This file is now immutable. Everything from here on is a *derivative* that points back at it by identity and hash.




Figure 2. The original 7AQF structure, with chains A and B, RV2 and waters. Metadata at right describes the whole imported entry, not the selected chain-A receptor. Deposited mmCIF SHA-256: `79fd3b96adca…`.

3.2 Make the receptor

Current workflow - three guided steps. The interface opens in **Guided preparation**. Older installed betas may differ; check the exact build against its release notes. The accepted historical receptor and Figure 3 below remain unchanged; they are not a new-method validation result.

The original 7AQF all-17-repair plan now stops at ARG A:300's incompatible observed coordinates (explained below). These steps describe how to review that case, not a guaranteed one-click successful re-preparation.

1. **Choose system.** For this example, select chain **A**, remove resolved waters and remove **RV2 A:401**. A distance reference such as RV2 is optional: it highlights proximity, not a docking box. No chain, water or component is removed without your choice. Press **Next · review repairs**.

2. **Review repairs.** The grouped actions can mark the **17 incomplete side chains** for repair and keep the **9 absent-residue gaps unmodelled**. They populate the draft only. Review individual rows in the table, especially alternate conformations, unusual residues and anything near the site. No loop coordinates or residue deletions are inferred. Press **Next · hydrogens and preparation** when every issue has a resolved decision.
3. **Prepare.** Select **Prepare for docking**, choose the target pH (**7.4** in this example), and press **Analyze pKa proposals** above the viewer. Review **Needs attention** and use **All proposals** for the complete list; filtering never drops selected states. Confirm **I reviewed the system, repairs and selected protonation states**, then **Apply explicit preparation plan**. Editing the system, repair settings, pH or selected states requires a fresh confirmation; structural/pH edits also invalidate the previous pKa analysis.

For any receptor, **What to keep** is the authoritative component decision: once you explicitly remove a component, its observations are excluded from the repair table and no second residue decision is required. The source remains unchanged. Retained incomplete components are identified separately; Ankora does not offer amino-acid reconstruction for a ligand or metal-containing component. Review its experimental role and use an appropriate preparation workflow when needed; removal is never an automatic workaround. The final plan lists the actual kept/removed components, not just a total. These general checks and their limits are documented in the workflow matrix.

New development plans also compare observed heavy-atom names with templates for the 20 standard amino acids, even when a local file has no missing-atom headers. The report does not infer hydrogens, terminal OXT or whole missing residues, and it does not guarantee completeness of each alternate conformation. Review those choices separately. Reopened historical records keep their original source-reported inspection method; no old preparation is silently upgraded.

New requests explicitly record **Topology-guarded repair**, with fixed observed atoms during reconstruction and connectivity/stereochemistry checks before protonation. The separate optional elastic relaxation is off by default and remains in **Advanced controls**, alongside the repair seed and legacy method. Switching modes preserves your decisions. Reopening an older record preserves its historical method; changing it creates another derivative, not an upgrade of the old evidence. The bounded new-method 7AQF acceptance is documented in the repair validation record. That record also explains a remaining source-coordinate conflict in **ARG A:300**: its observed anchors are too far apart for the missing NE to connect normally. The completed guard rejects the current all-17-repair plan before protonation. Do not treat a preliminary Meeko-generated file as a validated repair, delete the residue without justification, or silently move observed atoms. This case needs a scientific decision about rebuilding the observed side-chain segment under a separately explicit protocol.

Historical tutorial plan. The following settings and image describe the previously accepted receptor used in the recorded docking examples. In particular, its separate elastic relaxation was enabled; that is not a blanket recommendation to enable relaxation for every new receptor.

Step **2 · Receptor**. Complete the explicit preparation plan before applying it. The following describes this example, not a universal preparation recipe.

1. **Chains.** Keep **A** only.
2. **Waters.** Remove them.

3. **Components.** Remove `RV2 A:401` - the co-crystallized inhibitor. We will dock it back in later, so it must not be in the receptor.
4. **Structural issues.** Review each issue. The historical receptor repaired 17 observed residues with missing heavy atoms; absent residues were not modelled. Use the recorded per-residue decisions to reproduce that plan, not a blanket removal of every warning.
5. **Repair and protonation.** For the selected repairs, enable restrained relaxation and protonation at **pH 7.4** with the **AMBER** force field. Resolve blocking issues, analyze the PROPKA proposals, review residue states and confirm the explicit protonation choices before applying. In the current UI, inspect the PROPKA proposals and any ambiguity warnings; a pH value alone is not a review of residue-specific states.

For the historical receptor used here, the complete chain-A issue decisions were:

Action	Residues in chain A
Repair missing observed heavy atoms: LYS	28, 80, 104, 288
Repair: GLN	107, 174, 257, 303, 312
Repair: ASP	231
Repair: GLU	244, 313, 350, 351
Repair: ARG	271, 300
Repair: ILE	342
Leave absent residues unchanged	VAL 1; SER 336, 337, 338; VAL 343; SER 344; ALA 345; ARG 346; MET 347

These are **17 repaired residues and 9 absent-residue decisions**, not 26 removed residues. The original full-entry counts in §3.1 are a different scope. Removing all problematic residues would change the protein and is not this plan.




Figure 3. The accepted historical receptor reopened in Prepared mode. Only chain A is present; 481 resolved waters and RV2 were removed from this derivative. Original mode retains them; Overlay compares both without modifying either record.

Historical execution, not an instruction to rerun an unchecked plan. The accepted record ran, in order: PDBFixer for explicitly selected repairs, a restrained OpenMM relaxation (50.0 kcal mol^{-1} Å^{-2} positional restraint, at most 200 iterations), PDB2PQR with PROPKA for protonation, and Meeko to write the PDBQT.

Watch the **Activity** centre: each tool reports its own version, and each output is hashed as it is written. When it finishes the receptor is marked `docking_ready`.

Only reopen this historical receptor if its actual saved record is available in your project; the screenshots do not supply a receptor file. A new project must complete its own preparation. If a required repair is blocked, stop and resolve the scientific issue rather than docking an unprepared original or removing residues solely to make the pipeline finish.

The accepted receptor predates the current expanded protonation-review UI. It records PDB2PQR/PROPKA at pH 7.4 and the AMBER protocol, but must not be described as evidence that the newer review controls were exercised. In this tutorial it was **reopened**, not prepared again. Its measured maximum displacement of an observed atom during relaxation was **0.38 Å**; the docking PDBQT hash begins `83379bb5f78d…`.

If Meeko reports a connectivity or valence failure, inspect the identified residues and the technical evidence. Ankora must not silently remove them for you. An explicit **Repair**, **Remove** or **Leave unchanged** decision is part of the scientific plan, and removal should be justified before retrying.

> **Why the relaxation is restrained.** Rebuilt side chains can clash. Relaxing without restraints could displace experimentally observed coordinates. Ankora restrains previously observed atoms; they are not perfectly frozen. It measures their largest displacement and enforces the configured drift limit. This is local clash relief, not molecular dynamics or equilibration.

---

4. Ligand: preparing RV2

Step **3 · Ligand**. Ankora can take a ligand from a file, a SMILES string, a library - or, as here, **extract it from the crystal**.

4.1 Extract

Choose **Crystallographic** in **1 · Source**, select `RV2 A:401` and press **Extract RV2**. Ankora extracts it with its deposited 3D coordinates and assigns stereochemistry from those coordinates rather than guessing:

Formula	$C_{19}H_{13}ClN_2O_5$
Formal charge	0
Heavy atoms	27
Molecular weight	384.78 g/mol




Figure 4. Extracted RV2 with deposited geometry, neutral charge and molecular weight 384.775 g/mol. The preparation controls below describe a proposed derivative; they do not change the preserved reference.

4.2 Choose a protonation state - explicitly

Protonation is a scientific choice, not just a file-format conversion.

In **Single ligand** mode, the preparation panel proposes ionization states for the chosen pH range. Set both limits to **7.4**, inspect the candidate and any warnings. Dimorphite-DL 2.0.2 returns one candidate for RV2 at that pH:

> **$C_{19}H_{12}ClN_2O_5^-$**, formal charge **−1**

Ankora will not adopt it until you confirm. It is a different chemical state of the same parent compound - different hydrogen-bond donors, different Meeko atom typing, and in AutoDock4 a different electrostatic term. Confirm **Use exactly this species, ionization and settings**. A candidate is not a measured population or proof of the dominant bound state.

> **If you retain the imported state**, the neutral RV2 state is prepared. That is an explicit choice to justify scientifically, not evidence that the neutral state dominates at pH 7.4. The Methods section records it.

4.3 Generate and minimize a conformer

Open **Advanced settings** and review the conformer protocol. For this tutorial, leave **Minimize original geometry** off, use an independent pool of **20 ETKDGv3 conformers**, seed **20260819**, **MMFF94s**, at most **500 iterations**. Press **Prepare ligand for docking**. The current single-ligand UI combines the confirmed chemical-state, embedding, minimization and PDBQT stages; you do not need three separate preparation buttons.

Recorded on 9 October with RDKit 2025.09.6, reopened unchanged for this edition:

Check	Tutorial derivative
Formula / charge	$C_{19}H_{12}ClN_2O_5^-$ / −1
Molecular weight	383.767 g/mol
Initial / final MMFF energy	145.390 / 49.212 kcal/mol
MMFF energy change	−96.179 kcal/mol
Minimization	Converged
PDBQT preparation	Meeko 0.7.1, Gasteiger partial charges

The energy change assesses **this molecule's geometry**, not binding affinity and not its rank among other compounds. Values may change with a different chemical state, conformer protocol or toolkit version.

The coordinates are generated **independently of the deposited ones**. This matters for redocking: independent starting coordinates reduce bias from reusing the reference geometry as the search input.




Figure 5. Completed anionic derivative, its molecular weight and within-molecule MMFF energy change. The original/reference geometry remains independent; the derivative is ready as Meeko PDBQT.

Checkpoint. Do not continue with a failed minimization, unresolved fragment or undefined stereochemical decision. Inspect the status and warning, make the required explicit choice and create a new derivative. For libraries, follow §12 rather than preparing only the currently displayed row.

---

5. Binding site and docking

5.1 The box

Step **4 · Binding site** initially shows **Full protein (blind)**. That is a starting box, **not** a final pocket selection. For this case choose **Co-crystallized ligand**, pick `RV2 A:401`, set padding to **5.0 Å** and preview the box from the component's observed coordinates:

Centre (Å)	Size (Å)
35.4305, −2.9670, −0.7905	21.597 × 19.870 × 19.317

The box is editable and shown live in the 3D viewer. Once confirmed it becomes an immutable record - if you later change the receptor, every binding site that depended on it is marked stale rather than silently reused.




Figure 6. Co-crystallized RV2 defines the preview box with 5 Å padding. Numeric coordinates and the Cartesian handles refer to the same receptor coordinate frame. Finalization, not just preview, creates the saved site.

In **Move**, drag the white centre in the viewing plane, or an X/Y/Z handle for an axis-constrained movement. In **Resize**, drag a face handle. Changes update the box live; the numeric fields offer precise control. **Esc** cancels a drag. Rotating the camera does not rotate the Cartesian docking box.

Choose the appropriate source for your experiment:

Source	What you must decide
Co-crystallized ligand	Reference component and padding; useful for this redocking case
Selected residues	Explicit chain/residue selection and padding; review the preview extent
Full protein (blind)	Whole-receptor coverage, size and acknowledgement of a large search volume
Detected pocket	Run P2Rank, inspect candidates, choose a pocket, then adjust and confirm the box
Manual coordinates	Centre X/Y/Z and size X/Y/Z in Å, plus the rationale for that region

P2Rank uses the bundled private Java runtime. Its candidates are computational predictions, not experimentally confirmed sites. Selecting one positions an editable box; it does not automatically start docking.

Press **Define this binding site and continue to Docking** when the preview is correct. For manual adjustments use the equivalent final save action. Every mode requires a final definition; navigating away from a preview is not saving the experiment. The complete-protein box is much larger than this local box and may require greater sampling, not just the local-box settings copied below.

5.2 Dock with Vina

Step **5 · Docking**. Choose **Single ligand** and **AutoDock Vina 1.2.7**. Review the receptor, exact prepared ligand and finalized site. The light tutorial used the **Screening** sampling preset with these explicitly recorded parameters:

Exhaustiveness	**8**
Modes	9
Minimum inter-mode RMSD	1.0 Å
Energy range	3.0 kcal/mol
Seed	20260823
CPU threads	1 - intentionally small for this single-ligand tutorial
Timeout	360 minutes maximum, not an expected run duration




Figure 7. The selected job's Methods report confirms exhaustiveness, modes, inter-mode RMSD, energy range and seed. CPU allocation and timeout remain in the full job record.

Confirm the exact inputs and start docking. Screening progress is reported per molecule; a single-ligand job reports its execution state rather than a fabricated intra-molecule percentage. The run is cancellable, and if the machine stops mid-run the next launch preserves the interrupted attempt instead of pretending it never happened.

Preserved tutorial result: 9 poses, best Vina score −7.073 kcal/mol. This run completed in about 37 seconds on the tutorial machine; that is an observation, not a performance promise. Scores for modes 1-9 were −7.073, −6.798, −6.715, −6.652, −6.543, −6.526, −6.473, −6.294 and −6.245 kcal/mol.




Figure 8. The completed tutorial result contains one parent compound and nine preserved poses, with best score −7.07 kcal/mol. The parent-property/state-label caveat below is visible in this table; preparation evidence identifies the actual anionic docking input.

Important RMSD distinction. Vina's lower/upper RMSD columns describe distance from its best mode, not distance from crystallographic RV2. A zero in mode 1 is not successful redocking. Reference-pose validation is a separate calculation.

Parent versus prepared state. A result table may show the imported parent's name, formula or molecular weight. Here that parent is neutral RV2 (384.775 g/mol); the docked derivative is the confirmed anion (383.767 g/mol). Check the preparation record and Methods report to identify the actual input, especially where a historical table field is marked “not recorded”.

5.3 Optionally, the AutoDock4 family

AutoDock4 and AutoDock-GPU need precomputed affinity maps. Ankora runs AutoGrid4 once (0.375 Å spacing, 58 × 54 × 52 grid intervals for this box, with one more node along each axis) and can **reuse a compatible map set** for both backends. Reuse requires matching receptor, search geometry, atom types and map protocol.

The preserved Vina tutorial and the separate historical AutoDock4-family examples used different ligand states:

Engine	RV2 formal charge	Output	Best score (kcal/mol)
Vina 1.2.7	-1 (anion)	9 poses	-7.073
AutoDock4 CPU 4.2.6	0 (neutral)	10 runs	-4.96
AutoDock-GPU 1.6	-1 (anion)	10 runs	-5.70

The CPU example did not use the anionic conformer prepared in §4. These records illustrate interpretation; they are not a matched-input engine benchmark.

> **Do not combine these numbers.** A Vina score and an AutoDock4 binding energy come from different scoring functions. Ankora will show them side by side and will never merge them into a combined ranking.

5.4 On Linux: GNINA 1.3.3 CNN scoring, refinement and ensembles

On **Linux x86_64** (once `Ankora_0.1.0_gnina-cuda12-pack.tar.zst` is imported or `GNINA 1.3.3` is detected), Step **5 · Docking** also offers **GNINA** `1.3.3` for both **Single ligand** and **Virtual screening** (ADR-027, ADR-028).

- **Prepared inputs preserved verbatim:** GNINA consumes your Meeko-prepared receptor and ligand `.pdbqt` derivatives with `--addH 0 --stripH 0`, so the protonation, tautomer and stereochemical decisions confirmed in §3–§4 are never silently overwritten.
- **CNN scoring modes:**
- `rescore` (**CPU or CUDA 12.8 GPU**, default): performs empirical Monte Carlo sampling and local minimization, then evaluates each pose with the 3D CNN.
- `refinement` (**CUDA 12.8 GPU only**, requires `timeout >= 10` minutes): optimizes ligand coordinates directly against combined 3D CNN and empirical gradients. Ankora rejects CPU `refinement` fail-closed rather than silently downgrading to `rescore` or switching compute backends. Because CNN-favoured contacts can sit closer than Vina's hard steric wall, `minimizedAffinity` (`kcal/mol`) on CNN-refined poses can be higher or positive and is **not** an independent empirical energy check.
- **Built-in CNN models (pinned to verified** `GNINA 1.3.3` **SHA-256):**
- `dense_1_3` (`1` model, default)
- `default_1_3_ensemble` (`3` knowledge-distilled GNINA 1.3 models: `dense_1_3`, `dense_1_3_PT_KD_3`, `crossdock_default2018_KD_4`, invoked by omitting `--cnn`)
- `default1.0` (`5` GNINA 1.0 models)
- **Native CNN pose order and GPU verification:** Within every ligand, modes `1..N` remain ordered by descending `CNNscore` and are never re-sorted by `kcal/mol`. CUDA jobs enforce single-GPU VRAM reservations (`1.0` – `2.0 GiB` via `ResourceArbiter`) and verify that `nvidia-smi` observed the GNINA process on the expected GPU UUID without MIG/MPS remapping before publishing poses.

---

6. Validation: did the engine find the crystal pose?

This is the section worth reading twice.

Step **7 · Validation** compares a docked pose against the crystallographic ligand using **symmetry-aware heavy-atom RMSD, computed in place** - the pose is *not* superimposed first. Superimposing would measure whether the shapes match; we want to know whether the atoms are where the crystal says they are.

> Aligning the ligand alone can hide an incorrect placement in the pocket. Ankora therefore evaluates placement in the receptor's coordinate frame.

6.1 Create or read a validation

1. Extract the crystal ligand from the original structure in **Ligand**, keeping its original reference. Prepare an independent docking conformer and run it in **Docking · Single ligand** with Vina, AutoDock4 CPU, AutoDock-GPU or (on Linux) GNINA `1.3.3` (whose modes are evaluated in native descending `CNNscore` order).
2. Open **7 · Validation**. Choose the **completed individual result** to measure. This screen is available even after restarting without a loaded structure.
3. Choose its **original crystallographic reference**. The list contains only preserved 3D extractions in the receptor's original coordinate frame; minimized conformers and unrelated structures are not reference options. If the list is empty, extract the original ligand in the same project, then refresh the references. A screening campaign is not an individual redocking experiment.
4. Review the **recovery threshold** (default 2.0 Å), confirm the exact pair and press **Calculate RMSD and save validation**. This measures existing poses; it does **not** run docking again. Fingerprint or molecular-compatibility failures are reported without saving a verdict.
5. Read the separate sampling and ranking verdicts and the per-pose table below. The independent validation record is saved and can be reopened in the inspector. A read error offers a retry, not an endless loading indicator.




Figure 9. Current Redocking creation form: the completed tutorial Vina result, original crystal RV2 reference and explicit 2.0 Å criterion are selected. The acknowledgement remains unchecked; no new RMSD verdict is generated for this capture.

The reference and docking input are different roles. Keep the original crystal extraction with its deposited coordinates, then prepare an independent state and conformer for docking. A minimized reference, a ligand aligned after docking or a molecule from another receptor coordinate frame cannot substitute for the experimental reference.

If the form cannot continue	What to check
Result missing	Same project, completed **individual** Vina/AutoDock4 CPU/GPU job; not a library campaign
Reference list empty	Original 3D crystal extraction from the receptor's source structure; refresh after extraction
Compatibility rejected	Correct molecule, original source identity, heavy-atom correspondence and intact file fingerprints
Save button disabled	Result, reference, valid threshold and explicit acknowledgement are all required

A successful save creates another immutable validation record. Changing the threshold is a new measurement, not a reason to alter the earlier record or choose a cutoff after seeing which value would pass.

6.2 Interpret the saved result

Choose **7 · Validation**, then select a recorded validation in the inspector. Read its reference, threshold and per-pose RMSD table. The historical verdicts below used the different chemical states listed in §5.3 and a recorded 2.0 Å threshold. Neither this historical evidence set nor the preserved Vina tutorial contains a Vina reference-RMSD verdict; a docking score cannot supply one.

> **Do not substitute Vina's inter-mode RMSD.** Only the explicit comparison to the original crystal pose answers this question. “No redocking validation recorded yet” means no measurement has been saved, not successful validation.

	AutoDock4 CPU	AutoDock-GPU
Top-ranked pose RMSD	**3.139 Å**	**10.717 Å**
Best pose found, any rank	0.454 Å	1.331 Å
First rank that recovers	2	2
Poses within threshold	6 of 10	9 of 10
Sampling	✅ success	✅ success
Ranking	❌ **failure**	❌ **failure**
Outcome	`recovered_but_misranked`	`recovered_but_misranked`

Read that carefully. Both engines *found* the crystallographic pose - 0.45 Å is an excellent reproduction. Both then ranked a wrong pose first. If you had taken the top-ranked result and moved on, as most workflows invite you to do, you would have carried a 3.1 Å (or 10.7 Å) pose into your interpretation.

Ankora separates **sampling** from **ranking** and reports both, because they fail independently and they mean different things. A tool that reported only "RMSD = 3.139 Å, failed" would have hidden the fact that the search worked and the scoring function did not.




Figure 10. Preserved AutoDock4 CPU/neutral-RV2 evidence: top-1 RMSD 3.139 Å, best of top five 0.490 Å, best overall 0.454 Å. Sampling passed; ranking failed. This is not a validation of the anionic Vina tutorial job.

> **On reproducibility.** A seed alone does not establish reproducibility. Read the exact-repeat evidence attached to the selected result. For example, the separate 6OCO/M5V validation measured a 0.03 kcal/mol best-energy range across six GPU repeats and different cluster memberships. That observation is case-specific; it is not a universal GPU error bar or a guarantee of CPU bitwise identity elsewhere.

---

7. Results, interactions and figures

Step **6** · **Results** lists recorded campaigns, including failed or interrupted attempts, with each engine, receptor, site and counts. Click a card to open its molecules; double-click also opens it. In a molecule table, click the compound to reveal its poses or AutoDock cluster/run members. Choose the exact mode or run you want to inspect.




Figure 11. The newest Vina card is the 9 October tutorial; the other visible Vina card is historical. The catalog is chronological, not a ranking across campaigns.

Use the **Mode** and **Scoring** filters to locate results. Within a campaign, search by name or SMILES, sort by column headings and use the horizontal scrollbar to reach wide columns. Failed compounds remain visible and are not assigned a successful docking energy.

To remove a result, use **Delete open result**. For a group, choose **Select multiple**, select the exact cards, and review the confirmation. Campaigns and their dependent interaction/validation records move to Ankora's recoverable Trash; original structures, ligands, receptors and shared maps are not removed. Removal from active Results is not an irreversible scientific-data purge.

7.1 Analyze the exact pose

Open **Pose interactions** and select **Mode 1** of the tutorial Vina job. Read an existing entry in **Recorded analysis** if one is available. Otherwise press **Analyze this pose with ProLIF**; **Create another analysis** explicitly writes a new record rather than modifying the earlier one. ProLIF 2.2.1 runs over that exact pose against the exact prepared receptor, under the recorded profile `ankora-default-v1` (6.0 Å vicinity cutoff). The preserved Vina top-pose analysis has **17 atomic contacts, 5 contacting residues and 8 residue/subtype groups**. The historical top-pose record also has 17 contacts but is a separate identity. Your own project starts

without either analysis: analyze its own exact pose, and do not assume the count is unchanged after changing preparation, pose or versions.

You get three linked views of the same structured record - a 2D interaction diagram drawn by Ankora, a contact table, and the pose in Mol* with the contacting residues focused. Clicking a contact in one highlights it in the others.




Figure 12. One structured analysis feeds all three views. Summary mode displays 8 representative contacts from 17 positioned atomic contacts; the table retains all matching contacts.

7.2 Read summary groups without losing contacts

Residue summary is the default. Each residue/exact interaction subtype has one node, with **×N** for all its recorded atomic contacts. One shortest-distance contact, or your selected contact, represents the group in 2D and 3D. Grouping does not delete the underlying contacts.




Figure 13. THR A:120 has separate hydrogen-bond donor and acceptor groups. LYS A:122 has separate hydrophobic, acceptor and ionic groups. Colours are categories; exact subtypes are not merged just because they share a colour.

All atom contacts shows every matching positioned contact instead. The **Interaction type** menu filters the diagram, 3D lines and table together. Read the numerator and denominator: filtered contacts versus all recorded contacts. In this example, hydrophobic-only mode shows **13 / 17 contacts** in **4 residue/subtype groups**; all-atomic mode displays all 13 lines.




Figure 14. Hydrophobic-only mode selects 13 of 17 contacts in 4 groups. The 3D heading confirms 13 displayed / 13 positioned contacts in all-atomic mode. These are not 13 independent bonds or favourable energetic contributions.

Click a node or table contact to focus it in 3D. **Center on interaction site** returns to the pocket; **Reset Zoom** may show the whole receptor. Summary can make a dense first pose readable, while all-atomic detail supports inspection. If a historical contact lacks 3D endpoints, it remains in the table and 2D record with a visible notice; it must not be silently discarded.

7.3 Save the diagram, 3D view and coordinate complex

From here you can save the 2D diagram as SVG, PNG, TIFF or PDF; the 3D view supports PNG, TIFF or PDF, not SVG. You can also export the exact ligand-receptor complex as a PDB for other viewers. You choose the destination folder; Ankora never overwrites an existing file, and suffixes a taken name the way Windows does. The desktop **Choose folder...** selects a work directory. **Use the project** writes to the selected project's exports area. The browser-only capture environment cannot open the native folder chooser; the project destination was used and verified for this tutorial.




Figure 15. 3D supports raster output, not SVG. The separate Save PDB button in the ligand-receptor complex panel writes coordinates, not HTML, and does not rerun docking.

The PDB contains the exact prepared receptor plus the selected pose, without minimization or superposition. It is suitable for inspecting coordinates in an external molecular viewer; it is not a replacement for a chemically rich SDF or a record of Meeko partial charges. In the tutorial, the file `ligand_receptor_complex.pdb` was actually written, **480,421 bytes**, hash `b9f17aba7bdc…`, with a neighbouring `complex.json` identity record.




Figure 16. The 2D save panel: SVG is the vector original; PNG, TIFF and PDF are raster alternatives. An 85 mm figure at 300 dpi was saved as 1004 × 692 pixels in the tutorial.

1. Choose the formats you need. Use **SVG** for editable vector 2D artwork; use raster formats for the 3D rendering.
2. Choose the destination, width and resolution. These control the output, not the scientific calculation.
3. Press **Save figure**, wait for confirmation and inspect the written file.
4. For the complex, press **Save PDB** in the ligand-receptor complex panel. A saved figure does not automatically save molecular coordinates.

Saved diagrams preserve the selected summary/all-contact mode and counts. Scroll the **workspace** to reach the saving controls on a laptop. The contact table's horizontal/vertical bars only move its data, not the whole page.

> **What an interaction diagram is.** It is a geometric interpretation of one pose. It is not experimental evidence, not an energy decomposition, and not proof that a contact is favourable.

---

8. The Methods section

In **6 · Results**, select your result and use **Write the Methods section** in its inspector. This also supports the single-ligand example. For screening campaigns, the same report is available in **8 · Export**.

Choose the result whose protocol you intend to describe. A report for a 323-compound screening library is not the Methods section for this single RV2 job, even if both use 7AQF.

Ankora reads the provenance chain and writes the Methods text the campaign's own records support - the PDB entry and its resolution, the chains kept, the repair and relaxation parameters with the measured maximum displacement, the pH and force field, the box centre and dimensions, the embedding and minimization protocol, the charge model, the complete engine parameters, the executable's SHA-256, and the counts.

Three things about that text are worth noticing.

It marks what it cannot support. A missing artifact becomes a visible `[not recorded: …]` marker in the prose and an entry in the gap list shown above it. It is never replaced by a plausible sentence.

It states what was not done. If no pH-based protonation enumeration was recorded, the text says so explicitly. Your receptor section will name a pH; if the ligand section stayed silent a reader would reasonably assume the same pH applied. That silence would flatter the work, so Ankora breaks it.

It carries the references. The Software table lists every tool, its version, its role and a numbered reference from Ankora's recorded bibliography. Review these citations and the Methods text before including them in a manuscript.

Press **Copy to clipboard** and paste into your manuscript. What you get is the Markdown source, headings and table included.





Figure 17. The tutorial's actual Methods report: no provenance gaps reported, eight cited software entries. The visible receptor paragraph and start of the box section derive from the selected job's provenance chain; the report also records the ligand protocol.



Software

Software	Version	Role	References
AutoDock Vina	1.2.7	molecular docking	1, 2
Dimorphite-DL	2.0.2	ligand chemical-state resolution	3
Meeko	0.7.1	receptor PDBQT conversion	4
Meeko ligand preparation	0.7.1	ligand PDBQT conversion	4
OpenMM declash (PDBFixer worker)	1.12.0	restrained clash relaxation	5
PDB2PQR/PROPKA	pdb2pqr 3.7.1; propka 3.5.1	protonation and charge assignment	6, 7, 8
PDBFixer	1.12.0	missing side-chain repair	5
RDKit ETKDG/MMFF	2025.09.6	ligand conformer generation and minimization	9, 10, 11, 12, 13

References

1. Eberhardt J, Santos-Martins D, Tillack AF, Forli S. AutoDock Vina 1.2.0: New Docking Methods, Expanded Force Field, and Python Bindings. Journal of Chemical Information and Modeling. 2021;61(8):3891-3898. doi:10.1021/acs.jcim.1c00203
2. Trott O, Olson AJ. AutoDock Vina: improving the speed and accuracy of docking with a new scoring function, efficient optimization, and multithreading. Journal

Figure 18. The software table and start of the numbered references. Review tool-versus-worker version labels and citations before publication; a gap-free report still needs scientific editorial review. Copy to clipboard is a separate control below the preview.

The **campaign bundle** (also in step 8, currently `ankora_export_format = 4`) is the portable version of the same idea: a fail-closed ZIP with `manifest.json`, `results.csv`, `README.txt`, `methods.md`, existing interaction analyses and saved figures where available, and a SHA-256 integrity index across completed `Vina`, `AutoDock4 CPU`, `AutoDock-GPU` and (on Linux) `GNINA` screening campaigns. On Linux, GNINA single-ligand jobs also support portable evidence bundles preserving poses, separate CNN and empirical axes, interactions and redocking verdicts, while GNINA `Methods` reports cite Crossref-verified references (`McNutt et al., 2021` and `2025`), exact CNN ensemble member names, and `rescore` versus `refinement` semantics. Inspect the bundle's file list before using it as supplementary material; for screening campaigns it indexes summary and interaction evidence rather than every raw pose directory. Export the exact pose complex when you need that coordinate file.

Step **8 · Export** also catalogs existing figures and coordinate complexes. Use **All**, **Campaign bundles**, **Figures** or **Complexes** to find the artifact you need. Single-ligand Vina and AutoDock jobs expose their saved figures/complexes here and their Methods report in **6 · Results**; completed screening campaigns (and Linux GNINA single jobs) can also be packaged as portable ZIP archives.




Figure 19. The Export catalog lists the real SVG, PNG and figure manifest saved for RV2. The destination-path line is deliberately outside this crop; this edition contains no personal machine paths.

An export record does not relocate files. If an older export was saved outside the current project or its folder is no longer present, the catalog may list its filenames without offering file links. Restore access to that original folder or explicitly save a new export; do not treat the catalog entry alone as evidence that the files were copied into a new project.

Before sending a bundle to collaborators, inspect the integrity index, file list and any remaining missing-evidence notices. Share the specific output directory, not an entire personal project folder with unrelated experiments.

---

9. What Ankora will not do for you

This list is the product, not a disclaimer.

- **It will not choose a protonation state silently.** If you do not enumerate, the imported state is used and the Methods text says so.
- **It will not enumerate tautomers unless you ask.** Tautomer enumeration is available for screening microstates and is off by default; when it is off, the Methods text records that too.
- **It will not merge scores from different engines.** No combined ranking, no consensus score.
- **It will not call a score an affinity**, or claim a biological result.
- **It will not rank the candidate protonation or tautomer states it generates.** Neither Dimorphite-DL nor RDKit provides a population model that would justify reading the order as a preference, so the order is reported as unranked.
- **It will not modify your imported file**, ever.
- **It will not quietly reuse a stale derivative.** Change a receptor and everything downstream is marked stale.
- **It will not claim reproducibility it did not measure.** A campaign with no exact repeat reports "not assessed" - which is different from "not reproducible".

---

10. How to read a docking score

A short section, because this is where results get over-interpreted.

A Vina score and an AutoDock4 binding energy are **computational estimates from empirical scoring functions**, reported in kcal/mol. They are not measured binding affinities and they do not convert to one. The number's useful job is *rank-ordering ligands against one target*; it is much weaker at comparing across targets, and it is not a prediction of activity.

§6 is the concrete lesson: on this system the scoring function ranked a 3.1 Å pose above a 0.45 Å one. Sampling and scoring are different problems and they fail separately.

Engine / metric	Reported units & direction	What it measures — and what it does not
Vina score (`Vina 1.2.7`)	`kcal/mol` (more negative ranks higher within Vina)	Empirical scoring-function estimate; not experimental ΔG, and its inter-mode RMSD bounds are not crystal RMSD.
AutoDock4 energy (`4.2.6` CPU / `GPU 1.6`)	`kcal/mol` (more negative ranks higher within AutoDock4)	Semiempirical AMBER-based estimate over `AutoGrid4` maps; never pool numerically with Vina. Matched Vina and AutoDock4 CPU library campaigns can be compared only via rank order (Spearman ρ and Top-`N` overlap).
GNINA `CNNscore` (Linux `1.3.3`)	Dimensionless `[0, 1]` (closer to `1.0` ranks higher)	3D CNN pose-quality score governing within-ligand mode order (`1..N`); **not** a calibrated statistical probability.
GNINA `CNNaffinity` (Linux `1.3.3`)	`pK` units (higher ranks higher)	3D CNN predicted affinity on a $\log_{10}$ dissociation scale; distinct from empirical `kcal/mol` and experimental Kd/Ki.
GNINA `CNN_VS` (Linux `1.3.3`)	`CNNscore × CNNaffinity` (descending)	Screening hit-prioritization product (`ADR-028`) mitigating top-end `CNNscore` saturation across libraries. If any completed entry has `CNNaffinity <= 0` , Ankora records `GNINA_CNN_VS_NONPOSITIVE_AFFINITY` because negative `pK` values invert `CNNscore` monotonicity among weak decoys.

Practical consequences:

- Do not compare a Vina score to an AutoDock4 binding energy.
- Do not read small differences between ligands as meaningful ordering.
- Inspect poses. A good score on a chemically implausible pose is a scoring artifact, and the interaction view exists to make that visible.
- Where a co-crystal exists, redock it first (§6). If the engine cannot rank the known pose first on your target, treat its ranking on unknown ligands with matching scepticism.

11. If something goes wrong

Symptom	What it means
Tools missing	Open Tools → Scientific tool readiness and rescan. Report missing tools in a complete-installer candidate as an installation defect, not a request to configure paths yourself. Earlier backend-only candidates are incomplete.
A step is greyed out	Its inputs do not exist yet. The workflow panel names what is missing.
"stale" badge on a derivative	Something upstream changed. Recreate it; Ankora will not silently reuse it.
A run was interrupted	The next launch preserves the partial attempt as an explicit interrupted record. Retrying starts a new identity rather than appending to partial evidence.
Port 8765 in use	Another local process owns the port. Close a previous Ankora session if it is yours; do not terminate an unidentified process.
Warnings badge is lit	Read each finding and its required action. Some need a scientific decision; a preparation blocker cannot be ignored.
A preparation is queued with low CPU use	Inspect Activity and machine resources. The scheduler admits work only when CPU, GPU, memory and disk reservations fit; low CPU use is not evidence that multicore execution is disabled.
Molecule absent from 3D	Read the viewer error first. A downloaded record can exist even when the renderer fails. Report a CSP/module error as a software defect; do not change chemical preparation to fix a rendering problem.
Many 3D lines but fewer 2D nodes	Read atomic-contact and group counts, the interaction-type filter, and summary/all-atomic mode (§7.2). Multiplicities preserve contacts; nodes are not individual atom pairs.
A save control seems missing on a laptop	Scroll the workspace and collapse or resize panels. Scrollbars inside the contact table do not move the export panels.
No validation is listed	No measurement has been saved in this project yet. Open **7 · Validation**, select a completed individual Vina, AutoDock4 CPU/GPU or (on Linux) GNINA job and its compatible original reference from the same structure, and press **Calculate RMSD and save validation** (§6.1).
Crystal reference is missing	Extract the original 3D ligand from the same source structure and project. Minimized or unrelated structures are not eligible references.
Redocking rejects a fingerprint or molecule	Check the exact preserved files, source identity and heavy-atom correspondence; do not overwrite an artifact or align the pose to force a pass.
GNINA unavailable on Linux	Open **Tools** → **Scientific tool readiness** and import `Ankora_0.1.0_gnina-cuda12-pack.tar.zst` (zero `sudo` required). On Windows, GNINA remains intentionally deferred.

Logs live beside the project data; the **Provenance** panel in the status bar shows every command Ankora issued, with its arguments.

For a report, include Ankora version, engine/tool versions, the affected step, the error text, and whether this was a new or reopened project. Provide a minimal non-confidential example where possible. Check screenshots and logs for personal paths or unrelated compounds before sharing them.

---

12. From one ligand to virtual screening

The 7AQF/RV2 tutorial is a **single-ligand** run. Screening reuses the explicit 7AQF receptor and finalized box but processes a selected library, not just the molecule currently visible in Mol*. The 323-record library used to inspect the controls below is an existing illustrative import; **no new 323-compound screening campaign or performance benchmark was run for this guide**.

12.1 Import, inspect and filter before 3D preparation

1. In **3 · Ligand**, switch to **Virtual screening**.
2. Open a multi-record **SDF**, **SD-style MOL**, **SMI** or **SMILES** file, or reopen an imported library under **Already in this project**. Current limits are **10,000 records** and **100 MB** per import. Multiple molecules in a MOL input need actual SD-style record delimiters, not concatenated undelimited MOL blocks.
3. Inspect import counts, invalid records, names, formulae, molecular weights and SMILES. Source order and failed-record evidence remain traceable.
4. Review **Library filters** and press **Preview filters** when available. Preview calculates descriptors and decisions; it does not apply the selection.
5. Inspect exclusions and flagged compounds. Confirm **Apply this exact selection**, then **Apply filtered subset**. This creates an immutable selection manifest including properties, rule results, exclusions and IDs.




Figure 20. Real controls from the illustrative 323-record import. Lipinski and Veber are required by default; Ghose/Muegge are informative, QED is rank-only, PAINS/Brenk flag for review, and duplicate repeats are excluded. This is a policy preview, not a completed filtering result.

Control	Default role	What to consider before changing it
Lipinski	Required; up to one violation	A general oral-drug heuristic, not a universal definition of a useful ligand
Veber	Required	Permeability-related heuristic; adapt the policy to the research question
Ghose / Muegge	Informative until enabled	Enabling all rules can exclude useful chemical space; review why
QED	Ranking descriptor; minimum filter off	A numerical desirability descriptor, not biological activity
PAINS / Brenk	Flag for review	Alerts require scrutiny; a substructure match is not proof of assay interference
Duplicates	Exclude repeats	Inspect the recorded identity policy; don't mistake source names for chemical identity
Custom rules	Explicit required/informative choice	Record descriptor, comparison and cutoff; keep the rationale

These defaults are a starting policy, not a scientific claim that every library should be screened through all five drug-likeness filters. Structural alerts can be reviewed again among hits after docking; a docking score does not make an alert disappear. The implemented alert label is **Brenk**, not “BREAKS”.

12.2 Prepare the applied subset

Confirm **Prepare the applied filtered subset** and process the selected ligands. Review disconnected components, stereochemistry and failed molecules rather than silently selecting a fragment or inventing a stereoisomer.

Screening microstate handling is an explicit choice: retain the exact supplied state, or request bounded protonation/tautomer candidates and select the policy. Tautomer enumeration is off by default. Candidate order is **unranked** and does not predict populations. Changing a molecule's state also changes the actual prepared chemical input; retain the parent/derivative link when interpreting properties or results.

Independent ETKDGv3 geometry, MMFF minimization and Meeko PDBQT preparation run per selected molecule. Their statuses update independently; one failure should not erase its neighbours. **MMFF energy and ΔE are within-molecule geometry QC, not a cross-molecule ranking.** Use the library search, sortable headers, column chooser and horizontal scrollbar to inspect the complete table.

12.3 Dock the library and follow live progress

In **5 · Docking**, choose **Virtual screening**, the **applied prepared selection**, the exact site and one engine. The run confirmation must name the number of ligands to be docked. Selecting a row for viewing is not selecting the entire library for docking.

For Vina, set an explicit **Total CPU threads** budget and **Concurrent ligands**. The budget is divided among concurrent Vina processes; it is not multiplied by giving every process the entire budget. For example, a 15-thread budget with 15 concurrent ligands allocates one thread to each. This is an illustrative configuration, not a measured speed-up or a required setting for your machine.

For **AutoDock4 CPU**, Ankora runs a bounded pool of single-core processes over one shared immutable `AutoGrid4` map set; **AutoDock-GPU** executes one `--filelist` GPU batch over that map set so parallel GPU kernels do not compete across separate OS processes. On Linux, **GNINA virtual screening** executes prepared selection entries sequentially (`1` active job at a time with transactional SQLite state, cancellation and startup recovery), ranking completed compounds by descending `CNNscore` or `CNN_VS` (`hit_ranking_metric`) while keeping within-ligand modes in `CNNscore` order. When you run both **Vina** and **AutoDock4 CPU** library campaigns against the exact same receptor, finalized box and applied selection manifest, **6 · Results** can evaluate Spearman rank correlation and Top- `N` overlap without merging their score scales.

The progress strip reports **completed / running / queued / succeeded / failed**. Finished compounds appear incrementally in the sortable results table. The current-best banner identifies the lowest score **within that campaign**; it does not claim measured affinity or compare unrelated engines. Click a compound to open its poses, then inspect one exact pose in Results (§7).

CPU percentage depends on admitted work, search settings, memory and other software. For GPU runs, inspect device compatibility and the recorded protocol; CPU and GPU percentages are not interchangeable

evidence of throughput. Preserve partial failures and interruptions, then export the completed campaign and its Methods report (§8). A redocking tutorial is not prospective virtual-screening validation.

Citing Ankora

If Ankora contributed to published work, cite it using the metadata in `CITATION.cff` at the repository root (author: Samael Olascoaga, ORCID `https://orcid.org/0009-0008-5522-7938`), naming the version that produced your results. Cite the scientific tools separately - the Methods section Ankora generates lists them with their references.