

D

C

B



A

D

C

B

A




J3&J4 interface

NO.	SYMB
1	VCC5V
2	VCC5V
3	GND
4	GND
5	LCD_CS
6	LCD_MOSI
7	LCD_SCLK
8	LCD_INT
9	LCD_RST
10	LCD_MISO
11	CTP_INT
12	CTP_SCL
13	CTP_SDA
14	CTP_RST
15	NC
16	GND
17	NC
18	NC
19	NC
20	GND

P1 interface

NO.	SYMB
1	SF_CLK
2	SF_DI
3	SF_DO
4	SF_CS
5	LCD_RST
6	GND
7	NC
8	NC
9	3.3V
10	3.3V

SPI Flash烧录接口, 烧录前
LCD_RST引脚必须接地



Display Type:	7.0" IPS	Interface	SPI interface	Pixel Pitch:	0.1506mm×0.1432mm
Display Mode:	Normally Black	Operating Temp.	-20℃ to +70℃	Brightness:	350 cd/m ²
Viewing Direction:	ALL VIEW	Storage Temp.	-30℃ to +80℃	Backlight:	21 LED
Resolution:	1024 (RGB) X600	Structure:	LCD+TOUCH+PCB	Material Note:	ROHS Request
THIS DRAWING IS PROPERTY OF WAIKEN SMART CO. LTD, IT CANNOT BE REPRODUCED WITHOUT PERMISSION.					

Product NO:		WKS70WSV082-WCT			
Part Name:		LCM Outline	APPD:	Sandy	
REV:	V0	Unit:	mm	CHKD:	Eric
Date:	2023-4-7	Scale:	1:1	DWN:	Jason
Unmarked Tolerance: ±0.20 mm				Sheet:	1 OF 1