

rstac CQL2 extension development report

Gilberto Camara, Rolf Simoes, and Felipe Carvalho

2022-12-16

Introduction

Earth observation images are one of the most reliable and consistent ways to monitor Earth's surface. In the last decades, the number of orbital instruments for Earth observation has increased (Finer et al. 2018). Cloud computing has been adopted by industries and academics to store, access, process, and distribute big Earth observation data (Wagemann et al. 2021). In this context, Spatio-temporal Assets Catalog (STAC) [<https://stacspec.org>] is becoming a standard to describe and search satellite imagery service providers.

STAC is an OGC API Features (OAFeat) (OGC 2019) compliant standard. STAC enables users to search and access satellite images using a client. One of the main characteristics of STAC is its core simplicity, which supports basic search functionality. The standard also enables the development of new extensions to support more specific and complex functionality, for example, the Common Query Language 2 (CQL2) extension (OGC 2022).

CQL2 is part of the OAFeat standard that provides a complex way to search and retrieve spatial-temporal assets. Using CQL2 in a STAC service, users can search for spatial assets using various metadata information such as cloud cover and spatial relations. CQL2 is a powerful query language that allows users to create complex filtering criteria in an expressive way.

In the R language, the `rstac` package is the unique client to support STAC services (Simoes et al. 2021). `rstac` provides basic functionality to STAC core. This report shows the final status of CQL2 extension development in `rstac`. It also describes the activities realized during the project and how CQL2 works in the `rstac` package. The current version of the `rstac` package can be accessed at <https://github.com/brazil-data-cube/rstac>.

Project status

This section reports the final project status on developing CQL2 capability in the `rstac` package. We describe each project's milestones in the following topics.

Milestone 1 - Proof of concept version with examples that validate the idea of using the package

Status: concluded.

We used the abstract syntax tree (AST) of R language to develop the CQL2 extension in rstac. In computer science, AST is a way to represent a language expression in a formal way using data structures. AST representation informs the precedence on which and how an identifier will be evaluated. AST can be used to translate code from one language to another (Wickham, Hadley 2019). The advantage of this approach is that users can focus on filtering criteria putting less effort into checking the syntax consistency. Using R environments and lexical scoping, AST gave us a powerful way for translating R code into CQL2 query. This approach showed to be consistent with the CQL2 standard. We provide some examples of code translation in Appendix A.

Milestone 2 - Implementing integration testing with STAC services supporting CQL2

Status: concluded.

One of the main tasks we dedicated effort to in this project was implementing integration tests. CQL2 standard provides a comprehensive conformance test (OGC 2022). We have implemented most of the tests targeting the test dataset. The test dataset used in rstac conformance tests is provided by “Test Dataset for the CQL2 Test Suite” [<https://cql2test.ldproxy.net/ne110m4cql2>]. It is derived from Natural Earth [<https://www.naturalearthdata.com>], a public domain dataset containing features from three original data layers at scale 1:110 million: ne_110m_admin_0_countries, ne_110m_populated_places_simple, and ne_110m_rivers_lake_centerlines. Besides this test suite, we also have implemented tests using Microsoft Planetary Computer STAC service [<https://planetarycomputer.microsoft.com/api/stac/v1>]. These tests were critical to detect bugs and inconsistencies along with software development. The current rstac version is passing in all of them, which asserts rstac robust compliance to CQL2 standard. The list of conformance tests implemented in rstac is listed in Appendix B.

Milestone 3 - Pre-release version with documentation and testing

Status: concluded.

We pushed a pre-released version of rstac into its GitHub repository. This version passed all conformance tests referenced in the previous topic. CQL2 filtering functionality is implemented in the `ext_filter()` function. We have written function documentation available in `?ext_filter()` in the R console. Besides function description and parameters details, the documentation provides examples of using the CQL2 filtering function using the rstac package in actual STAC services.

Milestone 4 - CRAN submission and tutorial creation for users and developers.

Status: concluded.

We have submitted the `rstac` 0.9.2 version to Comprehensive R Archive Network (CRAN). Now R users can install the package directly from CRAN. A well-documented package and tutorials are important to promote new `rstac` users. In this `rstac` version, we have updated the package documentation and written new tutorials. Firstly, we have prepared a new R notebook on creating CQL2 expressions using `rstac`. We plan to submit it to the Microsoft Planetary Computer Examples repository [<https://github.com/microsoft/PlanetaryComputerExamples>] as soon as possible. We also prepared a new vignette in `rstac` to help R users see actual examples of CQL2 expressions.

Concluding remarks

This report describes the results of the CQL2 extension development in the `rstac` package. The project enumerated four milestones that were concluded as described above. The current version of the `rstac` package can be accessed at [<https://github.com/brazil-data-cube/rstac>] under the MIT license. The `rstac` package is open to the community and follows the “Contributor Covenant - version 1.0.0” code of conduct. We updated the package’s documentation and have prepared new tutorials on how to use `rstac` and its new CQL2 functionality.

Appendix A - CQL2 examples

Introduction

CQL2 is an OGC standard that enables complex filter expressions on OAFeat3 or STAC web services. CQL2 standard states that expressions can be represented in JSON or TEXT formats. Our implementation intends to convert native R expressions into CQL2 valid expressions without needing cumbersome nested lists or dictionaries. Also, we can make CQL2 filter requisition in JSON or TEXT formats with the same filter representation.

Translating R expressions to CQL2 syntax

To explain the difference between the TEXT and JSON CQL2 representation, let’s start with a simple example. In the following code, we have a valid CQL2 expression (in TEXT format) that refers to two properties, `vehicle_height` and `bridge_clearance`.

```
vehicle_height > (bridge_clearance - 1))
```

This filter expression can be passed in the HTTP GET verb implemented by the service to retrieve only those features that satisfy the condition. The same expression can be represented in JSON format, which is more suitable for HTTP POST requests:

```
{
  "op": ">",
  "args": [
    {"property": "vehicle_height"},
    {
      "op": "-",

```

```

    "args": [
      {"property": "bridge_clearance"},
      1
    ]
  }
]
}

```

Note how properties `vehicle_height` and `bridge_clearance` are represented in this format. They are elements of an object containing a property member. Also, they go as arguments of operators (in this case, `>` and `-` operators).

In the R language, the JSON above could be represented by nested lists, which would be somewhat cumbersome to write. To produce valid CQL2 filter expressions, we use the R abstract syntax tree (AST) from R expressions that can be converted to TEXT or JSON formats. Let us see the same previous example written in R CQL2:

```
library(rstac)
```

```
cql2_text(vehicle_height > (bridge_clearance - 1)) # TEXT format
#> vehicle_height > bridge_clearance - 1
```

```
cql2_json(vehicle_height > (bridge_clearance - 1)) # JSON format
#> {"op": ">", "args": [{"property": "vehicle_height"}, {"op": "-", "args": [{"property": "bridge_clearance"}, 1]}]}
```

In both cases, the same CQL2 object representation is built from the expression using AST of R expression evaluation. Then, the object is converted into TEXT or JSON format.

CQL2 filters in TEXT format are sometimes represented the same way as in the R expression. However, this should only sometimes be the case, as we can see in some examples provided below.

Data types and literal values

A literal value is any part of a CQL2 filter expression used the same as specified in the expression.

The scalar data types are: character string, number, boolean, timestamp, and date.

character string

```
cql2_text("Via dell'Avvento")
#> 'Via dell'Avvento'
cql2_json("Via dell'Avvento")
#> "Via dell'Avvento"
```

number

```
cql2_text(3.1415)
#> 3.1415
cql2_json(-100)
#> -100
```

boolean

```
cql2_text(TRUE)
#> true
cql2_json(FALSE)
#> false
```

timestamp

```
cql2_text(timestamp("1969-07-20T20:17:40Z"))
#> TIMESTAMP('1969-07-20T20:17:40Z')
cql2_json(timestamp("1969-07-20T20:17:40Z"))
#> {"timestamp":"1969-07-20T20:17:40Z"}
```

date

```
cql2_text(date("1969-07-20"))
#> DATE('1969-07-20')
cql2_json(date("1969-07-20"))
#> {"date":"1969-07-20"}
```

Property references

The property of an item can be evaluated in the CQL2 filter expression by its name.

```
cql2_text(windSpeed > 1)
#> windSpeed > 1
cql2_json(windSpeed > 1)
#> {"op": ">", "args": [{"property": "windSpeed"}, 1]}
```

Standard comparison predicates

A comparison predicate evaluates if two scalar expressions satisfy the specified comparison operator.

The standard comparison operators are: =, !=, <, >, <=, >=, and IS NULL.

```
cql2_text(city == "Crato")
#> city = 'Crato'
cql2_json(city == "Jacareí")
#> {"op": "=", "args": [{"property": "city"}, "Jacareí"]}
```

```
cql2_text(avg(windSpeed) < 4)
#> avg(windSpeed) < 4
cql2_json(avg(windSpeed) < 4)
#> {"op": "<", "args": [{"function": {"name": "avg", "args": [{"property": "windSpeed"}]}}, 4]}
```

```

cql2_text(balance - 150.0 > 0)
#> balance - 150 > 0
cql2_json(balance - 150.0 > 0)
#> {"op": ">", "args": [{"op": "-", "args": [{"property": "balance"}, 150]}, 0]}

```

```

cql2_text(updated >= date('1970-01-01'))
#> updated >= DATE('1970-01-01')
cql2_json(updated >= date('1970-01-01'))
#> {"op": ">=", "args": [{"property": "updated"}, {"date": "1970-01-01"}]}

```

IS NULL operator

```

cql2_text(!is_null(geometry))
#> geometry IS NOT NULL
cql2_json(!is_null(geometry))
#> {"op": "not", "args": [{"op": "isNull", "args": [{"property": "geometry"}]}]}

```

Advanced comparison operators

A comparison predicate evaluates if two scalar expressions satisfy the specified comparison operator.

Advanced comparison operators are: LIKE, BETWEEN, and IN.

LIKE operator

```

cql2_text(name %like% "Smith%")
#> name LIKE 'Smith%'
cql2_json(name %like% "Smith%")
#> {"op": "like", "args": [{"property": "name"}, "Smith%"]}

```

BETWEEN operator

```

cql2_text(between(depth, 100.0, 150.0))
#> depth BETWEEN 100 AND 150
cql2_json(between(depth, 100.0, 150.0))
#> {"op": "between", "args": [{"property": "depth"}, 100, 150]}

```

IN operator

```

cql2_text(cityName %in% list('Toronto', 'Frankfurt', 'Tokyo', 'New York'))
#> cityName IN ('Toronto', 'Frankfurt', 'Tokyo', 'New York')
cql2_json(cityName %in% list('Toronto', 'Frankfurt', 'Tokyo', 'New York'))
#> {"op": "in", "args": [{"property": "cityName"}, ["Toronto", "Frankfurt", "Tokyo", "New York"]}]}

```

```

cql2_text(!category %in% list(1, 2, 3, 4))
#> category NOT IN (1,2,3,4)
cql2_json(!category %in% list(1, 2, 3, 4))
#> {"op": "not", "args": [{"op": "in", "args": [{"property": "category"}, [1, 2, 3, 4]}]}]}

```

Spatial operators

A spatial predicate evaluates if two spatial expressions satisfy the specified spatial operator.

The supported spatial operators are: S_INTERSECTS, S_EQUALS, S_DISJOINT, S_TOUCHES, S_WITHIN, S_OVERLAPS, S_CROSSES, and S_CONTAINS.

```
poly <- list(type = "Polygon",
             coordinates = list(matrix(c(0,0,0,0,1,1), ncol = 2)))
cql2_text(s_intersects(geometry, {{poly}}))
#> S_INTERSECTS(geometry,POLYGON((0 0,0 1,0 1)))
cql2_json(s_intersects(geometry, {{poly}}))
#> {"op":"s_intersects","args":[{"property":"geometry"}, {"type":"Polygon",
  "coordinates": [[[0,0],[0,1],[0,1]]]]}]}
```

Note: We provide an escape to evaluate user variables using {{ or !!. Both symbols are largely used in the R Data Science community.

Temporal operators

A temporal predicate evaluates if two temporal expressions satisfy the specified temporal operator.

The supported temporal operators are: T_AFTER, T_BEFORE, T_CONTAINS, T_DISJOINT, T_DURING, T_EQUALS, T_FINISHEDBY, T_FINISHES, T_INTERSECTS, T_MEETS, T_METBY, T_OVERLAPPEDBY, T_OVERLAPS, T_STARTEDBY, and T_STARTS.

```
cql2_text(t_intersects(event_date, interval("1969-07-16T05:32:00Z", "1969-07-24
T16:50:35Z")))
#> T_INTERSECTS(event_date,INTERVAL('1969-07-16T05:32:00Z','1969-07-24T16:50:35Z
'))
cql2_json(t_intersects(event_date, interval("1969-07-16T05:32:00Z", "1969-07-24
T16:50:35Z")))
#> {"op":"t_intersects","args":[{"property":"event_date"}, {"interval
": ["1969-07-16T05:32:00Z", "1969-07-24T16:50:35Z"]}]}]
```

Support for functions in CQL2

Functions allow implementations to extend the language.

Example of a function that returns a geometry value.

```
cql2_text(s_within(road, Buffer(geometry, 10, "m")))
#> S_WITHIN(road,Buffer(geometry,10,'m'))
cql2_json(s_within(road, Buffer(geometry, 10, "m")))
#> {"op":"s_within","args":[{"property":"road"}, {"function":{"name":"Buffer",
  "args": [{"property":"geometry"},10,"m"]}]}]
```

Appendix B - rstac CQL2 conformance tests

Here, we list the conformance tests implemented in the rstac test suite. The tests run against “Test Dataset for the CQL2 Test Suite” [<https://cql2test.ldproxy.net/ne110m4cql2>] STAC service. rstac implements all conformance tests that aim to test predicates against the test dataset (except for conformance test #22, which is not present in “Test Dataset for the CQL2 Test Suite”).

Conformance Test	Number of tests
#7	27
#12	14
#16	10
#25	5
#34	12
#38	23
#45	7

References

- Finer, Matt, Sidney Novoa, Mikaela J. Weisse, Rachael Petersen, Joseph Mascaro, Tamia Souto, Forest Stearns, and Raúl García Martínez. 2018. “Combating Deforestation: From Satellite to Intervention.” *Science* 360 (6395): 1303–5. <https://doi.org/10.1126/science.aat1203>.
- OGC. 2019. *OGC API - Features - Part 1: Core*. Edited by Clemens Portele, Panagiotis A. Vretanos, and Charles Heazel. Version: 1.0. OGC Implementation Standard. OGC. <http://www.opengis.net/doc/IS/ogcapi-features-1/1.0>.
- . 2022. *Common Query Language (Cql2)*. Edited by Clemens Portele, Panagiotis A. Vretanos, and Charles Heazel. Version: 1.0.0-rc.1. OGC Implementation Standard. OGC. <http://www.opengis.net/doc/IS/cql2/1.0>.
- Simoes, Rolf, Felipe Carvalho de Souza, Matheus Zaglia, Gilberto Ribeiro de Queiroz, Rafael D. C. dos Santos, and Karine Reis Ferreira. 2021. “Rstac: An R Package to Access Spatiotemporal Asset Catalog Satellite Imagery.” In *2021 IEEE International Geoscience and Remote Sensing Symposium IGARSS*, 7674–77. Brussels, Belgium: IEEE. <https://doi.org/10.1109/IGARSS47720.2021.9553518>.
- Wagemann, Julia, Stephan Siemen, Bernhard Seeger, and Jörg Bendix. 2021. “A User Perspective on Future Cloud-Based Services for Big Earth Data.” *International Journal of Digital Earth* 14 (12): 1758–74. <https://doi.org/10.1080/17538947.2021.1982031>.
- Wickham, Hadley. 2019. *Advanced R*. 2nd. ed. CRC press. <https://adv-r.hadley.nz>.