

It is a tradition to use Turbo C for graphics in C/CPP. But it's also a pain in the neck. Here we are using Code::Blocks IDE, which will ease out our work.

Steps to run graphic code in CodeBlocks

1. Install Code::Blocks

- Make sure you have installed Code::Blocks IDE on your machine. If you don't have this IDE or have any issues with the compiler download and install it from here.
 - <http://sourceforge.net/projects/codeblocks/files/Binaries/16.01/Windows/codeblocks-16.01mingw-setup.exe>

2. Download the required header files

- We need a few files to be included in the lib folder of Code::Blocks.
- Download the files from here
 - <https://github.com/TheCiceerGuy/Graphics-Library>

3. Include graphics.h and winbgim.h

- Copy and Paste the **graphics.h** and **winbgim.h** files into **include folder** of Code::Blocks directory.
- Path:
 - **C:\Program Files (x86)\CodeBlocks\MinGW\include**

4. Include libbgi.a

- Copy and paste **libbgi.a** file in the **lib folder** of Code:Blocks
- Path:
 - **C:\Program Files (x86)\CodeBlocks\MinGW\lib**

5. Add Link Libraries in Linker Setting

- In the Code::Blocks application go to, **Settings > Compiler**
- In the **Global Compiler** setting, click on the **Linker Settings**
- In **Link Libraries**, Add and browse to C:\Program Files (x86)\CodeBlocks\MinGW\lib\ and select libbgi.a.
- Paste this in the Other Linker Option tab of Linker Settings (i.e. on the right-hand side)
-lbgi -lgdi32 -lcomdlg32 -luuid -loleaut32 -ole32
- Save the setting and restart the application

To test the setting, copy and paste the computer graphics code below to draw a circle:

```
#include <graphics.h>
#include <conio.h>

int main() {
    int gd = DETECT, gm;
    char driverPath[] = ""; // Fixes string constant warning

    initgraph(&gd, &gm, driverPath);
    circle(300, 300, 50);

    getch();
    closegraph();

    return 0;
}
```