

Programmieren 1



Atomic Data and Functions

Lectures


#	Date	Topic	HÜ→	HÜ←
1	14.10.	Organization, computers, programming, algorithms, PostFix introduction (execution model, IDE, basic operators, booleans, naming)	1	20.10. 23:59
2	21.10.	PostFix (primitive types, functions, parameters, local variables, tests), recipe for atomic data	2	27.10. 23:59
3	28.10.	PostFix (operators, array operations, string operations), recipes for enumerations, intervals, and itemizations	3	3.11. 23:59
4	4.11.	Recipes for compound and variant data, iteration and recursion, PostFix (loops, association arrays, data definitions)	4	10.11. 23:59
5	11.11.	C introduction (if, variables, functions, loops), Programming I C library	5	17.11. 23:59
6	18.11.	Data types, infix expressions, C language (enum, switch)	6	24.11. 23:59
7	25.11.	Compound and variant data, C language (formatted output, struct, union)	7	1.12. 23:59
8	2.12.	C language (arrays, pointers) arrays: fixed-size collections, linear and binary search	8	8.12. 23:59
9	9.12.	Dynamic memory (malloc, free), recursion (recursive data, recursive algorithms)	9	15.12. 23:59
10	16.12.	Linked lists, binary trees, search trees	10	22.12. 23:59
online → 11	23.12.	C language (program structure, scope, lifetime, linkage), function pointers, pointer lists	11	12.1. 23:59
12	13.1.	List and tree operations (filter, map, reduce), objects, object lists	12	19.1. 23:59
13	20.1.	Dynamic data structures (stacks, queues, maps, sets), iterators, documentation tools	(13)	
14	27.1.	C language (remaining C keywords), finite state machines, quicksort	(14)	

Review

- Programs = data (operands) and instructions (operators)
- Operators: arithmetic, logical, relational/equality
- PostFix execution model and environment
- Assignment (of a value to a name)
- Selection (conditional execution, if)
- Iteration (repeated execution, loop)
- Algorithms



stack of operands



named values


Preview

- PostFix
 - Types, data arrays, executable arrays
- Functions
 - Functions are named, reusable pieces of computation
 - Functions have parameters
 - Functions have local variables
- How to Design Programs
 - From problem statement to well-organized solution
- Simple Atomic (Nondivisible) Data

POSTFIX


Types

Data in PostFix is categorized into different types



Types

- | | |
|----------------|---|
| :Nil | value nil, "nothing" |
| :Bool | values true and false |
| :Int | signed integer values 123 |
| :Flt | floating-point values, 0.123 |
| :Num | numbers, either :Int or :Flt |
| :Str | strings, i.e., sequences of characters, enclosed in "..." |
| :Arr | arrays of arbitrary objects, written as [...] |
| :ExeArr | executable arrays of arbitrary objects, written as {...} |
| :Params | parameter lists, written as (...) |
| :Sym | symbols (names), written with a preceding or trailing colon, i.e., :x and x: denote the same symbol |



Arrays

- A collection of any number of elements
 - Array elements may be of different types
 - Array elements are accessed by their index (zero-based)
- Data arrays
 - `[]`
 - `[1 "two" false 3.14]`
 - `[1 [2 3]]`
- Executable arrays
 - `{ }`
 - `{1 "two" false 3.14}`
 - `{1 {2 3}}`
- Array operators
 - `[10 20 30] length → 3`
 - `[10 20 30] 0 get → 10`
 - `[10 20 30] 1 get → 20`
 - `[10 20 30] .1 → 20` # abbreviation for `[...] 1 get`

Data Arrays vs. Executable Arrays

- Parsing data arrays [...]: Elements executed immediately
- Parsing executable arrays {...}: Execution of elements is deferred (done later)
 - When executable array is being parsed, interpreter is in "deferred mode"
- Example program source code: [1 2 +] {1 2 +}

next token	stack
[ArrOpen
1	ArrOpen Int(1)
2	ArrOpen Int(1) Int(2)
+	ArrOpen Int(3)
]	Arr(Int(3))

next token	stack
{	ExeArrOpen
1	ExeArrOpen Int(1)
2	ExeArrOpen Int(1) Int(2)
+	ExeArrOpen Int(1) Int(2) Plus
}	ExeArr(Int(1) Int(2) Plus)

- Program result: [3] {1 2 +}
 a data array with one element an executable array with three elements

Executable Arrays

- Explicit execution of an executable array
`{1 2 +} exec` `# result: 3`
- Conditional execution of an executable array
`true {1 2 +} if` `# result: 3`
- Executable arrays are executed when referenced in dictionary
`{1 2 +} f!` `# store f → {...} in dictionary`
`f` `# reference and execute, result: 3`
- Referencing the array without executing
`:f vref` `# {1 2 +} (vref = value reference)`
`exec` `# explicit execution, result: 3`

Referenced Values are Automatically Executed

- Referencing: Looking up in dictionary and executing
`f` `# name without colon`
- Value-referencing: Referencing without executing, pushing
`:f` `# with colon, just push name on stack`
`vref` `# lookup value, but don't execute`
`exec` `# explicitly execute`

Two Ways of Naming Values

value name!

3 x!

4 y!

is equivalent to: name: value !

x: 3 !

y: 4 !

note the space

missing space

1

x: 1!

Error: Invalid variable name "1"

Choosing Names for Variables and Constants

- Short but meaningful names
 - Examples: `sum`, `greeting`
- Very short names for short-lived variables
 - Only used in small scope, e.g., for counting, indexing
 - Examples: `i`, `j`, `x`
- Longer name for long-lived variables
 - More descriptive
 - Need to be understood in larger scope
 - Examples: `input-text`, `input_text`, `inputText`
- Don't make the type name part of the variable name

FROM EXECUTABLE ARRAYS TO FUNCTIONS

From Executable Arrays to Functions

- We may give a name to a piece of code:

```
>> { 1 + } f! # Executable array { 1 + } is given the name f.
           # The stack is now empty.

>> 10 f      # The executable array is referenced...
11           # processes 10 and produces 11

>> f         # The executable array is referenced again...
12           # processes 11 and produces 12
```

From Executable Arrays to Functions

Program: { 1 + } f! 10 f f

Tokens	Stack	Dictionary	Comment
{ 1 + }	{ 1 + }		Push executable array on the stack
f!		f → { 1 + }	Enter executable array into dictionary
10	10	f → { 1 + }	Push 10
f	10	f → { 1 + }	Lookup f, execute array
1	10 1	f → { 1 + }	Push 1
+	11	f → { 1 + }	Execute +
f	11	f → { 1 + }	Lookup f, execute array
1	11 1	f → { 1 + }	Push 1
+	12	f → { 1 + }	Execute +

From Executable Arrays to Functions

- Executable array to compute $f(x) = x^2$:

```
>> { dup * } f! # Associate name f with this executable array.
      # The stack is now empty.
>> 3 f          # Duplicate the topmost value on the stack
      # and multiply it with itself.
9              # The result.
```

From Executable Arrays to Functions

Program: { dup * } f! 3 f

Tokens	Stack	Dictionary	Comment
{ dup * }	{ dup * }		Push executable array on stack
f!		f → { dup * }	Enter in dictionary
3	3	f → { dup * }	Push 3
f	3	f → { dup * }	Lookup f, execute array
dup	3 3	f → { dup * }	Duplicate top stack element
*	9	f → { dup * }	Execute *

Defining Variables in an Executable Array

Program: { x! x x * } f! 3 f

Tokens	Stack	Dictionary	Comment
{ x! x x * }			Push exec. array on the stack
f!		f → { x! x x * }	Enter exec. array into dict.
3	3	f → { x! x x * }	Push 3
f	3	f → { x! x x * }	Lookup f, execute array
x!		f → { x! x x * }, x → 3	Store argument in dict.
x	3	f → { x! x x * }, x → 3	Lookup x
x	3 3	f → { x! x x * }, x → 3	Lookup x, again
*	9	f → { x! x x * }, x → 3	Execute *

Defining Variables in an Executable Array

- With just one dictionary:

100 x!	# set x to 100
{ x! x x * } f!	# store executable array in dictionary
3 f	# executing f changes x to 3
x println	# output: 3, not 100

Defining Variables in an Array with a Local Dictionary

- Executable array with its own dictionary

```

100 x!
{ x! x x * } lam f!
3 f
x println

```

note the
lam

```

# set x to 100
# add new dict. to {...}, then store {...} in outer dict.
# x in {...} is different from outer x
# output: 100

```

Defining Variables in an Array without a Local Dictionary

Program: 100 x! { x! x x * } f! 3 f

Tokens	Stack	Dictionary	Comment
100	100		Push 100
x!		x → 100	Store 100 in dictionary
{...}	{...}	x → 100	Push exec. array on the stack
f!		x → 100, f → {...}	Store exec. array in dictionary
3	3	x → 100, f → {...}	Push 3
f	3	x → 100, f → {...}	Lookup f, execute array
x!		x → 3, f → {...}	Store argument in dict.
...

Defining Variables in an Array with a Local Dictionary

Program: 100 x! { x! x x * } lam f! 3 f

Tokens	Stack	Dictionary	Comment
100	100		Push 100
x!		x → 100	Store 100 in dictionary
{...}	{...}	x → 100	Push exec. array on the stack
lam	{...} lam	x → 100	Add copy of dict. to exec. array
f!		x → 100, f → {...} lam	Store exec. array in dictionary
3	3	x → 100, f → {...} lam	Push 3
f	3	x → 100	Lookup f, exec. array, switch dicts.
...

Defining Variables in an Array with a Local Dictionary

Program: 100 x! { x! x x * } lam f! 3 f





Tokens	Stack	Dictionary	Comment
...
f	3	x → 100	Lookup f, execute array, switch dicts.
x!		x → 3	Store argument in current dict.
x x	3 3	x → 3	Reference (execute) x twice
*	9	x → 3	Perform multiplication
	9	x → 100, f → {...} lam	Return from f, the outer dictionary is restored as the current dictionary

Local Variables


- Executing an executable array with a local dictionary
 - Make the local dictionary the current dictionary
 - Execute the contents of the array
 - Restore the previous dictionary

⇒ There is a stack of dictionaries

Current
Dictionary:



Program:



exec

time



Defining Functions in PostFix

- Functions in PostFix are executable arrays with a local dictionary
- How to define functions:
 1. `{...} lam f!`
 2. `f: {...} lam !` # equivalent to 1.
 3. `f: {...} fun` # equivalent to 2. (except puts f in f's dictionary)

fun stands for "function"
(not for fun, obviously)

Visibility of Variables

- `lam` and `fun` create independent copies of the current dictionary
- So, everything that is in the current dictionary when `lam` is executed is also present (visible) in the copied dictionary

Visibility of Variables

Program: 7 x! f: { y! x y * } fun 3 f

Tokens	Stack	Dictionary	Comment
7 x!		x → 7	
f: {...}	f: {...}	x → 7	
fun		x → 7, f → {...} lam	Copy current dict., associate copy with {...}, enter f → {...} lam
3	3	x → 7, f → {...} lam	
f	3	x → 7	Reference (execute) f: f's local dict. becomes the current dictionary
y!		x → 7, y → 3	Store y → 3 in the current dict.
x y *	21	x → 7, f → {...} lam	Return from f, restore the outer dict.

Functions

- Function: A reusable piece of code with a well-defined interface
 - Don't repeat yourself (DRY) principle
- An important form of abstraction
 - Functions encapsulate some computation
- Functions provide a well-defined interface
 - Describe **what** is done, ignore how
- Functions have an implementation
 - Defines **how** to compute the result from the parameters
- Not identical to functions in mathematics
 - Function may produce output or read input in addition to returning a result (side effects)
 - Some languages use the term "procedure"

Function: Difference between Two Numbers

```
minus: { x! y!   # defining function minus
        x y -
      } fun
```

```
1 2 minus      # calling function minus with arguments 1 and 2
```

Result: 1

Why?

Function: Difference between Two Numbers

Program: `diff: { x! y! x y - } fun 1 2 diff`

Tokens	Stack	Dictionary	Comment
1	1	<code>diff → {...} lam</code>	Push 1
2	1 2	<code>diff → {...} lam</code>	Push 2
<code>diff</code>	1 2		Reference (execute) <code>diff</code> : <code>diff</code> 's local dict. becomes the current dict.
<code>x!</code>	1	<code>x → 2</code>	Store <code>y → 2</code> in current dict.
<code>y!</code>		<code>x → 2, y → 1</code>	Store <code>y → 1</code> in current dict.
<code>x y</code>	2 1	<code>x → 2, y → 1</code>	Reference (execute) <code>x</code> and <code>y</code>
<code>-</code>	1	<code>x → 2, y → 1</code>	Compute the difference
	1	<code>diff → {...} lam</code>	Return from <code>diff</code> , restore the outer dictionary

Parameter Lists

- Reverse variable assignments:

```
minus: { y! x!  
      x y -  
} fun      1 2 minus # returns -1
```

- or use parameter lists:
- Parameter lists specify the parameters of a function

```
minus: (x y) {  
      x y -  
} fun      1 2 minus # returns -1
```

Parameter Lists with Types

- Parameter lists with types specify the inputs (arguments) and outputs (return values) of a function:

```
minus: (x :Num, y :Num -> :Num) {  
    x y -  
} fun
```

- Read parameter list as:
"The function takes two numbers as input and returns a single number. Within the function, the first input is named x and the second input is named y."

A Function on Strings

- Program:

```
emphasize: (s :Str -> :Str) {  
    s "!" +  
}  
fun  
"hello" emphasize
```

- Result:

```
"hello!"
```

HOW TO DESIGN PROGRAMS

Steps in Programming

From a problem statement to a well-organized solution

1. Problem statement
2. Data definition
3. Function name and parameter list
4. Function stub and purpose statement
5. Examples with expected results
6. Implementation
7. Test and revision

based on: http://www.ccs.neu.edu/home/matthias/HtDP2e/Draft/part_one.html

1. Problem statement (given)

"Design a function that converts degrees Celsius to degrees Fahrenheit."

The problem statement should answer these questions:


- What information needs to be represented?
- What should the program do with the data?
- What cases need to be considered?

2. Write a data definition

Express how you wish to represent information as data.

"temperature is a number"

"interpretation of the number is degrees Celsius"



based on: http://www.ccs.neu.edu/home/matthias/HtDP2e/Draft/part_one.html

3. Write a function name and parameter list


```
celsius-to-fahrenheit: (celsius :Int -> :Int)
```

function
name

parameter name
and type (input)

result type
(output)

Function consumes arguments and produces results



4. Write a function stub and purpose statement (documentation)

```
# Takes a temperature value in degrees Celsius and
# returns the corresponding value in degrees Fahrenheit.
```

```
celsius-to-fahrenheit: (celsius :Int -> :Int) {
```

```
  0
} fun
```

stub returns
arbitrary integer
value

- The function stub returns an arbitrary value from the function's domain.
- Runs, but does not provide the correct result yet.


```
#<
Diese Funktion quadriert eine Zahl.
@param x Zahl die quadriert wird.
@return Gibt das Quadrat der übergebenen Zahl zurück.
>#
sq square: ( x :Num -> :Num ) fun
  Diese Funktion quadriert eine Zahl.
  @param x – Zahl die quadriert wird.
  @return Gibt das Quadrat der übergebenen Zahl zurück.
4 square
```

5. Give examples with expected results

- Formula: $^{\circ} F = ^{\circ} C * 9 / 5 + 32$
- Given: 0, expect: 32
- Given: 10, expect: 50
- Given: -5, expect: 23
- Given: 100, expect: 212

6. Implement the function body

```
celsius-to-fahrenheit: (celsius :Int -> :Int) {  
    celsius 9 * 5 div 32 +  
} fun
```



div is the integer
division operator

The implementation defines how to compute the result from the parameters.

Implementing: Comments First

- When implementing it is often helpful to start with comments that describe the steps of algorithm and then implementing them.
- Example:
 - // Determine number of characters of result
 - // Allocate required memory
 - // Run through input and copy required characters
 - // Terminate the result string
- This already shows you the skeleton of your solution.

7a. Test the function

Apply the function to the test examples and check whether it yields the expected results:

- `0 celsius-to-fahrenheit # expect: 32`
- `10 celsius-to-fahrenheit # expect: 50`
- `-5 celsius-to-fahrenheit # expect: 23`
- `100 celsius-to-fahrenheit # expect: 212`

7b. Review and revise the function

Review and revise the function name, the parameter names, and the purpose statement. Improve them if necessary. The purpose statement should describe what the function computes (not how) and should mention the given inputs and produced result.

```
# Takes a temperature value in degrees Celsius
# and returns the corresponding value in
# degrees Fahrenheit.
celsius-to-fahrenheit: (celsius :Int -> :Int) {
    celsius 9 * 5 div 32 +
} fun
```

Complete Program (in celsius-to-fahrenheit.pf)

```
# Takes a temperature value in degrees Celsius  
# and returns the corresponding value in  
# degrees Fahrenheit.
```

```
celsius-to-fahrenheit: (celsius :Int -> :Int) {  
    celsius 9 * 5 div 32 +  
} fun
```

```
0 celsius-to-fahrenheit # expect: 32  
10 celsius-to-fahrenheit # expect: 50  
-5 celsius-to-fahrenheit # expect: 23  
100 celsius-to-fahrenheit # expect: 212
```

Test Cases

- A test case compares the actual result and expected result
 - `actual expected test=`
- Example
 - If function `celsius-to-fahrenheit` is given 0, we expect 32 as the result
 - Test case: `0 celsius-to-fahrenheit 32 test=`
- If actual is equal to expected result, then the output is:
`Check passed.`
- Otherwise the output is:
`Actual value 99 differs from expected value 32.`

Complete Program with Test Cases

```
# Takes a temperature value in degrees Celsius
# and returns the corresponding value in
# degrees Fahrenheit.
```

```
celsius-to-fahrenheit: (celsius :Int -> :Int) {
    celsius 9 * 5 div 32 +
} fun
```

```
0 celsius-to-fahrenheit 32 test=
10 celsius-to-fahrenheit 50 test=
-5 celsius-to-fahrenheit 23 test=
100 celsius-to-fahrenheit 212 test=
test-stats # print test statistics
```

Complete Program with Test Cases

```
0 celsius-to-fahrenheit 32 test=✓  
10 celsius-to-fahrenheit 50 test=✓  
-5 celsius-to-fahrenheit 23 test=✓  
100 celsius-to-fahrenheit 212 test=✓  
test-stats # print test statistics
```

✓ All 4 tests passed

RECIPE FOR ATOMIC DATA

Design Recipes

- Recipe for Atomic Data
- Recipe for Enumerations
- Recipe for Intervals
- Recipe for Itemizations
- Recipe for Compound Data (Product Types)
- Recipe for Variant Data (Sum Types)

Atomic Data

- Smallest conceptual unit of data
- Cannot be broken down further
- Example data types
 - integer numbers: -123 (:Int)
 - floating-point numbers: 3.14 (:Flt)
 - Boolean values: true, false (:Bool)
 - Strings: "hello" (:Str)

Strings are treated as atomic here, even though strings consist of characters

Steps in Programming

From a problem statement to a well-organized solution

1. Problem statement
2. Data definition
3. Function name and parameter list
4. Function stub and purpose statement
5. Examples with expected results
6. Implementation
7. Test and revision

based on: http://www.ccs.neu.edu/home/matthias/HtDP2e/Draft/part_one.html

1. Problem Statement

- Write down the problem statement as a comment.
 - What information needs to be represented?
 - What should the function (to be implemented) do with the data?
 - What cases need to be considered?

- Example

#<


Design a function that computes weekly wages with overtime from hours worked. The hourly rate is 10 €/hour. Regular working time is 40 hours/week. Overtime is paid 150% of the normal rate of pay.

>#

2. Data Definition

- How should domain information be represented as data in the program?
- How to interpret the data as real-world information?

- Informal data definition (comment)
:Int represents hours worked
:Int represents wage in cents



3. Function Name and Parameter List

- Find a good function name
 - Short, non-abbreviated, descriptive name that describes what the function does
- Find good parameter names
 - Short, non-abbreviated, descriptive name that describes what the parameter means
- Write parameter list
 - Parameter names and types left of the arrow
 - Result type right of the arrow
- Example

`hours-to-wages: (hours :Int -> :Int)`

4a. Function Stub

- Function stub returns an arbitrary value from the function's range
- The function stub compiles

- Example

```
hours-to-wages: (hours :Int -> :Int) {  
    0  
} fun
```

4b. Purpose Statement

- Briefly describes what the function does. Ideally as a single sentence. Multiple sentences may be necessary.
- Example
 - # Compute the wage in cents given the number of hours worked.

5. Examples with Expected Results

- Examples (wage is 10 € per hour, 15 € for overtime)
 - For 0 hours worked, expect 0 cents.
 - For 20 hours worked, expect $20 * 1000$ cents.
 - For 39 hours worked, expect $39 * 1000$ cents.
 - For 40 hours worked, expect $40 * 1000$ cents.
 - For 41 hours worked, expect $40 * 1000 + 1 * 1500$ cents.
 - For 45 hours worked, expect $40 * 1000 + 5 * 1500$ cents.

5. Examples with Expected Results (Test Function)

- Comparison of actual and expected result
- Examples (wage is 10 € per hour, 15 € for overtime)

```
hours-to-wages-test: {
    0 hours-to-wages 0 test=
    20 hours-to-wages 20 1000 * test=
    39 hours-to-wages 39 1000 * test=
    40 hours-to-wages 40 1000 * test=
    41 hours-to-wages 40 1000 * 1 1500 * + test=
    45 hours-to-wages 40 1000 * 5 1500 * + test=
    test-stats
} fun
```

6. Function Body

- Implementation of the function

- Example

```
hours-to-wages: (hours :Int -> :Int) {
  hours 40 <= {
    hours 1000 *
  } {
    40 1000 * hours 40 - 1500 * +
  } if
} fun
```

7a. Testing

- Call test function
`hours-to-wages-test`
- Test results
 - wages.pf, line 27: Check passed.
 - wages.pf, line 28: Check passed.
 - wages.pf, line 29: Check passed.
 - wages.pf, line 30: Check passed.
 - wages.pf, line 31: Check passed.
 - wages.pf, line 32: Check passed.
 - All 6 tests passed!

7b. Review and Revise

- Review the products of the steps
 - Improve function name
 - Improve parameter names
 - Improve purpose statement
 - Improve and extend tests
- Generalize the function
 - Constants
 - Templates for future functions on this data

Constants

- Don't hardcode literal values, don't repeat them
 - Don't repeat yourself (DRY) principle
- Instead: Define constants
- Constants give a name to a value
- Example

```
40 WEEKLY_HOURS! # regular work hours per week
1000 HOURLY_RATE_REGULAR! # in cents
1500 HOURLY_RATE_OVERTIME! # in cents
```

Generalizing the Function with Constants

```
hours-to-wages: (hours :Int -> :Int) {  
  hours 40 <= {  
    hours 1000 *  
  } {  
    40 1000 *  
    hours 40 - 1500 * +  
  } if  
} fun
```

Generalizing the Function with Constants

```

40 WEEKLY_HOURS! # regular work hours per week
1000 HOURLY_RATE_REGULAR! # in cents
1500 HOURLY_RATE_OVERTIME! # in cents

hours-to-wages: (hours :Int -> :Int) {
  hours WEEKLY_HOURS <= {
    hours HOURLY_RATE_REGULAR *
  } {
    WEEKLY_HOURS HOURLY_RATE_REGULAR *
    hours WEEKLY_HOURS - HOURLY_RATE_OVERTIME * +
  } if
} fun

```

Generalizing the Function with Additional Parameters

```

hours-to-wages: (
  weekly-hours :Int,
  hourly-rate-regular :Int,
  hourly-rate-overtime :Int,
  hours-worked :Int
-> :Int)
{
  hours-worked weekly-hours <= {
    hours-worked hourly-rate-regular *
  } {
    weekly-hours hourly-rate-regular *
    hours-worked weekly-hours - hourly-rate-overtime * +
  } if
} fun

```

Literal values, constants, or parameters?

- Is it a good idea to
 - generalize a function with constants?
 - generalize a function with additional parameters?
- It depends...!
 - Functions should be flexible pieces of computation
 - Functions should be easy to use
 - More parameters → more flexible, but more effort to use
 - Compromise: Constants for rarely changing data, parameters for frequently changing data

Use Constants and Parameters

- Constants for rarely changing data
- Parameters for frequently changing data
- Example (assuming WEEKLY_HOURS and OVERTIME_FACTOR change infrequently):

```
hours-to-wages: (hours :Int, rate :Int -> :Int) {
  hours WEEKLY_HOURS <= {
    hours rate *
  } {
    WEEKLY_HOURS rate *
    hours WEEKLY_HOURS - rate OVERTIME_FACTOR * *
    + round int
  } if
} fun
```

Helper Functions on a Wish List

- Designing functions requires thought
- A **different concern** should be outsourced in a helper function
 - A function should perform one well-defined task
- A **reusable subtask** should be outsourced in a helper function
 - Don't Repeat Yourself (DRY)
- When implementing a function you may find parts that (a) are different concerns or (b) are reusable subtasks
 - Put required helper functions on a wish list
 - Implement a stub for the helper functions

Summary

- PostFix
 - Types, data arrays, executable arrays
- Functions
 - Functions are named, reusable pieces of computation
 - Functions have parameters
 - Functions have local variables
- How to Design Programs
 - From problem statement to well-organized solution
- Simple Atomic (Nondivisible) Data