
CBL003

- 1. CBL003 CONNECTS EARTH GROUND BETWEEN THE RR-300-72 SMPS, MAGENTIC SHIELD, AND PEM
- 2. MAXIMUM VOLTAGE: 256 VAC (EMERGENCY ONLY)
- 3. BLADE CONNECTS ARE SIZED FPR 0.187" TERMINALS
- 4. BLADE CONNECTOR CRIMPS MAY BE SUBSTITUTED
- 5. 3-POSITION WAGO CONNECTOR MAY BE SUBSTITUTED WITH CRIMP
- 6. SILICONE WIRE INSULATION PREFERRED
- 7. UL WIRE STYLE 1430



CONDUCTOR	FROM REF.	WIRE	CRIMP
1	RR-300-72 SMPS GND	20 AWG, GREEN, STRANDED	1742883-1
2	MAGNETIC SHIELD	20 AWG, GREEN, STRANDED	1742883-1
3	PEM GND	20 AWG, GREEN, STRANDED	1742883-1

	REVISION HISTORY								
ZONE	REV	DESCRIPTION	DATE	ATE APPROVED					
	Α	INITIAL RELEASE	[24.06.12]	J. PHILLIPS					
	В	ADDED UL WIRE STYLE	[24.07.01]	J. PHILLIPS					

DESIGNED J. PHILLIPS	[24.06.12]				
APPROVED J. PHILLIPS [24.06.12]					
TITLE CBL003		RO			6
UNLESS OTHERWISE SPECIFIED		KU	DU		
		DEPARTMENT	PROJECT CODE PC-02		
			PROTOTYPE CO REVB	DE	
			UNITS mm	SCALE 1:2	SHEET NO. 1/1

