

SUMO SYSTEMS / STORAGE PLUS, INC.

SPI 200

Formerly the SCSI AT-R1




Data bus: 8-bit, ISA

Size: Half-length, full-height card

Hard drives supported: Up to seven SCSI devices

Floppy drives supported: Two 320KB, 720KB, 1.2MB OR 1.44MB



CONNECTIONS	
Function	Location
50-pin SCSI connector-internal	CN2
50-pin SCSI connector-external	CN3
34-pin control cable connector-floppy drive	CN4
4-pin connector-LED Drive Active	CN5

USER CONFIGURABLE SETTINGS			
Function		Location	Setting
»	Zero Wait State enabled	JP1/jumper 1	closed
	Zero Wait State disabled	JP1/jumper 1	open
»	Factory configured - do not alter	JP1/jumper 2	open
»	Floppy drive enabled	JP1/jumper 3	closed
	Floppy drive disabled	JP1/jumper 3	open

BIOS ADDRESS				
Address		JP1/jumper 4	JP1/jumper 5	JP1/jumper 6
»	D800h	closed	open	closed
	Disabled	open	open	open
	C800h	closed	closed	closed
	CC00h	open	closed	closed
	DC00h	open	open	closed

I/O PORT ADDRESS					
Address		JP1/jumper 7	JP1/jumper 8	JP1/jumper 9	JP1/jumper 10
	Disabled	N/A	N/A	N/A	open
	300h	closed	closed	closed	closed
»	310h	open	closed	closed	closed
	320h	closed	open	closed	closed
	330h	open	open	closed	closed
	340h	closed	closed	open	closed
	350h	open	closed	open	closed

