ervice Mal

Radio Cassette

Stereo Radio Cassette Player

64

Colour

₹ Black Type



Area

Ŝ	Europe F.R. Germany and Italy.	[E]
Colou	Areas	Suffix for



radiomuseum.org

radiomuseum.org

■ SPECIFICATIONS General:

Power Requirement: Battery: 3V (Two "AA" size, R6/LR6

batteries)

Headphones; 20 \(\rho\), \(\phi\)3.5 40mW (20mWx2)···RMS (max.)

Output: Dimensions:

Weight:

Power Output:

85.4(W)×120.1(H)×36.6(D)mm

166g without batteries

Radio Section: Radio Frequency Range: FM; 87.5~ 108MHz

Intermediate Frequency:

FM; 10.7MHz

AM; 520~1610kHz

Am; 459kHz

FM; $3.98 \mu V/0.5 mW$ output

-3dB Limit,

Sens)

AM; $100 \mu V/m/0.5 mW$ output

Sensitivity:

Frequency Response Tape Deck Section:

Program Tape Speed: Time:

−6dB)

Track System:

? · Notes:

Weights and dimensions shown are approximate

Design and

specifications

are

subject to

change without notice.

40~16,000Hz (Normal, CrO₂/Metal)

4-track, 2-channel, stereo playback hour with C-60 cassette tape

WARNING

A WARNING

This service information is designed for experienced repair technicians only and is not designed for use by the general public. It does not contain warnings or cautions to advise non-technical individuals of potential dangers in attempting to service a product. Products powered by electricity should be serviced or repaired only by experienced professional technicians. Any attempt to service or repair the product or products dealt with in this service information by anyone else could result in serious injury or death.

© 1995 Matsushita Electric Industrial Co., Ltd. All rights reserved. Unauthorized copying and distribution is a violation of law.