NTMSD3P102R2

FETKY™

P−Channel Enhancement−Mode Power MOSFET and Schottky Diode Dual SO−8 Package

Features

- High Efficiency Components in a Single SO−8 Package
- High Density Power MOSFET with Low $R_{DS(on)}$, Schottky Diode with Low V_F
- Independent Pin−Outs for MOSFET and Schottky Die Allowing for Flexibility in Application Use
- Less Component Placement for Board Space Savings
- SO−8 Surface Mount Package, Mounting Information for SO−8 Package Provided
- Pb−Free Packages are Available

Applications

- DC−DC Converters
- Low Voltage Motor Control
- Power Management in Portable and Battery−Powered Products, i.e.: Computers, Printers, PCMCIA Cards, Cellular and Cordless Telephones

MOSFET MAXIMUM RATINGS (T_J = 25°C unless otherwise noted).

Rating	Symbol	Value	Unit
Drain−to−Source Voltage	V_{DSS}	−20	V
Gate−to−Source Voltage − Continuous	V_{GS}	±20	V
Thermal Resistance − Junction−to−Ambient (Note 1) Total Power Dissipation @ T_A = 25°C Continuous Drain Current @ T_A = 25°C Continuous Drain Current @ T_A = 70°C Pulsed Drain Current (Note 4)	$R_{\theta JA}$ P_D I_D I_D I_{DM}	171 0.73 −2.34 −1.87 −8.0	°C/W W A A A
Thermal Resistance − Junction−to−Ambient (Note 2) Total Power Dissipation @ T_A = 25°C Continuous Drain Current @ T_A = 25°C Continuous Drain Current @ T_A = 70°C Pulsed Drain Current (Note 4)	$R_{\theta JA}$ P_D I_D I_D I_{DM}	100 1.25 −3.05 −2.44 −12	°C/W W A A A
Thermal Resistance − Junction−to−Ambient (Note 3) Total Power Dissipation @ T_A = 25°C Continuous Drain Current @ T_A = 25°C Continuous Drain Current @ T_A = 70°C Pulsed Drain Current (Note 4)	$R_{\theta JA}$ P_D I_D I_D I_{DM}	62.5 2.0 −3.86 −3.10 −15	°C/W W A A A
Operating and Storage Temperature Range	T_J, T_{stg}	−55 to +150	°C
Single Pulse Drain−to−Source Avalanche Energy − Starting T_J = 25°C (V_{DD} = −20 Vdc, V_{GS} = −4.5 Vdc, Peak I_L = −7.5 Apk, L = 5 mH, R_G = 25 Ω)	E_{AS}	140	mJ
Maximum Lead Temperature for Soldering Purposes, 1/8″ from case for 10 seconds	T_L	260	°C

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. Minimum FR−4 or G−10 PCB, Steady State.
2. Mounted onto a 2″ square FR−4 Board (1 in sq, 2 oz Cu 0.06″ thick single−sided), Steady State.
3. Mounted onto a 2″ square FR−4 Board (1 in sq, 2 oz Cu 0.06″ thick single sided), t ≤ 10 seconds.
4. Pulse Test: Pulse Width = 300 μs, Duty Cycle = 2%.

ON Semiconductor®

http://onsemi.com

MOSFET
−3.05 AMPERES
−20 VOLTS
0.085 Ω @ V_{GS} = −10 V

SCHOTTKY DIODE
1.0 AMPERE
20 VOLTS
470 mV @ I_F = 1.0 A



(TOP VIEW)

MARKING DIAGRAM & PIN ASSIGNMENT



SO−8
CASE 751
STYLE 18



E3P1	= Device Code
xx	= 02 or S
A	= Assembly Location
Y	= Year
WW	= Work Week
▪	= Pb−Free Package

(Note: Microdot may be in either location)

ORDERING INFORMATION

Device	Package	Shipping†
NTMSD3P102R2	SO−8	2500/Tape & Reel
NTMSD3P102R2G	SO−8 (Pb−Free)	2500/Tape & Reel
NTMSD3P102R2SG	SO−8 (Pb−Free)	2500/Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

SCHOTTKY MAXIMUM RATINGS (T_J = 25°C unless otherwise noted)

Rating	Symbol	Value	Unit
Peak Repetitive Reverse Voltage DC Blocking Voltage	V_{RRM} V_R	20	V
Thermal Resistance – Junction–to–Ambient (Note 5)	$R_{\theta JA}$	204	°C/W
Thermal Resistance – Junction–to–Ambient (Note 6)	$R_{\theta JA}$	122	°C/W
Thermal Resistance – Junction–to–Ambient (Note 7)	$R_{\theta JA}$	83	°C/W
Average Forward Current (Note 7) (Rated V_R, T_A = 100°C)	I_O	1.0	A
Peak Repetitive Forward Current (Note 7) (Rated V_R, Square Wave, 20 kHz, T_A = 105°C)	I_{FRM}	2.0	A
Non–Repetitive Peak Surge Current (Note 7) (Surge Applied at Rated Load Conditions, Half–Wave, Single Phase, 60 Hz)	I_{FSM}	20	A

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

5. Minimum FR–4 or G–10 PCB, Steady State.
6. Mounted onto a 2″ square FR–4 Board (1 in sq, 2 oz Cu 0.06″ thick single–sided), Steady State.
7. Mounted onto a 2″ square FR–4 Board (1 in sq, 2 oz Cu 0.06″ thick single sided), t ≤ 10 seconds.

SCHOTTKY ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted) (Note 8)

Characteristic	Symbol	Value		Unit
Maximum Instantaneous Forward Voltage I_F = 1.0 Adc I_F = 2.0 Adc	V_F	**T_J = 25°C**	**T_J = 125°C**	Volts
Maximum Instantaneous Forward Voltage I_F = 1.0 Adc I_F = 2.0 Adc	V_F	0.47 0.58	0.39 0.53	Volts
Maximum Instantaneous Reverse Current V_R = 20 Vdc	I_R	**T_J = 25°C** 0.05	**T_J = 125°C** 10	mA
Maximum Voltage Rate of Change V_R = 20 Vdc	dV/dt	10,000		V/μs

8. Indicates Pulse Test: Pulse Width = 300 μs max, Duty Cycle = 2%.

MOSFET ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted) (Note 9)

Characteristic		Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS						
Drain−to−Source Breakdown Voltage (V_{GS} = 0 Vdc, I_D = −250 μAdc) Temperature Coefficient (Positive)		$V_{(BR)DSS}$	 −20 −	 − −30	 − −	Vdc mV/°C
Zero Gate Voltage Drain Current (V_{DS} = −20 Vdc, V_{GS} = 0 Vdc, T_J = 25°C) (V_{DS} = −20 Vdc, V_{GS} = 0 Vdc, T_J = 125°C)		I_{DSS}	 − −	 − −	 −1.0 −25	μAdc
Gate−Body Leakage Current (V_{GS} = −20 Vdc, V_{DS} = 0 Vdc)		I_{GSS}	 −	 −	 −100	nAdc
Gate−Body Leakage Current (V_{GS} = +20 Vdc, V_{DS} = 0 Vdc)		I_{GSS}	 −	 −	 100	nAdc
ON CHARACTERISTICS						
Gate Threshold Voltage (V_{DS} = V_{GS}, I_D = −250 μAdc) Temperature Coefficient (Negative)		$V_{GS(th)}$	 −1.0 −	 −1.7 3.6	 −2.5 −	Vdc
Static Drain−to−Source On−State Resistance (V_{GS} = −10 Vdc, I_D = −3.05 Adc) (V_{GS} = −4.5 Vdc, I_D = −1.5 Adc)		$R_{DS(on)}$	 − −	 0.063 0.090	 0.085 0.125	Ω
Forward Transconductance (V_{DS} = −15 Vdc, I_D = −3.05 Adc)		g_{FS}	 −	 5.0	 −	Mhos
DYNAMIC CHARACTERISTICS						
Input Capacitance	(V_{DS} = −16 Vdc, V_{GS} = 0 Vdc, f = 1.0 MHz)	C_{iss}	−	518	750	pF
Output Capacitance		C_{oss}	−	190	350	
Reverse Transfer Capacitance		C_{rss}	−	70	135	
SWITCHING CHARACTERISTICS (Notes 10 & 11)						
Turn−On Delay Time	(V_{DD} = −20 Vdc, I_D = −3.05 Adc, V_{GS} = −10 Vdc, R_G = 6.0 Ω)	$t_{d(on)}$	−	12	22	ns
Rise Time		t_r	−	16	30	
Turn−Off Delay Time		$t_{d(off)}$	−	45	80	
Fall Time		t_f	−	45	80	
Turn−On Delay Time	(V_{DD} = −20 Vdc, I_D = −1.5 Adc, V_{GS} = −4.5 Vdc, R_G = 6.0 Ω)	$t_{d(on)}$	−	16	−	ns
Rise Time		t_r	−	42	−	
Turn−Off Delay Time		$t_{d(off)}$	−	32	−	
Fall Time		t_f	−	35	−	
Total Gate Charge	(V_{DS} = −20 Vdc, V_{GS} = −10 Vdc, I_D = −3.05 Adc)	Q_{tot}	−	16	25	nC
Gate−Source Charge		Q_{gs}	−	2.0	−	
Gate−Drain Charge		Q_{gd}	−	4.5	−	
BODY−DRAIN DIODE RATINGS (Note 10)						
Diode Forward On−Voltage	(I_S = −3.05 Adc, V_{GS} = 0 Vdc) (I_S = −3.05 Adc, V_{GS} = 0 Vdc, T_J = 125°C)	V_{SD}	 −	 −0.96 −0.78	 −1.25 −	Vdc
Reverse Recovery Time	(I_S = −3.05 Adc, V_{GS} = 0 Vdc, dI_S/dt = 100 A/μs)	t_{rr}	−	34	−	ns
		t_a	−	18	−	
		t_b	−	16	−	
Reverse Recovery Stored Charge		Q_{RR}	−	0.03	−	μC

9. Handling precautions to protect against electrostatic discharge are mandatory.
10. Indicates Pulse Test: Pulse Width = 300 μs max, Duty Cycle = 2%.
11. Switching characteristics are independent of operating junction temperature.

TYPICAL MOSFET ELECTRICAL CHARACTERISTICS



Figure 1. On−Region Characteristics



Figure 2. Transfer Characteristics



Figure 3. On−Resistance vs. Gate−to−Source Voltage



Figure 4. On−Resistance vs. Drain Current and Gate Voltage



Figure 5. On Resistance Variation with Temperature



Figure 6. Drain−to−Source Leakage Current vs. Voltage



Figure 7. Capacitance Variation



Figure 8. Gate−to−Source and Drain−to−Source Voltage vs. Total Charge



Figure 9. Resistive Switching Time Variation vs. Gate Resistance



Figure 10. Resistive Switching Time Variation vs. Gate Resistance



Figure 11. Diode Forward Voltage vs. Current



Figure 12. Diode Reverse Recovery Waveform



Figure 13. FET Thermal Response

TYPICAL SCHOTTKY ELECTRICAL CHARACTERISTICS



Figure 14. Typical Forward Voltage



Figure 15. Maximum Forward Voltage



Figure 16. Typical Reverse Current



Figure 17. Maximum Reverse Current



Figure 18. Typical Capacitance



Figure 19. Current Derating

TYPICAL SCHOTTKY ELECTRICAL CHARACTERISTICS



Figure 20. Forward Power Dissipation



Figure 21. Schottky Thermal Response

FETKY is a registered trademark of International Rectifier Corporation.

SCALE 1:1

SOIC−8 NB
CASE 751−07
ISSUE AK

DATE 16 FEB 2011



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSION A AND B DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 (0.006) PER SIDE.
5. DIMENSION D DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.127 (0.005) TOTAL IN EXCESS OF THE D DIMENSION AT MAXIMUM MATERIAL CONDITION.
6. 751−01 THRU 751−06 ARE OBSOLETE. NEW STANDARD IS 751−07.

	MILLIMETERS		INCHES	
DIM	MIN	MAX	MIN	MAX
A	4.80	5.00	0.189	0.197
B	3.80	4.00	0.150	0.157
C	1.35	1.75	0.053	0.069
D	0.33	0.51	0.013	0.020
G	1.27 BSC		0.050 BSC	
H	0.10	0.25	0.004	0.010
J	0.19	0.25	0.007	0.010
K	0.40	1.27	0.016	0.050
M	0°	8°	0°	8°
N	0.25	0.50	0.010	0.020
S	5.80	6.20	0.228	0.244

SOLDERING FOOTPRINT*



SCALE 6:1 (mm / inches)

*For additional information on our Pb−Free strategy and soldering details, please download the **onsemi** Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

GENERIC MARKING DIAGRAM*



XXXXX = Specific Device Code
A = Assembly Location
L = Wafer Lot
Y = Year
W = Work Week
▪ = Pb−Free Package

XXXXXX = Specific Device Code
A = Assembly Location
Y = Year
WW = Work Week
▪ = Pb−Free Package

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

STYLES ON PAGE 2

DOCUMENT NUMBER:	**98ASB42564B**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	**SOIC−8 NB**		**PAGE 1 OF 2**

SOIC−8 NB
CASE 751−07
ISSUE AK

DATE 16 FEB 2011

STYLE 1:
PIN 1. EMITTER
2. COLLECTOR
3. COLLECTOR
4. EMITTER
5. EMITTER
6. BASE
7. BASE
8. EMITTER

STYLE 2:
PIN 1. COLLECTOR, DIE, #1
2. COLLECTOR, #1
3. COLLECTOR, #2
4. COLLECTOR, #2
5. BASE, #2
6. EMITTER, #2
7. BASE, #1
8. EMITTER, #1

STYLE 3:
PIN 1. DRAIN, DIE #1
2. DRAIN, #1
3. DRAIN, #2
4. DRAIN, #2
5. GATE, #2
6. SOURCE, #2
7. GATE, #1
8. SOURCE, #1

STYLE 4:
PIN 1. ANODE
2. ANODE
3. ANODE
4. ANODE
5. ANODE
6. ANODE
7. ANODE
8. COMMON CATHODE

STYLE 5:
PIN 1. DRAIN
2. DRAIN
3. DRAIN
4. DRAIN
5. GATE
6. GATE
7. SOURCE
8. SOURCE

STYLE 6:
PIN 1. SOURCE
2. DRAIN
3. DRAIN
4. SOURCE
5. SOURCE
6. GATE
7. GATE
8. SOURCE

STYLE 7:
PIN 1. INPUT
2. EXTERNAL BYPASS
3. THIRD STAGE SOURCE
4. GROUND
5. DRAIN
6. GATE 3
7. SECOND STAGE Vd
8. FIRST STAGE Vd

STYLE 8:
PIN 1. COLLECTOR, DIE #1
2. BASE, #1
3. BASE, #2
4. COLLECTOR, #2
5. COLLECTOR, #2
6. EMITTER, #2
7. EMITTER, #1
8. COLLECTOR, #1

STYLE 9:
PIN 1. EMITTER, COMMON
2. COLLECTOR, DIE #1
3. COLLECTOR, DIE #2
4. EMITTER, COMMON
5. EMITTER, COMMON
6. BASE, DIE #2
7. BASE, DIE #1
8. EMITTER, COMMON

STYLE 10:
PIN 1. GROUND
2. BIAS 1
3. OUTPUT
4. GROUND
5. GROUND
6. BIAS 2
7. INPUT
8. GROUND

STYLE 11:
PIN 1. SOURCE 1
2. GATE 1
3. SOURCE 2
4. GATE 2
5. DRAIN 2
6. DRAIN 2
7. DRAIN 1
8. DRAIN 1

STYLE 12:
PIN 1. SOURCE
2. SOURCE
3. SOURCE
4. GATE
5. DRAIN
6. DRAIN
7. DRAIN
8. DRAIN

STYLE 13:
PIN 1. N.C.
2. SOURCE
3. SOURCE
4. GATE
5. DRAIN
6. DRAIN
7. DRAIN
8. DRAIN

STYLE 14:
PIN 1. N−SOURCE
2. N−GATE
3. P−SOURCE
4. P−GATE
5. P−DRAIN
6. P−DRAIN
7. N−DRAIN
8. N−DRAIN

STYLE 15:
PIN 1. ANODE 1
2. ANODE 1
3. ANODE 1
4. ANODE 1
5. CATHODE, COMMON
6. CATHODE, COMMON
7. CATHODE, COMMON
8. CATHODE, COMMON

STYLE 16:
PIN 1. EMITTER, DIE #1
2. BASE, DIE #1
3. EMITTER, DIE #2
4. BASE, DIE #2
5. COLLECTOR, DIE #2
6. COLLECTOR, DIE #2
7. COLLECTOR, DIE #1
8. COLLECTOR, DIE #1

STYLE 17:
PIN 1. VCC
2. V2OUT
3. V1OUT
4. TXE
5. RXE
6. VEE
7. GND
8. ACC

STYLE 18:
PIN 1. ANODE
2. ANODE
3. SOURCE
4. GATE
5. DRAIN
6. DRAIN
7. CATHODE
8. CATHODE

STYLE 19:
PIN 1. SOURCE 1
2. GATE 1
3. SOURCE 2
4. GATE 2
5. DRAIN 2
6. MIRROR 2
7. DRAIN 1
8. MIRROR 1

STYLE 20:
PIN 1. SOURCE (N)
2. GATE (N)
3. SOURCE (P)
4. GATE (P)
5. DRAIN
6. DRAIN
7. DRAIN
8. DRAIN

STYLE 21:
PIN 1. CATHODE 1
2. CATHODE 2
3. CATHODE 3
4. CATHODE 4
5. CATHODE 5
6. COMMON ANODE
7. COMMON ANODE
8. CATHODE 6

STYLE 22:
PIN 1. I/O LINE 1
2. COMMON CATHODE/VCC
3. COMMON CATHODE/VCC
4. I/O LINE 3
5. COMMON ANODE/GND
6. I/O LINE 4
7. I/O LINE 5
8. COMMON ANODE/GND

STYLE 23:
PIN 1. LINE 1 IN
2. COMMON ANODE/GND
3. COMMON ANODE/GND
4. LINE 2 IN
5. LINE 2 OUT
6. COMMON ANODE/GND
7. COMMON ANODE/GND
8. LINE 1 OUT

STYLE 24:
PIN 1. BASE
2. EMITTER
3. COLLECTOR/ANODE
4. COLLECTOR/ANODE
5. CATHODE
6. CATHODE
7. COLLECTOR/ANODE
8. COLLECTOR/ANODE

STYLE 25:
PIN 1. VIN
2. N/C
3. REXT
4. GND
5. IOUT
6. IOUT
7. IOUT
8. IOUT

STYLE 26:
PIN 1. GND
2. dv/dt
3. ENABLE
4. ILIMIT
5. SOURCE
6. SOURCE
7. SOURCE
8. VCC

STYLE 27:
PIN 1. ILIMIT
2. OVLO
3. UVLO
4. INPUT+
5. SOURCE
6. SOURCE
7. SOURCE
8. DRAIN

STYLE 28:
PIN 1. SW_TO_GND
2. DASIC_OFF
3. DASIC_SW_DET
4. GND
5. V_MON
6. VBULK
7. VBULK
8. VIN

STYLE 29:
PIN 1. BASE, DIE #1
2. EMITTER, #1
3. BASE, #2
4. EMITTER, #2
5. COLLECTOR, #2
6. COLLECTOR, #2
7. COLLECTOR, #1
8. COLLECTOR, #1

STYLE 30:
PIN 1. DRAIN 1
2. DRAIN 1
3. GATE 2
4. SOURCE 2
5. SOURCE 1/DRAIN 2
6. SOURCE 1/DRAIN 2
7. SOURCE 1/DRAIN 2
8. GATE 1

DOCUMENT NUMBER:	**98ASB42564B**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	**SOIC−8 NB**		**PAGE 2 OF 2**

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales