

External Video Camera Assembly

AD Aerospace's FV-0346 External Camera Assembly is designed to be used external to an aircraft flying up to 50,000 feet, and is sealed.

The window is aerodynamically shaped to allow water droplet removal as the aircraft moves in the air stream and has no "edges" to allow water droplets to be trapped.

The window is heated with an internally fitted 10W kapton heater, which allows for de-misting and de-icing functions.

The design has the lens option for satisfying the requirements for viewing the Main Deck Cargo Door and surrounding area.

The camera assembly is attached to the aircraft through mounting screws, and a cable is plugged in to a skin mounted connector which supplies power and provides the video connection.

Specifications

Specifications	
Size	19.5" x 5.5" x 3.5" (495mm x 140mm x 89mm)
Weight	1500g Maximum
Sensor	NTSC 768 (H) x 492 (V)
Sensitivity	Colour: 1.0 Lux. Monochrome: 0.1 Lux
Power Consumption	Maximum 3W Camera, plus 10W heating from 28V aircraft supply
TV Standard	525-line NTSC (colour)
Light Control	Auto electronic shutter to 1/100,000 seconds
Field of View	90 degrees
Resolution	Colour: Greater than 460 TV Lines. Monochrome: Greater than 520 TV Lines
Video Output	1.0V p-p into 100 ohms balanced

External Airborne Video Camera

Specifications continued

Material	Fairing: Investment cast Aluminium Alloy F357 Video Camera Body: Titanium alloy 6AL 4V Doubler: Stainless Steel 316 Fasteners: Stainless Steel 316 Grade A2
Window	Sapphire glass window single layer anti-reflective coating. Heated via a Kapton adhesive heater for de-icing.
Environmental Specification	RTCA DO160G Operating: -55°C to +70°C Storage: -55°C to +85°C Altitude: 45,000 ft

