

Internal Aerospace Camera with Integral IR Illuminator

The FV-0406 is a monochrome miniature video camera for general aerospace use. The camera is designed to be fitted within the aircraft, in a pressurised, heated area. This may be above the ceiling panels, and may therefore be subject to water, and to greater temperature extremes than the main cabin. The camera is designed to be panel mounted, and to view through the panel.

The Camera is qualified and designed for fitment with an FV-0950 CCU (Camera Control Unit) which receives 28VDC from the aircraft power supply and converts it to 9V for the FV-0406 camera.

The camera can be fitted onto the aircraft using a variety of mounting options, to allow the camera head to be angled as required and accommodate varying panel thickness.

Supplementary IR illumination is achieved through the use of the FV-1038, which is a small rugged unit comprising of an array of wide dispersion LEDs, designed based on general identification panel lighting in use on many aircraft types.

Specifications

Size	29.4mm x 29.4mm x 21mm deep (excluding lens, cable and connector)
Weight	86g Maximum (including 12" cable and connector)
Sensor	1/4" CMOS
Sensitivity	Better than 0.01 Lux
Power Consumption	Maximum 0.48W from 9V supply
TV Standard	625 line, CCIR or 525 line, EIA
Light Control	Auto electronic shutter to 1/100,000 seconds
Horizontal Field of View	Various lenses from 84 to 110
Material	Pressure die cast Zinc alloy body, ZA3 to ISO-752.
Resolution	Greater than 480 TV Lines per picture height (horizontal) in picture centre.

Internal Aerospace Camera with Integral IR Illuminator

Specifications continued

Video Output	1.0V p-p into 75R composite video
IR Performance (FV-1038)	Beam Spread of 150° at it widest Wavelength of 880nm with cut-on filter at 825nm +/-25nm
Connector	Camera Connector Fischer S 1031 A010-130
Environmental Qualification	ED-14E for Cabin Overhead mounted equipment, for use within an aircraft flying up to 50,000 feet but in an area normally pressurised to 15,000 feet.
Temperature	Operating: -15°C to +70°C Storage: -55°C to +85°C
MTBF	25,000 hours

phone: +44 (0)1928 280300 email: enquiry@ad-aero.com web: www.ad-aero.com

address: Electra House, Pepper Rd, Hazel Grove, Stockport, Cheshire, SK7 5BW

