

Video Switch Unit



AD Aerospace's FV-0530 is an airborne switcher designed to control images from external and/or internal cameras installed on board an aircraft. The unit is designed to be fitted in the cabin overhead (above ceilings) on B777 or B737 aircraft.

The unit is used as a security feature, across all Boeing models, and is therefore designed with the restrictions of the SCSRD (Standard Cabin Systems Requirement Document) Boeing D6-36440 Rev C.

Unit power input is protected by a 1A anti-surge fuse. Unit will also provide 24V output for peripherals, protected by a 0.65A resettable fuse.

Specifications

Size	376mm x 279mm x 109mm
Weight	4.0kg Maximum
Connectors	• Radial EPXB P/No: 617610182 • 9 pin standard D type for configuration
Material	Box: 1.6mm Al Alloy sheet BSEN 485:3103H4/5251H22 or 6061T4 Backplate: 3mm Al Alloy sheet BSEN 485:3103H4/5251H22 or 6061T
Video Input	The unit has 4 composite NTSC video inputs. Unit caters for both unbalanced and balanced video input.
Discrete input	The unit has 20 discrete inputs, active Low, where Low is defined as less than 3.5 Volts. There is an additional discrete input, in the form of a Program Pin, which changes the mode of operation of the unit from 737 mode to 777 mode.
Output	The unit outputs three composite video channels, each able to be selected independently and have OSD camera titling. The unit caters for both unbalanced and balanced output video

Video Switch Unit

Specifications continued

Discrete Output	The unit has 4 discrete outputs, active Low, capable of sinking 80mA each from a 28V source. An OSD function is included in the design to enable text to be defined and superimposed on the video.
Power	Maximum under normal operating conditions of 1.0 A at 115V 400HzAC to RTCA Do160D.
Environmental Specification	RTCA DO160D, for cabin overhead mounted equipment c.

