

Aerospace Video Server



AD Aerospace's FV-710 is a fully qualified (DO-160G) robust digital Video Transmission Unit (VTU) designed to be used in commercial aerospace applications, capable of streaming digital video over IP Ethernet links from up to 8 100Ω balanced composite video signals.

The unit is typically utilised as the centre of a Cockpit Door Security System (CDSS) on aircraft with EFB installations. However, other proven applications include:

- Cargo monitoring
- Ground Manoeuvring
- Visual Smoke detection
- Cabin monitoring
- External aircraft security

The VTU is contained in a simple compact aluminium box housing and can be fitted in the overhead area on aircraft as well as any Avionics Bay or even behind cabin trim due to its compact size.

Recording Method

Video signals are multiplexed, digitised and compressed in the VTU, then stored within the on-board removable storage (CF Card) with maximum combined rate of up to 100 pictures per second (@ CIF).

A 64Gb device gives 26 hours of recording at 4 frames a second with 8 cameras, or 52 hours with 4 cameras.

Camera Settings

- Video Motion Detection configuration
- User configuration
- Alarm configuration
- Camera configuration
- Search Criteria
- Time / Date
- Event Log
- Rewind / Relay

Aerospace Video Server

Specifications	
Size	250mm x 110mm x 58mm (excluding mounting brackets)
Weight	1.2kg Maximum
Qualifications	RTCA Do178B and Do160D / E.
Input	Video: 8 Balanced composite video inputs. Audio: 2 Inputs
Output	Ethernet: 3 Outputs
Ethernet	10/100 base T to IEEE 802.3
Power Input	28V dc to RTCA Do160D
Power Consumption	42W maximum on start up 14W normal operating conditions
Other	• Electronic Flight Bag compatible • Removable Flash Storage