

# GIS for Economists 5

Giorgio Chiovelli   Sebastian Hohmann   Tanner Regan

21/06/2021

# Overview

## The plan for today

### **Spatial Network in Applied Economics**

- Storeygard, 2016
- Replication of Donaldson and Hornbeck, 2015

### **Spatial Network Analysis in GIS**

- Introduction to Network
- Solving Best Route problem
- Dijkstra Algorithm

# Paper examples: network

Transport Costs and Economic Development: Storeygard (2016)

Storeygard, Adam (2016). “Farther on down the road: transport costs, trade and urban growth in sub-Saharan Africa” RES 123(1): 139-176.

## **Motivation**


How inter-city connectivity determines the income of sub-Saharan African cities.

## **Contribution**

Using road quality/type, lights, and oil price shock, estimates how growth is propagated far away from the city port. Negative elasticity of city economic activities wrt transport costs. Effect is heterogeneous in road quality (paved/unpaved).


# Paper examples: network

## Luminosity (2008) in Dar el Salaam




# Paper examples: network

## City Distribution in Tanzania



# Paper examples: network

## Roads connection to Dar el Salaam (Tanzania)



# Paper examples: network

## Trafficking Networks and the Mexican Drug War: Dell (2016)

Dell, Melissa (2016). “Trafficking Networks and the Mexican Drug War” AER

### **Motivation**


How crime repression policy affects spatial pattern of violence and crime .

### **Contribution**

Using close elections, disaggregated crime data, and road network, to identify how crime reacts to crackdown policy. Quantification of externalities and unintended consequences of crime repression.

# Paper examples: network


## Spillover Methodology





# Paper examples: network

## Roads Network and Predicted Trafficking Routes



# Market Access

## Railroads and American Economic Growth: Donaldson and Hornbeck (2015)

Donaldson, Dave and Hornbeck, Richard (2015). “Railroads and American Economic Growth: A “Market Access” Approach” QJE

### Motivation

- Evaluate the role of railway construction for US economic growth.

### Debate

- Local effect vs Aggregate effect for program evaluation. Particularly relevant if spillovers are present (SUTVA violation).

# Market Access

## Railroads and American Economic Growth: Donaldson and Hornbeck (2015)

### Contribution

- Combine transportation network over time and census data to show that expansion of the railway network fostered both local and aggregated economic growth.
- Theory-based application of intra-country trade model (Eaton and Kortum, 2002) in a reduce form framework to quantify the spillover effect of infrastructure project.

### Findings

- Railways expansion fostered US economic growth. Aggregate effects are considerably larger than local effects (due to higher “market access”).

# Market Access

Railroads and American Economic Growth: Donaldson and Hornbeck (2015)

Key expression that provides a first-order approximation to counties' market access:

$$MA_o \approx \sum_d \tau_{od}^{-\theta} N_d \quad (1)$$

where:

- $MA_o$ : Market Access at origin (o)
- $\tau_{od}$ : bilateral transportation cost between origin (o) and destination (d)
- $N_d$ : Population count at destination (d)

In our application, we are interested in deriving  $\tau_{od}$ .


# Market Access

## Railway expansion 1870-1890

C. Natural Waterways, Canals, and 1870 Railroads




D. Natural Waterways, Canals, and 1890 Railroads



# Market Access

Change in Market Access 1870-1890



# Market Access

## Regression Framework

$$\ln V_{ot} = \beta \ln(MA_{ot}) + \delta_o + \delta_{st} + f(x_o, y_o)\delta_t + \epsilon_{ot} \quad (2)$$

- $V_{ot}$  agricultural land values in county  $o$  and year  $t$
- $MA_{ot}$  market access
- $\delta_o$  county fixed effect
- $\delta_{st}$  state-by-year fixed effects
- $f(x_o, y_o)\delta_t$  cubic polynomial in county latitude and longitude interacted with year effects

# Market Access

## Replication DH network construction - Missouri

### Cost Parameters (Fogel, 1962)

- River = 0.0049 USD (tons/mile)
- Rail = 0.0063 USD (tons/mile)
- Wagon Routes = 0.231 USD (tons/mile)

**Total Cost = Parameter x Length (in miles)**



# Market Access

## Replication DH network construction - Missouri

### Solving the Best Routes Problem

- We are going to solve the network in **1870** and 1890
- We obtain a matrix of 114x114 of bilateral transportation costs
- This is the  $\tau$  in the Market Access expression
  - Cost Parameters (Fogel, 1962)
    - River = 0.0049 USD (tons/mile)
    - Rail = **0.0063 USD (tons/mile)**
    - Wagon Routes = **0.231 USD (tons/mile)**

**Total Cost = Parameter x Length (in miles)**

# What is a Network in GIS

- GIS networks represent routes upon which people and goods can travel.
  - interconnected lines (edges)
  - intersections (junctions)
- The object traversing the network follows the edges, and junctions appear when at least two edges intersect.
- Junctions and edges can have certain attributes increasing the cost of traveling in the network
- Networks are either directed or undirected

# Types of networks in GIS

- Utility networks
  - water mains, sewage lines, etc
- **Transportation networks**
  - roads, railroads, etc
- Networks based on social connections

# Common Applications in GIS Networks

- **Shortest Path.** Finding the shortest path between two points
  - Google Map and Waze
- **Traveling Salesman.** Reaching every point in a network in the most efficient way possible
  - UPS uses a traveling algorithm (no left turns!)
- **Network Partition.** Dividing up of regions in a network to zones or subcategories.
  - Optimal location of fire stations

# Spatial Network in Python

Networkx (and Geopandas + Shapely)

- **Networkx**

- Python package for the creation, manipulation, and study of the structure, dynamics, and functions of complex networks.
- Much more than “just” spatial network (classic graphs, random graphs, and synthetic networks)
- Convenient way of importing shapefile as network graph
- Install: `conda install -c anaconda networkx`
- Conflict with Python 3.9.
  - Solution: <https://github.com/smicallef/spiderfoot/issues/1124>


# Workflow

- Prepare your network
  - Clean your line (roads, railways) shapefile
  - Set your cost parameter, if needed. e.g. Railways faster than roads
- Construct you graph
  - Check connectivity
  - Add attribute to nodes and edges
- Solve for the best route problem (Dijkstra's algorithm)

→ open `network.ipynb`


# Dijkstra's algorithm

Aim: Wish to travel  $A \rightarrow F$  along **shortest path**.



# Dijkstra's algorithm

Aim: Wish to travel  $A \rightarrow F$  along **shortest path**.




## Algorithm

- 1 pick unvisited vertex with lowest distance (first vertex = 0)
- 2 calculate distance through each unvisited neighbour
- 3 pick unvisited neighbour with lowest distance as new current vertex
- 4 a vertex counts as visited once done with all its neighbours



# Dijkstra's algorithm

Aim: Wish to travel  $A \rightarrow F$  along **shortest path**.




## Algorithm

- 1 pick unvisited vertex with lowest distance (first vertex = 0)
- 2 calculate distance through each unvisited neighbour
- 3 pick unvisited neighbour with lowest distance as new current vertex
- 4 a vertex counts as visited once done with all its neighbours

# Dijkstra's algorithm

Aim: Wish to travel  $A \rightarrow F$  along **shortest path**.




## Algorithm

- 1 pick unvisited vertex with lowest distance (first vertex = 0)
- 2 calculate distance through each unvisited neighbour
- 3 pick unvisited neighbour with lowest distance as new current vertex
- 4 a vertex counts as visited once done with all its neighbours

# Dijkstra's algorithm

Aim: Wish to travel  $A \rightarrow F$  along **shortest path**.




## Algorithm

- 1 pick unvisited vertex with lowest distance (first vertex = 0)
- 2 calculate distance through each unvisited neighbour
- 3 pick unvisited neighbour with lowest distance as new current vertex
- 4 a vertex counts as visited once done with all its neighbours

# Dijkstra's algorithm

Aim: Wish to travel  $A \rightarrow F$  along **shortest path**.




## Algorithm

- 1 pick unvisited vertex with lowest distance (first vertex = 0)
- 2 calculate distance through each unvisited neighbour
- 3 pick unvisited neighbour with lowest distance as new current vertex
- 4 a vertex counts as visited once done with all its neighbours

# Dijkstra's algorithm

Aim: Wish to travel  $A \rightarrow F$  along **shortest path**.




## Algorithm

- 1 pick unvisited vertex with lowest distance (first vertex = 0)
- 2 calculate distance through each unvisited neighbour
- 3 pick unvisited neighbour with lowest distance as new current vertex
- 4 a vertex counts as visited once done with all its neighbours

# Dijkstra's algorithm

**Shortest path:** *ABDF*, **search steps** 6, **distance** 20.



## Algorithm

- 1 pick unvisited vertex with lowest distance (first vertex = 0)
- 2 calculate distance through each unvisited neighbour
- 3 pick unvisited neighbour with lowest distance as new current vertex
- 4 a vertex counts as visited once done with all its neighbours

# An application

- The Water Jugs (Jackson and Willis, 1995) :  
<https://youtu.be/5ujdpliqP6Y>
- More containers?  
<http://blancosilva.github.io/post/2016/07/29/decanting.html>