




# nonconform: Conformal Anomaly Detection (Python)

Oliver Hennhöfer <sup>1</sup>

<sup>1</sup> Intelligent Systems Research Group, Karlsruhe University of Applied Sciences, Karlsruhe, Germany

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

## Software

- [Review](#) 
- [Repository](#) 
- [Archive](#) 

Editor: [Open Journals](#) 

Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

## License

Authors of papers retain copyright  
and release the work under a  
Creative Commons Attribution 4.0  
International License ([CC BY 4.0](#))

## Summary

The ability to quantify uncertainty is a fundamental requirement for AI systems in safety-critical and costly-to-error domains, as reliable decision-making strongly depends on it. The Python package nonconform offers statistically principled uncertainty quantification for semi-supervised anomaly detection based on one-class classification (Petsche & Gluck, 1994). The package implements methods from conformal anomaly detection (Bates et al., 2023; Jin & Candès, 2023; Laxhammar & Falkman, 2010), grounded in the principles of conformal inference (Lei & Wasserman, 2013; Papadopoulos et al., 2002; Vovk et al., 2005).

The nonconform package calibrates anomaly detection models to produce statistically valid  $p$ -values from raw anomaly scores. The calibration process uses a hold-out set  $\mathcal{D}_{\text{calib}}$  of size  $n$  containing normal instances, where the model has been trained on a separate set of normal data. For a new observation  $X_{n+1}$  with anomaly score  $\hat{s}(X_{n+1})$ , this is achieved by comparing it to the empirical distribution of calibration scores  $\hat{s}(X_i)$  for  $i \in \mathcal{D}_{\text{calib}}$ . The conformal  $p$ -value  $\hat{u}(X_{n+1})$  is then defined as the normalized rank of  $\hat{s}(X_{n+1})$  among the calibration scores (Liang et al., 2024):

$$\hat{u}(X_{n+1}) = \frac{|\{i \in \mathcal{D}_{\text{calib}} : \hat{s}(X_i) \leq \hat{s}(X_{n+1})\}|}{n}.$$

By framing anomaly detection as a sequence of statistical hypothesis tests, these  $p$ -values enable systematic control of the False Discovery Rate (FDR) (Bates et al., 2023; Benjamini & Hochberg, 1995) at a pre-defined significance level by respective statistical procedures. The library integrates seamlessly with the widely used pyod library (Chen et al., 2024; Zhao et al., 2019), facilitating the application of conformal techniques across a broad range of anomaly detection models.

## Statement of Need

A central challenge in anomaly detection lies in setting an appropriate detection threshold, as it directly determines the false positive rate. In high-stakes domains such as fraud detection, medical diagnostics, and industrial quality control, controlling false positives is critical: excessive false alarms can cause *alert fatigue* and ultimately render a system impractical. The nonconform package addresses this issue by replacing raw anomaly scores with  $p$ -values, thereby enabling formal FDR control. As a result, the conformal methods become effectively *threshold-free*, since decision thresholds are determined by the underlying statistical procedures.

$$FDR = \frac{\text{Efforts Wasted on False Alarms}}{\text{Total Efforts}}$$

(Benjamini et al., 2009)

Moreover, conformal methods are *non-parametric* and *model-agnostic*, and thus apply to any model that produces consistent anomaly scores on arbitrarily distributed data. A key requirement of these methods is the statistical assumption of exchangeability between calibration and test data, which ensures the validity of conformal  $p$ -values. Exchangeability requires only that the joint distribution of data is invariant under permutations, making it considerably more general (and thus less restrictive) than the independent and identically distributed (*i.i.d.*) assumption commonly imposed in classical machine learning.

To operationalize this assumption in practice, the nonconform package provides several strategies for constructing calibration sets from training data, including approaches tailored to low-data regimes (Hennhofer & Preisach, 2024), that do not rely on a dedicated hold-out set. Based on obtained calibration sets, the package derives either standard conformal  $p$ -values or weighted conformal  $p$ -values (Jin & Candès, 2023), which are particularly useful under covariate shift when exchangeability is only approximate. By offering these tools, nonconform enables researchers and practitioners to build anomaly detectors whose outputs are statistically controlled to maintain the FDR at a chosen nominal level.

Overall, the reliance on exchangeability makes these methods well suited for cross-sectional data, but less appropriate for time-series applications where temporal ordering carries essential information.

## Acknowledgements

This work was conducted in part within the research projects *Biflex Industrie* (grant number 01MV23020A) funded by the *German Federal Ministry of Economic Affairs and Climate Action*.

## References

- Bates, S., Candès, E., Lei, L., Romano, Y., & Sesia, M. (2023). Testing for outliers with conformal  $p$ -values. *The Annals of Statistics*, 51(1). <https://doi.org/10.1214/22-aos2244>
- Benjamini, Y., Heller, R., & Yekutieli, D. (2009). Selective inference in complex research. *Philosophical Transactions of the Royal Society A: Mathematical, Physical and Engineering Sciences*, 367(1906), 4255–4271. <https://doi.org/10.1098/rsta.2009.0127>
- Benjamini, Y., & Hochberg, Y. (1995). Controlling the false discovery rate: A practical and powerful approach to multiple testing. *Journal of the Royal Statistical Society. Series B (Methodological)*, 57(1), 289–300. <https://doi.org/10.2307/2346101>
- Chen, S., Qian, Z., Siu, W., Hu, X., Li, J., Li, S., Qin, Y., Yang, T., Xiao, Z., Ye, W., Zhang, Y., Dong, Y., & Zhao, Y. (2024). PyOD 2: A python library for outlier detection with LLM-powered model selection. *arXiv Preprint arXiv:2412.12154*.
- Hennhofer, O., & Preisach, C. (2024). Leave-One-Out-, Bootstrap- and Cross-Conformal Anomaly Detectors. *2024 IEEE International Conference on Knowledge Graph (ICKG)*, 110–119. <https://doi.org/10.1109/ICKG63256.2024.00022>
- Jin, Y., & Candès, E. J. (2023). *Model-free selective inference under covariate shift via weighted conformal p-values*. <https://api.semanticscholar.org/CorpusID:259950903>
- Laxhammar, R., & Falkman, G. (2010). Conformal prediction for distribution-independent anomaly detection in streaming vessel data. *Proceedings of the First International Workshop on Novel Data Stream Pattern Mining Techniques*, 47–55. <https://doi.org/10.1145/1833280.1833287>
- Lei, J., & Wasserman, L. (2013). Distribution-free prediction bands for non-parametric regression. *Journal of the Royal Statistical Society Series B: Statistical Methodology*, 76(1), 71–96. <https://doi.org/10.1111/rssb.12021>

- 79 Liang, Z., Sesia, M., & Sun, W. (2024). Integrative conformal p-values for out-of-distribution  
80 testing with labelled outliers. *Journal of the Royal Statistical Society Series B: Statistical*  
81 *Methodology*, 86(3), 671–693. <https://doi.org/10.1093/jrssb/qkad138>
- 82 Papadopoulos, H., Proedrou, K., Vovk, V., & Gammerman, A. (2002). Inductive confidence  
83 machines for regression. In *Machine learning: ECML 2002* (pp. 345–356). Springer Berlin  
84 Heidelberg. [https://doi.org/10.1007/3-540-36755-1\\_29](https://doi.org/10.1007/3-540-36755-1_29)
- 85 Petsche, T., & Gluck, M. (1994). Workshop on novelty detection and adaptive system  
86 monitoring. *Advances in Neural Information Processing Systems (NIPS)*.
- 87 Vovk, V., Gammerman, A., & Shafer, G. (2005). *Algorithmic learning in a random world*.  
88 Springer-Verlag. ISBN: 0387001522
- 89 Zhao, Y., Nasrullah, Z., & Li, Z. (2019). PyOD: A python toolbox for scalable outlier detection.  
90 *Journal of Machine Learning Research*, 20(96), 1–7. [http://jmlr.org/papers/v20/19-011.](http://jmlr.org/papers/v20/19-011.html)  
91 [html](http://jmlr.org/papers/v20/19-011.html)

DRAFT